



PUBLIC
2026-01-20

SAP Service Cloud Version 2 Integration with Qualtrics

Content

1	Overview.	3
2	Case-Closed Feedback Scenario with Qualtrics.	4
3	Case from Survey Response.	10
3.1	Configure Integration Flows in SAP Cloud Integration.	10
3.2	Configure SAP Customer Experience Action Task in Qualtrics.	11

1 Overview

Configure end-to-end connectivity between SAP Service Cloud Version 2 and Qualtrics using SAP Cloud Integration.

Two typical cases of Qualtrics with SAP Service Cloud Version 2 include:

- to capture feedback once a case is processed and closed.
- to create a case from the received survey responses.

2 Case-Closed Feedback Scenario with Qualtrics

Case-closed feedback process is useful for capturing feedback during different stages of processing a case.

A typical scenario to capture scores is when case processing is complete.

To set up a case-closed feedback scenario, you must configure:

- Qualtrics
- SAP Service Cloud Version 2
- SAP Cloud Integration

Configure Qualtrics

Configuration on Qualtrics involves:

Designing Survey on the Qualtrics System

1. Design a survey in Qualtrics with NPS question. For more information, see [Creating a Project](#) .
2. Maintain a score for the NPS question. For more information, see [Net Promoter Score Questions: Examples and Template](#) .
3. Create an embedded data field with the name contextId. For more information, see [Creating an Embedded Data Field](#) .

Note

The value for the contextId is set from the URL and it's a mandatory placeholder.

Survey Metadata Publishing Workflow

Set up a workflow to send Qualtrics Survey Metadata to SAP Service Cloud Version 2 using integration flow *Replicate Qualtrics Survey Definition Data*.

1. On the Qualtrics home page, navigate to [Workflows](#) page using the left navigation.
2. Go to [Create a workflow](#) [Started when a event is received](#) , and then provide a name for your workflow and choose a location to save the workflow.
3. In the [Select an extension that matches what you want to do](#) pop up, search for [Survey Definition Event](#) , and select the tile.
4. On the [Survey Definition Event](#) popup, select [Published](#) as the trigger and choose [Save](#) .
5. Select the Workflow event as [Survey Definition Event](#) and trigger as [Published](#) .
6. On the workflow editor page, click the add icon (+) and then select [Add a task](#) .
7. In the [Select an extension that matches what you want to do](#) pop up, search for [WebService](#) , select it, and then click [Next](#) .
8. On the [WebService](#) page, select [Authenticated web service](#) , and click [Next](#) .

- On the [WebService - Authenticated web service](#) page, select a user account, or create a new account choosing [Add a user account](#).

Note

The selected user account must be able to authenticate the SAP Cloud Integration tenant.

- Save the WebService task with the following details, and publish the survey.

Request

Request		POST	
URL		URL of integration flow <i>Replicate Qualtrics Survey Definition Data</i>	
Headers			
Content-Type		Application/JSON	
Body (JSON Key Value Pairs)			
Key	Value	Data Type	Mandatory
SurveyID	`\${e://Field/SurveyID}`	String	Yes

Note

- The request body must contain the Qualtrics survey SurveyID to retrieve the survey metadata from Qualtrics.
- The workflow must be set up and activated before the Survey is designed and published.

Survey Response Publishing Workflow

Set up a workflow to send Survey Response information to SAP Service Cloud Version 2 using the integration flow *Replicate Qualtrics Survey Response Data* with the following information:

- Select the Workflow event as [Survey Response](#) and trigger as [Newly created responses](#).
- Add a [Web Service](#) task.
- Select type as [Authenticated Web service](#).
- Select the user account, or create a new account selecting [Add a user account](#).

Note

The selected user account must be able to authenticate the SAP Cloud Integration tenant.

- Save the Web Service task with the following details:

Request

Request	POST
URL	Endpoint URL of integration flow <i>Replicate Qualtrics Survey Definition data</i>
Headers	
Content-Type	Application/JSON

Body (JSON Key Value Pairs)

Key	Value	Data Type	Mandatory
SurveyID	\${e://Field/SurveyID}	String	Yes
ResponseID	\${rm://Field/ResponseID}	String	Yes

Configure SAP Service Cloud Version 2

Configuration on SAP Service Cloud Version 2 involves the following steps:

Setting Up Email Channel

1. Log in to the system as an administrator.
2. Navigate to user profile on the right-top corner, and access the [Settings](#) page.
3. Go to ► [All Settings](#) ► [Emails](#) ► [Channels](#) ►.
4. Click the add icon (+) on the [All Emails Channel](#) page, enter a channel name for [Channel Name](#), enter the email ID from which the emails are sent for [Channel Email](#), and choose Feedback as the [Object](#) from the dropdown.
5. [Save](#) and [Activate](#) the email channel.

Setting Up Email Template

1. Log in to the system as an administrator.
2. Navigate to user profile on the right-top corner, and access the [Settings](#) page.
3. Go to ► [All Settings](#) ► [Emails](#) ► [Templates](#) ►.
4. Click the add icon (+) on the [Templates](#) page, enter a name for [Template Name](#). Under [General Information](#), choose Feedback Template as the [Template Type](#), Case for [Object Type](#), and Email for [Channel Type](#) from the respective dropdowns.

ⓘ Note

The email content must contain the survey link to be sent along with the fixed placeholder `{{sourceContext}}`. This placeholder is required to pass the context, which is auto-populated, while triggering the feedback email. For example: <https://surveyLink?{{sourceContext}}>.

The survey must be created in a survey engine, and the link must be provided. The `{{sourceContext}}` is filled in to an embedded data field 'contextId' defined on the Qualtrics service.

5. Choose [Save](#) to save the email template.

Setting Up Feedback Flow

1. Log in to the system as an administrator.
2. Navigate to user profile on the right-top corner, and access the [Settings](#) page.
3. Go to ► [All Settings](#) ► [Business Flow](#) ► [Feedback](#) ►.
4. Click the add icon (+) on the [Feedback](#) page, choose Case as the [Business Entity](#) from the dropdown, and enter a description for the business entity.

Note

For now, Case is the only supported business entity. Contact of account or individual account for Case, Reported by of Case, and Contact of supplier of Case are the supported role-base recipients.

5. In the [Email Template](#) section, enter a subject in the subject line and link the preconfigured email template.
6. Link the preconfigured email channel.
7. Select a role-based recipient for the feedback flow per the business requirement, and click [Save](#).
8. Choose [Activate](#) to activate your feedback flow.

Adding Feedback Step to Case Type

1. Log in to the system as an administrator.
2. Navigate to user profile on the right-top corner, and access the [Settings](#) page.
3. Go to [All Settings](#) > [Cases](#) > [Case Type](#).
4. Create a new Case Type, or Open any existing Case Type.
5. On a draft Case Type, add [Step](#) and select [Feedback](#) step.
6. Enter a name and help text.
7. Select the preconfigured Feedback Flow.
8. Add preconditions, if necessary, and click [Create](#) to save the feedback step.

Note

Preconditions aren't mandatory, if no preconditions are maintained then feedback flow is executed. If Auto-Trigger is enabled, then Feedback Step is executed when preconditions are satisfied.

Case and Feedback Data

Once a user fills the survey and submits the response, the Feedback tab in the Case detail page is populated with Feedback data such as Survey ID, Survey Name, Responded By, Satisfaction Score, and other details.

Configure Cloud Integration

To realize the closed case feedback process, SAP provides a standard integration package with Qualtrics, which contains two integration flows.

Package: Qualtrics Integration with SAP Sales Cloud and Service Cloud Version 2

Configure *Replicate Qualtrics Survey Definition Data* Integration Flow

Enter the following parameters:

For Receiver: Qualtrics

Parameter	Value
Receiver	Qualtrics
Adapter Type	HTTP

Parameter	Value
Qualtrics Base URL	Qualtrics URL, similar to the following example. https://<qualtrics_tenant>.qualtrics.com

More Tab - Additional Configuration

Parameter	Value
Type	All Parameters
Qualtrics API Token	Secure parameter name for your Qualtrics API token

For Receiver: SAPSalesAndServiceCloudV2

Parameter	Value
Receiver	SAPSalesAndServiceCloudV2
Adapter Type	HTTP
SAP Sales And Service Cloud v2 Base URL	https://<your_SalesAndServiceCloudV2_Tenant_URL>
Authentication	Basic or Client Certificate
Credential Name	- If you select Basic Authentication, enter the user credential name (security artifact) you created when you configured cloud integration. - If you select Client Certificate, enter the private key alias provided while adding the key pair in the Manage Keys UI.

Configure Replicate Qualtrics Survey Response Data Integration Flow

Enter the following parameters:

For Receiver: Qualtrics

Parameter	Value
Receiver	Qualtrics
Adapter Type	HTTP
Qualtrics Base URL	Qualtrics URL, similar to the following example. https://<qualtrics_tenant>.qualtrics.com

More Tab - Additional Configuration

Parameter	Value
Type	All Parameters
Qualtrics API Token	Secure parameter name for your Qualtrics API token

For Receiver: SAPSalesAndServiceCloudV2

Parameter	Value
Receiver	SAPSalesAndServiceCloudV2
Adapter Type	HTTP

Parameter	Value
SAP Sales And Service Cloud v2 Base URL	https://<your_SalesAndServiceCloudV2_Tenant_URL>
Authentication	Basic or Client Certificate
Credential Name	- If you select Basic Authentication, enter the user credential name (security artifact) you created when you configured cloud integration. - If you select Client Certificate, enter the private key alias provided while adding the key pair in the Manage Keys UI.

Note

- The user, used in Basic Authentication, must have access to feedback service in SAP Sales and Service Cloud V2.
- Use an API token for a Qualtrics user with authorizations to read the survey metadata and response using the Qualtrics API. For example, the survey owner or the survey collaborator. Store the Qualtrics API token as a secure parameter. To set up a secure parameter, go to: [► Overview ► Manage Security Material ► New Secure Parameter ► Enter a name for the Qualtrics API token ►](#). Enter that same secure parameter name in the API token field in the [Additional Configuration](#) section.

Related Information

[Configure Inbound Email Channels to Create Cases](#)

[Create Email Templates](#)

<https://api.qualtrics.com/ZG9jOjg3NjYzMg-api-key-authentication> 

<https://www.qualtrics.com/support/survey-platform/actions-module/setting-up-actions/> 

<https://www.qualtrics.com/support/survey-platform/actions-module/actions-reporting/> 

3 Case from Survey Response

Use an action task to automatically create a case in SAP Service Cloud Version 2 based on a survey response in Qualtrics.

To set up case creation scenario from survey responses, you must:

- Configure integration flows in SAP Cloud Integration.
- Configure SAP Customer Experience Action Task in Qualtrics.

3.1 Configure Integration Flows in SAP Cloud Integration

Configure integration flows in CI to enable case creation from a survey response.

Prerequisites

Ensure you've the following:

- User credential (security artifact) from CI, or client certificate key-pair private key alias.

Procedure

1. Configure the integration flow [Create Case in SAP Service Cloud Version 2](#) in SAP Cloud Integration. Enter the following parameters:

For Receiver: SAPServiceCloud

Parameter	Value
Receiver	SAPServiceCloud
Adapter Type	HTTP
SAP Service Cloud Base URL	https://<your_ServiceCloudV2_Tenant_URL>
Authentication	Basic or Client Certificate

Parameter	Value
Credential Name	- If you select Basic Authentication, enter the user credential name (security artifact) you created when you configured CI. - If you select Client Certificate, enter the private key alias provided while adding the key pair in the Manage Keys UI.

2. Configure the integration flow [Fetch Code Description for Case from SAP Service Cloud Version 2](#) in SAP Cloud Integration. Enter the following parameters:

For Receiver: SAPServiceCloud

Parameter	Value
Receiver	SAPServiceCloud
Adapter Type	HTTP
SAP Service Cloud Base URL	https://<your_ServiceCloudV2_Tenant_URL>
Authentication	Basic or Client Certificate
Credential Name	- If you select Basic Authentication, enter the user credential name (security artifact) you created when you configured CI. - If you select Client Certificate, enter the private key alias provided while adding the key pair in the Manage Keys UI.

3.2 Configure SAP Customer Experience Action Task in Qualtrics

Set up the action task in Qualtrics to create a case in SAP Service Cloud Version 2 from a survey response.

Prerequisites

You've created an account for **SAP Customer Experience** in Qualtrics.

Procedure

1. On the Qualtrics home page, navigate to [Workflows](#) page using the left navigation.
2. Go to  [Create a workflow](#)  and then provide a name for your workflow and choose a location to save the workflow.

3. In the *Select an extension that matches what you want to do* pop up, search for *Survey response*, and click *Finish*.
4. Click the **+** icon and select *Add a task* button.
5. In the *Select an extension that matches what you want to do* pop up, search for *SAP Customer Experience* tile, select *Create Case* radio button from the list, and click *Next*.
6. On the *Choose account* page, either add a new account by selecting **+ Add a user account** or choose one of the existing user accounts, and click *Next*.
7. In the next page, select a *Case Type*, *Subject*, and *Email*, and in addition also add additional fields such as *Priority*, *Description*, and *Custom Field* as required, and choose *Save*.

Note

Once you add a *Custom Field*, ensure you enter the custom field key value fetching it from the *Extensibility* settings and also choose a corresponding value for the custom field.

Note

Limitation: Additional fields such as *Case Type* and *Priority* are only available in the English Language. The translated versions do not show up on the user interface.

Important Disclaimers and Legal Information

Hyperlinks

Some links are classified by an icon and/or a mouseover text. These links provide additional information.

About the icons:

- Links with the icon  : You are entering a Web site that is not hosted by SAP. By using such links, you agree (unless expressly stated otherwise in your agreements with SAP) to this:
 - The content of the linked-to site is not SAP documentation. You may not infer any product claims against SAP based on this information.
 - SAP does not agree or disagree with the content on the linked-to site, nor does SAP warrant the availability and correctness. SAP shall not be liable for any damages caused by the use of such content unless damages have been caused by SAP's gross negligence or willful misconduct.
- Links with the icon  : You are leaving the documentation for that particular SAP product or service and are entering an SAP-hosted Web site. By using such links, you agree that (unless expressly stated otherwise in your agreements with SAP) you may not infer any product claims against SAP based on this information.

Videos Hosted on External Platforms

Some videos may point to third-party video hosting platforms. SAP cannot guarantee the future availability of videos stored on these platforms. Furthermore, any advertisements or other content hosted on these platforms (for example, suggested videos or by navigating to other videos hosted on the same site), are not within the control or responsibility of SAP.

Beta and Other Experimental Features

Experimental features are not part of the officially delivered scope that SAP guarantees for future releases. This means that experimental features may be changed by SAP at any time for any reason without notice. Experimental features are not for productive use. You may not demonstrate, test, examine, evaluate or otherwise use the experimental features in a live operating environment or with data that has not been sufficiently backed up.

The purpose of experimental features is to get feedback early on, allowing customers and partners to influence the future product accordingly. By providing your feedback (e.g. in the SAP Community), you accept that intellectual property rights of the contributions or derivative works shall remain the exclusive property of SAP.

Example Code

Any software coding and/or code snippets are examples. They are not for productive use. The example code is only intended to better explain and visualize the syntax and phrasing rules. SAP does not warrant the correctness and completeness of the example code. SAP shall not be liable for errors or damages caused by the use of example code unless damages have been caused by SAP's gross negligence or willful misconduct.

Bias-Free Language

SAP supports a culture of diversity and inclusion. Whenever possible, we use unbiased language in our documentation to refer to people of all cultures, ethnicities, genders, and abilities.

© 2026 SAP SE or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP SE or an SAP affiliate company. The information contained herein may be changed without prior notice.

Some software products marketed by SAP SE and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP SE or an SAP affiliate company for informational purposes only, without representation or warranty of any kind, and SAP or its affiliated companies shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP or SAP affiliate company products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP SE (or an SAP affiliate company) in Germany and other countries. All other product and service names mentioned are the trademarks of their respective companies.

Please see <https://www.sap.com/about/legal/trademark.html> for additional trademark information and notices.

