



PUBLIC

2026-02-10

SAP Service Cloud Version 2 Utilities Integration with SAP S/4HANA

Content

1	Utilities Integration with SAP S/4HANA.	3
2	Prerequisites.	4
3	Configuration.	5
3.1	Configuration in SAP Service Cloud Version 2.	5
	Create Communication System.	6
	Create Communication Configurations.	7
3.2	Configuration in SAP S/4HANA.	8
	Maintain Trust between SAP Cloud Integration and SAP S/4HANA.	8
	SAP S/4HANA Web Service Configuration (SOA Management).	10
3.3	Configuration in SAP Cloud Integration.	14
	Copy Integration Package.	14
	Deploy Security Credentials.	15
	Configure and Deploy Integration Flows.	16
	Configure Master Data Replication.	18
3.4	Configuration in SAP Cloud Connector.	19
3.5	Replication of Master Data Initial Load.	20
	Setting Up SAP S/4HANA Utilities for Contract Account Replication.	21
	(Deprecated) Technical Master Data Replication.	23
	Technical Master Data Replication.	25
	Load Business Partner and Business Partner Relationships.	28
4	Extensibility.	29
4.1	Cloud Integration (CI).	29
	Custom Extensions.	29
5	Appendix.	34

1 Utilities Integration with SAP S/4HANA

This document describes the procedure to manually configure the integration between SAP S/4HANA and SAP Service Cloud Version 2 for Utilities using SAP Cloud Integration (SCI).

SAP does not deliver the configuration steps as they are customer specific, and those must be completed by the customer. This document describes the general configuration steps to manually set up the configuration within the existing system landscape. If you have any queries or feedback about this document, please create a ticket using the component [CA-GTF-INT-CFC](#).

2 Prerequisites

Prerequisites for integrating SAP S/4HANA with SAP Service Cloud Version 2.

You've access to SAP Service Cloud Version 2 system which includes:

- Initial user and access information for your SAP Service Cloud Version 2 tenant provided via email by Cloud Management Service.

You've access to SAP Cloud Integration system. This includes:

- Integration developer persona assigned to your user in your SAP Cloud Integration tenant to import and deploy integration flows on SAP Cloud Integration.
- Initial user and access information for your SAP Cloud Integration tenant.
- SAP Cloud Integration Client Certificate.

Required Information

While performing the activities described here, you must enter or provide system-specific information. Before you start the integration process, it's recommended that you have the information listed. The information ensures a smooth and efficient integration of the SAP S/4HANA and SAP Service Cloud Version 2.

- SAP Service Cloud Version 2
- SAP S/4HANA system
- SAP Cloud Integration
- SAP Cloud Connector

3 Configuration

Configurations required for integrating SAP S/4HANA with SAP Service Cloud Version 2.

The following sections describe all the settings required.

[Configuration in SAP Service Cloud Version 2 \[page 5\]](#)

This integration package enables you to integrate master data between SAP Sales Cloud and SAP Service Cloud Version 2 and SAP S/4HANA.

[Configuration in SAP S/4HANA \[page 8\]](#)

An overview of how to configure integration with S/4HANA system.

[Configuration in SAP Cloud Integration \[page 14\]](#)

SAP provides prepackaged, generic integration content called integration flows for the integration between SAP S/4HANA and SAP Service Cloud Version 2 for Utilities using SAP Cloud Integration.

[Configuration in SAP Cloud Connector \[page 19\]](#)

SAP Cloud connector allows SAP BTP applications to securely access remote services that run on the Internet or SAP S/4HANA.

[Replication of Master Data Initial Load \[page 20\]](#)

In the following sections, we describe the replication of contract account, utilities technical master data (Connection object and premise), and business partner.

3.1 Configuration in SAP Service Cloud Version 2

This integration package enables you to integrate master data between SAP Sales Cloud and SAP Service Cloud Version 2 and SAP S/4HANA.

Configuration in SAP Service Cloud Version 2 in the Core Integration Guide (Set-up Instructions for SAP Service Cloud Version 2, SAP Cloud Integration, and SAP S/4HANA) briefly explains the procedure to configure.

For more information refer to [SAP Sales Cloud and SAP Service Cloud Version 2 Integration for Master Data with SAP S/4HANA or SAP S/4HANA Cloud](#) 

3.1.1 Create Communication System

A communication system represents an external system that is used for application integration. Communication systems can be, for example, an external time recording or master data system.

Context

On the [Communication Systems](#) page, you can filter the communication systems by status and authentication type. You can create and edit communication systems to exchange data across systems electronically.

Procedure

1. Log in to the system as an administrator.
2. Navigate to user profile on the right-top corner, and access the [Settings](#) page.
3. Go to ► [All Settings](#) ► [Integration](#) ► [Communication Systems](#) ►.
4. Click the + (Add) icon on the [Communication Systems](#) page, enter the [Display ID](#) and [Description](#) for the communication system.

Note

Display ID must be the Business System ID of your external system.

5. Click + [Create](#) button in the [Inbound](#) tab, enter a password or upload a certificate file for authentication.
6. Click [Save and Activate](#) to create the inbound communication system.

Note

By default the user is created while creating communication system. The communication user ID is same name as the communication system and the password is maintained in the inbound communication tab of the communication system.

7. Click + [Create](#) button in the [Outbound](#) tab, choose a protocol, enter a host name, select an authentication method from the dropdown, and click [Save and Activate](#) to create the outbound communication system.

Results

You've now successfully created a communication system, which you can use for integrating applications.

Related Information

[Create Communication Systems](#)

3.1.2 Create Communication Configurations

Configure communication between SAP Service Cloud Version 2 and the SAP S/4HANA you are integrating it with.

Context

Procedure

1. Go to [User Menu](#) > [Settings](#) > [All Settings](#) > [Integration](#) > [Communication Configuration](#).
2. To integrate Service Cloud Utilities Master Data with SAP S/4HANA, select the following communication configurations:
 - Integrate Service Cloud Utilities with SAP S/4HANA- Premise
 - Integrate Service Cloud Utilities with SAP S/4HANA- Move
 - Integrate Service Cloud Utilities with SAP S/4HANA- Common
 - Integrate Service Cloud Utilities with SAP S/4HANA- Financials
 - Integrate Service Cloud Utilities with SAP S/4HANA- Collections
 - Integrate Service Cloud Utilities with SAP S/4HANA - Contract Account
 - Integrate Service Cloud Utilities Master Data with SAP S/4HANA

You can also click **+** (Create) to create a communication configuration for your requirements.

3. Click  (Copy).
4. Go to the [Communication Configuration](#) page and click the copied communication configuration.
5. Edit [Communication System](#) and select the name of the communication system.
6. Repeat the same for all the communication configurations which you copied.

Target message entity is the structure in which the target system expects the data to arrive. [Target Message Entity API Path](#) is the path to which the data is stored. Source entity is the structure in which the source sends the data to connector.

The test icon gives the connection status.

Note

- The [Target Message Entity API Path](#) must match the respective iflow endpoints.
- For all the modules except Integrate Service Cloud Utilities Master Data with SAP S/4HANA, the synchronous calls and services list are under HTTP data. For Integrate Service Cloud Utilities

Master Data with SAP S/4HANA, the synchronous calls and services list are under Inbound Configuration.

7. In [HTTP Data](#), use the search icon to select the configurations relevant to your scope.

Related Information

[Create Communication Configurations](#)

[View Inbound Configurations](#)

[View Outbound Configurations](#)

3.2 Configuration in SAP S/4HANA

An overview of how to configure integration with S/4HANA system.

Prerequisites

Ensure the administrator has business user access before starting the configuration in SAP S/4HANA.

Upgrade the software component `IS-UT 808 FPS1` and implement `OSS Note 3502558` to enable all the new features of the SAP Service Cloud Version 2 release.

3.2.1 Maintain Trust between SAP Cloud Integration and SAP S/4HANA

3.2.1.1 Download SAP Cloud Integration Certificate to SAP S/4HANA

Trust relationships enable you to establish secure connections between known servers whose identity can be confirmed by a signed certificate.

Context

You need to download the certificate of SAP Cloud Integration tenant via a web browser and import it to SAP S/4HANA. Google Chrome is used as the default browser.

Procedure

1. Access SAP Cloud Integration using the URL `https://<tenant management node>/itspaces`.
2. In the browser, choose the lock icon and then [Certificate](#) (Valid) of your secure connection.
3. In the [Certificate](#) dialog box, go to the [Details](#) tab.
4. Choose [Copy to File](#).
5. In the [Certificate Export Wizard](#) dialog box, choose [Next](#).
6. Choose [Base-64 encoded X.509 \(.CER\)](#) and choose [Next](#).

Certificates can be exported in a variety of file formats.

7. Specify the name of the file and save it to the desktop by default. Choose [Next](#).
8. Choose [Finish](#).

A message tells you that the export was successful.

3.2.1.2 Upload SAP Cloud Integration Certificate to SAP S/4HANA

Uploading SAP Cloud Integration certificates to SAP S/4HANA is a crucial step in establishing a secure communication setup between the two systems. Certificates are used for authentication, ensuring that the communication between SAP Cloud Integration and SAP S/4HANA is secure and trusted.

Procedure

1. Log on to your SAP S/4HANA system as an administrator (SAP_BR_ADMINISTRATOR).
2. Open [Maintain Certificate Trust List](#).

3. Next to the [Certificate Trusts](#) table, choose **+** (Add) icon.
4. In the [Upload Certificate](#) dialog box, browse for the SAP Cloud Integration certificate that you've downloaded and choose [Upload](#). A system message informs you that the certificate has been uploaded.

3.2.2 SAP S/4HANA Web Service Configuration (SOA Management)

This feature is intended for technical system administrators who configure inter-system connections and manage security settings in the system landscape.

To use web services with Web Services Reliable Messaging, you must have the web service runtime configured.

The configuration of the web service runtime is client-specific and must be performed in each productive client.

User Action	Entry Value
Transaction Code	SOAManager

For all the S/4H inbound and outbound web service names, refer the [SAP Note](#) 

3.2.2.1 Outbound Web Service Configuration

Procedure

1. Open [Service Administration](#) tab and browse [Web Service Configuration](#). For each entity in the following table, search for the entity name and complete the steps that follow.

Entity Name	Name
CO_ISU_C4C_V2_PREM_CONNOBJ_REP	UtilitiesPremiseConnectionObjectReplicateRequest_Out
CO_FKK_MDG_CONTRACT_ACCOUNT_BU	ContractAccountBulkReplicateRequest_Out
CO_ISU_C4C_V2_POD_REPL	UtilitiesPointOfDeliveryReplicateRequest_Out
CO_ISU_C4C_V2_UTIL_PREMISE_POD	UtilitiesPremisePointOfDeliveryRelationshipReplicateRequest_Out

2. Configure the logical port.

If the logical port is already configured for a different system then follow the steps in [SAP Master Data Integration service Business Partner configuration without using Default Logical Port on SAP S/4HANA](#) and skip below steps.

3. Choose [Create](#).

4. Choose [Manual Configuration](#).
5. Under [Logical Port Name](#), add the logical port name. For example, LP_<system name to connect to>.
6. Check the Logical port as default box.
7. Add the port description. For example, <For Premise Replication>.
8. Choose [Next](#).
9. Under [Consumer Security](#), configure authentication and authorization as described for the authorization type in your integration flow:

Integration Flow Authorization Type

User Role	Choose the User ID/Password option. Add the SCI User ID and password to connect to the SCI tenant.
Client Certificate	Choose X.509 SSL Client Certificate for Authentication Settings . Choose an item for your SSL Client PSE of transaction STRUST.

10. Choose [Next](#).
11. Under [HTTP/ Transport](#) Settings, in the **URL** field, add the SCI integration flow end point.
In case you are adding the URL-by-URL components then in the [Protocol](#) field, add HTTPS.
12. Choose [Next](#).
13. Under [SOAP Protocol /Messaging](#), add the fields as shown:

Field Name	Value
RM Protocol	<SAP RM>
Message ID Protocol	<SAP Message ID>
Data Transfer Scope	<Basic Data Transfer>
Transfer Protocol	<Transfer via SOAP header>

14. Choose [Next](#).
15. Choose [Finish](#).
16. Repeat the same steps for creating the logical port for the other entity.

Note

The SAP Note 3253818 provides gives all information about the S/4 web service names, CI integration flow names and service cloud communication configuration details. The attached excel in the note has all the technical information for the integration setup.

3.2.2.2 Inbound Web Service Configuration

Activate the SAP S/4HANA inbound web service to set up the connection for communication from SAP Cloud Integration to SAP S/4HANA.

Context

You can activate the inbound web services listed in the table for communication from SAP Cloud Integration to the SAP S/4HANA system by enabling the service definitions in SAP S/4HANA.

Inbound Web Service Names

Service Name
isu_c4c_v2_premise_service
isu_c4c_v2_premise_bp
isu_c4c_v2_meter_read
isu_c4c_v2_contracts_get
isu_c4c_v2_move_in
isu_c4c_v2_move_in_mdt
isu_c4c_v2_move_out
isu_c4c_v2_rate_category
isu_c4c_v2_bp_data
isu_c4c_v2_object_search
isu_c4c_v2_object_address_get
isu_c4c_v2_util_mdt_ca crt
isu_c4c_v2_bank_master
isu_c4c_v2_bank_data
isu_c4c_v2_ca_overview
isu_c4c_v2_financial_amount
isu_c4c_v2_open_item_graph
isu_c4c_v2_invoices
isu_c4c_v2_budget_bill_plan

Service Name

isu_c4c_v2_open_items

isu_c4c_v2_manual_posting

isu_c4c_v2_promise_to_pay

isu_c4c_v2_consumption

isu_c4c_v2_bpem

isu_c4c_v2_bp_security_dep

isu_c4c_v2_installment_plan

isu_c4c_v2_otp_create

isu_c4c_v2_payments

isu_c4c_v2_financial_doc

isu_c4c_v2_payment_plan

isu_c4c_v2_write_off

isu_c4c_v2_dunning

isu_c4c_v2_returns

isu_c4c_v2_corresp_hist_get

isu_c4c_v2_collections

isu_c4c_v2_bill_amount

isu_c4c_v2_ca_details

isu_c4c_v2_mdt_ca crt

isu_c4c_v2_ca_details

isu_c4c_v2_move

isu_c4c_v2_transfer_sec

isu_c4c_v2_ami_ping

isu_c4c_v2_device

isu_c4c_v2_alerts

isu_c4c_v2_locks

Service Name

isu_c4c_v2_disconn_doc

isu_c4c_v2_bill_document

isu_c4c_v2_locks

isu_c4c_v2_ca_payment_data

Procedure

1. Go to the **SOA Management** (SOAMANAGER) transaction in your SAP S/4HANA system.
2. Choose *Simplified Web Service Configuration*.
3. Enter the web service definition name in the *Search Pattern* field and choose *Go*.
4. In the result list, select the Username/Password (Basic) check box for the web service definition.
5. Choose *Save*.

3.3 Configuration in SAP Cloud Integration

SAP provides prepackaged, generic integration content called integration flows for the integration between SAP S/4HANA and SAP Service Cloud Version 2 for Utilities using SAP Cloud Integration.

Note

You must not make any updates to the standard package delivered by SAP. Doing this will lead to missing of auto-update of the integration package, and you can see an error message stating the failure of uniqueness check. For more details on the error, see [\[https://me.sap.com/notes/\]0003531297](https://me.sap.com/notes/]0003531297) .

3.3.1 Copy Integration Package

The prepackaged integration package such as *SAP Service Cloud V2 for Utilities Master Data Integration with SAP S/4HANA*, *SAP Service Cloud V2 for Utilities Contract Account Integration with SAP S/4HANA*, and *SAP*

Service Cloud V2 for Utilities Premise Integration with SAP S/4HANA contains integration flows that need to be copied and configured.

Procedure

1. Log in to the SAP Cloud Integration tenant.
2. From the ☰ (Menu), select *Discover*.
3. Click *Integration*.

All the SAP delivered integrations packages are listed.

4. Search and select the utilities *SAP Service Cloud V2 for Utilities Master Data Integration with SAP S/4HANA* package.
5. Click  (Copy).
6. Repeat the same steps for the other integration packages.

3.3.2 Deploy Security Credentials

The communication between SAP Cloud Integration and SAP Service Cloud Version 2 is established via basic authentication over HTTPS. User credential needs to be deployed in the SAP Cloud Integration tenant, which is used for sending messages to SAP Service Cloud Version 2.

Procedure

1. Log in to the SAP Cloud Integration tenant.
2. From the ☰ (Menu), select *Monitor*.
3. Under *Manage Security*, select *Security Material*.
4. From the *Create* dropdown, select *User Credentials*.
5. In *Create User Credentials*, enter the required details.

Use the credential maintained in ► *SAP Service Cloud Version 2* ► *Settings* ► *Integration* ► *Communication Systems* ► *Inbound* .

6. Click *Deploy* to deploy the user credential artifact.
7. For basic authentication of inbound messages in SAP S/4HANA, repeat the steps for the user authorized to execute messages in the SAP S4H system.

3.3.3 Configure and Deploy Integration Flows

After copying the integration packages to your workspace, you need to set up and deploy the integration flows.

The integration packages are as follows:

- SAP Service Cloud V2 for Utilities Premise Integration with SAP S/4HANA
- SAP Service Cloud V2 for Utilities Contract Account Integration with SAP S/4HANA

There are two methods to configure and deploy the integration flows:

1. Configure and deploy each integration flow individually
2. Configure and deploy all integration flows concurrently

Note

SAP recommends the customers to choose the first method of configuration.

3.3.3.1 Configure and Deploy Each Integration Flow Individually

After copying the integration packages to your workspace, you need to set up and deploy the integration flows.

Procedure

1. Log in to the SAP Cloud Integration tenant.
2. Configure the integration flows, from the ☰ (menu), select [Design](#).
3. Select the copied integration package SAP Service Cloud Version 2 for Utilities Contract Account Integration with SAP S/4HANA.

All integration flows are displayed on the [Artifacts](#) tab.

4. Select the required integration flow.
5. From the [Actions](#) menu, select [Configure](#).
6. Configure the sender system (**SAP Service Cloud Version 2**) and the receiver system (**S4H**) details:
 - a. In the [Sender](#) tab, select the [Authorization and User Role](#) options.
 - b. Click the [Receiver](#) tab and do the following:
 - In [Address](#), enter the endpoint address of the receiving S4H system.
The URL needs to start with a protocol, host, and port name of the S4H system. By default S4 host, port, and client are defined as properties. Replace **{property.S4HostandPort}** and **{property.S4Client}** with your S4 host, port, and client details, for example, `http://ldcabc.wdf.sap.corp:56007/sap/bc/srt/scs/sap/isu_c4c_v2_promise_to_pay?sap-client=001`. You can locate the inbound endpoint URL for each S4 service in the S4H system by navigating to transaction Tx.SOAMANAGER.

📘 Note

Ensure these properties are retained and deployed when configuring using method 2.

- c. From the *Proxy Type* dropdown, select *On-Premise* (for connectivity via SAP Cloud Connector) or *Internet* (for connectivity via reverse proxy based infrastructure).

Delete the property `\${property.LocationID}` and update your Location ID if you are using one; otherwise, leave this parameter blank.

📘 Note

You can connect multiple Cloud Connectors to a sub account, provided each has a unique location ID. The location ID identifies which Cloud Connector is used to establish the connection. By default, the location ID is an empty string, indicating the Cloud Connector connected without a specific location ID.

- d. From the *Authentication* dropdown, select *Basic*.
 - e. In the *Credential Name* field, enter the name of the credential deployed in security artifacts.
 - f. Repeat the same procedure for all the integration flows that have the same sender as SAP Service Cloud Version 2 and the receiver as **S4H** systems.
7. Repeat the steps from 3 to 6 for the integration package *SAP Service Cloud V2 for Utilities Premise Integration with SAP S/4HANA*.

Related Information

[SAP S/4HANA Web Service Configuration \(SOA Management\) \[page 10\]](#)

This feature is intended for technical system administrators who configure inter-system connections and manage security settings in the system landscape.

3.3.3.2 Configure and Deploy all Integration Flows Concurrently

This approach can significantly reduce implementation time.

Before deploying all integration flows, deploy the *Automated Integration Flow Deployment Configurator* first by providing the configurable parameters. This integration flow saves the parameters as variables, which are then used by other integration flows at runtime.

📘 Note

- The variable expires after a retention period of 400 days.
- The retention period begins once the integration flow containing the variable is successfully processed for the first time.
- The retention period for the variable is extended with each successful processing of the integration flow.

- By default, a timer is set to deploy the integration flow annually, but you can also schedule it according to your convenience.

1. Log in to the SAP Cloud Integration tenant.
2. To configure the integration flows, from the  (menu), select [Design](#).
3. Select the copied integration package SAP Service Cloud Version 2 for Utilities Contract Account Integration with SAP S/4HANA.
All integration flows are displayed on the [Artifacts](#) tab.
4. Select the [Automated Integration Flow Deployment Configurator](#) artifact.
5. From the [Actions](#) menu, select [Configure](#).
6. Enter the fields accordingly:
 - CloudConnectorLocationID
 - S4Client
 - S4Host and Port
7. Select **Deploy**.
This saves the configurable parameters as variables, which will be utilized at runtime once all the integration flows are deployed.
8. Now select rest all other integration flows expect [Automated Integration Flow Deployment Configurator](#).
9. From the [Actions](#) menu, select [Configure](#).
10. Click **Deploy All**.
All integration flows will be deployed simultaneously.

3.3.4 Configure Master Data Replication

Procedure

1. Select the integration flow [Replicate Utilities Premise Connection Object from S4HANA](#) that you want to configure.
2. Select the details for the sender system (S4H), and the receiver systems (SAP Sales Cloud and SAP Service Cloud Version 2 and S4H).
In the [Sender](#) tab, select the [Authorization](#) and the [User Role](#) options.
3. Choose the [Receiver](#) tab and create the following entries:
 - a. Host: SCV2 tenant's URL (without https://)
 - b. Port: 443
4. Choose proxy type as [Internet](#).
5. Choose [Allow Chunking](#).
6. Select [Basic Authentication](#) from dropdown.
7. Provide the credential name which is deployed under security artifacts.
8. Choose [Save](#).

9. Choose [Deploy](#).

Repeat the same procedure for the integration flow Replicate Utilities Contract Account from S/4HANA.

3.4 Configuration in SAP Cloud Connector

SAP Cloud connector allows SAP BTP applications to securely access remote services that run on the Internet or SAP S/4HANA.

Context

If you already have a reverse proxy setup, you can reuse it. Refer to [Outbound/On-Premise: Reverse Proxy or SAP Cloud Connector](#) to determine the best option for your specific situation.

This section describes the configuration in SAP Cloud Connector.

Procedure

1. Log on to the SCC administration UI.
2. Select the relevant sub account.
3. Choose [Cloud to SAP S/4HANA](#) under the sub account menu.
4. Under [Access Control](#) tab select **+** (Add) button in [Mapping Virtual To Internet System](#) section.

Field Name	Entry Value
Back-end Type	ABAP System
Protocol	HTTPS
Internal Host	ldciqvp.devsys.net.sap (example)
Internal Port	44300
Virtual Host	qvp (example)
Virtual Port	443
Principal Type	None
Host in Request Header	Use Virtual Host
Description	(Not mandatory)
Check Internal Host	True

5. After each step select the [Next](#) button and then [Finish](#).
6. Select the newly created entry.
7. On the Resources of qvp:443 (example) section select **+** (Add) button.

Field Name	Entry Value
URL Path	/sap/bc/srt/
Activate	True

8. Save the entry.
9. To check if the configuration was done correctly follow these steps:
 - a. Open SAP BTP Cockpit.
 - b. Navigate to the [Connectivity](#) tab.
 - c. Select [Cloud Connectors](#).
 - d. Check if the new entry is available under [Exposed Back-end System](#) section.

Related Information

<https://help.sap.com/docs/cloud-integration/sap-cloud-integration/connecting-customer-system-to-cloud-integration?version=Cloud>

3.5 Replication of Master Data Initial Load

In the following sections, we describe the replication of contract account, utilities technical master data (Connection object and premise), and business partner.

Procedure

1. Load contract account replication
2. Load technical object replication.
3. Load business partner and business partner replication.

Note

- Start loading data in small chunks, check if they are loaded successfully, and then later increase the size of the data.
- After loading the data, go to ► [SAP Service Cloud Version 2](#) ► [Integration](#) ► [Message Monitoring](#) ► and check the status of the operation.

3.5.1 Setting Up SAP S/4HANA Utilities for Contract Account Replication

Set up SAP S/4HANA Utilities to replicate contract accounts to SAP Service Cloud Version 2.

3.5.1.1 Creating the Outbound Service for Contract Accounts in the SOA Manager Tool

You create the contract account outbound service in the SOA Manager tool for the data exchange from SAP S/4HANA Utilities to SAP Service Cloud Version 2.

Procedure

1. Use transaction **SOAMANAGER** from the S/4HANA system.
2. Under the *Service Administration* tab, choose *Web Service Configuration*.
3. Search for the object name **CO_FKK_MDG_CONTRACT_ACCOUNT_BU**.
4. Choose the internal name of the object.
5. Choose *Create* and then select *Manual Configuration*.
6. Configure the logical port name as follows and then choose *Next*.
 - a. In the *Logical Port Name* field, enter the logical port name of the system to which you're connecting.
 - b. Select the *Logical Port is Default* checkbox.
 - c. Enter a description such as **Utilities Contract Account Replication**.
7. Configure the consumer security with one of the following forms of authentication and then choose *Next*:

- **Basic Authentication**

Enter the user ID and password that you use to connect to your SAP Cloud Integration tenant.

Note

By default, the *User ID / Password* radio button is selected.

- **Certificate-Based Authentication**

1. Select the *X.509 SSL Client Certificate* radio button.
 2. Choose the value help of the *SSL Client PSE of transaction STRUST* field.
 3. Choose the PSE in which the client certificate that was issued by Certification Authority (CA) and supported by SAP Cloud Integration is stored.
8. Configure the HTTP settings as follows and then choose *Next*.
 - a. In the *URL* field, enter the runtime URL from SAP Cloud Integration and append the following string to it: **/cxf/Utilities/contractAccountReplication**.
 - b. Enter a name such as **Proxy** for the proxy host.
 - c. Enter a port number such as **8080** for the proxy host.

9. Configure the SOAP protocol as follows and then choose *Finish*.
 - a. In the *RM Protocol* dropdown menu, select *SAP RM*.
 - b. In the *Message ID Protocol*, select *SAP Message ID*.
 - c. In the *Data transfer scope* dropdown menu, select *Basic Data Transfer*.

3.5.1.2 Configuring the Data Replication Framework for Contract Account Replication

You configure the data replication framework for contract account replication.

Procedure

1. Use transaction **DRFIMG** in the S/4HANA system.
2. Navigate to Customizing for *Define Technical Settings for Business Systems* under **Data Replication** **Define Custom Settings for Data Replication** **Define Technical Settings**.
3. Add a new entry for the business system of SAP Marketing Cloud and then save your changes.
4. Select the business system and then double-click the *Define Bus. Systems, BOs* node in the dialog structure.
5. Configure a new entry as follows and then save your changes.
 - a. In the *BO Type* field, enter **DRF_0036**.
 - b. Select the *System Filter* checkbox.
6. Select the business object type then double-click the *Define Bus. Systems, BOs, Communication Channel* node in the dialog structure.
7. In the *Communication Channel* dropdown menu, select *Replication via Services* and then save your changes.
8. Navigate to Customizing for *Define Replication Models* under **Data Replication** **Define Custom Settings for Data Replication**.
9. Configure a new entry as follows and then save your changes.
 - a. In the *Replication Model* field, enter a name.
 - b. Enter a description.
 - c. In the *Log Days* field, enter a value such as **50**.
10. Select the replication model and then double-click the *Assign Outbound Implementation* node in the dialog structure.
11. Configure a new entry as follows and then save your changes.
 - a. In the *Outbound Implementation* field, enter **DRF_0036_3**.
 - b. In the *Sequence* field, enter **1**.
12. Select the outbound implementation and then double-click the *Assign Target Systems for Repl. Model / Outb. Impl* node in the dialog structure.
13. Add a new entry using the business system that you created in step 3 and then save your changes.

14. Select the business system and then double-click the *Assign Outbound Parameter* node in the dialog structure.
15. Configure a new entry as follows and then save your changes.
 - a. In the *Outbound Parameter* field, enter **PACK_SIZE_BULK**.
 - b. In the *Outbound Parameter Value* field, enter a value such as **20**.
16. Double-click the *Define Replication Model* node in the dialog structure.
17. Select the replication model and then choose *Activate*.

3.5.1.3 Configuring the Delta Replication of Contract Accounts

The delta replication of contract accounts uses a function module to monitor for events that are triggered by the creation of or an update to a contract account and then sends requests for the data to be replicated.

Procedure

1. Use transaction **FQEVENTS** in the S/4HANA system.
2. In the *Event* column, double-click **1031**.
3. Choose the *Function Modules* tab.
4. In the *Installation-Specific Function Modules or Cloud BAdI* section, choose *Change Customizing*.
5. In the *Active Module* field, add a new entry for the **FKK_MDG_OUTBOUND** function module and then save your changes.

3.5.2 (Deprecated) Technical Master Data Replication

Use the Technical Objects Replication Report: ISU_C4C_TECH_OBJECTS_REPL to replicate the technical object to the cloud solution.

Configuration in S/4HANA System

To run the ISU_C4C_TECH_OBJECTS_REPL report in the S/4HANA system, you need to create logical ports with transaction code SOAMANAGER in order to send web service calls to the PI or other middleware system. Follow these configuration steps:

1. Go to transaction code SOAMANAGER in the S/4HANA system.
2. Choose *Service Administration* as *Web Service Configuration*.
3. Search for consumer proxy CO_UTILITIES_TECHNICAL_OBJECT.
4. Choose *Create a Manual* configuration.

5. Enter information based on your middleware configuration. Here is an example value that needs to be adjusted according to your configuration. **Example URL Path:** `https://{{cloudintegrationhost}}/cxf/Utilities/PremiseReplication`.
6. To confirm that the logical port was created and configured correctly, ping the Web service. If the ping is successful, a confirmation message appears.

Report for Initial Load - ISU_C4C_TECH_OBJECTS_REPL

Schedule periodic runs for the initial load report S/4HANA system to transfer the utilities technical master data to the cloud solution. This report offers a single interface to replicate the following objects:

- Premise
- Connection Object

Follow these steps to run the report:

1. In the dialog screen for *Utilities Technical Objects Replication*, select and specify value in one of the fields- *Premise ID* or *Connection Object ID*.
2. Specify the *Logical Port ID*.

Note

Language key is set to *sy-langu* if empty. Also the *From-Date* is set to today's date if empty. And the *To-Date* will be set to 31.12.9999 if empty.

3. Specify a number for the field *Maximum Size*. With the field "MaximumSize", you can control how many technical master data is sent in a single message. The web service can upload several Connection Object IDs, Premises, and PoDs at once. Technical Master Data (Connection Object, Premise, and Point of Delivery) will be distributed accordingly.

Delta Replication- Connection Object

Create or change of a connection object triggers delta replication. Follow these steps to trigger a delta replication for connection object data:

1. In the transaction code SM30, enter the table / view SWFDVEVTY2.
2. Add the entries for the events *CHANGED* and *CREATED* for the object CONNOBJ.

Note

Creating or changing a connection object triggers the delta replication for connection objects.

Delta Replication- Premise

Follow these steps to trigger a delta replication for premise data:

1. In the transaction code **SM30**, enter the table / view **SWFDVEVTY2**.
2. Add the entries for the events **CHANGED** and **CREATED** for the object **PREMISES**.

Note

Creating or changing a connection object triggers the delta replication for premises.

Note

Along with the existing fields the **District** field is enabled for replication under the Premise.

Extensibility for Initial Data Replication Report and for Delta Replication

A Business Add-In (BAI) to modify the standard implementation for the initial data replication report and for the delta replication runs.

- **Enhancement Spot:** COD_UTIL_TECH_OBJS_REPLICATION
- **BAI:** COD_UTIL_TECH_OBJS_REPLICATION
- **Interface:** IF_COD_UTIL_TECH_OBJS_REPL
- **Methods:** CONN_OBJ_ADJUST_DATA, PREMISE_ADJUST_DATA, TMD_ADJUST_DATA, SENDER_ADJUST_DATA, RECEIVER_ADJUST_DATA

3.5.3 Technical Master Data Replication

This data includes connection objects and premises replicated to the SAP Service Cloud Version 2.

The old procedure has been deprecated, so please follow the latest setup instructions for configuration.

3.5.3.1 Integration in SAP Service Cloud Version 2 for Utilities

Integrate the SAP Service Cloud Version 2 for utilities with S/4HANA to replicate the premise master data.

Procedure

1. Go to ► **User Menu** ► **Settings** ► **All Settings** ► **Integration** ► **Communication Configuration** ►.
2. Select **Integrate Service Cloud Utilities Master Data with SAP S/4HANA** module.
3. Delete the **Replicate Utilities Technical Master Data from SAP S/4HANA** configuration (if existing) in the Inbound Configuration section.

4. Search and add [Replicate Premise from SAP S/4HANA](#) configuration.

3.5.3.2 Integration in SAP S/4HANA

Integrate the SAP S/4HANA with SAP Service Cloud Version 2 for utilities to replicate the premise master data.

Procedure

1. Maintain the system level to the minimum required IS-UT 808 SP0 package and implement below OSS note **3484932**.
2. Set up SOA Manager configuration for the service **CO_ISU_C4C_V2_PREM_CONNOBJ_REP**.
3. Implement the BAdI [ISU_C4C_V2_TECH_OBJS_REPL](#) and pass the receiver system data using [RECEIVER_ADJUST_DATA](#).
Optional: The customer can switch to the sender system by using the SENDER_ADJUST_DATA BAdI.
4. The initial load report [ISU_C4C_V2_TECH_OBJECTS_REPL](#) is created in the backend to replicate the premise data.
5. Maintain a workflow configuration for delta replication using event class [CL_ISU_C4C_V2_TECH_OBJ_REP](#).
 - a. Go to SWE2 T.Code
 - b. Maintain the configuration for [CONNOBJ](#) and [PREMISE](#) business objects.
 - c. For Connection Object maintain the change event as:
 - Enter the receiver type as **ISU_C4C_V2_TECHOBJ_REP**.
 - Maintain class name as **CL_ISU_C4C_V2_TECH_OBJ_REP**.
 - Enable the **Linkage Activated** check box.
 - Save the configuration.

Note

For connection object create event is not required.

- d. For Premise business object maintain create and change events as:
 - Enter the receiver type **ISU_C4C_V2_TECHOBJ_REP**.
 - Maintain class name as **CL_ISU_C4C_V2_TECH_OBJ_REP**.
 - Enable the **Linkage Activated** check box.
 - Save the configuration.
6. To extend the replication, implement the BAdI's for extensibility **isu_c4c_v2_tech_objs_repl**.

Note

The BAdIs implemented in V1 cannot be used for the V2 new services. Therefore, a new BAdI must be implemented for V2.

7. In new service, customer can extend the proxy structures **Premise_ConnOBJ** in S/4HANA and re-generate the service using SProxy(T.Code) - **UtilitiesPremiseConnectionObjectReplicateRequest_Out** under the namespace <http://sap.com/xi/C4CS4/IS-UT>.

8. Implement appropriate BAdI `isu_c4c_v2_tech_objs_repl` method to map the custom fields.

Related Information

[SAP S/4HANA Web Service Configuration \(SOA Management\) \[page 10\]](#)

This feature is intended for technical system administrators who configure inter-system connections and manage security settings in the system landscape.

3.5.3.3 Integration in CPI

Integrate the CPI with SAP Service Cloud Version 2 for utilities to replicate the premise data.

Procedure

1. Update the CPI package *SAP Service Cloud V2 for Utilities Master Data Integration with SAP S/4HANA* to latest version.
2. Undeploy the existing **Replicate Utilities Technical Master Data from SAP S4HANA** and **Replicate Utilities Technical Master Data from S4HANA Extensibility** integration flows configured in your system.
3. Configure and deploy the latest integration flow **Replicate Utilities Premise Connection Object from S4HANA**.

For more information about configure and deploy integration flows refer the related link section.

Related Information

[Configure and Deploy Integration Flows \[page 16\]](#)

After copying the integration packages to your workspace, you need to set up and deploy the integration flows.

3.5.4 Load Business Partner and Business Partner Relationships

For business partners you must use data replication framework.

Procedure

1. Run the *DRFOUT* transaction code.
2. In *Replication Model*, select your replication model.
3. In *Outbound Implementation*, select *986_3*.
4. In *Replication Mode*, select *Manual*.
5. Click *Manual replication Filter Criteria*.
6. Select the required business partners and relations.

4 Extensibility

Extensibility allows you and your partners to extend the software platform without having to modify the original codebase. So, you can add to the base functionality, thereby offering new capabilities and outputs.

4.1 Cloud Integration (CI)

The platform integration packages include both synchronous integration flows (transactional data) and asynchronous integration flows (master data).

The types of integration flows are as follows:

- **Asynchronous flow:** Initiating from the S4H system in XML format, the integration flow includes mapping that converts XML data into JSON format before sending it to the SAP Service Cloud Version 2 system.
- **Synchronous flow:** These consist of two types: **Get calls** and **Post calls**. Get calls retrieve transactional data from S4H, while Post calls retrieve data and create, update, or delete data in the S4H system.
 - **Get Integration Flow:** Originating from the SAP Service Cloud Version 2 system via HTTP query, this flow uses two Groovy scripts: one processes HTTP query parameters to structure JSON in message headers, and the other converts JSON data into custom XML format stored in the message body. The XML request is then sent to the S4 system, which responds with XML. Response mapping converts the XML response into JSON format.
 - **Post Integration Flow:** Starting from the SAP Service Cloud Version 2 system in JSON format, this flow undergoes request mapping before sending the XML request to the S4H system. The S4H system responds with XML, and response mapping converts the XML response into JSON format before sending it back to the SAP Service Cloud Version 2 system.

All integration flows use either message mapping, Groovy scripts, or a combination of both to map data formats between systems, converting between XML and JSON as needed.

4.1.1 Custom Extensions

Based on the customers requirements, some enhancements are needed at the mapping level to allow for the transfer of additional information between SAP Service Cloud Version 2 and S4H systems, which are not included in the standard mapping content but are specific to the customers implementation.

📌 Note

One way of handling this is editing the standard integration flows. It is important to note that editing the standard integration flows will result in them no longer receiving updates from SAP. Therefore, it is recommend enabling the extensibility feature which are provided for all the utilities standard integration flows.

Custom Exists

The integration flows are designed with custom exit points, allowing users or customers to enhance SAP delivered content without modifying the standard integration flow. This ensures that users or customers are always notified of future patches and enhancements for those artifacts.

Each integration flow offers parameters that determine the need for a custom extension: Custom Exit for Asynchronous, Request Exit, and Response Exit for Synchronous. If the parameter value is set to **true**, the source payload is saved to a message header property and makes a call to the local integration flow via the process direct adapter. If the parameter value is set to **false**, the default route is taken, and the standard mapping is applied without further extension.

In the local integration flow, customers or users can specify their requirements without modifying any standard integration flows.

Note

Both standard and custom integration flows are deployed on the same tenant and processed together, communicating with each other using the **Process Direct Adapter**.

4.1.1.1 Asynchronous Master Data Replication

Let us consider **Replicate Utilities Premise Connection Object from S/4HANA** as an example to understand the flow in detail.

This integration flow replicates Premise and Connection Object master data from SAP S/4HANA to SAP Service Cloud Version 2.

The messages are sent via SOAP (XML) format from S/4HANA to SAP Cloud Integration, where they are converted to JSON format and delivered to the SAP Service Cloud Version 2 system. The integration flow includes a parameter (Custom Exit) that determines if a custom extension is needed. If the parameter is set to **true**, the source payload is saved to a message header property and an exit flow call is made via the **Process Direct** adapter.

The address of the process direct adapter is externalized and can be configured during the integration flow setup. Customers must ensure that the address of the process direct receiver adapter matches the one used in the process direct sender adapter of the local integration flow.

Note

Due to differing data formats, they cannot be combined into a multi mapping message (which only supports combining messages of a single data format) in the local integration flow. Therefore, a Groovy script is used to enrich the message to meet customer-specific requirements

The sample Groovy code snippet is as below:

Sample Code

```
import com.sap.gateway.ip.core.customdev.util.Message
import groovy.json.JsonOutput
```

```

import groovy.json.JsonSlurper
import groovy.util.XmlSlurper
def Message processData(Message message) {
    def body = message.getBody(java.io.Reader)
    def json = new JsonSlurper().parse(body)
    def xmlString = message.getHeader("sourcePayload", java.io.Reader)
    def xml = new XmlSlurper().parse(xmlString)
    json.messageRequests.eachWithIndex { request, index ->
        // Extracting the first field
        def previousName1 =
xml.PremiseConnObjReplicateRequestMessage[index].PremiseConnectionObject.Premi
seType.text()
        // Extracting the second field
        def previousName2 =
xml.PremiseConnObjReplicateRequestMessage[index].PremiseConnectionObject.Conne
ctionObjectId.text()
        // Extracting the third field
        //def previousName3 =
xml.PremiseConnObjReplicateRequestMessage[index].PremiseConnectionObject.comme
nt2.text()
        // Adding the first field to the extensions array
        request.body.extensions = ["Ext_PremiseType": previousName1]
        // Adding the second field to the extensions array
        request.body.extensions << ["Ext_connectionObjectId": previousName2]
        // Adding the third field to the extensions array
        //request.body.extensions << ["Demo_TECH": previousName2]
    }
    def modifiedJson = JsonOutput.toJson(json)
    message.setBody(modifiedJson)
    return message
}

```

The following codes are executed by the script:

1. **Read the JSON and XML Data:** The script retrieves JSON data from the message body and XML data from the message header.
2. **Extract Information from XML:** It extracts specific information from the XML data.
3. **Add Information to JSON:** The extracted information is then added to each JSON request as additional details.
4. **Update the Message:** The script converts the updated JSON data back to a string format.
5. **Return the Updated Message:** Finally, it sets the updated JSON as the new message body and returns the message.

The modified/enriched JSON is sent to main integration flow which in turn is delivered to target system.

4.1.1.2 Synchronous Replication

Synchronous extensibility allows users to customize integration flows to meet specific business requirements, such as adding new fields or custom logic to the integration process.

To illustrate this, let's examine the **Create Bank Account for Business Partner Integration Flow**, which handles sending requests from SAP Service Cloud Version 2 to SAP S/4HANA, which then responds with a message back to SAP Service Cloud Version 2.

Messages are initially sent in JSON format from SAP Service Cloud Version 2 to SAP Service Cloud Version 2, where they undergo request mapping to convert them into SOAP (XML) format before being delivered back to the SAP S/4HANA system. The SAP S/4HANA system responds in SOAP (XML) format, and response mapping converts the XML data to JSON format and sends it to the SAP Service Cloud Version 2 system.

The integration flow includes parameters i.e Request Exit and Response Exit, which determines if a custom extension is needed or not. If the parameter is set to true, the source payload is saved to a message header property as **CNSRequestPayload**. A Groovy script in the request mapping is executed to convert the JSON format to XML format, and then the Request Exit flow is called via the process direct adapter.

Request Exit

In the **Request Exit** integration flow, a Groovy script takes the data stored in the message header property of the main integration flow, extracts specific fields from the header, adds custom fields, and forms the XML body payload. It then returns the updated message, now containing both standard fields and customer extension fields, which is sent back to the main integration flow.

The sample Groovy code snippet is as below:

Sample Code

```
import com.sap.gateway.ip.core.customdev.util.Message
import groovy.xml.XmlUtil
import groovy.util.XmlSlurper
import groovy.json.JsonSlurper
def Message processData(Message message) {
    // Get header value
    def header = message.getHeaders().get("CNSRequestPayload")
    def jsonSlurper = new JsonSlurper()
    def headerValue = jsonSlurper.parseText(header as String)
    // Extract required fields from header
    def BusinessPartnerId = headerValue.extensions.ZbusinessPartnerId
    //def premiseId = headerValue.extensions.ZpremiseId
    // Get existing body payload
    def bodyPayload = message.getBody(String) ?: ''
    def xml = new XmlSlurper().parseText(bodyPayload)
    // Add extracted fields to the XML body
    xml.appendNode {
        IvBusinessPartner(BusinessPartnerId)
        // IvLanguage(premiseId)
    }
    // Convert updated XML back to string
    def updatedPayload = XmlUtil.serialize(xml)
    // Set updated payload to message body
    message.setBody(updatedPayload)
    return message
}
```

The following codes are executed by the script:

1. **Retrieve Header Data:** The script retrieves the value of a specific header from the message, which contains JSON data.
2. **Extract Information from JSON:** It passes this JSON data to extract specific fields, such as the Business Partner ID.
3. **Read Existing XML Body:** It reads and passes the existing XML data from the message body.
4. **Update XML with New Data:** It adds the extracted information from the JSON into the XML data as new elements.
5. **Update and Return Message:** The script converts the updated XML back to a string format, sets this updated XML as the new message body, and returns the message.

Response Exit

The request XML data is sent to the SAP S/4HANA system via a SOAP adapter, and the system responds with XML containing both standard and custom fields. This data is saved as **S4HResponsePayload** in the main integration flow. The standard response message mapping is then executed, but the output does not include the custom fields. After the response message mapping, a response Exit call is made, which triggers **Response Exit Integration Flow**.

The Response Exit integration flow uses a Groovy script to handle the message by extracting XML data from the header **S4HResponsePayload**, adding specific XML content as an extension to the JSON payload in the message body, and updating the message body with the modified JSON. It then returns the updated message, which now includes both standard and custom fields, to the main integration flow. The main integration flow subsequently sends the response back to SAP Service Cloud Version 2.

The sample Groovy code snippet is as below:

Sample Code

```
import com.sap.gateway.ip.core.customdev.util.Message
import groovy.json.JsonOutput
import groovy.json.JsonSlurper
import groovy.util.XmlSlurper
def Message processData(Message message) {
    def body = message.getBody(java.io.Reader)
    def json = new JsonSlurper().parse(body)
    def xmlString = message.getHeader("S4HResponsePayload", java.io.Reader)
    def xml = new XmlSlurper().parse(xmlString)
    // Extracting the first field
    def previousName1 = xml.EsBankDetail.BankName.text()
    // Assuming json is a single record and not a list
    // Adding the extensions segment to the json
    json.value.extensions = [
        zBankName: previousName1.toString()
    ]
    // Add more fields as necessary
    // Convert the modified JSON object back to a JSON string
    def modifiedJson = JsonOutput.toJson(json)
    message.setBody(modifiedJson)
    return message
}
```

The following codes are executed by the script:

1. **Read the JSON Body:** The script retrieves and reads the JSON data from the message body.
2. **Get XML Data from Header:** It extracts XML data from a specific header in the message.
3. **Extract Data from XML:** The script extracts specific information (e.g., bank name) from the XML.
4. **Update JSON with Extracted Data:** It adds the extracted information as an extension to the JSON data.
5. **Update and Return Message:** The script converts the updated JSON data back to a string format, sets it as the new message body, and returns the message.

5 Appendix

Check Endpoint Name in SAP Cloud Integration (SCI)

1. Connect to the Tenant Management node of the SAP Cloud Integration with <https://<tenant management node>/itspaces>.
2. At the top left, choose the *Monitor / Operations* view icon.
3. Under *Manage Integration Content*, choose *All*.
4. Select the needed *Integration Flow* from the list and copy the URL/path under *Endpoints*.

Ticket Component

In case that you have any issues, please raise an incident via the SAP Support Portal via <https://support.sap.com/en/index.html> 

Component	Comment
CA-GTF-INT-CFC	For issues relevant to documentation
CEC-CRM-UTIL	For other technical issues

Important Disclaimers and Legal Information

Hyperlinks

Some links are classified by an icon and/or a mouseover text. These links provide additional information.

About the icons:

- Links with the icon  : You are entering a Web site that is not hosted by SAP. By using such links, you agree (unless expressly stated otherwise in your agreements with SAP) to this:
 - The content of the linked-to site is not SAP documentation. You may not infer any product claims against SAP based on this information.
 - SAP does not agree or disagree with the content on the linked-to site, nor does SAP warrant the availability and correctness. SAP shall not be liable for any damages caused by the use of such content unless damages have been caused by SAP's gross negligence or willful misconduct.
- Links with the icon  : You are leaving the documentation for that particular SAP product or service and are entering an SAP-hosted Web site. By using such links, you agree that (unless expressly stated otherwise in your agreements with SAP) you may not infer any product claims against SAP based on this information.

Videos Hosted on External Platforms

Some videos may point to third-party video hosting platforms. SAP cannot guarantee the future availability of videos stored on these platforms. Furthermore, any advertisements or other content hosted on these platforms (for example, suggested videos or by navigating to other videos hosted on the same site), are not within the control or responsibility of SAP.

Beta and Other Experimental Features

Experimental features are not part of the officially delivered scope that SAP guarantees for future releases. This means that experimental features may be changed by SAP at any time for any reason without notice. Experimental features are not for productive use. You may not demonstrate, test, examine, evaluate or otherwise use the experimental features in a live operating environment or with data that has not been sufficiently backed up.

The purpose of experimental features is to get feedback early on, allowing customers and partners to influence the future product accordingly. By providing your feedback (e.g. in the SAP Community), you accept that intellectual property rights of the contributions or derivative works shall remain the exclusive property of SAP.

Example Code

Any software coding and/or code snippets are examples. They are not for productive use. The example code is only intended to better explain and visualize the syntax and phrasing rules. SAP does not warrant the correctness and completeness of the example code. SAP shall not be liable for errors or damages caused by the use of example code unless damages have been caused by SAP's gross negligence or willful misconduct.

Bias-Free Language

SAP supports a culture of diversity and inclusion. Whenever possible, we use unbiased language in our documentation to refer to people of all cultures, ethnicities, genders, and abilities.

© 2026 SAP SE or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP SE or an SAP affiliate company. The information contained herein may be changed without prior notice.

Some software products marketed by SAP SE and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP SE or an SAP affiliate company for informational purposes only, without representation or warranty of any kind, and SAP or its affiliated companies shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP or SAP affiliate company products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP SE (or an SAP affiliate company) in Germany and other countries. All other product and service names mentioned are the trademarks of their respective companies.

Please see <https://www.sap.com/about/legal/trademark.html> for additional trademark information and notices.

