

Practical-06

1st code

*)Server

```
GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <fcntl.h>
#include <sys/stat.h>
#include <unistd.h>

#define FIF01 "client_to_server"
#define FIF02 "server_to_client"

int main()
{
    char message[100];
    int fd1, fd2;

    mkfifo(FIF01, 0666);
    mkfifo(FIF02, 0666);

    printf("Server waiting for client...\n");

    fd1 = open(FIF01, O_RDONLY);

    read(fd1, message, sizeof(message));
    printf("Client: %s\n", message);

    close(fd1);

    fd2 = open(FIF02, O_WRONLY);

    strcpy(message, "Hello Client, message received!");

    write(fd2, message, strlen(message) + 1);

    close(fd2);

    unlink(FIF01);
    unlink(FIF02);

    return 0;
}
```

Output

```
a_sri_chaitanya@Chaitanya:~/2520090094_OSSP/2520090094_Practical$ gcc Server.c -o Server
a_sri_chaitanya@Chaitanya:~/2520090094_OSSP/2520090094_Practical$ ./Server
Server waiting for client...
Client: Hello Server!
```

2nd Code

*)Client

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <fcntl.h>
#include <sys/stat.h>
#include <unistd.h>

#define FIF01 "client_to_server"
#define FIF02 "server_to_client"

int main()
{
    char message[100];
    int fd1, fd2;

    fd1 = open(FIF01, O_WRONLY);

    strcpy(message, "Hello Server!");
    write(fd1, message, strlen(message) + 1);
    close(fd1);

    fd2 = open(FIF02, O_RDONLY);
    read(fd2, message, sizeof(message));
    printf("Server: %s\n", message);
    close(fd2);

    return 0;
}
```

Output

```
a_sri_chaitanya@Chaitanya:~/2520090094_OSSP/2520090094_Practical$ gcc client.c -o client
a_sri_chaitanya@Chaitanya:~/2520090094_OSSP/2520090094_Practical$ ./client
Server: Hello Client, message received!
a_sri_chaitanya@Chaitanya:~/2520090094_OSSP/2520090094_Practical$
```