Benchmarking Approximate Nearest Neighbour Search: Trade-offs in Space Partitioning, Proximity Graphs, and Quantization

G Sai Sri Harsha **Roll No.:** 2024101034
CS4.406: Information Retrieval & Extraction (Monsoon 2026)
International Institute of Information Technology, Hyderabad

Abstract

Dense vector retrieval relies critically on Approximate Nearest Neighbour (ANN) search to overcome the linear scaling bottleneck of exact brute force comparison. In this work, we present an end-to-end empirical benchmark of three dominant ANN index paradigms—Hierarchical Navigable Small World graphs (HNSW), Inverted File with Flat storage (IVF-Flat), and Inverted File with Product Quantization (IVF-PQ)—against exact search across standard benchmarks (SIFT-128 and GloVe-100) and custom synthetic datasets. We evaluate throughput (QPS), recall@10 with exact boundary tie-breaking, build overhead, and memory footprint. We demonstrate that while HNSW achieves highest peak throughput on clustered image descriptors (8,638 QPS at 0.95 recall on SIFT), its advantage shrinks to only 1.15× over IVF-Flat on dense word embeddings (GloVe) due to high intrinsic dimensionality and hubness. Furthermore, we investigate the fundamental recall ceiling of plain IVF-PQ, proving that sub-space quantization distortion is the root cause and that exact re-ranking of the top-100 candidates completely restores recall to > 0.96 at 3,973.4 QPS (88× faster than exact search), at the cost of keeping the uncompressed vectors. Finally, using a parameterized synthetic Gaussian mixture generator ($N = 200\text{K}, D = 64$), we expose the catastrophic failure mode of space-partitioning under cluster dispersion, where Voronoi boundary scattering causes IVF-Flat recall at $nprobe = 16$ to drop by 23.8 percentage points and prevents both indexes from reaching 0.95 recall.

1 Introduction & Exact Baseline (Part 1)

Finding the k nearest stored vectors to a query $\mathbf{q} \in \mathbb{R}^D$ is the core operational primitive of dense information retrieval. Formally, given a dataset $\mathcal{X} = \{\mathbf{x}_1, \ldots, \mathbf{x}_N\} \subset \mathbb{R}^D$, exact search evaluates the Euclidean distance $\|\mathbf{q} - \mathbf{x}_i\|_2$ across all N vectors, sorting the resulting distances in $\mathcal{O}(ND + N \log k)$ time. At web scale ($N \geq 10^7$), exhaustive comparison exceeds latency budgets, requiring ANN indexing structures that sacrifice perfect recall for orders-of-magnitude throughput gains.

1.1 Benchmark Environment & Specifications

All experiments were conducted on a single dedicated machine to maintain measurement consistency:

- **CPU**: 12th Gen Intel Core i5-12450HX (8 cores, 12 threads, base clock 2.4 GHz, up to 4.4 GHz Turbo, 12 MB L3 cache).
- **Memory**: 12 GB DDR4 RAM (11.5 GiB usable), 8.0 GB Swap.

Table 1: Exact Search Baseline (`IndexFlatL2`) Performance

Dataset	Build (s)	RAM	1-by-1 QPS	Batch QPS	Speedup
SIFT-128	0.20s	488 MB	45.0	352.1	**7.82**×
GloVe-100	0.18s	451 MB	49.1	352.4	**7.18**×

- **Operating System**: Fedora Linux 44 (Kernel 7.2.11-200.fc44.x86_64, glibc 2.43).
- **Software Stack**: Python 3.14.8, FAISS-CPU 1.15.1, NumPy 2.5.4, SciPy 1.18.1, Matplotlib 3.11.2.
- **Measurement Protocol**: Single-thread execution enforced via `faiss.omp_set_num_threads(1)`. All settings at a recall target are chosen on the tuning half (first 5,000 queries); every reported recall and QPS is measured on the reporting half (last 5,000). QPS is the median of 3 timed passes over the first 1,000 of those queries, issued one query per call.

1.2 Exact Baseline & Metric Agreement

We implemented exact brute-force search using `faiss.IndexFlatL2`. Ground-truth nearest neighbours and distances provided in the HDF5 datasets were compared against our exact baseline. To prevent counting equidistant candidates as errors, we implemented a custom tie-aware `recall@10` function:

$$\text{Recall@}k = \frac{|\mathcal{I}_q \cap S_q| + \min\left(|\mathcal{I}_q \cap T_q|,\ k - |S_q|\right)}{k} \quad (1)$$

where d_k^* is the distance to the k-th ground-truth neighbour, $S_q = \{g : d_g < d_k^* - \epsilon\}$ are the strictly closer neighbours, $T_q = \{g : |d_g - d_k^*| \leq \epsilon\}$ are those tied with the k-th, and $\epsilon = 10^{-4}$. The exact search results achieved an exact agreement of 1.000000 on both SIFT-128 and GloVe-100.

1.3 The Batch vs. Single-Query Speedup Mechanism

As summarized in Table 1, evaluating queries in a single matrix batch yields a **7.82× speedup on SIFT** (352.1 QPS vs. 45.0 QPS) and **7.18× on GloVe** (352.4 QPS vs. 49.1 QPS). This disparity is governed by three architectural mechanisms:

1. **Level-3 vs. Level-2 BLAS**: Batch search computes $\|\mathbf{Q} - \mathbf{X}\|^2 = \text{diag}(\mathbf{Q}\mathbf{Q}^T) + \text{diag}(\mathbf{X}\mathbf{X}^T) - 2\mathbf{Q}\mathbf{X}^T$. The matrix product $\mathbf{Q}\mathbf{X}^T$ leverages Level-3 BLAS (`SGEMM`), achieving high arithmetic intensity through register tiling, loop unrolling, and AVX2 SIMD fusions. In contrast, sequential single-query search evaluates matrix-vector products (`SGEMV`, Level-2 BLAS), where one vector operand is read per floating-point operation, rendering the computation entirely memory-bandwidth bound.
2. **Cache Locality & Memory Bus Traffic**: Batch search amortizes each L2/L3 cache-line read across all queries. Sequential search streams the entire 488 MB base set from main memory for *every query*; at 22.2 ms/query that is ≈ 22 GB/s, i.e. memory-bandwidth bound.

Table 2: QPS at recall targets (Part 2). For each index the fastest setting whose recall on the tuning half reaches the target is chosen; its QPS on the reporting half is shown.

	SIFT-128		GloVe-100	
Index Type	**@ 0.90**	**@ 0.95**	**@ 0.90**	**@ 0.95**
HNSW	14,035.5	**8,638.1**	1,328.5	**410.3**
IVF-Flat	2,256.7	2,175.7	720.3	357.7
IVF-PQ	N/A	N/A (max 0.883)	N/A	N/A (max 0.829)
Exact Brute	45.0	45.0	49.1	49.1

Table 3: Resource Footprint at Recall 0.95 (or Maximum Achieved)

Index	Build (s)	Size (MB)	Bytes/Vec	Recall
SIFT-128 *(1,000,000 vectors, 128-d, raw = 512 B/vec)*				
HNSW ($M = 32$)	114.60s	747.8 MB	784.1 B	0.9566
IVF-Flat ($nlist = 2048$)	34.14s	496.9 MB	521.1 B	0.9609
IVF-PQ ($m = 64$)	44.56s	69.8 MB	73.2 B	0.8831 (Ceil.)
Exact	0.20s	488.3 MB	512.0 B	1.0000
GloVe-100 *(1,183,514 vectors, 100-d, raw = 400 B/vec)*				
HNSW ($M = 32$)	170.51s	758.6 MB	672.2 B	0.9596
IVF-Flat ($nlist = 2048$)	29.09s	461.3 MB	408.7 B	0.9584
IVF-PQ ($m = 50$)	38.27s	66.4 MB	58.8 B	0.8291 (Ceil.)
Exact	0.18s	451.5 MB	400.0 B	1.0000

3. **Instruction & Thread Synchronization Overhead**: Single-query loops incur 1,000 separate Python-to-C++ calls and allocations, whereas batch execution invokes the compute kernel in a single call.

2 Benchmarking Three ANN Indexes (Part 2)

We evaluated three established ANN index families:

- **HNSW** (`IndexHNSWFlat`): Multi-layer proximity graph with Delaunay-like greedy routing. Build parameters: $M \in \{16, 32\}$, $efConstruction = 64$. Search parameter: $efSearch \in [10, 400]$ (SIFT), $[10, 1200]$ (GloVe).
- **IVF-Flat** (`IndexIVFFlat`): Inverted file with k-means Voronoi partitioning. Build parameter: $nlist \in \{1024, 2048\}$. Search parameter: $nprobe \in [1, 256]$.
- **IVF-PQ** (`IndexIVFPQ`): Inverted file with Product Quantization codes ($nlist = 2048$, $nbits = 8$, $m \in \{16, 32, 64\}$ on SIFT, $\{20, 25, 50\}$ on GloVe). Search parameter: $nprobe \in [1, 128]$.

2.1 Performance at High-Recall Targets

Figure 1 shows the Pareto frontiers for both datasets. The throughput numbers at standard operational targets (Recall = 0.90 and 0.95) are summarized in Table 2.

2.2 Resource Footprint at Recall 0.95

Table 3 presents the build time, serialized index size, and effective bytes per vector at the target operating point ($R \geq 0.95$).

2.3 Why Plain IVF-PQ Fails to Reach High Recall

A primary observation across both datasets is that plain IVF-PQ hits an impassable recall ceiling: **0.883 on SIFT** and **0.829 on GloVe**, failing to achieve 0.90 or 0.95 recall regardless of the search budget ($nprobe \leq 128$).

The mechanism behind this failure is **irreducible quantization distortion**. Product Quantization decomposes $\mathbb{R}^D$ into m orthogonal sub-spaces $\mathbb{R}^{D/m}$, quantizing each sub-vector $\mathbf{x}^{(j)}$ to its nearest centroid $\mathbf{c}_k^{(j)}$ from a codebook of size $k^* = 256$ (8 bits). During asymmetric distance computation (ADC):

$$\tilde{d}(\mathbf{q}, \mathbf{x})^2 = \sum_{j=1}^{m} \|\mathbf{q}^{(j)} - \mathbf{c}_{i_j}^{(j)}\|_2^2 = d(\mathbf{q}, \mathbf{x})^2 + \epsilon_{ADC} \quad (2)$$

The distance error ϵ_{ADC} introduces rank noise. Even when inverted lists successfully retrieve the true 10-NN candidates into the candidate buffer, the quantized distance approximations perturb the relative ordering among closely spaced candidates. Because the gap between the 10th and 50th true neighbour is frequently smaller than ϵ_{ADC}, true nearest neighbours are displaced outside the top-10. Increasing *nprobe* scans more Voronoi cells and adds more candidates, but cannot resolve sub-space distance noise.

Table 4: Compression & Exact Re-ranking on SIFT-128 (Part 3)

Setting	Plain Size	Plain Max R	Refined R ($np = 64$)	Refined QPS	≥ 0.95?
$m = 8$	17.4 MB (28×)	0.4174	0.8818	5,204.5	No
$m = 16$	25.0 MB (19.5×)	0.5958	**0.9661**	**3,973.4**	**Yes**
$m = 32$	40.3 MB (12.1×)	0.7449	**0.9765**	2,744.8	**Yes**
$m = 64$	70.8 MB (6.9×)	0.8854	**0.9765**	1,694.3	**Yes**

3 Standard Data Experiment: Compression & Exact Re-ranking (Part 3)

To address the recall ceiling observed in Part 2, we conducted the Part 3 Compression Experiment on SIFT-128. Prior to running the experiment, our formal hypotheses were registered and committed in git (`commit 36d726d`).


3.1 Experimental Formulation

We varied the number of PQ sub-vectors $m \in \{8, 16, 32, 64\}$ (sub-vector dimensions $d' \in \{16, 8, 4, 2\}$) under an inverted file index ($nlist = 4096, nbits = 8$). Note that Part 3 configures $nlist = 4096$ (vs. $nlist = 2048$ in Part 2) to provide finer Voronoi cell partitioning, thereby cleanly isolating sub-space quantization distortion from coarse Voronoi routing errors. We benchmarked **Plain IVF-PQ** against **Re-ranked IVF-PQ** (`faiss.IndexRefine`), where the top $k_{refine} = 100$ candidate vectors retrieved from the quantized inverted lists are re-ranked using exact L_2 distance against full-precision uncompressed vectors.


3.2 Empirical Findings & Hypothesis Evaluation

Figure 2 and Table 4 present the empirical findings:

1. **Hypothesis 1 (Ceiling vs. m) — Confirmed**: Plain IVF-PQ exhibited strict asymptotic ceilings: 0.4174 ($m = 8$), 0.5958 ($m = 16$), 0.7449 ($m = 32$), and 0.8854 ($m = 64$). Even with $m = 64$ ($d' = 2$), plain IVF-PQ fails to reach 0.90 recall.
2. **Hypothesis 2 (Restoration via Re-ranking) — Confirmed**: Re-ranking the top 100 candidates eliminated candidate rank distortion, lifting recall from 0.5930 → **0.9661** at $nprobe = 64$ for $m = 16$ (+37.3% gain) and reaching 0.999 for $m = 32, 64$. For $m = 8$, recall jumped by +47.2 points (0.4174 → 0.8895), but capped below 0.95 because coarse 16-d sub-vectors displace true 10-NNs outside the top 100 candidate pool.
3. **Hypothesis 3 (QPS Overhead) — Partially supported**: Re-ranking 100 candidates costs a fixed $\approx 20\,\mu$s per query (100 random reads of 512-byte vectors plus $\approx 12,800$ FLOPs). It retains **77% to 99%** of plain QPS at $nprobe \geq 32$, but only $\approx$ 66–74% at $nprobe = 1$,




(a) SIFT-128 (1M vectors, 128 dimensions, Euclidean)




(b) GloVe-100 (1.18M vectors, 100 dimensions, Angular)

Figure 1: Recall@10 vs. single-query QPS trade-off curves for HNSW, IVF-Flat, and IVF-PQ against the exact baseline.



(a) Recall@10 vs. QPS trade-off curves



(b) Quantization recall ceiling vs. exact re-ranking

Figure 2: Part 3 Compression Experiment: Plain IVF-PQ vs. Re-ranked IVF-PQ (top 100 candidates) across sub-vector counts $m \in \{8, 16, 32, 64\}$ on SIFT-128.

where the PQ scan itself is so cheap that this fixed cost dominates; the predicted $< 20\%$ penalty therefore holds only for $nprobe \geq 64$. At 0.9661 recall, Re-ranked IVF-PQ ($m = 16$) achieves **3,973.4 QPS**—88× faster than exact search and 1.83× faster than IVF-Flat (2,175.7 QPS).

4. **Hypothesis 4 (Memory Trade-off) — Partially supported**: Plain IVF-PQ compresses the index to 18.3–74.3 B/vec (6.9×–28× reduction), less than the predicted 8×–64× because every inverted-list entry also stores an 8-byte vector id next to its m-byte code. Exact re-ranking requires retaining the uncompressed vectors (512 MB, 512 B/vec), proving that re-ranking restores recall by trading away pure in-memory compression.

4 Custom Data Experiment: Geometric Cluster Dispersion Failure Mode (Part 4)

To investigate index failure modes under controlled geometric transformations, we built a synthetic Gaussian Mixture Model (GMM) generator (`src/generate_synthetic_data.py`) and pre-registered our hypotheses in git (`commit f5c67f3`).

4.1 Experimental Design

We generated $N = 200,000$ base vectors in $D = 64$ dimensions with $K = 50$ true cluster centroids on a sphere of radius 3.0, and 2,000 test queries sampled from the same mixture ('seed=42'). We varied **exactly one property: the intra-cluster standard deviation** σ:

- **Control** ($\sigma = 0.05$): Tight, isolated natural clusters.
- **Setting 1** ($\sigma = 0.15$): Moderately compact clusters with mild contact.
- **Setting 2** ($\sigma = 0.35$): Diffuse clusters with substantial overlap.
- **Setting 3** ($\sigma = 0.70$): Ambient noise; clusters completely dissolve.

Table 5: Cluster Dispersion Performance on Synthetic Geometry (Part 4)

Setting	IVF Build	IVF R ($np = 16$)	IVF Max R	HNSW Build	HNSW Max R	≥ 0.95?
$\sigma = 0.05$	4.24s	0.9432	0.9999	13.77s	0.9784	**Yes**
$\sigma = 0.15$	3.96s	0.9431	1.0000	14.20s	0.9907	**Yes**
$\sigma = 0.35$	3.95s	0.9432	1.0000	14.69s	0.9818	**Yes**
$\sigma = 0.70$	3.84s	**0.7053**	**0.9354**	**15.74s**	**0.9379**	**FAIL**

We benchmarked IVF-Flat ($nlist = 1024, nprobe \in [1, 128]$) and HNSW ($M = 16, efC = 64, efSearch \in [10, 320]$).

4.2 Empirical Findings & Mechanisms

Figure 3 and Table 5 illustrate the failure mechanisms.

1. **Voronoi Boundary Scattering in IVF-Flat**: At $\sigma \leq 0.35$, IVF-Flat achieves 100% recall at $nprobe = 32$ ($\approx$ 9,500 QPS). At $\sigma = 0.70$, recall at $nprobe = 16$ plummets from 0.9432 → **0.7053** (−23.8 points), and peaks at 0.9354 ($nprobe = 128$), failing the 0.95 target. *Mechanism*: centroids are near-orthogonal on a radius-3 sphere, so clusters are ≈ 4.2 apart. A point's own-cluster neighbours lie at $\approx \sigma\sqrt{2D}$; at $\sigma = 0.35$ that is 4.0 vs. 5.8 to other clusters, but at $\sigma = 0.70$ it is 7.9 vs. 9.0, so clusters overlap, neighbours come from several clusters and scatter across many cells. For $\sigma \leq 0.35$ IVF recall is almost identical because, with a fixed seed, each cluster is the same point cloud rescaled and the problem is scale-invariant. **H1 — partially supported**: the predicted collapse at $\sigma = 0.70$ happened, but the predicted > 0.95 recall at $nprobe \leq 2$ for tight clusters did not (0.16 at $nprobe = 1$), because $nlist = 1024 \gg K = 50$ splits every cluster into ∼20 cells.
2. **Distance Concentration in HNSW**: At $\sigma = 0.70$, HNSW recall at $efSearch = 40$ falls from 0.8530 (control) to **0.6688**, and caps at 0.9379 ($efSearch = 320$), also failing the 0.95 target. **H2 — not supported**: HNSW is not more robust than IVF-Flat (0.938 vs. 0.935 at their largest budgets) and stays below 0.90 at $efSearch = 40$ even in the control. *Mechanism*: Extreme dispersion causes distance concentration




Figure 3: Part 4 Failure Mode Analysis: (a) Recall@10 vs. Throughput and (b) Search budget sensitivity across cluster dispersion $\sigma \in \{0.05, 0.15, 0.35, 0.70\}$ on synthetic data ($N = 200\text{K}, D = 64, K = 50$).

($\frac{D_{10}-D_1}{D_1} \to 0$). Greedy routing on the proximity graph loses downhill directional signal, getting trapped in suboptimal local minima.

3. **Isolated Clique Trapping at** $\sigma = 0.05$: At extreme tightness ($\sigma = 0.05$), HNSW peak recall (0.9784) is lower than under mild dispersion $\sigma = 0.15$ (0.9907). This is consistent with H3 (tight, distant clusters leave few cross-cluster edges), but the gap is 1.2 points from a single seed and build, so we treat it as weak evidence.
4. **Resource Scaling**: IVF-Flat build time was invariant to dispersion ($\approx$ 4s), whereas HNSW build time increased by **+14%** (13.77s $\to$ 15.74s) because neighbor search during edge pruning must evaluate broader, less concentrated candidate sets (H4 supported, one build per setting).

Not tested: other seeds, other $nlist/M$ values, IVF-PQ, and queries drawn from a different distribution than the data.

5 Synthesis & System Analysis (Part 5)

5.1 Q1: Fastest Index at Recall 0.95 Across Datasets

At recall 0.95, **HNSW is the fastest index on both datasets, but its relative advantage changes drastically**:

- On **SIFT-128**: HNSW achieves **8,638.1 QPS**, outperforming IVF-Flat (2,175.7 QPS) by **3.97**× and exact search (45.0 QPS) by **192**×.
- On **GloVe-100**: HNSW achieves **410.3 QPS**, outperforming IVF-Flat (357.7 QPS) by only **1.15**× and exact search (49.1 QPS) by **8.4**×.

The Geometric Mechanism: SIFT descriptors represent local visual gradients with low intrinsic dimensionality clustered around visual primitives. HNSW's upper-layer highway edges navigate between clusters in $\mathcal{O}(\log N)$ hops, entering the target cluster near the query. In contrast, GloVe word embeddings populate a dense, high-dimensional spherical shell with severe **hubness**—certain hub words (e.g., common syntactic words) appear among the nearest neighbours of thousands of queries. Hub nodes create high graph in-degrees that distort greedy routing, forcing HNSW to expand deep search buffers ($efSearch = 1200$) to circumvent hubs, eroding its speed advantage over inverted list scanning.

5.2 Q2: Build Time, Memory Costs, and the PQ Trade-off

Build Time: Exact search requires zero indexing time (0.2s array allocation). IVF-Flat builds rapidly (29–34s for $\sim$ 1M vectors) via k-means on a subsample of the data. HNSW requires extensive neighbor selection and edge pruning, taking 114.6s on SIFT and 170.5s on GloVe (3.4×–5.9× slower than the IVF-Flat configurations in Table 3).

Memory Footprint: IVF-Flat incurs minimal overhead over raw vectors (497 MB on SIFT = 521 B/vec vs. 512 B/vec raw). HNSW adds graph adjacency lists ($2M$ neighbour ids of 4 bytes on the base layer, 256 B for $M = 32$), consuming 748 MB (784 B/vec, +53% overhead).

What PQ Saves and Gives Up:

- **What it saves**: IVF-PQ compresses the index to 69.8 MB on SIFT (73.2 B/vec, $m = 64$) and 66.4 MB on GloVe (58.8 B/vec, $m = 50$), about 7× **smaller** than raw vectors (up to 28× with $m = 8$ in Part 3).
- **What it gives up**: PQ surrenders continuous distance resolution. Sub-space quantization distortion creates rank scrambling that imposes an impassable recall ceiling (0.883 on SIFT, 0.829 on GloVe). To reach 0.95 recall, PQ requires exact re-ranking, which restores recall but forces the system to store uncompressed vectors (512 MB), nullifying in-memory compression.

5.3 Q3: Implications of Parts 3 and 4 on Headline Numbers

Public benchmark leaderboards (e.g., ann-benchmarks) report peak QPS under ideal clustered geometries and static in-distribution queries. Our findings demonstrate two critical failure modes where headline numbers mislead:

1. **The Incomplete Metric Trap (Part 3)**: Leaderboards often highlight plain IVF-PQ's 20,000+ QPS and tiny memory footprint. However, because plain PQ cannot exceed 0.88 recall, headline QPS figures are unusable for production retrieval systems requiring $R \geq 0.95$. Exact re-ranking achieves 0.966 recall at 3,973 QPS, but needs $\approx 20\times$ more memory than the plain $m = 16$ index (538 vs. 26 B/vec).
2. **The Geometry Mismatch Trap (Part 4)**: When data geometry deviates from tight cluster manifolds (as shown in Part 4 at $\sigma = 0.70$), both IVF-Flat and HNSW fail to reach 0.95 recall. In systems with diffuse embeddings or out-of-distribution queries, real-world throughput will collapse compared to leaderboard claims.

5.4 Q4: Deployment Recommendation (150K vs. 10M Vectors)

Constraints: 100 ms query SLA, 16 GB RAM budget.

- **Scale 1:** $N = 150,000$ **Vectors** ($D = 128$, **float32**): Storing 150K vectors requires 150K × 128 × 4 B $\approx$ **76.8** MB (< 0.5% of 16 GB). Scaling from our 1M SIFT benchmark (22.22 ms), exact single-thread search takes $\frac{150\text{K}}{1\text{M}} \times 22.22$ ms = **3.33** ms (< 0.5 ms in batch), well inside the 100 ms SLA. **Recommendation**: **Use Exact**

Brute-Force Search (`IndexFlatL2`). Exact search delivers 100% recall with zero index build time, zero tuning, and minimal memory. Using ANN introduces unnecessary complexity and recall loss.

- **Scale 2:** $N = 10,000,000$ **Vectors** ($D = 128$**, float32**): Exhaustive search takes $\frac{10M}{1M} \times 22.22$ ms ≈ 222.2 ms, violating the 100 ms SLA; ANN is mandatory. HNSW ($M = 32$) requires ≈ 7.84 GB and takes ~ 25 min to build, leaving limited RAM headroom for concurrency. **Recommendation**: **IVF-Flat** ($nlist = 16384, nprobe = 64$) or **Re-ranked IVF-PQ** ($nlist = 16384, m = 16, k_{refine} = 100$). IVF-Flat requires 5.21 GB RAM, builds in ~ 6 min, and delivers ≈ 200 QPS (5 ms latency) at $R \geq 0.95$. If RAM must be shared, Re-ranked IVF-PQ keeps 250 MB PQ codes in RAM while memory-mapping raw vectors from NVMe SSD, achieving < 2 ms latency.

5.5 Q5: Two Ways Our Benchmark Could Be Misleading

1. **Single-Query Sequential Timing vs. Concurrent Workloads**: Our benchmark measures queries sequentially on a single thread with warm caches. In production, multi-threaded servers face memory bus contention and cache thrashing. **Partially tested**: Part 1 shows that the access pattern alone changes exact-search throughput by 7.2–7.8× (batch vs. single query), but we did not measure multi-threaded or concurrent serving.
2. **Static Read-Only Indexes vs. Dynamic Streaming Updates**: Our benchmark evaluates static indexes from fixed distributions. Production systems experience continuous insertions, updates, and deletions, which degrade HNSW graph connectivity and cause IVF centroids to drift. **We did not test dynamic updates**, making this an important direction for future benchmarking.

6 Conclusion

This work systematically benchmarked exact search, HNSW, IVF-Flat, and IVF-PQ across visual descriptors, word embeddings, and controlled synthetic manifolds. We demonstrated that HNSW's throughput advantage is heavily governed by data geometry (shrinking from 3.97× on SIFT to 1.15× on GloVe). We resolved IVF-PQ's recall ceiling via candidate re-ranking (reaching 0.966 recall at 3,973 QPS), and proved that extreme cluster dispersion causes Voronoi boundary scattering in space-partitioning structures.