



MAX-SEAL UPGRADE!

Max-Seal's Performance Series of resilient seated BFV, over ten years of great performance in high pressure applications - trouble-free performance.

Current Rated Pressure Size

2"-12" 200/wog	2"-12" 225/wog
14"-20" 175/wog	14"-24" 200/wog

New Pressure Rated

All size valves have been tested up to 275 & 250 PSIG.

Body Style

Lug design model 52.

Body Material

Ductile iron-rugged heavy duty casting.

Valve Stem

High strength 17-4ph ss

Seat

Field replaceable phenolic-bonded cartridge, field replaceable.

Dead-end Services

Lug type body, standard design.

Ideal design incorporates a unique machined "step" into the valve body. This step will positively retain the valve seat and prevent seat blow-out.

Vacuum Service

Provided up to 28 inches of Hg.

Actuator Mounting

ISO-5211

Top flange. All valve stems are ISO square design

O-RINGS are molded in the seat on the top and bottom

SEAT

HIGH FLOW DISC DESIGN

PIN

2 PC STEM DESIGN

VALVE BODY

1 BUSHING

O-RING

PIN

SEAT MATERIAL OFFERING

- EPDM
- Viton
- Buna
- Teflon

Food Grade Options

NOT JUST
ANOTHER
BOOT SEATED
VALVE!

MAXSEALINC.COM • SALES@MAXSEALINC.COM • 910.738.2866