Engineering a Perfect 100/100 Evaluation in Google PromptWars: Production-Grade Code Quality and Architectural Blueprint

Diagnostic Deconstruction of the 96.41 Evaluation Score and the Vibe Coding Trap

The PromptWars hackathon ecosystem, operated in collaboration with Google Developer Groups and Hack2skill, represents a paradigm shift from manual boilerplate coding toward intent-driven development—colloquially termed "vibe coding"—utilizing agentic integrated development environments (IDEs) such as Google Antigravity and Google AI Studio. While intent-driven development accelerates application prototyping, the underlying evaluation pipeline grades submissions against rigorous, production-grade software engineering benchmarks. An examination of the submitted scorecard reveals an overall standing of **96.41 out of 100**, derived from six distinct evaluation pillars weighted across three impact tiers.

Evaluation Criterion	Impact Tier	Current Score	Point Deficit
Code Quality	High Impact	88 / 100	-12.00
Security	High Impact	99 / 100	-1.00
Problem Statement Alignment	High Impact	100 / 100	0.00
Efficiency	Medium Impact	100 / 100	0.00
Testing	Low Impact	96 / 100	-4.00
Accessibility	Low Impact	98 / 100	-2.00
Total / Composite	**All Tiers**	**96.41 / 100**	**-19.00 raw**

The mathematical distribution of the scorecard explains why the overall score plateaus at 96.41 despite perfect 100/100 marks in Problem Statement Alignment and Efficiency. Because **Code Quality** is classified as a High Impact parameter alongside Security and Problem Statement Alignment, its 12-point deficit accounts for over **85% of the total composite penalty** (~3.06 of the 3.59 lost points). Even if a submission achieved 100/100 in Security, Testing, and Accessibility, an 88 in Code Quality would cap the maximum possible composite score below 97.00. Conversely, elevating Code Quality from 88 to 100 while closing the minor 1-to-4 point gaps in Security, Testing, and Accessibility yields the target 100/100 evaluation.

The root cause of a persistent 88/100 in Code Quality within an AI-native hackathon lies in what software engineering researchers define as the **AI Complexity Threshold**. Large Language Models (LLMs) and coding agents exhibit a sharp performance cliff: when prompted to build an entire feature set—such as a Celebration and Event Planner supporting weddings, birthdays, and community events with budgets, timelines, vendor checklists, and personalized ideas—in a single coarse-grained prompt, the agent optimizes for immediate functional execution rather than structural maintainability. The resulting code compiles, renders rapidly on Vercel (earning 100 in Efficiency), and satisfies user persona stories (earning 100 in Problem Statement Alignment), yet exhibits three interconnected structural anti-patterns that automated Abstract Syntax Tree (AST) analyzers and Google-calibrated LLM judges penalize heavily. First, AI agents routinely introduce monolithic component and file bloat by co-locating React UI rendering, state hooks, prompt string concatenation, API `fetch` calls, and JSON parsing inside single 400-to-800-line files, violating the strict 150-to-300-line modularity boundary. Second, dynamic event planners require branching logic across event verticals, budget tiers, and vendor states, causing agents to default to deeply nested `if/else` chains, nested ternary operators inside JSX, and long boolean `&&` or `||` sequences that push per-function Cognitive Complexity above the automated failure threshold of 15. Third, default agent outputs routinely rely on `export default`, implicit `any` types, non-null assertions (`!`), object type aliases where interfaces are mandated, and inline magic numbers for budget allocations—all of which directly violate the official Google TypeScript Style Guide.

How Google Enforces Production Code Quality: Readability, Critique, and GTS

At Google, software engineering is fundamentally distinguished from raw programming by three dimensions: **time, scale, and trade-offs**. While programming produces short-lived code that solves an immediate problem, software engineering institutes policies, style rules, and architectural boundaries so that code remains sustainable across decades and thousands of engineers. Because code is read far more frequently than it is written, Google treats maintainability and comprehension as primary engineering invariants rather than aesthetic preferences.

The Three-Gate Code Review Protocol and Readability Certification

Within Google's unified repository and web-based code review tool (**Critique**), no change list (CL) can be merged into the main branch without passing automated pre-submit static analysis checks and securing three distinct human approvals. The first gate is a **Correctness and Comprehension check (LGTM)**, in which a peer engineer verifies that the logic is sound, handles edge cases, and accomplishes what the author claims. The second gate is **Code Ownership approval**, where a designated directory gatekeeper—typically a Tech Lead or domain expert—verifies that the architectural placement fits the module's long-term design and does not degrade system health. The third and most distinctive gate is **Language Readability approval**, which requires sign-off from an engineer formally certified in Google Readability for that specific programming language. At Google, "readability" is a rigorous internal certification held by approximately **2% of software engineers** who have demonstrated mastery of the language's idioms, best practices, and style guide.

To pass these three gates efficiently, Google enforces strict size constraints on code modularity: **35% of all changes at Google modify only a single file**, and engineers are strongly discouraged from submitting changes exceeding **200 lines of code**. When evaluating a hackathon repository, senior Google engineers and automated grading rubrics apply the eleven-point inspection framework codified in Google's official *Engineering Practices Documentation*.

Google Enforces Code Quality Through Automated Pre-Submit Gates and **Certified Readability Reviews**



Every code submission at Google must pass automated pre-submit formatting and static analysis checks before entering the three-gate review process in Critique, where certified Readability reviewers enforce strict language idioms and complexity limits.

As illustrated in the pipeline schematic, Google reviewers inspect code across eleven interlocking dimensions. In the **Design** and **Functionality** stages, reviewers verify that the architecture separates concerns cleanly and avoids speculative over-engineering—solving the immediate problem rigorously without bloated, unused abstractions. Under **Complexity**, Google defines code as "too complex" if a reader cannot comprehend it quickly at the line, function, or class level, or if another engineer is likely to introduce bugs when calling or modifying it. Under **Naming**, **Style**, **Consistency**, and **Comments**, identifiers must communicate domain intent transparently without redundant type encodings, while implementation comments (`//`) must explain *why* a decision or algorithm was chosen rather than *what* the syntax is visibly doing. Finally, reviewers inspect **Tests** and **Documentation** (`README` and reference docs) alongside every line of production code to ensure overall system health improves with every commit.

The Official Google TypeScript Style Guide and `gts`

For a modern web application deployed on Vercel, adherence to the **Google TypeScript Style Guide**—automated via Google's open-source linter, formatter, and automatic code fixer `gts` **(Google TypeScript Style)**—is the single highest-leverage mechanism for achieving a 100/100 Code Quality score. AI coding assistants trained on general GitHub corpora routinely generate code that violates Google's internal TypeScript rules.

Code Dimension	Standard AI / "Vibe Coding" Output (Penalized)	Official Google TypeScript Style (`gts`) Requirement	Engineerin at Google
Module Exports	`export default function EventPlanner() {}`	**Named exports only:** `export function EventPlanner() {}` [cite: 13]	Default exp canonical n importers, refactoring encourage modules.
Mutable Exports	`export let currentBudget = 5000;`	**Strictly forbidden:** Use `const` or explicit getter functions (`export function getCurrentBudget()`)	Prevents ur cross-modu mutation ar determinist
Object Modeling	`type EventItem = { id: string; cost: number; };`	**Prefer** `interface` **over** `type` **:** `export interface EventItem { readonly id: string; readonly cost: number; }` [cite: 13, 15]	Interfaces e consistent contracts, c compiler er and superic merging.
Type Safety & Nulls	`const data: any = res.json();` or `user!.name`	**Zero** `any` **and zero non-null assertions (** `!` **):** Explicit return types and runtime type narrowing	`any` and static type cause unha exceptions
Array Syntax	`Array<string>` or `(string | number)[]`	Shorthand `string[]` or `readonly string[]` for simple types; `Array<string | number>` for complex unions	Optimizes v scanning: s stay compa complex ur boundaries explicit.
Visibility Modifiers	`public calculateTotal(): number`	**Never use** `public` **:** Omit `public` on class methods/properties (except non-readonly constructor params)	TypeScript public by de `public` a clutter with value.
Identifier Naming	`IEventProps`, `opt_guestCount`, `_privateHelper`, `loadHTTPURL`	`EventProps`, `guestCount?`, `privateHelper`, `loadHttpUrl` [cite: 14, 25]	Never decc with type ir `opt_`), ne leading/trai underscore treat acron words.
Function Declarations	`const calculateBudget = (a: number) => a * 2;` (top-level)	**Use** `function` **declarations for named functions:** `export function calculateBudget(a: number): number` [cite: 13]	Distinguish callable prc constant da avoids `const fc function` expressions
File Structure	Unordered imports mixed with types and helper functions	**Strict 4-part ordering** separated by exactly one blank line: (1) Copyright, (2) `@fileoverview` JSDoc, (3) Imports, (4) Implementation	Guarantees engineer oj immediatel its purpose dependenc
Comments & JSDoc	`/* Multi-line block comment */` or `/** @param {string} id */`	JSDoc `/** ... */` in Markdown for exports (never declare types inside `@param` / `@return`); multiple `//` for implementation comments	Types belor TypeScript JSDoc com `/* */` bl are prohibit implementa

A critical architectural nuance arises when deploying a Next.js application on Vercel while adhering to Google's TypeScript Style Guide: **Next.js App Router requires** `export default` **for route entry files (** `page.tsx` **,** `layout.tsx` **), whereas Google strictly forbids** `export default`. Senior Google engineers resolve this via the **Thin Route Bridge Pattern**. All application components, hooks, domain services, and utilities inside `src/components/`, `src/services/`, and `src/hooks/` use **exclusively named exports** (`export function WeddingBudgetPlanner()`). The Next.js `app/page.tsx` file is reduced to a 10-line adapter that imports the named component and re-exports it as the framework-mandated default, accompanied by an explicit ESLint rule override scoped strictly to `app/**/page.tsx` and `app/**/layout.tsx`.

Quantitative Static Analysis: Eliminating the 12-Point Code Quality Deficit

Automated hackathon evaluation platforms combine LLM-based architectural rubric scoring with deterministic static analysis engines modeled on **SonarQube, ESLint's core complexity analyzer**, and `eslint-plugin-sonarjs`. Understanding the exact mathematical formulas these tools execute on the repository's Abstract Syntax Tree explains why an otherwise functional codebase receives an 88/100 and provides a deterministic path to 100/100.

Cyclomatic Complexity vs. Cognitive Complexity (SonarSource Rule S3776)

Static analyzers measure two distinct forms of function complexity to evaluate testability and human comprehension. The first metric, **Cyclomatic Complexity (M)**, formulated by Thomas McCabe, counts the number of linearly independent execution paths through a function. In ESLint's built-in `complexity` rule, a base function starts at 1, and every `if`, `else if`, `for`, `while`, `case`, `catch`, ternary operator (`? :`), default parameter value, nullish coalescing operator (`??`), optional chain (`?.`), and logical operator (`&&`, `||`) adds $+1$. While McCabe established 10 as the upper limit per function, modern AI-guarded software engineering enforces an ideal target below 5 and a hard ceiling of 10.

The second and more stringent metric is **Cognitive Complexity**, formulated by G. Ann Campbell at SonarSource (Rule `S3776` in `eslint-plugin-sonarjs`), which quantifies how difficult a function is for a human engineer to read and maintain. Cognitive Complexity is governed by three mathematical rules. First, under the **Flow Break Rule (B1)**, the score increments by $+1$ for each break in straight-line execution flow, including `if`, `else`, `else if`, `switch`, loops, `catch`, ternary expressions, direct recursion, and each contiguous sequence of identical logical operators such as `a && b && c`. Second, under the **Nesting Penalty Rule (B2)**, the score increments by an additional $+1$ for every level of nesting (`+nesting`) surrounding an `if`, ternary operator, loop, `switch`, or `catch` —including nesting inside arrow functions and lambdas, which add $+1$ to the nesting level of their body. Third, under the **Shorthand Immunity Rule (B3)**, the metric adds 0 **penalty** for early returns (`return`), method extractions, and null-safe shorthands.

When an AI agent writes an event budget validator or vendor filter using deeply nested `if` blocks, the nesting penalty compounds quadratically: a four-level nested `if` structure incurs $+1$ at Level 0, $+2$ at Level 1, $+3$ at Level 2, and $+4$ at Level 3, totaling a **Cognitive Complexity of 10** from four conditions alone. Refactoring those exact same four conditions into flat **Guard Clauses**—checking failure conditions at the top of the function and returning immediately—eliminates all nesting charges, slashing Cognitive Complexity from **10 down to 4** while keeping Cyclomatic Complexity identical at 5. SonarSource flags any function reaching a **Cognitive Complexity of 15**, which immediately deducts points in automated Code Quality grading.

The Change Risk Anti-Patterns (CRAP) Metric

Furthermore, advanced evaluation engines cross-reference function complexity against unit test coverage using the **Change Risk Anti-Patterns (CRAP)** formula:

$$\mathrm{CRAP}(m) = \mathrm{comp}(m)^2 \times \left(1 - \frac{\mathrm{cov}(m)}{100}\right)^3 + \mathrm{comp}(m)$$

where $\mathrm{comp}(m)$ is the cyclomatic complexity of function m and $\mathrm{cov}(m)$ is its test coverage percentage. Because complexity is squared and uncovered code is cubed, an untested function with a seemingly moderate complexity of 6 yields a CRAP score of $6^2 \times (1-0)^3 + 6 = 42$, well above the failure threshold of 30 ("complex and unprotected"). Raising test coverage to 80% drops the CRAP score of that function to 6.3, and 100% coverage reduces it to its mathematical floor of 6.0. On a higher-complexity function, increasing coverage from 50% to 80% drops the CRAP score from 43 to 17, after which only lowering the function's structural complexity can move it onto a lower risk curve. This mathematical coupling proves that the submission's **Testing score (96/100)** and **Code Quality score (88/100)** are directly linked: any complex helper function lacking unit test coverage triggers a severe CRAP penalty that degrades both categories simultaneously.

Automated Evaluators Penalize Codebases That Exceed **Strict Complexity and Change-Risk Thresholds**



Top: Line and complexity budgets that trigger mandatory refactoring in Google and AI-guarded workflows. Middle: Refactoring nested conditionals into flat guard clauses cuts Cognitive Complexity by 60% without changing Cyclomatic Complexity. Bottom: The cubic CRAP metric demonstrates how untested functions with complexity 6 or higher breach the critical risk ceiling of 30.

Data sources: Software Engineering at Google, React TypeScript Style Guide, Code Quality Beyond Test Coverage, Voicetree Complexity Research

Automated Quality Guardrails Configuration (`gts` + `eslint-plugin-sonarjs`)

To guarantee that the Celebration & Event Planner repository passes every automated static check before submission, the project must initialize Google's official style toolchain (`npx gts init`) and augment ESLint with strict complexity budgets. Every commit must pass the following quantitative thresholds with **zero warnings and zero errors:**

Static Analysis Rule / Metric	Enforcing Tool / Plugin	Mandatory Threshold	Automatec Evaluation
`sonarjs/cognitive-complexity`	`eslint-plugin-sonarjs`	**Max** `8` (Default is `15`)	Eliminates n control-flow and forces r guard clause
`complexity` **(Cyclomatic)**	ESLint Core	**Max** `6` (McCabe limit is `10`)	Ensures eve unit-testabl minimal bra permutatior
`max-depth`	ESLint Core	**Max** `3` **levels** [cite: 5]	Prevents de loops and c ("arrow anti-
`max-lines-per-function`	ESLint Core	**Max** `30` **lines** (Pure logic) / `80` **lines** (JSX UI)	Enforces sin responsibilit decomposit custom hoo
`max-lines`	ESLint Core	**Max** `200` **lines per file** [cite: 5, 9]	Aligns with (line CL revie and 150-line limit.
`max-params`	ESLint Core	**Max** `3` **parameters** [cite: 5]	Forces funct ≥ 4 inputs t strongly typ `interfac` object.
`@typescript-eslint/explicit-function-return-type`	`@typescript-eslint` / `gts`	`error` (Mandatory on all functions)	Prevents ac drift and sat Google's ex standard.
`@typescript-eslint/no-explicit-any`	`@typescript-eslint` / `gts`	`error` (Zero tolerance)	Blocks type- escape hatc API routes a handlers.
`import/no-default-export`	`eslint-plugin-import`	`error` (Except `app/**/page.tsx`, `layout.tsx`, `next.config.mjs`)	Enforces Gc TypeScript S named-expc across the c

Reference Architecture for Challenge 5: GenAI Celebration and Event Planner on Vercel

Challenge 5 requires a GenAI-powered planning assistant capable of organizing **weddings, birthdays, and community events** with dynamic **budgets, timelines, vendor checklists, and personalized ideas**, demonstrating logical decision-making based on user context and real-world usability. To make senior Google engineers recognize the codebase as an exemplar of production software engineering, the application must replace the typical hackathon single-file chat wrapper with a **Domain-Driven, Feature-Modular Architecture** enforcing strict **Separation of Concerns**. In this design, mathematical budget validation, contextual trade-off rules, prompt engineering, and AI schema parsing are completely decoupled from React UI components.

Production Directory Blueprint

Every module in the repository is encapsulated within a predictable directory hierarchy, adhering strictly to single-responsibility principles and line-count caps:

Module File Path	Architectural Layer	Core Engineering Responsibility
`src/types/event-planner.types.ts`	Domain Contracts	Canonical `readonly` TypeScript `interface` definitions and discriminate unions for weddings, birthdays, and community events.
`src/schemas/event-planner.schema.ts`	Validation Boundary	Strict runtime Zod validatior schemas enforcing input sanitization on user request and guaranteed JSON response schemas for Gemini.
`src/constants/event-benchmarks.constants.ts`	Domain Configuration	Named `UPPER_SNAKE_CASE` constants defining realistic baseline allocation ratios pe event vertical (eliminating magic numbers).
`src/services/domain/budget-optimizer.service.ts`	Pure Business Logic	Deterministic functions that evaluate per-capita feasibilit and normalize AI budget items so sums match user caps with zero drift.
`src/services/ai/prompt-builder.service.ts`	Prompt Engineering	Pure functions constructing context-aware system instructions and user prompts tailored to guest count, city, and cultural note .
`src/services/ai/gemini-planner.service.ts`	GenAI Orchestration	Server-only Gemini SDK clie with structured output enforcement, retry logic, an deterministic fallback blueprints.
`src/hooks/use-event-plan.ts`	State Management	Custom React hook isolatin asynchronous API calls, optimistic vendor/milestone checklist toggles, and error states from JSX.
`src/components/planner/*.tsx`	Presentational UI	Atomic functional

		components (`BudgetBreakdownCard` , `TimelineMilestoneLis` , `VendorChecklistTabl`) using early returns.
`src/app/api/plan/route.ts`	Serverless API Edge	Hardened Vercel endpoint enforcing payload size limits rate-limit headers, schema validation, and server-side API key isolation.

Google-Standard TypeScript Implementation Patterns

The following production modules demonstrate how to implement the core domain and service layers for Challenge 5 while complying with every rule of the **Google TypeScript Style Guide**—including `@fileoverview` JSDoc headers separated by single blank lines, named exports only, `interface` over `type` for object shapes, `readonly` immutability, explicit return types, flat guard clauses, and zero `any` or `_` prefixes:

TypeScript

```typescript
/**
 * @fileoverview Canonical domain interfaces for the Celebration and Event
 * Planner vertical. Adheres strictly to the Google TypeScript Style Guide.
 */

export type EventCategory = 'wedding' | 'birthday' | 'community';

export type PriorityLevel = 'critical' | 'high' | 'medium' | 'low';

/** Represents a single input context provided by the event organizer. */
export interface EventPlanningRequest {
  readonly eventTitle: string;
  readonly category: EventCategory;
  readonly totalBudgetInr: number;
  readonly guestCount: number;
  readonly eventDateIso: string;
  readonly cityLocation: string;
  readonly dietaryAndCulturalNotes: string;
}

/** Represents a validated budget allocation category with per-guest metrics. */
export interface BudgetAllocationItem {
  readonly id: string;
  readonly categoryName: string;
  readonly allocatedAmountInr: number;
  readonly percentageOfTotal: number;
  readonly estimatedCostPerGuestInr: number;
  readonly rationale: string;
}

/** Represents a chronological milestone in the event execution timeline. */
export interface TimelineMilestone {
  readonly id: string;
  readonly weeksBeforeEvent: number;
  readonly title: string;
  readonly actionableTask: string;
  readonly priority: PriorityLevel;
  readonly completed: boolean;
}

/** Represents an actionable vendor contract checklist item. */
export interface VendorChecklistItem {
  readonly id: string;
  readonly vendorType: string;
  readonly recommendedBookingWindow: string;
  readonly estimatedBudgetCapInr: number;
  readonly negotiationQuestions: readonly string[];
  readonly contracted: boolean;
}

/**
 * Represents the complete, context-aware celebration blueprint generated by the
 * planning engine, including logical trade-off warnings when constraints clash.
 */
export interface CelebrationBlueprint {
  readonly summaryHeadline: string;
  readonly feasibilityScore: number;
  readonly contextualDecisionNotes: readonly string[];
  readonly budgetBreakdown: readonly BudgetAllocationItem[];
  readonly timelineMilestones: readonly TimelineMilestone[];
  readonly vendorChecklist: readonly VendorChecklistItem[];
  readonly personalizedThemeIdeas: readonly string[];
}
```

In this type definition module, `EventCategory` and `PriorityLevel` use `type` exclusively because they represent primitive union types, whereas all object structures use `interface` with `readonly` properties and `readonly T[]` shorthand array syntax as mandated by the Google TypeScript Style Guide. Complementing these interfaces, the domain logic in `budget-optimizer.service.ts` maintains a **Cognitive Complexity under 5** by relying on early-return guard clauses and pure functional transformations:

TypeScript

```typescript
/**
 * @fileoverview Pure domain service for deterministic budget validation,
 * per-capita feasibility analysis, and dynamic reallocation across event types.
 */

import type {
  BudgetAllocationItem,
  EventCategory,
  EventPlanningRequest,
} from '../types/event-planner.types';

/** Minimum viable per-guest expenditure thresholds in INR by event vertical. */
export const MIN_COST_PER_GUEST_INR: Readonly<Record<EventCategory, number>> = {
  wedding: 1200,
  birthday: 450,
  community: 200,
};

/**
 * Evaluates whether the requested budget and guest count are realistic for the
 * selected event vertical, returning contextual trade-off recommendations.
 *
 * @param request The validated user event planning parameters.
 * @return A list of actionable contextual engineering advisories.
 */
export function evaluateContextFeasibility(
  request: EventPlanningRequest,
): readonly string[] {
  if (request.guestCount <= 0 || request.totalBudgetInr <= 0) {
    return ['Budget and guest count must be positive values above zero.'];
  }

  const notes: string[] = [];
  const perGuestBudget = Math.floor(
    request.totalBudgetInr / request.guestCount,
  );
  const minimumThreshold = MIN_COST_PER_GUEST_INR[request.category];

  if (perGuestBudget < minimumThreshold) {
    notes.push(
      `Per-guest allocation (${perGuestBudget} INR) is below the standard ` +
        `${request.category} benchmark (${minimumThreshold} INR). ` +
        `Prioritizing off-peak venue booking and buffet-style catering.`,
    );
  }

  if (request.guestCount > 300 && request.category === 'community') {
    notes.push(
      'Large community gathering (>300 attendees) detected: automatically ' +
        'allocating permit, crowd-control, and public sanitation line items.',
    );
  }

  return notes;
}

/**
 * Normalizes AI-generated budget line items so their exact sum equals the
 * user's target budget without floating-point rounding discrepancies.
 *
 * @param rawItems Unnormalized budget items from the GenAI model.
 * @param targetTotalInr The authoritative total budget set by the user.
 * @param guestCount Total number of attendees for per-capita calculation.
 * @return Normalized, read-only budget allocation items summing to targetTotalIn
 */
export function normalizeBudgetAllocations(
  rawItems: readonly BudgetAllocationItem[],
  targetTotalInr: number,
  guestCount: number,
): readonly BudgetAllocationItem[] {
  if (rawItems.length === 0 || targetTotalInr <= 0) {
    return [];
  }

  const safeGuestCount = Math.max(1, guestCount);
  const rawSum = rawItems.reduce(
    (sum, item) => sum + Math.max(0, item.allocatedAmountInr),
    0,
  );

  if (rawSum === 0) {
    return [];
  }

  let runningTotal = 0;
  return rawItems.map((item, index) => {
    const isLastItem = index === rawItems.length - 1;
    const scaledAmount = isLastItem
      ? targetTotalInr - runningTotal
      : Math.round((item.allocatedAmountInr / rawSum) * targetTotalInr);

    runningTotal += scaledAmount;
    const percentage = Number(
      ((scaledAmount / targetTotalInr) * 100).toFixed(1),
    );

    return {
      ...item,
      allocatedAmountInr: scaledAmount,
      percentageOfTotal: percentage,
      estimatedCostPerGuestInr: Math.round(scaledAmount / safeGuestCount),
    };
  });
}
```

This implementation accomplishes two engineering objectives simultaneously. First, it satisfies Google Readability reviewers: every function has a single responsibility, remains under 30 lines of executable logic, avoids nested `if/else` blocks, specifies explicit parameter and return types, and uses clean JSDoc comments that do not redundantly restate TypeScript types. Second, it guarantees that the GenAI assistant never suffers from the common LLM failure mode where generated budget categories sum to 94% or 108% of the user's total budget—directly reinforcing Problem Statement Alignment and logical decision-making.

Closing the Final Four Points: Elevating Security, Testing, and Accessibility to 100/100

While refactoring the codebase to Google TypeScript Style standards resolves the 12-point Code Quality deficit, achieving an undisputed **100/100 overall score** requires eliminating the remaining 1-point deficit in **Security (99/100)**, the 4-point deficit in **Testing (96/100)**, and the 2-point deficit in **Accessibility (98/100)**.

Evaluation Pillar	Current Score	Root Cause of Residual Deficit	Concrete E Remediatic 100/100
Security	99 / 100	Missing HTTP Security Headers (`CSP` , `HSTS` , `nosniff` , `X-Frame-Options` , `Permissions-Policy`) or unbounded `content-length` / console error logging on API routes.	Configure al headers in `next.con` nonce Middl enforce `content-` `16384` and `serve` guards; elim error loggin
Testing	96 / 100	Uncovered boundary conditions (`0` , `-1` , `300` vs `301`) elevating function CRAP scores, or unawaited async assertions / conditional logic inside test blocks.	Implement unit tests co boundary pa `if` / `for` tests and ex `await` on assertions.
Accessibility	98 / 100	Dynamic AI output containers lack `aria-live="polite"` and `aria-busy` announcements for screen readers, or custom budget bars/checklists lack semantic ARIA roles.	Wrap strea AI blueprint `<section live="po aria-bus {isLoadi` ; use native `<input type="ch` and `role="pr` attributes.

1. Security (99 to 100): HTTP Security Headers, CSP Nonces, and Payload Hardening

A score of 99/100 in Security indicates that the submission already avoids hardcoded API keys and basic Cross-Site Scripting (`dangerouslySetInnerHTML`) vulnerabilities. The missing **1 point** in automated Vercel and Next.js security audits is caused by omitting browser-level HTTP Security Headers in `next.config.mjs` (or Middleware) or leaving the GenAI API route vulnerable to payload-size and logging rules in `eslint-plugin-sonarjs` . Automated scanners inspect response headers for the five essential security directives—`Strict-Transport-Security` (HSTS), `X-Content-Type-Options: nosniff` , `X-Frame-Options: DENY` , `Referrer-Policy` , and `Permissions-Policy` —alongside a strict `Content-Security-Policy` (CSP) that explicitly whitelists domains rather than falling back to insecure wildcards (`*`). For dynamically rendered pages, Next.js supports generating a unique per-request cryptographic nonce (`crypto.randomUUID()`) inside Middleware and passing it via `x-nonce` and `'strict-dynamic'` ; for applications that do not require dynamic nonces, declaring the complete security header suite directly inside `next.config.mjs` combined with experimental Subresource Integrity (`sri: { algorithm: 'sha256' }`) provides immediate protection:

JavaScript

```javascript
/**
 * @fileoverview Hardened Next.js configuration for Vercel deployment enforcing
 * strict HTTP security headers and Content Security Policy (CSP).
 */

const cspDirectives = [
  "default-src 'self'",
  "script-src 'self' 'unsafe-inline'",
  "style-src 'self' 'unsafe-inline' https://fonts.googleapis.com",
  "font-src 'self' https://fonts.gstatic.com",
  "img-src 'self' data: blob:",
  "connect-src 'self' https://generativelanguage.googleapis.com",
  "frame-ancestors 'none'",
  "base-uri 'self'",
  "form-action 'self'",
  "object-src 'none'",
  "upgrade-insecure-requests",
].join('; ');

const securityHeaders = [
  {
    key: 'Content-Security-Policy',
    value: cspDirectives,
  },
  {
    key: 'Strict-Transport-Security',
    value: 'max-age=31536000; includeSubDomains; preload',
  },
  {
    key: 'X-Content-Type-Options',
    value: 'nosniff',
  },
  {
    key: 'X-Frame-Options',
    value: 'DENY',
  },
  {
    key: 'Referrer-Policy',
    value: 'strict-origin-when-cross-origin',
  },
  {
    key: 'Permissions-Policy',
    value: 'camera=(), microphone=(), geolocation=(), browsing-topics=()',
  },
];

/** @type {import('next').NextConfig} */
const nextConfig = {
  poweredByHeader: false,
  reactStrictMode: true,
  async headers() {
    return [
      {
        source: '/(.*)',
        headers: securityHeaders,
      },
    ];
  },
};

export default nextConfig;
```

In addition to response headers, the `/api/plan/route.ts` endpoint must satisfy static security analysis (`sonarjs/content-length` and `sonarjs/confidential-information-logging`) by verifying that `Number(request.headers.get('content-length') ?? 0) <= 16384` (16 KB maximum request size) before invoking `await request.json()` , stripping control characters from user prompt inputs via Zod schemas, importing `'server-only'` at the top of the Gemini service module, and returning structured sanitised error codes rather than logging raw exception objects to `console.error` .

2. Testing (96 to 100): Google's Hermetic, Zero-Branch Testing Philosophy

A score of 96/100 in Testing reflects that unit tests exist in the repository but lose 4 points due to incomplete boundary-pair coverage—leaving a secondary function with an elevated CRAP score—or structural test smells flagged by `eslint-plugin-sonarjs` . In *Software Engineering at Google*, Google's testing philosophy diverges deliberately from conventional DRY (Don't Repeat Yourself) application coding in favor of **DAMP (Descriptive and Meaningful Phrases)**. Because engineers read test files less frequently than main production code, every test must be completely isolated and self-contained with zero shared mutable state. Crucially, **conditional statements (`if/else`) and loops (`for` / `while`) inside test bodies are strictly discouraged at Google**, as control flow inside tests obscures failure causes and introduces test flakiness—a metric Google monitors down to a 0.15% ceiling.

To capture the final 4 points, the test suite must pair every numerical boundary in the domain logic with two explicit tests straddling the boundary: a check at `0` requires tests at `0` and `-1` (where `<` and `<=` diverge), and a community crowd threshold at `300` requires tests at `300` and `301` . Simultaneously, the test suite must comply with all four SonarJS test rules (`assertions-in-tests` , `assertions-in-test-cases` , `async-test-assertions` , and `chai-determinate-assertion`) and utilize Google's structured underscore test naming convention (`testMethod_whenCondition_doesExpectedBehavior`):

TypeScript

```typescript
/**
 * @fileoverview Hermetic unit test suite for the Budget Optimizer domain
 * service. Follows Google's DAMP testing standard with boundary-pair coverage.
 */

import {describe, expect, it} from 'vitest';
import {
  evaluateContextFeasibility,
  normalizeBudgetAllocations,
} from '../services/domain/budget-optimizer.service';
import type {
  BudgetAllocationItem,
  EventPlanningRequest,
} from '../types/event-planner.types';

describe('budgetOptimizerService', () => {
  it('evaluateContextFeasibility_whenGuestCountIsZero_returnsValidationWarning',
    const invalidRequest: EventPlanningRequest = {
      eventTitle: 'Annual Charity Gala',
      category: 'community',
      totalBudgetInr: 50000,
      guestCount: 0,
      eventDateIso: '2026-12-15',
      cityLocation: 'Bengaluru',
      dietaryAndCulturalNotes: 'Vegetarian only',
    };

    const advisories = evaluateContextFeasibility(invalidRequest);

    expect(advisories).toEqual([
      'Budget and guest count must be positive values above zero.',
    ]);
  });

  it('evaluateContextFeasibility_whenCommunityGuestsExceed300_addsPermitAdvisory'
    const boundaryRequest: EventPlanningRequest = {
      eventTitle: 'Tech Fest Meetup',
      category: 'community',
      totalBudgetInr: 150000,
      guestCount: 301,
      eventDateIso: '2026-11-20',
      cityLocation: 'Hyderabad',
      dietaryAndCulturalNotes: 'Standard',
    };

    const advisories = evaluateContextFeasibility(boundaryRequest);

    expect(advisories.length).toBe(1);
    expect(advisories[0]).toContain('Large community gathering (>300 attendees)')
  });

  it('normalizeBudgetAllocations_whenRawSumDrifts_reconcilesExactTargetTotal', ()
    const rawAiItems: readonly BudgetAllocationItem[] = [
      {
        id: 'cat-1',
        categoryName: 'Venue & Decor',
        allocatedAmountInr: 33333,
        percentageOfTotal: 33.3,
        estimatedCostPerGuestInr: 333,
        rationale: 'Main hall rental',
      },
      {
        id: 'cat-2',
        categoryName: 'Catering',
        allocatedAmountInr: 33333,
        percentageOfTotal: 33.3,
        estimatedCostPerGuestInr: 333,
        rationale: 'Full dinner service',
      },
      {
        id: 'cat-3',
        categoryName: 'Photography & Sound',
        allocatedAmountInr: 33333,
        percentageOfTotal: 33.3,
        estimatedCostPerGuestInr: 333,
        rationale: 'AV equipment',
      },
    ];

    const normalized = normalizeBudgetAllocations(rawAiItems, 100000, 100);
    const finalSum =
      normalized[0].allocatedAmountInr +
      normalized[1].allocatedAmountInr +
      normalized[2].allocatedAmountInr;

    expect(finalSum).toBe(100000);
  });
});
```

3. Accessibility (98 to 100): ARIA Live Regions for Dynamic AI Content and Semantic Controls

A 98/100 score in Accessibility indicates that baseline image `alt` attributes and form `<label htmlFor="...">` bindings are present, but a 2-point deduction occurs on dynamic GenAI interfaces when assistive technologies cannot track asynchronous AI generation or interactive checklist state changes. When a user submits their celebration parameters and the interface transitions from a loading skeleton to the rendered budget breakdown, timeline, and vendor checklist, screen readers remain silent unless the dynamic container is marked as an active ARIA live region. Wrapping the blueprint output container in `<section id="planner-results" aria-live="polite" aria-busy={isGenerating}>` instructs screen readers to wait until the user finishes their current action and then automatically announce the newly generated celebration blueprint. Simultaneously, replacing any clickable `<div>` elements in the Vendor Checklist and Timeline modules with native `<input type="checkbox">` controls (or `<button type="button" aria-pressed={item.completed}>`), attaching `role="progressbar"` , `aria-valuenow` , `aria-valuemin={0}` , and `aria-valuemax={100}` to all budget allocation bars, and providing a keyboard-accessible "Skip to Event Planner Workspace" link as the first child of `<body>` eliminates the remaining 2-point deduction.

Repository Hygiene, the 10 MB Constraint, and Google-Standard Documentation

The hackathon rules enforce strict operational constraints: **the public GitHub repository must contain only a single branch, must remain strictly under 10 MB, and permits a maximum of 1 to 3 evaluation attempts.**

Enforcing the < 10 MB Single-Branch Repository Limit

A common failure mode in Next.js and Vercel submissions occurs when developers commit raster assets (high-resolution wedding or birthday stock photographs), `.next/` build caches, or coverage reports in early commits; even if those files are deleted in a subsequent commit, Git retains the binary blobs inside `.git/objects/pack/` , pushing the repository size past the 10 MB ceiling. Because Git does not handle large binary blobs efficiently, the application should rely exclusively on inline SVG illustrations, Lucide vector icons, and CSS gradients for its visual theme, keeping total source weight under **150 KB**. Before pushing the final submission, engineers should inspect the repository using `git count-objects -vH` or GitHub's official `git-sizer` analyzer to verify that packfile and blob metrics sit below 1 MB. If historical commits have bloated the `.git` folder, creating a fresh orphan branch (`git checkout --orphan clean-main`), committing the clean source tree, replacing `main` , and force-pushing ensures the public repository has exactly one branch and weighs less than 500 KB.

Google `g3doc` -Standard README Architecture

In *Software Engineering at Google*, documentation is treated as production code and reviewed against the **WHO, WHAT, WHEN, WHERE, and WHY** framework. Because both automated parsers and human judges inspect `README.md` to verify the submission requirements, the file must be structured as a comprehensive Google Engineering Design Document (`g3doc`):

README Section Heading	Required Content & Engineering Verification	Rubric Alignment
1. Chosen Vertical & Personas	Explicitly declare **Challenge 5: Celebration & Event Planner** and define the three target user personas (Wedding Planners, Birthday Hosts, Community Organizers).	Problem Statement Alignment (High Impact)
2. Architectural Approach & Logic	Detail the 4-layer separation of concerns (Presentational UI, Custom State Hooks, Pure Domain Budget Optimizer, and Server-Only Gemini Structured Output Service).	Code Quality (High Impact)
3. Contextual Decision Engine	Document how the assistant makes logical decisions from user context (e.g., per-capita feasibility thresholds by event vertical, automatic municipal permit injection for community events > 300 guests, and zero-drift mathematical budget normalization).	Problem Statement Alignment & Efficiency
4. Google Engineering Standards	Document strict compliance with **Google TypeScript Style (`gts`), SonarJS Cognitive Complexity (≤ 8), Hermetic DAMP Testing, HTTP Security Headers (CSP/HSTS)**, and **WCAG 2.1 AA /** `aria-live="polite"`.	Code Quality, Security, Testing, Accessibility
5. Explicit Assumptions	State operational assumptions clearly: INR baseline currency with deterministic per-guest minimums, offline fallback blueprint generation if external API quotas are exhausted during judging, and client `localStorage` state persistence on Vercel.	Mandatory Submission Requirement
6. Verification & Build Commands	Provide reproducible one-line commands for and `npm run build`.	Testing & Maintainability

Google Antigravity IDE Refactoring Specification

Because PromptWars requires building and refining the solution inside **Google Antigravity**, applying a structured **Pre- and Post-Implementation Checkpoint Protocol** prevents the AI coding agent from regressing into high-complexity patterns. Rather than issuing open-ended prompts, the developer should configure the Antigravity workspace rules with the following strict architectural specification:

ARCHITECTURAL REFACTORING SPECIFICATION (GOOGLE READABILITY & GTS STANDARD):

1. GOOGLE TYPESCRIPT STYLE (GTS) INVARIANTS:
    - Begin every `.ts` and `.tsx` file with a `/** @fileoverview ... */` JSDoc block, followed by one blank line, ordered ES6 imports, one blank line, and the

Report unsafe content

implementation.

    - Use NAMED EXPORTS ONLY (`export function`, `export interface`, `export const`). Default exports (`export default`) are strictly prohibited except in Next.js `app/**/page.tsx`, `app/**/layout.tsx`, and `next.config.mjs`.
    - Use `interface` (never `type`) for all object shapes and component Props. Mark all interface properties `readonly`.
    - Prohibit `any`, non-null assertions (`!`), `var`, `namespace`, and the `public` modifier.
    - Require explicit return types on all functions. Treat acronyms in identifiers as whole words (`eventDateIso`, `totalBudgetInr`). Never prefix interfaces with `I` or identifiers with `_`.
2. AST COMPLEXITY & MODULARITY BUDGETS:
    - Cognitive Complexity (SonarSource S3776) must not exceed 8 per function. Refactor all nested `if/else` chains and nested ternaries into flat top-level Guard Clauses (`if (...) return ...;`).
    - Cyclomatic Complexity must not exceed 6 per function. Maximum nesting depth is 3. Maximum function parameter count is 3 (encapsulate 4+ parameters in a typed `interface`).
    - Pure logic functions must not exceed 30 lines; React functional components must not exceed 120 lines; total file length must not exceed 200 lines. Decouple all domain math, prompt templates, and API calls from UI components.
3. SECURITY, TESTING, AND ACCESSIBILITY COMPLETENESS:
    - Configure HTTP Security Headers (Content-Security-Policy, Strict-Transport-Security, X-Content-Type-Options: nosniff, X-Frame-Options: DENY, Referrer-Policy, Permissions-Policy) in `next.config.mjs` and enforce payload `content-length <= 16384` and Zod validation in `/api/plan/route.ts`.
    - Provide hermetic DAMP unit tests in Vitest covering exact numerical boundary pairs (0, negative values, and threshold + 1) with zero conditionals or loops inside test bodies.
    - Wrap dynamic AI blueprint outputs in `<section aria-live="polite" aria-busy={isLoading}>` and use semantic HTML controls (`<input type="checkbox">`, `role="progressbar"`) across all interactive views.

By systematically executing `npx gts fix`, verifying zero violations under `eslint-plugin-sonarjs`, confirming 100% boundary test coverage across all domain functions, and validating the HTTP security headers and `aria-live` regions, the submission directly eliminates the 12-point Code Quality penalty alongside the 7 remaining minor deductions—transforming a 96.41 prototype into a 100/100 Google-grade reference implementation.

Report unsafe content

Report unsafe content