05/2/24

Introduction to Pyspark

* Pyspark is an Apache spark library written in Python to run python applns using Apache spark capabilities
* Using Pyspark we can run applns parallely on distributed cluster (multiple nodes)
* Pyspark is python API ⇒ analytical processing engine for large-scale powerful distributed data processing & ML applns.

Apache Spark :-

* open-source unified analytics engine ⇒ used for large scale data processing ⇒ known as Spark.
* Spark
  - → fast
  - → flexible
  - → easy to use
  - → Processing large-scale data sets.
  - → runs operations on billions & trillions of data on distributed clusters.
  - → 100 times faster than traditional applns
  - → can run on single-node machines or multi node machines
  - → uses in-memory processing (solves the limitations of Map Reduce).
  - → Procss realtime streaming
  - → Multi-language engine

Multilanguage engine

It provides APIs and libraries for several programming languages like Scala, Java, Python, R.

* Spark offers
  - Scala
  - Java API
  - Python API
  - R API

Who uses PySpark?

- Data Science
- Machine Learning
- Numpy, Tensor flow
- Since it efficiently processes large datasets, it is used by many organizations
  - walmart, Trivago
  - sanofi etc.,

* For development, we can use Anaconda distribution which contains many useful tools like 1) Jupyter Notebook
  2) Spyder IDE.

  to run Pyspark applns.

* used in many machine learning applns.

Features of PySpark

1) In-memory computation
2) Distributed processing using parallelize
3) can be used with many cluster managers (Spark, Yarn, Mesos etc.,)
4) Fault-tolerant
5) Immutable
6) Lazy evaluation

7) cache & persistence
8) Inbuild - optimization when using Dataframes
9) Supports ANSI SQL.

Advantages of Pyspark

1) process data efficiently in distributed fashion
2) Appln running on pyspark - 100 times faster than traditional systems
3) used for data ingestion pipelines
4) we can process data from Hadoop HDFS, AWS S3 and many file systems using pyspark.

Kafka - open source distributed event stream platform used by thousands of companies for high performance datapipelines, streaming analytics
5) used to process real-time data using Streaming and Kafka.
6) Using pyspark streaming, we can stream files from file system and also from socket.
7) has machine learning & graph libraries.

Version Python Pyspark supports

Pyspark 3.5 is compatible with
- Python 3.8 & above
- R 3.5
- Java 8, 11, 13, 17 & later
- Scala 2.12 & 2.13 beyond

deprecated ⇒ no longer used.

PySpark Architecture

Apache Spark works in a master-slave architecture

Master ⇒ driver

Slaves ⇒ workers.

* When we run a Spark appln, Spark Driver creates a context that is entry point to our application.
* All operations (transformations & actions) are executed on worker nodes.
* Resources are managed by Cluster Manager.

Cluster Manager Types

Spark supports below cluster managers :-

1) Standalone :- a simple cluster manager included with Spark that makes it easy to set up a cluster.
2) Mesos - It is a cluster manager that can also run Hadoop, Map Reduce and PySpark applns.
3) Hadoop Yarn - resource manager in Hadoop 2. Mostly used as cluster manager.
4) Kubernetes - open-source system for automating deployment, scaling.

local ⇒ not a cluster manager ⇒ used for master() to run Spark on our laptop/pc.

Modules & packages

1) PySpark RDD (pyspark.RDD)
2) PySpark DataFrame and SQL (pyspark.sql)
3) PySpark Streaming (pyspark.streaming)
4) PySpark MLlib (pyspark.ml, pyspark.mllib)
5) PySpark GraphFrames (GraphFrames)
6) PySpark Resource (pyspark.resource) => new in PySpark 3.0

Read the data of file:-

⇒ Create RDD :-

There are two ways to create RDD
(i) loading an external dataset
(ii) distributing a set of collection of objects.

Parallelize() method

It takes an already existing collection in our program and pass the same to spark Context.

Ex:-

① from pyspark.sql import SparkSession

```
# create SparkSession
spark = SparkSession.builder
        .master("local[1]")
        .appName("Spark-Examples")
        .getOrCreate()
# using parallelize()
```

create RDD from parallelize

```
datalist = [("Java",20000),("Python",10000),
            ("Scala",3000)]

df = spark.sparkContext.parallelize(datalist)
```

use collect() method

```
df.collect()
```

2) Using csv file

```
from pyspark.sql import SparkSession
spark = SparkSession.builder.appName("Employee
        Details").getOrCreate()

spark
df = spark.read.csv("file path with \\")
df
df.show()
```

Find type of df1

```
df1 = spark.read.csv("file path \\", header = True,
                     inferSchema = True)
df1.show()
print(type(df1))   # dataframe
```

Returning top 2 records

```
df1.head(2)
```

Printing schema

```
df1.printSchema()
```

printing columns

df1.columns

③ Using text file

```
from pyspark.sql import SparkSession
spark = SparkSession.builder.appName("Data from
        text file").getOrCreate()

spark
df = spark.SparkContext.textFile("path")
df
df.collect()
```