

# 6


## React JSX

# Objectives

After completing this lesson, you should be able to do the following:

- Creating Components
- Basic Component
- Nesting Components
- Props





JSX


- JavaScript XML -- ( Extension to the JavaScript Language Syntax )
- In React Lib Helps Writing XML – Like Code for Elements and Components
- Just Like XML [ JSX Tags have a Tag Name, Attributes and Children ]
- Is it Need to React Application
  - Ans is No [ JSX is Not a Necessity to Write React Application ]
- Why ?
  - JSX Makes your React Code Simpler and Elegant
- JSX Ultimately transpiles to Pure JavaScript which is Understood by the Browsers

# Creating React Applications

- Lets see what does the code look like without JSX
- Let's create a react component using JSX and without using JSX
- That way we will not only understand how JSX translates to regular javascript but also appreciate how it brings out simplicity in your code

## Lets Create Hello.js

- This Component will be Simple Functional Component which Render HelloMSG [ Using JSX ]



```
EXPLORER
└─ LESSON03-HELLOWO...
   └─ my-app
      ├── node_modules
      ├── public
      └── src
         └── components
            ├── JS Greet.js
            ├── JS Hello.js
            └── JS Welcome.js
└─ # App.css
└─ JS App.js
└─ JS App.test.js
└─ # index.css
└─ JS index.js
└─ logo.svg
```

```
JS App.js M
JS Hello.js U X
JS Welcome.js U
JS Greet.js U

my-app > src > components > JS Hello.js > [default]
1  import React from 'react';
2
3  const Hello = () => {
4    return (
5      <div>
6        <h1>Hello React !</h1>
7      </div>
8    )
9  }
10
11  export default Hello
```

## Include Component in App.js

```
JS App.js M X JS Hello.js U JS Welcome.js U JS Greet.js U
my-app > src > JS App.js > ...
1 | import React, { Component } from 'react';
2 | import logo from './logo.svg';
3 | import './App.css';
4 | import { Greet } from './components/Greet';
5 | import Welcome from './components/Welcome';
6 | import Hello from './components/Hello';
7 |
8 | class App extends Component {
9 |   render() {
10 |     return (
11 |       <div className="App">
12 |         {/* <Greet />
13 |         <Welcome /> */}
14 |
15 |         <Hello />
16 |       </div>
17 |     );
18 |   }
19 | }
20 |
```



# Rewrite the Component Without Using JSX

- To Do So React Lib Provides createElement() Method

The screenshot shows a code editor with two panels. The left panel displays a JavaScript file named `Hello.js` with the following code:

```
1 import React from 'react';
2
3 const Hello = () => {
4   // return (
5   //   // <div>
6   //   //   <h1>Hello React !</h1>
7   //   // </div>
8   // )
9
10  return React.createElement('div', null, '<h1>Hello React !</h1>');
11
12
13  export default Hello;
```

The right panel shows the rendered HTML output. It includes a `<noscript>` block and a `<div id="root">` container. Inside the root container, there is a `<div class="App">` which contains the text `<h1>Hello React !</h1>`. A red box highlights this text, indicating that it is treated as plain text rather than an HTML element.

- Output is not as Expected, Since it has Considered `<h1>` as Simple Text Content



# Solution

JS App.js M

JS Hello.js U X

JS Welcome.js U

JS Greet.js U

my-app > src > components > JS Hello.js > [🔗] Hello

```
1  import React from 'react';
2
3  const Hello = () => {
4    // return (
5    //    // <div>
6    //    //    <h1>Hello React !</h1>
7    //    // </div>
8    // )
9
10   return React.createElement('div', null, React.createElement('h1', null, 'Hello React !'));
11 }
12
13 export default Hello;
```

**Hello React !**

## Importance of 2<sup>nd</sup> Parameter in createElement()

- Second parameter basically is an object of key value pairs that will be applied to the element
- For example let's say we need an **ID attribute** on this **div tag** we can specify an object key is ID and the value is hello

```
JS App.js M JS Hello.js U X JS Welcome.js U JS Greet.js U
my-app > src > components > JS Hello.js > [e] default
1 import React from 'react';
2
3 const Hello = () => {
4   // return (
5   //   // <div>
6   //   //   <h1>Hello React !</h1>
7   //   // </div>
8   // )
9
10  return React.createElement(
11    'div',
12    {id: 'helloDiv'},
13    React.createElement('h1', null, 'Hello React !'));
14  }
15
16 export default Hello;
```

```
<!DOCTYPE html>
<html lang="en">
  <head>...</head>
  <body>
    <noscript>You need to enable JavaScript to run this app.</noscript>
    <div id="root">
      <div class="App">
        ... <div id="helloDiv"> == $0
        <h1>Hello React !</h1>
      </div>
    </div>
  </body>
</html>

<!--
  This HTML file is a template.
  If you open it directly in the browser, you will see an empty page.

  You can add webfonts, meta tags, or analytics to this file.
  The build step will place the bundled scripts into the <body> tag.

  To begin the development, run `npm start` or `yarn start`.
  To create a production bundle, use `npm run build` or `yarn build`.
```

```
JS App.js M JS Hello.js U X JS Welcome.js U JS Greet.js U
my-app > src > components > JS Hello.js > [0] default
1 import React from 'react';
2
3 const Hello = () => {
4   // return (
5   //   // <div>
6   //   //   <h1>Hello React !</h1>
7   //   // </div>
8   // )
9
10  return React.createElement(
11    'div',
12    {id: 'helloDiv' , class: 'dummy'},
13    React.createElement('h1', null, 'Hello React !'));
14  }
15
16  export default Hello;
```


```
<!DOCTYPE html>
<html lang="en">
  <head> </head>
  <body>
    <noscript>You need to enable JavaScript to run this app.</noscript>
    <div id="root">
      <div class="App">
        <div id="helloDiv" class="dummy"> == $0
          <h1>Hello React !</h1>
        </div>
      </div>
    </div>
    <!--
      This HTML file is a template.
      If you open it directly in the browser, you will see an empty page.

      You can add webfonts, meta tags, or analytics to this file.
      The build step will place the bundled scripts into the <body> tag.

      To begin the development, run `npm start` or `yarn start`.
      To create a production bundle, use `npm run build` or `yarn build`.
    -->
  </body>
</html>
```

# Error in Console

- In JS class is a Keyword, So Ended up with this.



## JSX is Better Than Normal createElement()

- Our example just has two elements but imagine a component with ten or a hundred elements it starts to become really clumsy
- JSX on the other hand will keep the code elegant simple and readable

# JSX Differences

- Follow the Link for More
- <https://github.com/facebook/react/issues/13525>

---

Class -> className

for -> htmlFor

camelCase property naming convention

- onclick -> onClick
- tabindex -> tabIndex



# Summary

In this lesson, you should have learned how to:

- Creating Components
- Basic Component
- Nesting Components
- Props

