

8

Data Manipulation

Objectives

After completing this lesson, you should be able to do the following:

- Describe each data manipulation language (DML) statement
- Insert rows into a table
- Update rows in a table
- Delete rows from a table
- Control transactions



Course Roadmap

Lesson 1: Introduction

Unit 1: Retrieving, Restricting,
and Sorting Data

Unit 2: Joins, Subqueries, and
Set Operators

Unit 3: DML and DDL



**Lesson 10: Managing Tables Using DML
Statements**

You are here!



Lesson 11: Introduction to Data Definition
Language



Lesson 12: Other Schema Objects

HR Application Scenario

It is time for me to update the employee directory! Let me first delete the employees who have quit and insert new hires.



Ben

HR Application

	Emp_ID	First Name	Last Name	Salary
<input type="checkbox"/>	100	Steven	King	24000
<input checked="" type="checkbox"/>	104	Bruce	Ernst	6000
<input type="checkbox"/>	141	Trenna	Rajs	3500

...

INSERT

UPDATE

DELETE

Clicks INSERT and enters values for the new employee.

Selects a record and clicks DELETE to delete an employee.


Lesson Agenda

- Adding new rows in a table
 - INSERT statement
- Changing data in a table
 - UPDATE statement
- Removing rows from a table:
 - DELETE statement
 - TRUNCATE statement
- Database transaction control using COMMIT, ROLLBACK, and SAVEPOINT
- Read consistency
- Manual Data Locking
 - FOR UPDATE clause in a SELECT statement
 - LOCK TABLE statement




Data Manipulation Language

- A DML statement is executed when you:
 - Add new rows to a table
 - Modify existing rows in a table
 - Remove existing rows from a table
- A *transaction* consists of a collection of DML statements that form a logical unit of work.



Insert



Update



Delete

Adding a New Row to a Table

DEPARTMENTS

	DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	10	Administration	200	1700
2	20	Marketing	201	1800
3	50	Shipping	124	1500
4	60	IT	103	1400
5	80	Sales	149	2500
6	90	Executive	100	1700
7	110	Accounting	205	1700
8	190	Contracting	(null)	1700

70 Public Relations	100	1700
---------------------	-----	------

New row

Insert a new row
into the
DEPARTMENTS table.

	DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	70	Public Relations	100	1700
2	10	Administration	200	1700
3	20	Marketing	201	1800
4	50	Shipping	124	1500
5	60	IT	103	1400
6	80	Sales	149	2500
7	90	Executive	100	1700
8	110	Accounting	205	1700
9	190	Contracting	(null)	1700

INSERT Statement Syntax

- Add new rows to a table by using the INSERT statement:

```
INSERT INTO  table [(column [, column...])]  
VALUES      (value [, value...]);
```

- With this syntax, only one row is inserted at a time.



Inserting New Rows

- Insert a new row containing values for each column.
- List values in the default order of the columns in the table.
- Optionally, list the columns in the INSERT clause.

```
INSERT INTO departments (department_id,  
                        department_name, manager_id, location_id)  
VALUES (70, 'Public Relations', 100, 1700);  
1 rows inserted
```

- Enclose character and date values in single quotation marks.

Inserting Rows with Null Values

- Implicit method: Omit the column from the column list.

```
INSERT INTO departments (department_id,  
                        department_name  )  
VALUES (30, 'Purchasing');  
1 rows inserted
```

- Explicit method: Specify the NULL keyword in the VALUES clause.

```
INSERT INTO departments  
VALUES (100, 'Finance', , );  
1 rows inserted
```

Inserting Special Values

- The SYSDATE function records the current date and time.

```
INSERT INTO employees (employee_id,  
                        first_name, last_name,  
                        email, phone_number,  
                        hire_date, job_id, salary,  
                        commission_pct, manager_id,  
                        department_id)  
VALUES  
    (113,  
     'Louis', 'Popp',  
     'LPOPP', '515.124.4567',  
     SYSDATE, 'AC_ACCOUNT', 6900,  
     NULL, 205, 100);
```

1 rows inserted

Inserting Specific Date Values

- Add a new employee.

```
INSERT INTO employees
VALUES      (114,
             'Den', 'Raphealy',
             'DRAPHEAL', '515.127.4561',
             TO_DATE('FEB 3, 1999', 'MON DD, YYYY'),
             'AC_ACCOUNT', 11000, NULL, 100, 30);
```

1 rows inserted

- Verify your addition.

	EMPLOYEE_ID	FIRST_NAME	LAST_NAME	EMAIL	PHONE_NUMBER	HIRE_DATE	JOB_ID	SALARY	COMMISSION_PCT
1	114	Den	Raphealy	DRAPHEAL	515.127.4561	03-FEB-99	AC_ACCOUNT	11000	(null)

Creating a Script

- Use & substitution in a SQL statement to prompt for values.
- & is a placeholder for the variable value.

```
INSERT INTO departments
      (department_id, department_name, location_id)
VALUES (&department_id, '&department_name', &location);
```

Enter Substitution Variable X

DEPARTMENT_ID:

40

OK

Enter Substitution Variable X

DEPARTMENT_NAME:

Human Resources

OK

Enter Substitution Variable X

LOCATION:

2500

OK Cancel

Copying Rows

- Write your `INSERT` statement with a subquery:

```
INSERT INTO sales_reps(id, name, salary, commission_pct)
  SELECT employee_id, last_name, salary, commission_pct
 FROM   employees
 WHERE  job_id LIKE '%REP%';
```

4 rows inserted

- Do not use the `VALUES` clause.
- Match the number of columns in the `INSERT` clause to those in the subquery.

Lesson Agenda

- Adding new rows in a table
 - `INSERT` statement
- Changing data in a table
 - `UPDATE` statement
- Removing rows from a table:
 - `DELETE` statement
 - `TRUNCATE` statement
- Database transaction control using `COMMIT`, `ROLLBACK`, and `SAVEPOINT`
- Read consistency
- Manual Data Locking
 - `FOR UPDATE` clause in a `SELECT` statement
 - `LOCK TABLE` statement



Changing Data in a Table

EMPLOYEES

EMPLOYEE_ID	FIRST_NAME	LAST_NAME	EMAIL	HIRE_DATE	JOB_ID	SALARY	DEPARTMENT_ID	COMMISSION_PCT
100	Steven	King	SKING	17-JUN-87	AD_PRES	24000	90	(null)
101	Neena	Kochhar	NKOCHHAR	21-SEP-89	AD_VP	17000	90	(null)
102	Lex	De Haan	LDEHAAN	13-JAN-93	AD_VP	17000	90	(null)
103	Alexander	Hunold	AHUNOLD	03-JAN-90	IT_PROG	9000	60	(null)
104	Bruce	Ernst	BERNST	21-MAY-91	IT_PROG	6000	60	(null)
107	Diana	Lorentz	DLORENTZ	07-FEB-99	IT_PROG	4200	60	(null)
124	Kevin	Mourgos	KMOURGOS	16-NOV-99	ST_MAN	5800	50	(null)

Update rows in the EMPLOYEES table:


EMPLOYEE_ID	FIRST_NAME	LAST_NAME	EMAIL	HIRE_DATE	JOB_ID	SALARY	DEPARTMENT_ID	COMMISSION_PCT
100	Steven	King	SKING	17-JUN-87	AD_PRES	24000	90	(null)
101	Neena	Kochhar	NKOCHHAR	21-SEP-89	AD_VP	17000	90	(null)
102	Lex	De Haan	LDEHAAN	13-JAN-93	AD_VP	17000	90	(null)
103	Alexander	Hunold	AHUNOLD	03-JAN-90	IT_PROG	9000	30	(null)
104	Bruce	Ernst	BERNST	21-MAY-91	IT_PROG	6000	30	(null)
107	Diana	Lorentz	DLORENTZ	07-FEB-99	IT_PROG	4200	30	(null)
124	Kevin	Mourgos	KMOURGOS	16-NOV-99	ST_MAN	5800	50	(null)

UPDATE Statement Syntax

- Modify existing rows with the UPDATE statement:

```
UPDATE      table  
SET         column = value [, column = value, ...]  
[WHERE      condition];
```

- Update more than one row at a time (if required).



Updating Rows in a Table

- Specific row or rows are modified if you specify the `WHERE` clause:

```
UPDATE employees  
SET    department_id = 70  
WHERE  employee_id = 113;  
1 rows updated
```

- All rows in the table are modified if you omit the `WHERE` clause:

```
UPDATE    copy_emp  
SET       department_id = 110;  
22 rows updated
```

Updating Two Columns with a Subquery

- Update employee 114's job and salary to match that of employee 205.

```
UPDATE employees
SET   job_id = (SELECT job_id
                FROM   employees
                WHERE  employee_id = 205),
      salary = (SELECT salary
                FROM   employees
                WHERE  employee_id = 205)
WHERE employee_id = 114;
1 rows updated
```

Updating Rows Based

- Use subqueries in UPDATE statements to update rows in a table based on values from another table:

```
UPDATE copy_emp
SET    department_id = (SELECT department_id
                        FROM employees
                        WHERE employee_id = 100)
WHERE  job_id        = (SELECT job_id
                        FROM employees
                        WHERE employee_id = 200);
```

1 rows updated

Lesson Agenda

- Adding new rows in a table
 - INSERT statement
- Changing data in a table
 - UPDATE statement
- Removing rows from a table:
 - DELETE statement
 - TRUNCATE statement
- Database transaction control using COMMIT, ROLLBACK, and SAVEPOINT
- Read consistency
- Manual Data Locking
 - FOR UPDATE clause in a SELECT statement
 - LOCK TABLE statement



Removing a Row from a Table

DEPARTMENTS

	DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	30	Purchasing	(null)	(null)
2	40	Human Resources	(null)	2500
3	10	Administration	200	1700
4	20	Marketing	201	1800
5	50	Shipping	124	1500
6	60	IT	103	1400


Delete a row from the DEPARTMENTS table:

	DEPARTMENT_ID	DEPARTMENT_NAME	MANAGER_ID	LOCATION_ID
1	40	Human Resources	(null)	2500
2	10	Administration	200	1700
3	20	Marketing	201	1800
4	50	Shipping	124	1500
5	60	IT	103	1400

DELETE Statement

- You can remove existing rows from a table by using the `DELETE` statement:

```
DELETE [FROM] table  
[WHERE condition];
```



Deleting Rows from a Table

- Specific rows are deleted if you specify the `WHERE` clause:

```
DELETE FROM departments  
WHERE department_name = 'Finance';  
1 rows deleted
```

- All rows in the table are deleted if you omit the `WHERE` clause:

```
DELETE FROM copy_emp;  
22 rows deleted
```


Deleting Rows Based

- Use subqueries in DELETE statements to remove rows from a table based on values from another table:

```
DELETE FROM employees
WHERE department_id =
    (SELECT department_id
     FROM departments
     WHERE department_name
           LIKE '%Public%');
```

1 rows deleted

TRUNCATE Statement

- Removes all rows from a table, leaving the table empty and the table structure intact
- Is a data definition language (DDL) statement rather than a DML statement; cannot easily be undone
- Syntax:

```
TRUNCATE TABLE table_name;
```

- Example:

```
TRUNCATE TABLE copy_emp;
```

Lesson Agenda

- Adding new rows in a table
 - INSERT statement
- Changing data in a table
 - UPDATE statement
- Removing rows from a table:
 - DELETE statement
 - TRUNCATE statement
- Database transaction control using COMMIT, ROLLBACK, and SAVEPOINT
- Read consistency
- Manual Data Locking
 - FOR UPDATE clause in a SELECT statement
 - LOCK TABLE statement



Database Transactions

A database transaction consists of one of the following:

- DML statements that constitute one consistent change to the data
- One DDL statement
- One data control language (DCL) statement



Database Transactions: Start and End

- Begin when the first DML SQL statement is executed
- End with one of the following events:
 - A COMMIT or ROLLBACK statement is issued.
 - A DDL or DCL statement executes (automatic commit).
 - The user exits SQL Developer or SQL*Plus.
 - The system crashes.


**Database transaction
on table/s**




Advantages of COMMIT and ROLLBACK Statements

Using COMMIT and ROLLBACK statements, you can:

- Ensure data consistency
- Preview data changes before making changes permanent
- Group logically related operations




COMMIT




ROLLBACK

Explicit Transaction Control Statements



Implicit Transaction Processing

- An automatic commit occurs in the following circumstances:
 - A DDL statement is issued
 - A DCL statement is issued
 - A normal exit from SQL Developer or SQL*Plus, without explicitly issuing `COMMIT` or `ROLLBACK` statements
- An automatic rollback occurs when there is an abnormal termination of SQL Developer or SQL*Plus, or a system failure.



State of Data Before COMMIT or ROLLBACK

- You can recover the data of the previous state.
- You can review the results of the DML operations by using the `SELECT` statement in the current session.
- Other sessions *cannot* view the results of the DML statements issued by the current session.
- The affected rows are *locked*; other sessions cannot change the data in the affected rows.

Current session changes
stored in buffer



State of Data After COMMIT

- Data changes are saved in the database.
- The previous state of the data is overwritten.
- All sessions can view the results.
- Locks on the affected rows are released; those rows are available for other sessions to manipulate.
- All savepoints are erased.



COMMIT

Committing Data

➤ Make the changes:

```
DELETE FROM employees
WHERE employee_id = 99999;
1 rows deleted

INSERT INTO departments
VALUES (290, 'Corporate Tax', NULL, 1700);
1 rows inserted
```


➤ Commit the changes:

```
COMMIT;
Commit complete
```

State of Data After ROLLBACK

- Discard all pending changes by using the ROLLBACK statement:
 - Data changes are undone.
 - Previous state of the data is restored.
 - Locks on the affected rows are released.

```
DELETE FROM copy_emp;  
ROLLBACK ;
```



ROLLBACK

State of Data After ROLLBACK: Example

```
DELETE FROM test;  
4 rows deleted.
```

```
ROLLBACK;  
Rollback complete.
```

```
DELETE FROM test WHERE id = 100;  
1 row deleted.
```

```
SELECT * FROM test WHERE id = 100;  
No rows selected.
```

```
COMMIT;  
Commit complete.
```


Lesson Agenda

- Adding new rows in a table
 - INSERT statement
- Changing data in a table
 - UPDATE statement
- Removing rows from a table:
 - DELETE statement
 - TRUNCATE statement
- Database transaction control using COMMIT, ROLLBACK, and SAVEPOINT
- Read consistency
- Manual Data Locking
 - FOR UPDATE clause in a SELECT statement
 - LOCK TABLE statement




Read Consistency

- Read consistency guarantees a consistent view of data at all times.
- Changes made by one user do not conflict with the changes made by another user.
- Read consistency ensures that, on the same data:
 - Readers do not wait for writers
 - Writers do not wait for readers
 - Writers wait for writers



Implementing Read Consistency



Lesson Agenda

- Adding new rows in a table
 - INSERT statement
- Changing data in a table
 - UPDATE statement
- Removing rows from a table:
 - DELETE statement
 - TRUNCATE statement
- Database transaction control using COMMIT, ROLLBACK, and SAVEPOINT
- Read consistency
- **Manual Data Locking**
 - FOR UPDATE clause in a SELECT statement
 - LOCK TABLE statement



FOR UPDATE Clause in a SELECT Statement

- Locks the rows in the EMPLOYEES table where job_id is SA_REP.

```
SELECT employee_id, salary, commission_pct, job_id
FROM employees
WHERE job_id = 'SA_REP'
FOR UPDATE
ORDER BY employee_id;
```

- Lock is released only when you issue a ROLLBACK or a COMMIT.
- If the SELECT statement attempts to lock a row that is locked by another user, the database waits until the row is available, and then returns the results of the SELECT statement.

FOR UPDATE Clause: Examples

- You can use the `FOR UPDATE` clause in a `SELECT` statement against multiple tables.

```
SELECT e.employee_id, e.salary, e.commission_pct
FROM employees e JOIN departments d
USING (department_id)
WHERE job_id = 'ST_CLERK'
AND location_id = 1500
FOR UPDATE
ORDER BY e.employee_id;
```

- Rows from both the `EMPLOYEES` and `DEPARTMENTS` tables are locked.
- Use `FOR UPDATE OF column_name` to qualify the column that you intend to change; then only the rows from that specific table are locked.

The following statements produce the same results:

```
DELETE FROM copy_emp;
```

```
TRUNCATE TABLE copy_emp;
```

- a. True
- b. False



Summary

In this lesson, you should have learned how to:

Function	Description
INSERT	Adds a new row to the table
UPDATE	Modifies existing rows in the table
DELETE	Removes existing rows from the table
TRUNCATE	Removes all rows from a table
COMMIT	Makes all pending changes permanent
SAVEPOINT	Is used to roll back to the savepoint marker
ROLLBACK	Discards all pending data changes
FOR UPDATE clause in SELECT	Locks rows identified by the SELECT query



Practice 8: Overview

This practice covers the following topics:

- Inserting rows into the tables
- Updating and deleting rows in the table
- Controlling transactions

