

Product List ■■■

Entrance Facility Products

Entrance Camera Phone



SHN-5180XL SHT-5180XL

- Door access control (User access code & RF ID card)
- Call to households
- Visitor's image save (SHN-5180)

■ Product Components

Item	Monitor/Wall pad	Door Camera
SHN-5180XL	SHN-8610	SHT-CN510
	SHT-3107	
	SHT-7171	
SHT-5180XL	SHT-7070	SHT-CP610
	SHT-7507	

■ Specifications (SHN-5180XL)

Item	Contents	Description
Power	Input Power	DC 12V (SHT-PS17X)
Camera	Lens	320k (PAL)
	Power consumption	100mA
Communication	Type	Speaker Phone (VoIP)
	Transmission	Ethernet
	Image Transmission	Ethernet
Dimension		223x320x13mm (WxHxD)
Imbedded Box		SHT-ZBXSD
Cover		SHT-ZCXA500
IP Rate		IP44

■ Specifications (SHT-5180XL)

Item	Contents	Description
Power	Input Power	DC 12V (SHT-PS17X)
Camera	Lens	320k (PAL)
	Power consumption	100mA
Communication	Type	Speaker Phone (RS-485)
	Transmission	RS-485
	Image Transmission	Analog
Dimension		223x320x13mm (WxHxD)
Imbedded Box		SHT-ZBXSD
Cover		SHT-ZCXA500
IP Rate		IP44



SHT-5082ML (2 Button) SHT-5084ML (4 Button) SHT-5086ML (6 Button) SHT-5088ML (8 Button)

- Door access control
- Call to households

■ Product Components

Monitor
SHT-3006XM
SHT-3207XM
SHT-6805XM
SHT-3305LM/WM

■ Specifications

Contents	Description
Power	DC 12V,330mA (Max)
Lens	1/3" Color (320k pixel)
Power Consumption	230mA
Dimension	123x308x18mm (WxHxD)
Installation	Flush Mounting
IP Rate	IP43
Type	Hands-free Type

SHT-5004EP (4 Button) SHT-5008EP (8 Button) SHT-5012EP (12 Button) SHT-5016EP (16 Button) SHT-5020EP (20 Button) SHT-5024EP (24 Button)

• Common use for B/W and color



NEW SHT-5080XL

- Door access control (User access code & RF card)
- LCD Screen
- Applicable to single family homes and apartments (200 households)

■ Product Components

Monitor
SHT-3006BM

■ Specifications

Contents	Description
Power	DC 17V ~ 24V
Lens	1/3" B/W (270k Pixel)
Power Consumption	520mA
Display	Dots LCD (122x32mm)
Dimension	124x347x18mm (WxHxD)
Installation	Flush Mounting
IP Rate	IPX3
Type	Hands-free Type

Security Phone



SHT-552XS/ES

- Communication function
- Condition data collection function

■ Product Components

Monitor
SHT-552XS
SHT-3107
SHT-7171
SHT-7070
SHT-7507
SHT-552ES
SHT-3006BM

■ Specifications

Contents	Description
Power	AC110~220V (50/60Hz)
Dimension	245x228.6x82.5mm (WxHxD)
Type	Handset Type



Door Camera



SHT-CN510

- Plastic color door camera

■ Product Components

Main Monitor
SHT-3006
SHT-3207
SHT-6805
SHT-3305
SHT-7171
SHT-7070
SHT-3107
SHN-8610

■ Specifications

Item	Contents	Description
Power	Input Power	DC12V/ 150mA (max)
Camera	Power Consumption	90mA (MAX)
	Sensor	1/3" CCD Color (320k Pixel)
	Lens	3.6mm Board Lens (92°)
	Dimension	92x136x12mm (WxHxD)
Mainbody	IP Rate	IPX1
	Imbedded Box	SHT-ZBX5C

SHT-CP610

SHT-CW610E/EN

SHT-CP611



- Metal color door camera

■ Product Components

Main Monitor
SHT-3006
SHT-3207
SHT-6805
SHT-3305

■ Specifications

Item	Contents	Description
Power	Input Power	DC12V/ 150mA (max)
	Power Consumption	90mA (MAX)
Camera	Sensor	SHT-CP610/SHT-CP611 : 1/3" CCD Color (320k Pixel) SHT- CW610E : 1/3" CMOS (320k Pixel)
	Lens	3.6mm pinhole type (92°)
	Dimension	SHT-CP610/CW610E : 97x130x24 mm(WxHxD) SHT-CP611 : 74x133x10
Mainbody	IP Rate	IPX3
	Imbedded Box	SHT-ZBX5C

Main Control Unit



SHT-5500M

- Main control units to transfer all related data among the devices within home network

■ Product Components

Monitor
SHT-7171
SHT-7070
SHT-3107
SHT-7507

■ Specifications

Contents	Description
Power Supply	AC110~220V (50/60Hz)
Power Consumption	Main Unit : 26W
Transfer Method	RS-485
Transfer Speed	9600bps
Phone Loop	Short Loop
Impedance	600± 10%
Path	3 Communication Paths

■ Capacity

Compatibility	Capacity
Entrance Camera Phone	40
Security Office	40
Household (Units)	1,200 (120 Households/Slot)
Main Control Unit	10