HTTPie CLI Cheat Sheet

`http [flags] [METHOD] URL [ITEM …]` · v3.2.4 · also `https`, `httpie`

BASICS

`http pie.dev/get`	GET (default when there's no body)
`http pie.dev/post a=1`	POST JSON (data present → POST)
`http PUT pie.dev/put a=1`	Explicit method
`http :3000/x`	→ localhost:3000/x
`https example.org`	https:// by default
`http --offline URL a=1`	Print the request, don't send it

REQUEST ITEMS

`H:v`	Header
`H;` · `H:`	Empty header · remove default header
`H:@file`	Header value read from a file
`q==v` · `q==@f`	Query param (value or file)
`k=v`	String field
`k:=json`	Raw JSON: `n:=1 ok:=true`
`k=@f` · `k:=@f.json`	Field read from a file (text / JSON)
`f@path;type=m`	File upload (multipart)
`a[b][]=x a[c]:=1`	Nested JSON
`@body.json`	File contents as the body
`'a\==b'`	Escape a separator

REQUEST BODY

`-j` (default)	JSON object
`-f`	Form (multipart if files)
`--multipart`	Always multipart (`--boundary`)
`--raw 'txt'`	Raw body string
`cmd | http POST URL`	Body from stdin
`-x` · `-xx`	Deflate · forced
`--chunked`	Chunked encoding

OUTPUT

`-p HBhbm`	Req **H**dr/**B**ody, resp **h**dr/**b**ody, **m**eta
`-h` · `-b` · `-m`	Response headers · body · meta
`-v` · `-vv`	Request + response (+meta)
`--all` · `-P WHAT`	Show redirect hops / what to print for them
`-q` · `-qq`	Quiet · also hide warnings
`-S`	Stream by line (tail -f)
`-o FILE`	Write output to a file

Defaults: `hb` on a TTY · `b` when piped · `HB` with --offline

FORMATTING

`--pretty=all`	all · colors · format · none
`-s monokai`	Color style (default auto)
`--unsorted`	Don't sort keys/headers
`--format-options=`	`json.indent:2,xml.indent:4`
`--response-mime=`	Force formatter type
`--response-charset=`	Force display encoding

DOWNLOAD

`http -d URL`	Save to a file (name auto-detected)
`-d -o f.zip`	Explicit filename
`-dco f.zip`	Resume (needs `-o`)

`-d` implies `-F`; progress bar on stderr.

AUTH

`-a user:pass`	Basic (`-a user` prompts)
`-A digest -a u:p`	Digest
`-A bearer -a TOKEN`	Bearer token
`--ignore-netrc`	Skip ~/.netrc

SESSIONS

`--session=dev`	Named session, per host (headers, cookies, auth)
`--session=./s.json`	Session at an explicit path
`--session-read-only=dev`	Use but don't save
`httpie cli sessions upgrade-all`	Migrate format

NETWORK / TLS

`-F`	Follow redirects (max 30)
`--max-redirects=N`	Redirect limit
`--timeout=5`	Seconds
`--proxy=https:http://h:p`	socks5 OK; env vars honored
`--verify=no|ca.pem`	TLS verification
`--cert c.pem --cert-key k`	Client certificate
`--ssl=tls1.2` · `--ciphers`	TLS version · ciphers
`--path-as-is`	Keep `/../` in the URL
`--default-scheme=https`	Scheme when the URL has none
`--no-FLAG`	Unset a default/config flag

SCRIPTING & EXIT CODES

`http -I --check-status --timeout=3 URL`

`-I` (ignore stdin) stops cron jobs and scripts from hanging

0	OK	4	HTTP 4xx*
1	Error	5	HTTP 5xx*
2	Timeout	6	Too many redirects
3	HTTP 3xx* (no -F)	7	Plugin error
	* with --check-status	130	Ctrl-C

CONFIG

`$HTTPIE_CONFIG_DIR` → `%APPDATA%\httpie` → `~/.httpie` → `~/.config/httpie`

`config.json`: `{"default_options": ["--style=fruity"], "plugins_dir": "…"}`

MANAGER (HTTPIE)

`httpie cli plugins install X`	Also: list / upgrade / uninstall
`httpie cli check-updates`	Check for a new version
`httpie cli export-args`	Export the CLI spec as JSON

DEVELOPING THE REPO

`make all`	venv + install + tests
`source venv/bin/activate`	Use the dev `http`
`make test` · `test-cover`	pytest (· coverage)
`pytest tests/f.py::C::t`	Run a single test
`make codestyle`	flake8
`make test-all`	+ dist + style
`http --debug …`	Info for bug reports

CODE MAP

`core.py`	main → raw_main → program
`cli/definition.py`	Every flag
`cli/argparser.py`	Arg post-processing
`cli/requestitems.py`	Item → request parts
`client.py`	Build & send requests
`output/`	Writer, streams, formatters
`sessions.py` · `config.py`	Persistence · config
`plugins/base.py`	Plugin base classes
`tests/utils::http()`	In-process CLI test helper

Full manual: docs/README.md · httpie.io/docs/cli

Test API: pie.dev