Start here: HTTPie CLI

HTTPie is a command-line HTTP client for talking to APIs: `http` and `https` send a request built from short `key=value` arguments and print a colored, formatted response. This repo (version 3.2.4) is the Python package behind those commands and the `httpie` management tool.

```
git clone https://github.com/httpie/cli.git && cd cli
python3 -m venv venv && ./venv/bin/pip install -e '.[dev]'
./venv/bin/http --offline pie.dev/post name=Ada age:=36
```

`--offline` builds and prints the request without sending it, which makes it the quickest way to see what your change does:

```
POST /post HTTP/1.1
Content-Type: application/json
User-Agent: HTTPie/3.2.4
...
{"name": "Ada", "age": 36}
```

Users install it with `pip install httpie` (Python 3.7+). Full user docs live in `docs/README.md` and at https://httpie.io/docs/cli.

Repo map

Path	What lives there
`httpie/__main__.py`, `httpie/core.py`	Entry point, error handling, the main request loop
`httpie/cli/`	Argument definition (`definition.py`), parsing (`argparser.py`), request items (`requestitems.py`), nested JSON syntax (`nested_json/`)
`httpie/client.py`	Turns parsed args into a `requests` request, sends it, follows redirects
`httpie/output/`	Formatting, colors, streaming to the terminal
`httpie/sessions.py`, `config.py`	Saved sessions and the config directory
`httpie/plugins/`	Plugin base classes and loader
`httpie/manager/`	The `httpie cli ...` command (plugins, sessions, update checks)
`tests/`	pytest suite; `tests/utils/__init__.py` has the `http()` test helper

Day 1: run the tests

The `Makefile` wraps the setup. `make all` creates `./venv`, installs `.[dev]` and `.[test]` plus an editable HTTPie, and runs the tests. After that:

```
make test                # pytest over httpie/ and tests/ (doctests included)
make codestyle           # flake8, required to pass in CI
python -m pytest tests/test_uploads.py::TestMultipartFormDataFileUpload::test_upload_ok
```

On Windows, CI skips `make`: `python -m pip install -e .[dev]`, then `python -m pytest ./httpie ./tests`.

Tests run against a local httpbin server from `pytest-httpbin`, so most need no network. Two markers in `pytest.ini` exist for restricted environments: `requires_installation` and `requires_external_processes`.

To skip both:

```
python -m pytest -m 'not requires_installation and not requires_external_processes'
```

On a fresh checkout with Python 3.11, `charset-normalizer` 3.5.2 and `requests` 2.34.2, the suite gave 999 passed and 14 failed. Twelve failures were in `tests/test_plugins_cli.py` (it runs a real `pip install` of a dummy plugin) and two were Big5 charset-detection cases in `tests/test_encoding.py`. Compare with `master` CI before chasing them.

How a request flows

1. `httpie/__main__.py:main` calls `httpie.core.main` (`core.py:146`), which hands the parser from `cli/definition.py:956` to `raw_main` (`core.py:32`).
2. `raw_main` loads plugins, prepends `default_options` from the config file, then parses args with `HTTPieArgumentParser` (`cli/argparser.py:138`). Request items like `name=Ada` become headers, params, data, and files in `RequestItems.from_args` (`cli/requestitems.py:37`).
3. `program` (`core.py:170`) iterates over `collect_messages` (`client.py:43`). That generator loads the session, builds kwargs (`make_request_kwargs`, `client.py:325`), yields the prepared request, sends it unless `--offline`, follows redirects, and saves the session afterwards.
4. Each yielded request or response goes to `write_message` (`output/writer.py:27`) for formatting. With `--check-status` or `--download`, `status.py` maps the HTTP status to the exit code.

To add an option, define it in `cli/definition.py`, handle it in `argparser.py` or `client.py`, and test it with the `http()` helper, using `--offline` when no response is needed.

Request item syntax

Everything after the URL is a request item. The separator decides where it goes (`cli/constants.py:15`).

Item	Becomes	Example
`Name:value`	Header	`X-Token:abc`
`Name;`	Header with empty value	`X-Empty;`
`name==value`	Query parameter	`q==1`
`name=value`	JSON string field (form field with `-f`)	`name=Ada`
`name:=json`	Raw JSON value	`age:=36`, `tags:='["a"]'`
`name=@file` / `name:=@file`	Field from file contents (text / JSON)	`data=@f.txt`
`name@file`	File upload, forces multipart	`-f doc@f.txt`

If any data item is present and no method is given, the method is POST. Nested JSON works with brackets: `user[name]=Ada tags[]=a` sends `{"user": {"name": "Ada"}, "tags": ["a"]}`. A URL starting with `:` means localhost: `:8000/api` goes to `localhost:8000`.

Conventions that aren't obvious

Rule	Why
Every behavior change needs a test, and user-facing ones a docs change in `docs/README.md`	`CONTRIBUTING.md` says PRs without them generally don't get merged
Add a `CHANGELOG.md` entry	`CONTRIBUTING.md` asks for one with each change
Don't hand-edit `extras/man/*.1`	They are generated from `cli/definition.py` by `make man`; a CI job opens an automated PR on `master`

Rule	Why
Keep `setup.cfg` ASCII-only	distutils reads it with the system locale (issue #1039)
CI tests Python 3.7 to 3.12 on Linux, macOS, and Windows, each with and without pyOpenSSL	Avoid syntax newer than 3.7
Reproduce bugs with `http --debug ...`	Prints version, environment, and request kwargs

Gotchas

- `-h` is `--headers` (print only response headers), not help. Use `--help`.
- `age=36` sends the string `"36"`. Use `age:=36` for a number, boolean, or list.
- When stdin is not a terminal (cron, CI, a pipe), HTTPie reads the body from stdin. Adding `key=value` items then exits 1 with "Request body (from stdin, --raw or a file) and request data (key=value) cannot be mixed". Pass `--ignore-stdin` (`-I`) in scripts.
- Without `--check-status`, a 404 or 500 still exits 0. With it, 3xx/4xx/5xx exit 3/4/5 (`status.py`).
- `default_options` in `config.json` apply to every call, including your manual tests. Set `HTTPIE_CONFIG_DIR` to an empty folder to isolate them. The default config dir is `~/.config/httpie` (or the legacy `~/.httpie` if it exists, or `%APPDATA%\httpie` on Windows).
- Sessions (`--session=name`) are saved after every request, including new headers and auth. Use `--session-read-only` to load without writing.

Next: `docs/README.md` for every flag, `httpie/plugins/base.py` for the auth, transport, converter, and formatter plugin interfaces.