


## SCD3 Design approach:

This is one of most widely used design approach.

SRC->SQ->LKP->EXP->RTR->UPD->TGT1 & TGT2

**Understanding the Mapping:** The Type 3 Dimension mapping performs the following tasks:

1. Selects all rows.
2. Caches the existing target as a lookup table.
3. Compares logical key columns in the source against corresponding columns in the target lookup table.
4. Compares source columns against corresponding target columns if key columns match.
5. Flags new rows and changed rows.
6. Creates two data flows: one for new rows, one for updating changed rows.
7. Generates a primary key and optionally notes the effective date for new rows.
8. Inserts new rows to the target.
9. Writes previous values for each changed row into previous columns and replaces previous values with updated values.
10. Optionally uses the system date to note the effective date for inserted and updated values.
11. Updates changed rows in the target.



**Lookup:** Lookup on Target table. Join condition between Source and Lookup/target is EMPID.

Edit Transformations

Transformation

Ports

Properties

Condition

Metadata Extensions

Select transformation:

LKP\_GetData

Transformation type:

Lookup Procedure

	Port Name	Datatype	Prec	Scale	I	O	L	R	Associated Expression	I...	I...
1	IN_EMPID	double	15	0	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	- N/A -	<input type="checkbox"/>	<input type="checkbox"/>
2	EMPID	double	15	0	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	- N/A -	<input type="checkbox"/>	<input checked="" type="checkbox"/>
3	LOCATION	string	100	0	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	- N/A -	<input type="checkbox"/>	<input type="checkbox"/>
4	PM_PRIMARYKEY	decimal	10	0	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	- N/A -	<input type="checkbox"/>	<input type="checkbox"/>

Default value:

Description:

OK

Cancel

Apply

Help

Edit Transformations

Transformation

Ports

Properties

Condition

Metadata Extensions

Select transformation:

LKP\_GetData

Transformation type:

Lookup Procedure

Transformation Attribute	Value
Lookup Sql Override	
Lookup table name	DIM_EMP
Lookup Source Filter	
Lookup caching enabled	<input checked="" type="checkbox"/>
Lookup policy on multiple match	Use Any Value
Lookup condition	EMPID = IN_EMPID
Connection Information	\$Target
Source Type	Database
Tracing Level	Normal
Lookup cache directory name	\$PMCacheDir
Lookup cache persistent	<input type="checkbox"/>
Lookup Data Cache Size	Auto
Lookup Index Cache Size	Auto
Dynamic Lookup Cache	<input type="checkbox"/>
Synchronize Dynamic Cache	<input type="checkbox"/>
Output Old Value On Update	<input type="checkbox"/>
Update Dynamic Cache Condition	TRUE

Lookup Sql Override


Replacement query for lookup values

OK

Cancel


Apply

Help



**Expression:** Derive Flag which can mark incoming records as either INSERT or UPDATE.

LOCATION from Lookup table is mapped as PREV\_LOCATION in Expression.



Edit Transformations

Transformation Ports Properties Metadata Extensions

Select transformation: EXP\_DetectChanges



Transformation type: Expression

	Port Name	Datatype	Prec	Scale	I	O	V	Expression
1	ChangedFlag	integer	10	0	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	IIF(NOT ISNULL(PM_PRIMARYKEY)...
2	NewFlag	integer	10	0	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	IIF(ISNULL(PM_PRIMARYKEY),TRUE,FA...
3	PM_PRIMARYKEY	decimal	10	0	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	PM_PRIMARYKEY
4	LOCATION	string	100	0	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	LOCATION
5	PM_PREV_LOCATION	string	100	0	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	PM_PREV_LOCATION

Default value:


Description:

OK Cancel Apply Help




**Sequence Generator:** Used to generate sequence for loading surrogate key

**Router:** Rout records for either INSERT or UPDATE pipeline.



**UPDATE:** DD\_UPDATE to update the record in target. Ensure that Target structure is having a key as primary key otherwise their update does not work as expected. Please map the Location attribute coming from source to Target.Location. Please map Location coming from Lookup to Target.Prev\_Location.



**SESSION:** Ensure that session is marked as DATA DRIVEN as shown below.