Test Plan: KAN-4

[VWO] Add Passkey and SSO Login Options to VWO Login Page

Issue: KAN-4 (Story)
Priority: Medium (as recorded in Jira)
Status: Draft - pending human review
Prepared: 10 Nov 2026
Components / fix version: Not specified
Linked issues / attachments: None returned by Jira

> **Draft only.** This plan is not approved and must be reviewed by a QA owner. No detailed test cases or automation are authorized until the human review gate is cleared.

1. Scope & Objectives

Story goal: Allow a user to sign in to VWO using Passkey or Single Sign-On (SSO), in addition to the existing authentication methods, for more secure and convenient access.

Objective: Assess the new login options' visibility, expected success and failure outcomes, compatibility, accessibility/responsiveness, and security properties against KAN-4. Pass requires agreed acceptance criteria to be met in the designated staging environment; staging deployment is stated in the ticket's Definition of Done.

In scope:

- Visibility and ordering of both buttons below "Sign in with Google".
- SSO success, invalid-credential handling, and operation with configured identity providers.
- Successful login with a registered passkey, no-passkey guidance/fallback, passkey failure, and unsupported browser/device messaging.
- Responsive/accessibility checks requested by the ticket, plus the stated secure-protocol and sensitive-data protections.

Out of scope: Passkey registration (explicitly assigned to a separate story) and SSO provider configuration. Existing login methods are included only for targeted regression around the changed login page; broader authentication regression scope needs confirmation.

Acceptance-criteria identifiers used for traceability:

- **AC-1 - UI:** Both named options are visible on the login page below Google sign-in.
- **AC-2 - SSO:** Valid SSO authenticates and redirects to the dashboard; invalid credentials show an appropriate error.
- **AC-3 - Passkey:** A registered, verified passkey authenticates and redirects to the dashboard; no passkey produces fallback or guidance.
- **AC-4 - Errors:** Failed SSO, passkey failure, and unsupported browser/device conditions show appropriate messages.
- **AC-5 - Compatibility:** Passkeys work on supported browsers/devices; SSO works with all configured identity providers.
- **AC-6 - Security:** Flows use secure protocols (OAuth/SAML/WebAuthn); sensitive data is not exposed in UI or network logs.
- **TS-1..TS-7 - Ticket-listed scenarios:** Visibility/order, SSO success/failure, passkey success/no passkey, unsupported platforms, and responsive/accessibility checks.

2. Gaps & Questions for the Author

These are unresolved requirements, not assumed behavior. Resolve the blocking items before execution or sign-off.

ID	Finding	Question for the author	Execution impact
G-01	SSO identity providers, tenant routing, and account eligibility are unnamed.	Which configured IdPs and account/tenant types must be covered, and how is each selected?	Blocks complete SSO compatibility coverage.
G-02	"Appropriate error messages" is not defined for SSO rejection.	Which invalid/failure conditions and user-visible messages/recovery actions are expected? Are lockout, retry, and rate-limit behaviors in scope?	Blocks expected-result sign-off for failure paths.
G-03	Passkey fallback and failure recovery are unspecified.	What exact guidance or fallback should appear when no credential exists, an authenticator is unavailable, or verification fails?	Blocks expected-result sign-off for passkey recovery.
G-04	Supported passkey browser/device matrix is not listed.	Which browsers, versions, operating systems, and device/authenticator combinations are supported or unsupported?	Blocks compatibility matrix completion.
G-05	Test identities and authentication data are not provided.	Provide safe staging accounts for valid/invalid SSO, configured IdPs, a registered passkey, and a no-passkey account, with expected account ownership.	Blocks repeatable end-to-end execution.
G-06	Security controls and observability scope are broad.	Which OAuth/SAML/WebAuthn profiles and sensitive fields/log sources are in scope? What role/ownership, replay, session, and redaction checks are required?	Blocks security acceptance beyond basic no-disclosure checks.
G-07	Accessibility is named without a conformance target.	Which WCAG version/level and assistive-technology/browser combinations are required?	Blocks accessibility exit criteria.
G-08	Responsive behavior is named without viewport or device targets.	Which viewport sizes and mobile/tablet layouts should be supported?	Limits responsive coverage.
G-09	No performance/load expectation is stated.	Are response-time, throughput, or load targets required for either login flow?	Performance is not currently an acceptance gate.
G-10	No localization/language requirement is stated.	Which locales and translated messages, if any, must this change support?	Localization coverage is undefined.
G-11	Audit and logging expectations are not specified; the ticket only prohibits sensitive data in UI/network logs.	Which audit events and log sources should be checked, and what safe event fields are expected?	Limits observability verification.
G-12	Regression and backward-compatibility scope is not stated.	Which existing login methods, account types, browsers, and sessions must remain unaffected?	Blocks defining regression exit coverage.
G-13	Staging is mentioned but URL, configuration, and feature flags are absent.	What is the staging URL, required configuration, and flag state for each flow?	Blocks environment readiness.
G-14	Boundary/state behavior is missing.	What should happen on user cancellation, timeout, retry, expired/invalid authentication response, and repeated attempts?	Blocks boundary and state-transition assertions.
G-15	No feature-flag or rollback behavior is documented.	Is the feature gated, and what rollback/disable behavior must be verified?	Operational recovery remains untested.
G-16	Terms such as "seamlessly", "smooth user experience", "supported", and "appropriate" lack measurable outcomes.	Can these terms be replaced with observable UX and compatibility criteria?	Prevents objective pass/fail decisions for those claims.

ID	Finding	Question for the author	Execution impact
G-17	No design/mockup link or exact visual specification is attached to the issue.	Is a design reference available for spacing, labels, responsive layout, and error states?	Placement can be checked only against AC-1's stated order.

3. Test Scenarios

Priority is a proposed risk ranking for review: P0 = core authentication/security gate; P1 = important UX/compatibility; P2 = lower-risk follow-up. It does not change the Jira priority.

ID	Priority	Type	Scenario / expected observation	Trace
TP-01	**P1**	Positive / UI	Open the login page and confirm both exact button labels are visible below "Sign in with Google"; check no overlap or clipping at agreed viewport sizes.	AC-1, TS-1, G-08, G-17
TP-02	**P0**	Positive / SSO	Use a valid staging identity from each configured IdP; verify authentication succeeds and the user reaches the dashboard for the expected account.	AC-2, AC-5, TS-2, G-01, G-05
TP-03	**P0**	Negative / SSO	Attempt SSO with invalid/rejected credentials; verify no authenticated dashboard access and the agreed, non-sensitive error/recovery message is shown.	AC-2, AC-4, TS-3, G-02
TP-04	**P0**	Positive / Passkey	Sign in with a registered passkey and verify successful authentication, correct account, and redirect to the dashboard.	AC-3, TS-4, G-04, G-05
TP-05	**P1**	Negative / Empty state	For an account with no registered passkey, verify the agreed fallback or guidance appears and the user is not incorrectly authenticated.	AC-3, TS-5, G-03, G-05
TP-06	**P0**	Negative / Passkey	Cause a passkey verification failure using approved staging data; verify access is denied and the agreed error/retry path appears without exposing secrets.	AC-4, AC-6, G-03, G-06
TP-07	**P1**	Negative / Compatibility	Attempt passkey sign-in on each agreed unsupported browser/device; verify unsupported capability is handled with the agreed guidance and no misleading success state.	AC-4, AC-5, TS-6, G-04
TP-08	**P1**	Compatibility	Run passkey sign-in across the approved supported browser/device matrix and SSO across every configured IdP; record any platform-specific behavior.	AC-5, TS-6, G-01, G-04
TP-09	**P0**	Security / Negative	Inspect rendered UI and available network/log evidence during approved staging flows; confirm no sensitive authentication data is exposed. Verify a credential for one test account cannot authenticate as a different account.	AC-6, G-05, G-06, G-11
TP-10	**P1**	Responsive / Accessibility	At agreed viewport and assistive-technology combinations, verify both options remain perceivable, operable, and understandable; include keyboard focus/order and error-message association.	TS-7, G-07, G-08, G-17
TP-11	**P1**	Regression	Confirm existing login options still render and their basic flow is not disrupted by the added controls; limit full regression to the scope agreed by the author.	G-12
TP-12	**P2**	Boundary / State	Once expected behavior is defined, exercise cancellation, timeout, retry, and repeated-attempt transitions; confirm no stale or success-shaped state remains.	G-02, G-03, G-14

Coverage note: TP-01 through TP-10 cover every scenario explicitly listed in KAN-4. TP-11/TP-12 are proposed risk-based additions and require the noted scope/behavior confirmations. Test execution is not represented as complete.

4. Test Data & Environment

- **Environment:** Staging is required by the ticket's Definition of Done. URL, build, flags, and environment setup are TBD (G-13).

- **Data:** Safe staging users with valid and invalid SSO, accounts for each configured IdP, a registered passkey, and a no-passkey account. No real user credentials or production secrets should be used (G-05).
- **Platform matrix:** Supported/unsupported browser, OS, device, and authenticator combinations must be confirmed before execution (G-04).
- **Roles / permissions:** User roles, account eligibility, and passkey ownership expectations are not specified (G-01, G-06).
- **Evidence:** Capture sanitized screenshots and approved test logs/network evidence only; do not retain credentials, tokens, or private authentication material.

5. Risks & Assumptions

- **Risk:** Missing provider and browser matrices can leave compatibility gaps despite apparently passing tests.
- **Risk:** Undefined error/fallback copy makes failure-path results subjective and can conceal user lockout or unsafe recovery.
- **Risk:** Inadequate staging identities or authenticator setup can prevent valid end-to-end coverage.
- **Risk:** Broad security language lacks measurable protocol and logging requirements; security sign-off cannot be inferred from happy-path tests.
- **Assumption:** Dashboard means the authenticated landing destination for the test account; exact route and redirect details are unconfirmed.
- **Assumption:** The ticket's listed flows and outcomes are authoritative; this plan does not infer a provider setup or passkey-registration feature.
- **Company context (provided, unverified):** The supplied company note describes VWO as a "Bingify" product focused on A/B testing and states approximately 5,000 employees. The supplied logo image is branded TheTestingAcademy; its relationship to the company is unconfirmed. Confirm the company name and branding before external circulation.

6. Entry / Exit Criteria

Entry

- Feature is deployed and accessible in the named staging environment; test flags/configuration are documented.
- QA-approved test identities, IdP access, registered/no-passkey accounts, and platform matrix are available.
- Blocking expected behaviors and the required accessibility/security scope are agreed (G-01 through G-08, G-13, G-14).

Exit

- All agreed acceptance criteria and required scenarios have recorded results and traceable evidence.
- No open Critical or High defects remain, consistent with the ticket's Definition of Done; remaining defects have explicit owner and acceptance.
- Security, compatibility, accessibility, and regression results are reviewed against approved criteria; deviations are documented.
- QA owner approves this plan and the execution results. No approval is implied by this draft.

7. Resource Allocation

Role	Contribution needed	Owner / allocation
QA owner / test lead	Resolve scope, approve criteria, review results and sign off.	TBD
QA engineer	Execute login, error, compatibility, responsive, and accessibility scenarios; record evidence.	TBD
Identity / authentication engineer	Provide staging IdPs, safe identities, supported-platform details, and log/security guidance.	TBD
Product / story author	Answer open behavior, UX, and scope questions.	TBD
Accessibility reviewer	Confirm and assess accessibility expectations if required.	TBD

8. Timelines & Sprint Details

The Jira response provided no sprint, fix version, or test dates. Target dates, duration, and execution sequence are **TBD**; confirm with the QA owner after entry criteria are met. The ticket requires staging deployment and QA sign-off but does not state a schedule.

Requirement Checklist

Checklist status reflects the ticket only: **Present** = stated clearly; **Ambiguous** = partially stated or not measurable; **Missing** = not specified.

Area	Requirement	Status	Evidence / gap
Functional	Clear user story / goal	Present	Explicit user story explains sign-in goal.
Functional	Acceptance criteria testable	Ambiguous	Core outcomes exist; "appropriate", "supported", and secure-protocol detail are undefined (G-02, G-04, G-06, G-16).
Functional	Happy path fully described	Present	SSO and verified passkey success redirect to dashboard.
Functional	Negative / error paths described	Ambiguous	Failure classes listed, but expected messages/recovery are unspecified (G-02, G-03).
Functional	Boundary & empty states	Missing	No timeout, cancellation, retry, or repeated-attempt rules (G-14).
Functional	State transitions / workflow steps	Ambiguous	Click, authenticate, and redirect are stated; intermediate/cancel/error transitions are absent (G-14).
Data & environment	Test data specified or derivable	Missing	No accounts or identity data are supplied (G-05).
Data & environment	Environment / configuration / flags	Ambiguous	Staging deployment is required; URL and configuration are absent (G-13).
Data & environment	External dependencies / integrations	Ambiguous	Configured IdPs and WebAuthn-capable platforms are implied but unnamed (G-01, G-04).
Data & environment	Preconditions / setup	Missing	Test-account and authenticator setup are not stated (G-05, G-13).
Non-functional	Performance / load expectations	Missing	No threshold or workload is stated (G-09).
Non-functional	Security / authorization	Ambiguous	Protocols and no-disclosure intent are stated; ownership, roles, and specific controls are not (G-06).
Non-functional	Accessibility expectations	Ambiguous	Accessibility scenario is requested; standard/level is not stated (G-07).
Non-functional	Internationalization / localization	Missing	No locale or language criteria are stated (G-10).
Non-functional	Audit / logging / observability	Ambiguous	Network-log data exposure is prohibited; audit events and log sources are undefined (G-11).
Cross-cutting	Impact on existing features	Ambiguous	Options are added beside existing methods; regression expectations are absent (G-12).
Cross-cutting	Backward compatibility / migration	Missing	No compatibility or migration statement is included (G-12).
Cross-cutting	Mobile / responsive / browser matrix	Ambiguous	Responsive and passkey support are mentioned without targets (G-04, G-08).
Cross-cutting	Rollback / feature-flag behavior	Missing	No rollout/rollback controls are described (G-15).
Clarity	Unambiguous wording	Ambiguous	"Smooth", "seamlessly", and "appropriate" have no measurable definition (G-16).
Clarity	Terms defined consistently	Ambiguous	SSO is expanded; supported providers/platforms and fallback terminology need definition (G-01, G-04, G-16).
Clarity	Mockups / designs linked and aligned	Missing	No design or visual reference was returned (G-17).

HUMAN REVIEW GATE - REQUIRED

Assumed: "Dashboard" is the authenticated landing destination; staging is the execution environment because the Definition of Done requires deployment there; no registration flow or provider configuration is in scope.

Could not confirm: Supported browser/device and IdP matrices, staging access details, test data, exact errors/fallbacks, non-functional thresholds, regression scope, sprint/timing, and the company/logo identity pairing.

Open questions blocking sign-off: Resolve the blocking questions in G-01 through G-08, G-13, and G-14; agree the remaining security, accessibility, regression, and operational scope.

QA owner action: Review and approve or edit this draft before it is treated as an approved plan or before detailed test cases/automation are written.

Source: Jira KAN-4, fetched 10 Nov 2026. Components, fix versions, linked issues, and attachments were not returned. Status remains draft pending human approval.