



12:11



alakshmicolleges.org



REC-CIS

2

3

1

Explanation

The input array is [1, 3, 2, 4, 5], so the reverse of the input array is [5, 4, 2, 3, 1]

Sample Case 1**Sample Input For Custom Testing**

4

17

10

21

45

Sample Output

45

21

10

17

Explanation

The input array is [17, 10, 21, 45], so the reverse of the input array is [45, 21, 10, 17].

Answer: (penalty regime: 0 %)

Reset answer

```

1. /*
2.  * Complete the 'reverseArray' function below
3.  *
4.  * The function is expected to return an int*
5.  * The function accepts INTEGER_ARRAY arr and int n as parameters.
6.  */
7.
8. /*
9.  * To return the integer array from the function, you must:
10.  * - Store the size of the array to be returned in a variable (e.g., result_count)
11.  * - Allocate the array statically or dynamically (e.g., using malloc)
12.  *
13.  * For example,
14.  * int* return_integer_array_using_static_allocation(int n)
15.  * {
16.  *     static int a[5] = {1, 2, 3, 4, 5};
17.  *     return a;
18.  * }
19.  *
20.  * int* return_integer_array_using_dynamic_allocation(int n)
21.  * {
22.  *     int* result_count = 5;
23.  *     int* a = malloc(5 * sizeof(int));
24.  *     for (int i = 0; i < 5; i++) {
25.  *         *(a + i) = i + 1;
26.  *     }
27.  *     return a;
28.  * }
29.  */
30.
31. int* reverseArray(int n, int *a, int *result_count)
32. {
33.     int *b=(int*)malloc(sizeof(int)*n);
34.     for(int i=0;i<n;i++){
35.         b[i]=a[n-i-1];
36.     }
37.     return b;
38. }
39.
40.
41.
42.
43.
44.
45.

```

Test

```

✓ int arr[] = {1, 3, 2, 4, 5};
  int result_count;
  int* result = reverseArray(5, arr, &result_count);
  for (int i = 0; i < result_count; i++)
      printf("%d\n", *(result + i));

```

Passed all tests! ✓



REC-CIS

STDIN Function

3 → lengths[] size n = 3
5 → lengths[] = [5, 6, 2]
6
2
12 → minLength = 12

Sample Output

Impossible

Explanation

The uncut rod is $5 + 6 + 2 = 13$ units long. After making either cut, the rod will be too short to make the second cut.

Answer: (penalty regime: 0 %)

Reset answer

```
1 /*
2  * Complete the 'cutThemAll' function below.
3  *
4  * The function is expected to return a string.
5  * The function accepts following parameters:
6  * 1. LONG_INTEGER_ARRAY lengths
7  * 2. LONG_INTEGER minLength
8  */
9
10 /*
11  * To return the string from the function
12  *
13  * For example,
14  * char* return_string_using_static_allocation() {
15  *     static char s[] = "static allocation";
16  *     return s;
17  * }
18  *
19  * char* return_string_using_dynamic_allocation() {
20  *     char* s = malloc(100 * sizeof(char));
21  *     s = "dynamic allocation of string";
22  *     return s;
23  * }
24  *
25  * }
26  */
27
28 #include<stdio.h>
29
30 int cmp(const void*a,const void*b){
31     return(*(int*)a)-*(int*)b;
32 }
33
34 char* cutThemAll(int n, long *a, long mL)
35 {
36     int s=0;
37     for(int i=0;i<n;i++){
38         s+=a[i];
39     }
40     long r=s;
41     qsort(a,n,sizeof(long),cmp);
42     for(int i=0;i<n;i++){
43         if(r==mL){
44             return "Possible";
45         }
46         if(r>mL){
47             r-=a[i];
48         }
49         else{
50             return "Impossible";
51         }
52     }
53 }
```

	Test	Ex
✓	long lengths[] = {3, 5, 4, 3}; printf("%s", cutThemAll(4, lengths, 9))	Pos
✓	long lengths[] = {5, 6, 2}; printf("%s", cutThemAll(3, lengths, 12))	Im

Passed all tests! ✓