



To find the day of year number for a standard date, scan down the Jan column to find the day of month, then scan across to the appropriate month column and read the day of year number. Reverse the process to find the standard date for a given day of year.

Write a program to print the Day of Year of a given date, month and year.

Sample Input 1

18

6

2020

Sample Output 1

170

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {
4     int d,m,y,feb;
5     scanf("%d%d%d",&d,&m,&y);
6     if((y%100!=0&& y%400)|| (y%4!=0))
7     {
8         feb=29;
9     }
10    else
11    {
12        feb=28;
13    }
14    switch(m)
15    {
16        case 1:
17            printf("%d",d);
18            break;
19        case 2:
20            printf("%d",31+d);
21            break;
22        case 3:
23            printf("%d",31+feb+d);
24            break;
25        case 4:
26            printf("%d",31+feb+31+d);
27            break;
28        case 5:
29            printf("%d",31+feb+31+30+d);
30            break;
31        case 6:
32            printf("%d",31+feb+31+30+31+d);
33            break;
34        case 7:
35            printf("%d",31+feb+31+30+31+30+d);
36            break;
37        case 8:
38            printf("%d",31+feb+31+30+31+30+31+d);
39            break;
40        case 9:
41            printf("%d",31+feb+31+30+31+30+31+30+d);
42            break;
43        case 10:
44            printf("%d",31+feb+31+30+31+30+31+30+31+d);
45            break;
46        case 11:
47            printf("%d",31+feb+31+30+31+30+31+30+31+30+d);
48            break;
49        case 12:
50            printf("%d",31+feb+31+30+31+30+31+30+31+30+31+d);
51            break;
52    }

```

	Input	Expected	Got	
✓	18	170	170	✓
	6			
	2020			

Passed all tests! ✓

Correct

Marked out of
7.00

Flag question

squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```

1 #include <stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d%d%d",&a,&b,&c);
6     if(a>b&&a>c)
7     {
8         if(c*c+b*b==a*a)
9         {
10            printf("yes");
11        }
12        else
13        {
14            printf("no");
15        }
16    }
17    else if(b>a&&b>c)
18    {
19        if(a*a+c*c==b*b)
20        {
21            printf("yes");
22        }
23        else
24        {
25            printf("no");
26        }
27    }
28    else if(c>a&&c>b)
29    {
30        if(a*a+b*b==c*c)
31        {
32            printf("yes");
33        }
34        else{
35            printf("no");
36        }
37    }
38    return 0;
39 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓



24

Sample Output 1

Not Weird

Explanation*Sample Case 0: $n = 3$* n is odd and odd numbers are weird, so we print **Weird**.*Sample Case 1: $n = 24$* $n > 20$ and n is even, so it isn't weird. Thus, we print **Not Weird**.**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int a;
5     scanf("%d",&a);
6     if(a%2==0)
7     {
8         if(a>20)
9         {
10             printf("Not Weird");
11         }
12         else if(a>5&&a<21)
13         {
14             printf("Weird");
15         }
16         else if(a>2&&a<5)
17         {
18             printf("Not Weird");
19         }
20     }
21     else if(a%2!=0)
22     {
23         printf("Weird");
24     }
25     return 0;
26 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓



ng Using C-2024

Status Finished**Started** Monday, 23 December 2024, 5:33 PM**Completed** Saturday, 9 November 2024, 11:19 AM**Duration** 44 days 6 hours

Question 1

Correct

Marked out of
3.00[Flag question](#)

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```

1 #include <stdio.h>
2 int main()
3 {
4     int a,b;
5     scanf("%d%d",&a,&b);
6     a=a%10;
7     b=b%10;
8     if(a==b)
9     {
10         printf("true");
11     }
12     else
13     {
14         printf("false");
15     }
16     return 0;
17 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question 2

Question 3

Correct

Marked out of
7.00

Flag question

Superman is planning a journey to his home planet. It is very important for him to know which day he arrives there. They don't follow the 7-day week like us. Instead, they follow a 10-day week with the following days: Day Number Name of Day
1 Sunday 2 Monday 3 Tuesday 4 Wednesday 5 Thursday 6 Friday 7 Saturday 8 Kryptonday 9 Coluday 10 Daxamday
Here are the rules of the calendar: • The calendar starts with Sunday always. • It has only 296 days. After the 296th day, it goes back to Sunday. You begin your journey on a Sunday and will reach after n. You have to tell on which day you will arrive when you reach there.

Input format: •

Contain a number n ($0 < n$)

Output format: Print the name of the day you are arriving on

Example Input

7

Example Output

Kryptonday

Example Input

1

Example Output Monday

Answer: (penalty regime: 0 %)

```

1 #include <stdio.h>
2 int main()
3 {
4     int n, day;
5     scanf("%d", &n);
6     if(n < 296)
7         day = n;
8     else
9         day = n - 296;
10    day %= 10;
11    day = day + 1;
12    day %= 10;
13    switch(day)
14    {
15        case 1:
16            printf("Sunday");
17            break;
18        case 2:
19            printf("Monday");
20            break;
21        case 3:
22            printf("Tuesday");
23            break;
24        case 4:
25            printf("Wednesday");
26            break;
27        case 5:
28            printf("Thursday");
29            break;
30        case 6:
31            printf("Friday");
32            break;
33        case 7:
34            printf("Saturday");
35            break;
36        case 8:
37            printf("Kryptonday");
38            break;
39        case 9:
40            printf("Coluday");
41            break;
42        case 10:
43            printf("Daxamday");
44            break;
45    }
46    return 0;
47 }
```

	Input	Expected	Got	
✓	7	Kryptonday	Kryptonday	✓
✓	1	Monday	Monday	✓

Passed all tests! ✓



REC-CIS

100

Sample Input 4

G

8

8

Sample Output 4

0

Sample Input

C

9

10

Sample Output 4

0

Explanation:

- First is output of area of rectangle
- Then, output of area of triangle
- Then output of area square
- Finally, something random, so we print 0

Answer: (penalty regime: 0 %)

```

1 #include <stdio.h>
2 int main() {
3     int area,tarea,side1,side2;
4     char a;
5     scanf("%c",&a);
6     scanf("%d",&side1);
7     scanf("%d",&side2);
8     area=side1*side2;
9     tarea=area/2;
10    if(a=='T' || a=='R'){
11        printf("%d",area);
12    }
13    else if(a=='S'){
14        printf("%d",tarea);
15    }
16    else{
17        printf("0");
18    }
19    return 0;
20 }

```

	Input	Expected	Got	
✓	T 10 20	200	200	✓
✓	S 30 40	600	600	✓
✓	B 2 11	0	0	✓
✓	R 10 30	300	300	✓
✓	S 40 50	1000	1000	✓

Passed all tests! ✓