

```

5
1 1 4 1 1
4
2 0 0 0
4
0 0 2 0

```

Sample Output 1

```

YES
YES
YES

```

Explanation 1

In the first test case, $arr[2] = 4$ is between two subarrays summing to 2

In the second case, $arr[0] = 2$ is between two subarrays summing to 0

In the third case, $arr[2] = 2$ is between two subarrays summing to 0

Answer: (penalty regime: 0 %)

```

1 #include<stdio.h>
2 int main()
3 {
4     int t,n,ls,rs,m;
5     scanf("%d",&t);
6     for(int i=0;i<t;i++)
7     {
8         ls=0;
9         rs=0;
10        scanf("%d",&n);
11        int arr[n];
12        for(int j=0;j<n;j++)
13            scanf("%d",&arr[j]);
14        m=n/2;
15        if(arr[m]==0)
16        {
17            for(m=0;arr[m]==0 && m<n;m++)
18            }
19            for(int j=0;j<=m;j++)
20                ls=ls+arr[j];
21            for(int j=m;j<n;j++)
22                rs=rs+arr[j];
23            printf("%s\n",(ls==rs)? "YES" : "N
24        }
25        return 0;
26    }

```

	Input	Expected	Got	
✓	3	YES	YES	✓
	5	YES	YES	
	1 1 4 1 1	YES	YES	
	4			
	2 0 0 0			
	4			
	0 0 2 0			
✓	2	NO	NO	✓
	3	YES	YES	
	1 2 3			
	4			
	1 2 3 3			

Passed all tests! ✓

10

203 204 205 206 207 208 203 204 205 206

13

203 204 204 205 206 207 205 208 203 206 205 206 204

Sample Output

204 205 206

Explanation

204 is present in both arrays. Its frequency in **arr** is **2**, while its frequency in **brr** is **3**. Similarly, **205** and **206** occur twice in **arr**, but three times in **brr**. The rest of the numbers have the same frequencies in both lists.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,m,c,cl=0,co;
5     scanf("%d",&n);
6     int arr[n];
7     for(int a=0;a<n;a++)
8     {
9         scanf("%d",&arr[a]);
10    }
11    scanf("%d",&m);
12    int brr[m],ans[n];
13    for(int b=0;b<m;b++)
14    {
15        scanf("%d",&brr[b]);
16    }
17    for(int j=0;j<m;j++)
18    {
19        c=0;
20        for(int i=0;i<n;i++)
21        {
22            if(arr[i]==brr[j])
23            {
24                c++;
25                arr[i]=-1;
26                break;
27            }
28        }
29        if(c==0)
30        {
31            ans[cl]=brr[j];
32            cl++;
33        }
34    }
35    for(int a=0;a<cl;a++)
36    {
37        co=0;
38        for(int b=0;b<cl;b++)
39        {
40            if(ans[b]<ans[a])
41                co++;
42        }
43        int temp=ans[a];
44        ans[a]=ans[co];
45        ans[co]=temp;
46    }
47    for(int i=0;i<cl;i++)
48        printf("%d ",ans[i]);
49    return 0;
50 }
```

	Input
✓	10 203 204 205 206 207 208 203 204 205 206 13 203 204 204 205 206 207 205 208 203 206 205 206 204

Passed all tests! ✓

2
4
5
1 4 5 3 2
4
4
2 2 4 3

Sample Output

1 4
1 2

Explanation

Sunny and Johnny make the following two trips to the parlor:

1. The first time, they pool together $m = 4$ dollars. Of the five flavors available that day, flavors **1** and **4** have a total cost of $1 + 3 = 4$.
2. The second time, they pool together $m = 4$ dollars. Of the four flavors available that day, flavors **1** and **2** have a total cost of $2 + 2 = 4$.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int t,m,n,c=0;
5     scanf("%d",&t);
6     for(int i=0;i<t;i++)
7     {
8         c=0;
9         scanf("%d\n%d",&m,&n);
10        int arr[n];
11        for(int j=0;j<n;j++)
12        {
13            scanf("%d",&arr[j]);
14        }
15        for(int a=0;a<n-1;a++)
16        {
17            for(int b=a+1;b<n;b++)
18            {
19                if(arr[a]+arr[b]==n)
20                {
21                    printf("%d %d\n",a+1,b+1);
22                    c=1;
23                    break;
24                }
25            }if(c==1) break;
26        }
27    }
28    return 0;
29 }
```

	Input	Expected	Got	
✓	2	1 4	1 4	✓
	4	1 2	1 2	
	5			
	1 4 5 3 2			
	4			
	4			
	2 2 4 3			

Passed all tests! ✓