



Railway Track Allocation System

Deadlock Avoidance using Banker's Algorithm for Safe Junction Management

The Junction Challenge

Railway junctions are high-risk bottlenecks where multiple paths converge. Without precise control, trains from different directions can compete for shared track sections simultaneously.

A **Deadlock** occurs when Train A waits for a track held by Train B, which is waiting for a track held by Train A. This circular wait paralyzes the entire system.

Proposed Solution Architecture



Central Controller

A smart allocation unit that processes resource requests from incoming trains based on global system state.



Safe State Logic

Uses Banker's Algorithm to simulate the outcome of a request before granting access to a track.



Resource Mapping

Tracks are treated as non-preemptive resources, ensuring integrity of the physical path.

Mapping Banker's Algorithm to Rail

Classical Algorithm

Processes (P)

Resource Types (R)

Maximum Demand

Available Resources

Railway Context

Approaching Trains (T)

Track Sections (S)

Full Path Requirement

Vacant Track Segments

System State Matrices

To evaluate safety, the system maintains four key data structures:

Allocation Matrix

Track sections currently occupied by each train.

Max Demand Matrix

The complete set of sections a train needs to exit the junction.

Available Vector

Current count of free sections per track type.

$$\text{Need} [i , j] = \text{Max} [i , j] - \text{Allocation} [i , j]$$

Snapshot: Three Trains, Three Sections

Train ID	Allocated (S1, S2, S3)	Max Demand (S1, S2, S3)	Available (S1, S2, S3)
Train T1 (Express)	[0, 1, 0]	[7, 5, 3]	[3, 3, 2]
Train T2 (Freight)	[2, 0, 0]	[3, 2, 2]	
Train T3 (Commuter)	[3, 0, 2]	[9, 0, 2]	

Calculated Need Matrix

The system calculates the remaining resources each train requires to finish its journey across the junction.

📊 T1 Need: [7, 4, 3]

📊 T2 Need: [1, 2, 2]


📊 T3 Need: [6, 0, 0]

Safety Check: Can we satisfy T2's need?

Available [3, 3, 2] $\geq$ T2 Need [1, 2, 2].

Yes! T2 can proceed and eventually release its resources.

Safety Sequence Execution



Start

Avail: [3, 3, 2]

Step 1: T2

T2 Finishes.
New Avail: [5, 3, 2]

Step 2: T3


T3 Finishes.
New Avail: [8, 3, 4]

Step 3: T1

T1 Finishes.
Safe State!

Resulting Safe Sequence: < T2, T3, T1 >

Section Utilization Comparison



The Banker's Algorithm prevents any request that would push these metrics into an "Unsafe Region" where deadlock is possible.

Modern Traffic Control Integration



- ✓ **Real-time Monitoring:** Sensors relay current track occupancy.
- ✓ **Automated Denial:** If a train's move makes the system unsafe, it is held at a signal.
- ✓ **Optimization:** Dynamically recalculates safety with every signal change.

Benefits of Banker's Approach

100%

Deadlock Immunity

Mathematically guaranteed avoidance of circular wait conditions.

0

Human Error

Automation removes the risk of manual signaling mistakes during peak hours.

High

Throughput

Trains are packed closer together without compromising safety limits.



Conclusion & Questions

The Railway Track Allocation System leveraging Banker's Algorithm provides a robust, mathematical foundation for modern rail safety, ensuring junctions remain fluid and free from paralysis.

Lead Architect: Engineering Team

System State: SAFE

Image Sources



https://images.stockcake.com/public/1/9/9/199408cc-3c91-4dea-aa8c-1b19ab8041f3_medium/intricate-rail-network-stockcake.jpg

Source: stockcake.com



https://storage.googleapis.com/consortdigital-327d9.firebaseiostorage.app/portfolio/train-radio-control-panel-5205/gallery/main/slot_1.webp

Source: consortdigital.com