Reg.No: 210701259

Exp.No: 8

IMPLEMENT SVM/DECISION TREE CLASSIFICATION TECHNIQUES

AIM:

To write an R code to implement SVM/decision tree classification techniques.

PROCEDURE:

- 1. Install and load the required packages (e1071 for SVM and rpart for Decision Tree) and load the iris dataset.
- 2. Split the dataset into training (70%) and testing (30%) sets using a reproducible random sampling method.
- 3. Fit the SVM model with a radial kernel using the training data, print the model summary, and evaluate its performance using a confusion matrix and accuracy calculation.
- 4. Fit the Decision Tree model using the rpart function with the training data, print the model summary, visualize the tree, and evaluate its performance using a confusion matrix and accuracy calculation.
- 5. Predict the test set results for both SVM and Decision Tree models and assess their accuracy.

PROGRAM CODE:

a) SVM IN R

```
# Install and load the e1071 package (if not already installed)
install.packages("e1071") library(e1071)

# Load the iris dataset data(iris)

# Inspect the first few rows of the dataset head(iris)

# Split the data into training (70%) and testing (30%) sets set.seed(123)

# For reproducibility
sample_indices <- sample(1:nrow(iris), 0.7 * nrow(iris)) train_data
<- iris[sample_indices, ]

test_data <- iris[-sample_indices, ]

# Fit the SVM model svm_model <- svm(Species ~ ., data = train_data, kernel = "radial")
```

Reg.No: 210701259

```
# Print the summary of the model summary(svm_model)


# Predict the test set predictions <- predict(svm_model,
newdata = test_data)

# Evaluate the model's performance
confusion_matrix <- table(Predicted = predictions, Actual = test_data$Species)
print(confusion_matrix)

# Calculate accuracy
accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix) cat("Accuracy:",</pre>
```

OUTPUT:

accuracy * 100, "%\n")



b) Decision tree in R

Load the iris dataset data(iris)

```
# Install and load the rpart package (if not already installed) install.packages("rpart") library(rpart)
```

```
# Split the data into training (70%) and testing (30%) sets set.seed(123)
# For reproducibility
sample_indices <- sample(1:nrow(iris), 0.7 * nrow(iris)) train_data
<- iris[sample_indices, ]
test_data <- iris[-sample_indices, ]
```

```
# Fit the Decision Tree model
tree_model <- rpart(Species ~ ., data = train_data, method = "class")
```

Print the summary of the model summary(tree_model)

Reg.No: 210701259

```
text(tree_model, pretty = 0)


# Predict the test set predictions <- predict(tree_model, newdata =
test_data, type = "class")

# Evaluate the model's performance
confusion_matrix <- table(Predicted = predictions, Actual = test_data$Species)
print(confusion_matrix)

# Calculate accuracy
accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix) cat("Accuracy:",
accuracy * 100, "%\n")</pre>
```

OUTPUT:

Plot the Decision Tree plot(tree model)



RESULT:

Thus the R program to implement SVM/decision tree classification techniques has been executed and verified successfully.