

Vijay's Blog

 Follow

Fundamentals of Ansible



vijaykumar guntireddy

Aug 26, 2024 •  12 min read

Table of contents

Configuration Management

Ansible

Sample Playbook which will do Ping operation

Ansible Variables

Ansible variables preference order

Ansible inventory

Ansible Datatypes

Ansible conditions

Ansible Gathering Facts

Ansible loops



Ansible Functions/Filters

Command vs Shell

Challenges and solutions

Possible interview questions

Show less ^

Configuration Management

- Converting a plain server to ready serve a application

Disadvantages of Shell scripting

- Not Idempotent
- Error handling
- Homogenous
- not scalable when too many servers
- syntax is not easy to understand

CM tools - Ansible , puppet , chef , rundeck etc.

We have two types of architecture in CM

- push vs pull


Lets understand this with simple example

- we are getting a courier from Delhi to Hyderabad.
- we have two options
 - Go to the courier office everyday and check for courier - **PULL**

- Wait in the home and courier office will deliver when every package is received. - **PUSH**
- Disadvantages in PULL
 - more traffic in internet
 - bandwidth
 - cost

Ansible

- Ansible is push based architecture



- Ansible will connect to all nodes(servers) and loads the configuration

- Ansible uses SSH protocol.
- In Ansible 10% cases it uses PULL.
- The system where ansible is loaded is called ansible server and all nodes will be connected to this ansible server.

Ansible Inventory

- List of servers ansible is managing
- Linux commands - dnf etc → these are called as modules in ansible.
- Do following operations
 - Connect to node
 - install nginx
 - run nginx

COPY

```
#From ansible server
$ansible -i 172.31.41.249, all -e ansible_user=ec2-user -e ansible_
172.31.41.249 | UNREACHABLE! => {
    "changed": false,
    "msg": "Failed to connect to the host via ssh: ssh: connect to
    "unreachable": true
}

#install it as a root option -b
$ansible -i 18.209.110.154, all -e ansible_user=ec2-user -e ansible_
18.209.110.154 | CHANGED => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3"
    },
    "changed": true,
    "msg": "",
```



```

    "rc": 0,
    "results": [
        "Installed: nginx-filesystem-1:1.20.1-14.el9_2.1.noarch",
        "Installed: nginx-core-1:1.20.1-14.el9_2.1.x86_64",
        "Installed: redhat-logos-httpd-90.4-2.el9.noarch",
        "Installed: nginx-1:1.20.1-14.el9_2.1.x86_64"
    ]
}

#if already installed state will not change
$ ansible -i 18.209.110.154, all -e ansible_user=ec2-user -e ansible_
18.209.110.154 | SUCCESS => {
    "ansible_facts": {
        "discovered_interpreter_python": "/usr/bin/python3"
    },
    "changed": false,
    "msg": "Nothing to do",
    "rc": 0,
    "results": []
}

#To start nginx
$ansible -i 18.209.110.154, all -e ansible_user=ec2-user -e ansible_

```


Adhoc commands

- command issued from ansible server targeting node manually, basically on some emergency/adhoc purpose

Running these commands in one file with simple syntax can be done with Ansible

Playbooks (yet another markup language)

- list of plays which contains modules that can do specific task in the ansible server.



- Ansible modules documentation :
https://docs.ansible.com/ansible/2.9/modules/list_of_all_modules.html

Sample Playbook which will do Ping operation

created 01-ping.yaml file with below content

COPY

```

- name: ping operation
  host: web #which hosts ansible can connect to
  task: # list of modules
    - name: ping the server
      ansible.builtin.ping:
          
```

Inventory - List of servers where we can group .

created inventory.ini file with IP address of the node

COPY

```

[web]
172.31.35.211
          
```



add this folder to your github repository

COPY

```

vijay@vijay_lenovo MINGW64 /c/Vijay/devops (master)
$git remote add origin <github url>
$git add . ; git commit -m "ansible" ; git push origin master

```

download these files in AWS ansible server and execute ansible command

The ansible node will be pinged from Ansible server.

COPY

```

#install ansible
$ sudo dnf install ansible -y
#download the project
$ git clone https://github.com/qtivijay/devopsaws.git
$ cd devopsaws/
$ cd ansible1/
#execute ansible command
$ ansible-playbook -i inventroy.ini -e ansible_user=ec2-user -e ans

```

```
PLAY [ping the server] *****
```

```

TASK [Gathering Facts] *****
ok: [172.31.35.211]

```

```

TASK [ping the server] *****
ok: [172.31.35.211]

```

```

PLAY RECAP *****
172.31.35.211          : ok=2    changed=0    unreachable=0

```



Multiplay example

COPY

```
- name: multiplay
  hosts: web
  tasks:
    - name: play01 task01
      ansible.builtin.debug:
        msg: "This is from PLAY-01 and TASK-01"

- name: multiplay
  hosts: web
  tasks:
    - name: play02 task01
      ansible.builtin.debug:
        msg: "This is from PLAY-02 and TASK-01"
```

Install and run nginx (imp: **become**)

COPY

```
- name: nginx install and run
  hosts: web
  become: yes #take sudo access
  tasks:
    - name: install nginx
      ansible.builtin.package: #heterongenous module that can work for
        name: nginx
        state: present

    - name: run nginx
      ansible.builtin.service:
        name: nginx
```




```
state: started
enabled: yes
```

Ansible Variables

1 . Declaring variables in yaml (**vars**)

COPY

```
- name: variables to print
hosts: web
vars:
  COURSE: "DevOps with AWS"
  DURATION: "120HRS"
  TRAINER: "Sivakumar Reddy M"
tasks:
- name: print the information
  ansible.builtin.debug:
    msg: "Hi, I am learning {{COURSE}}, Duration is: {{DURATION}}"
```

2. Task level variables (**vars**)

COPY

```
- name: variables to print
hosts: web
vars: #play level, all tasks in this play have access to this
  COURSE: "DevOps with AWS"
  DURATION: "120HRS"
  TRAINER: "Sivakumar Reddy M"
tasks:
- name: print the information
  ansible.builtin.debug:
    msg: "Hi, I am learning {{COURSE}}, Duration is: {{DURATION}}"
```



```
- name: print the information again
vars: #task level variables override play level
  COURSE: "Ansible"
ansible.builtin.debug:
  msg: "Hi, I am learning {{COURSE}}, Duration is: {{DURATION}}

- name: print the information again and again
ansible.builtin.debug:
  msg: "Hi, I am learning {{COURSE}}, Duration is: {{DURATION}}"
```

3. variables in another file (**vars_file**)

[COPY](#)

```
- name: variables from files
hosts: web
vars_files:
- vars.yaml
tasks:
- name: print the course information
  ansible.builtin.debug:
    msg: "Hi, I am learning {{COURSE}}, Duration is: {{DURATION}}"
```

vars.yaml

[COPY](#)

```
COURSE: "DevOps with AWS from Files"
DURATION: "150HRS"
TRAINER: "Sivakumar Reddy M"
```



4. Variables through prompt (**vars_prompt** , **prompt** , **private**)

```

- name: variables from prompt
  hosts: web
  vars_prompt:
    - name: COURSE
      prompt: Please enter the course name
      private: false # not confidential
    - name: TRAINER
      prompt: Please enter the trainer name
      private: false # not confidential
    - name: DURATION
      prompt: Please enter the duration
      private: false # not confidential
  tasks:
    - name: print the course information
      ansible.builtin.debug:
        msg: "Hi, I am learning {{COURSE}}, Duration is: {{DURATION}}

```

5. Variables from inventory file ([web:vars])

```

[web]
172.31.43.207

[web:vars]
COURSE="AWS"
DURATION="10HRS"
TRAINER="Sivakumar Reddy"

```

```

- name: variables to print
  hosts: web
  tasks:

```



```
- name: print the information
  ansible.builtin.debug:
    msg: "Hi, I am learning {{COURSE}}, Duration is: {{DURATION}}"
```

6. Variables from command arguments (-e "args")

```
- name: variables to print
  hosts: web
  tasks:
    - name: print the information
      ansible.builtin.debug:
        msg: "Hello {{NAME}}, Good {{GREETING}}"
```

COPY

```
command : ansible-playbook -i inventroy.ini -e ansible_user=ec2-user
```

COPY

Ansible variables preference order

```
#1. command line/args
#2. Task level - vars
#3. Files - vars_files:
#4. prompt - vars_prompt
#5. Play - vars
#6. inventory - [web:vars]
```

COPY



COPY

```
- name: variables to print
hosts: web
# vars:
#   COURSE: "DevOps with AWS from PLAY level"
#   DURATION: "120HRS"
#   TRAINER: "Sivakumar Reddy M"
# vars_files:
# - vars.yaml
# vars_prompt:
# - name: COURSE
#   prompt: Please enter the course name
#   private: false # not confidential
tasks:
- name: print the information
  vars:
    #COURSE: "DevOps with AWS from TASK level"
    DURATION: "120HRS"
    TRAINER: "Sivakumar Reddy M"
  ansible.builtin.debug:
    msg: "Hi, I am learning {{COURSE}}"
```

Ansible inventory

In Ansible inventory we have three types

- ungrouped
- grouped
- group of groups

COPY

192.168.1.1

192.168.1.2

192.168.1.3



```
[web]
```

```
172.31.45.75
```

```
[web:vars]
```

```
DURATION="10HRS"
```

```
TRAINER="Sivakumar Reddy"
```

```
[backend]
```

```
192.168.1.4
```

```
192.168.1.5
```

```
192.168.1.6
```

```
[mysql]
```

```
192.168.1.7
```

```
192.168.1.8
```

```
192.168.1.9
```

```
[servers:children]
```

```
web
```

```
backend
```

```
[local]
```

```
localhost
```

```
[web:vars]
```

```
ansible_user=ec2-user
```

```
ansible_password=DevOps321
```

[COPY](#)

```
# ansible -i inventroy.ini ungrouped --list-hosts
```

```
hosts (3):
```

```
192.168.1.1
```

```
192.168.1.2
```

```
192.168.1.3
```



```
# ansible -i inventroy.ini mysql --list-hosts
```

```
hosts (3):  
  192.168.1.7  
  192.168.1.8  
  192.168.1.9
```

```
# ansible -i inventroy.ini servers --list-hosts
```

```
hosts (4):  
  172.31.45.75  
  192.168.1.4  
  192.168.1.5  
  192.168.1.6
```

```
# ansible -i inventroy.ini all --list-hosts
```

```
hosts (11):  
  192.168.1.1  
  192.168.1.2  
  192.168.1.3  
  192.168.1.7  
  192.168.1.8  
  192.168.1.9  
  localhost  
  172.31.45.75  
  192.168.1.4  
  192.168.1.5  
  192.168.1.6
```

Ansible Datatypes


Strings,numbers,maps,lists,boolean

connection: local → ansible will not ask for username and password



COPY

```
- name: devops course information
hosts: local
connection: local # for localhosts
vars:
  course: "DevOps with AWS" #string
  duration: 120 #number
  topics: #list
    - Linux
    - Shell
    - Ansible
    - Terraform
    - AWS
    - K8
  live: true #boolean
  tools: #map/dictionary
    ci: jenkins # string
    cm: ansible
    cloud: aws
    aws:
      - IAM
      - S3
  tasks:
    - name: print the course information
      ansible.builtin.debug:
        msg: "Hi, I am learning {{ course }}, with duration: {{ durat
```



Below command

- automatically picks the localhost (inventory.ini) for that username and password is not required



COPY


```
ansible-playbook -i inventroy.ini 10-datatypes.yaml
```

Ansible conditions

Ansible "When" is used to decide whether particular task/module run or not .

https://docs.ansible.com/ansible/latest/playbook_guide/playbooks_conditionals.html

COPY

```
- name: check a number is less than 10 or not
hosts: local
connection: local
vars_prompt:
- name: my_number
  prompt: Please enter the number
  private: false # not confidential
# vars:
#   my_number: 139 # number
tasks:
- name: print this if less than 10
  ansible.builtin.debug:
    msg: "Given number {{ my_number }} is less than 10"
  when: my_number | int < 10 # conditional expression

- name: print this if greater than or equal to 10
  ansible.builtin.debug:
    msg: "Given number {{ my_number }} greater than or equal to 10"
  when: my_number | int >= 10
```

Lets understand with another example

Task is to create a new user

- Check already user exists or not
- if exists don't create
- if doesn't exists create

For above tasks ansible doesn't have modules then we will use commands

COPY

```
- name: create user
  hosts: web
  become: yes
  tasks:
    - name: check user exist or not
      ansible.builtin.command: id expense
      register: USER #here USER is a variable that gets output from a
      ignore_errors: True

    - name: print the user information
      ansible.builtin.debug:
        msg: "user info: {{ USER }}"

    - name: create user
      ansible.builtin.command: useradd expense
      when: USER.rc != 0
```

Things to watch out in above file

- "ignore_errors : True" → Ansible will not stop if the task failed, it will ignore and proceed with next command

- "register"→ helps to store output from the command
- For "id username" , for below output "**rc : 1**" means no such user (based on this yaml conditon can be written)

COPY

```
"user info: {
'changed': True,
'stdout': '',
'stderr': 'id: 'expense': no such user',
'rc': 1,
'cmd': ['id', 'expense'],
'start': '2024-09-04 07:36:02.795263',
'end': '2024-09-04 07:36:02.807144',
'delta': '0:00:00.011881',
'failed': True,
'msg': 'non-zero return code',
'stdout_lines': [],
'stderr_lines': ['id: 'expense': no such user']}"
```

- If user already there then we will get following output

COPY

```
"user info:
{'changed': True,
'stdout': 'uid=1002(expense) gid=1002(expense) groups=1002(expense)
'stderr': '',
'rc': 0,
'cmd': ['id', 'expense'],
'start': '2024-09-04 07:48:41.651891',
'end': '2024-09-04 07:48:41.659323',
'delta': '0:00:00.007432',
'msg': '',
```




```
'stdout_lines': ['uid=1002(expense) gid=1002(expense) groups=1002(e
'stderr_lines': [], 'failed': False}
```

Ansible Gathering Facts

Facts and variables both are same

Ansible, before connections to the servers/hosts it will collect entire information. so that it can take decisions based on that information



```
PLAY [create user] *****
TASK [Gathering Facts] *****
ok: [172.31.43.207]
TASK [check user exist or not] *****
changed: [172.31.43.207]
TASK [print the user information] *****
msg: user info: { 'changed': True, 'stdout': 'uid=1002(expense) gid=1002(expense) groups=1002(expense)', 'cmd': ['id', 'expense'], 'start': '2024-09-04 07:48:41.651891', 'end': '2024-09-04 07:48:41.651891', 'stderr_lines': [], 'stdout_lines': ['uid=1002(expense) gid=1002(expense) groups=1002(expense)'], 'stderr_lines': [] }
```

Lets understand "Gathering Facts" with an example

- we already have below package information for loading nginx in redhat
 - redhat → ansible.builtin.dnf
- Now we have to use same ansible to support loading nginx in ubuntu
 - ubuntu → ansible.builtin.apk
- Lets see how we can resolve this ..?

```
- name: gathering facts
  hosts: web
```



COPY

```

become: yes
tasks:
- name: print the facts
  ansible.builtin.debug:
    msg: " {{ ansible_facts }}"


```

"ansible_facts" variable is there in ansible which is used to print the "gathering facts"

after beautifying the output is

<https://github.com/qtivijay/devopsaws/blob/master/ansible1/facts.json>

we will use below variable from `ansible_facts` json to know whether it is ubuntu or redhat



```

{
  "distribution_file_parsed": true,
  "distribution_file_search_string": "Red Hat",
  "os_family": "RedHat",
  "virtualization_role": "guest",
  "virtualization_type": "kvm",
  "virtualization_tech_guest": ["kvm"],
}

```

COPY

```

- name: install nginx
  become: yes
  hosts: web
  tasks:
    - name: print the stats
      ansible.builtin.debug:
        msg: "{{ ansible_facts }}"

    - name: install nginx if redhat
      ansible.builtin.dnf:
        name: nginx
        state: present

```



```
when: ansible_os_family == "RedHat"

- name: install nginx if Debian
  ansible.builtin.apt:
    name: nginx
    state: present
  when: ansible_os_family == "Debian"
```

The above yaml will install the nginx based on os.

Ansible loops

COPY

```
- name: loops demo
  hosts: local
  connection: local
  tasks:
    - name: print names
      ansible.builtin.debug:
        msg: "Hello {{ item }}"
      loop:
        - Ramesh
        - Suresh
        - Robert
        - Raheem
```

item is a reserved ansible keyword to parse the loop

COPY

```
- name: loops demo
  hosts: web
  become: yes
  tasks:
```



```
- name: install packages
ansible.builtin.package:
  name: "{{ item }}"
  state: present
loop:
- mysql
- nginx
- postfix
- httpd
```

COPY

```
- name: loops demo
hosts: web
become: yes
tasks:
- name: install packages
  ansible.builtin.package:
    name: "{{ item.name }}"
    state: "{{ item.state }}"
  loop:
  - { name: 'mysql', state: 'present' }
  - { name: 'nginx', state: 'absent' }
  - { name: 'postfix', state: 'absent' }
  - { name: 'nginx', state: 'present' }
```

Ansible Functions/Filters

- Ansible allow user to write custom functions (using python language)
- But 90% of cases we use built-in ansible functions in project.
- https://docs.ansible.com/ansible/latest/playbook_guide/playbooks_filters.html

- Ansible filters are used to manipulate data within your playbooks.
(Pipe |)

COPY

```
- name: demo on filters/functions
hosts: local
connection: local
tasks:
- name: print the default variable
  ansible.builtin.debug:
    msg: "Hello {{ course | default('Ansible') }}"

- name: convert to uppercase
  vars:
    greeting: "Hello Ramesh"
  ansible.builtin.debug:
    msg: " {{ greeting | upper }}"

- name: convert to lowercase
  vars:
    greeting: "Hello Ramesh"
  ansible.builtin.debug:
    msg: " {{ greeting | lower }}"

- name: get the unique values
  vars:
    numbers: [1,2,3,45,4,3,2]
  ansible.builtin.debug:
    msg: " {{ numbers | unique }}"

- name: get the min and max
  vars:
    numbers: [1,2,3,45,4,3,2]
  ansible.builtin.debug:
    msg: " Min: {{ numbers | min }} Max: {{ numbers | max }}"
```



```

- name: convert map to list
  vars:
    course:
      name: "DevOps with AWS"
      duration: 120
      trainer: "sivakumar reddy"
  ansible.builtin.debug:
    msg: "{{ course | dict2items }}"

- name: convert list to map
  vars:
    course:
      - { "key": "name", "value": "DevOps with AWS" }
      - { "key": "duration", "value": 120 }
      - { "key": "trainer", "value": "sivakumar reddy" }
  ansible.builtin.debug:
    msg: "{{ course | items2dict }}"

- name: check ip address
  vars:
    myip: "356.168.1.1"
  ansible.builtin.debug:
    msg: "{{ myip | ansible.utils.ipv4 }}"

```

Command vs Shell

- **Use** `command` when you need to run simple commands that do not require shell features. It is more secure and should be preferred for basic tasks.
- **Use** `shell` when you need to leverage shell features like pipes, redirection, or environment variables. It provides more flexibility but should be used with caution due to potential security risks

ansible.builtin.command , ansible.builtin.shell

COPY

- name: check the process
 ansible.builtin.shell: ps -ef | grep ssh
 register: output

- name: check the process
 ansible.builtin.command: ps -ef | grep ssh # will fail as pipe
 register: output



Challenges and solutions

1. Downloaded the code from the github and made some changes
 and again i want to revert to latest changes in github , how to do it
..?

COPY

```
git reset --hard origin/master
```

2. Adding file to staging area to commit and to github in online ..?

COPY

```
git add . ; git commit -m "ansible" ; git push origin master
```



Possible interview questions

1. Write ansible code to download and run nginx ..?

1. <https://github.com/qtivijay/devopsaws/blob/master/ansible1/03-nginx.yaml>
2. What is difference between command vs shell in ansible ..?
 1. check command vs shell section

Subscribe to my newsletter

Read articles from **Vijay's Blog** directly inside your inbox. Subscribe to the newsletter, and don't miss out.

SUBSCRIBE[ansible](#)

Written by



vijaykumar guntireddy

Results-oriented Global Management Professional with diverse experience of >19 years in different capacities primarily in end-to-end product management, quality, delivery of critical business applications, and project management.

[Follow](#)

MORE ARTICLES



vijaykumar guntireddy