RAJALAKSHMI ENGINEERING COLLEGE

Srinivasan R 251001269-2025-IT S2

Started on	Wednesday, 5 August 2026, 8:37 AM
State	Finished
Completed on	Wednesday, 5 August 2026, 9:38 AM
Time taken	1 hour 1 min
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main(){
int n;
scanf("%d",&n);
int count=0;
 int i= 1;
 count++;
 int s =1;
 count++;
while(s<=n){
count++;
i++;
count++;
s+=i;
count++;
}
count++;
printf("%d",count);
}
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Srinivasan R 251001269-2025-IT

S2

Started on	Tuesday, 11 August 2026, 11:05 PM
State	Finished
Completed on	Tuesday, 11 August 2026, 11:23 PM
Time taken	17 mins 14 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

void func(int n) {
    int count = 0;

    count++;
    if(n==1) {
        count++;
    } else {
        for(int i=1; i<=n; i++) {
            count++;

            for(int j=1; j<=n; j++) {
                count++;

                count++;

                count++;

                count++;
                break;
            }
        }
        count++;
    }
    printf("%d", count);
}

int main() {
    int n;
    if(scanf("%d", &n) == 1) {
        func(n);
    }
    return 0;
}
```

```
36
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Srinivasan R 251001269-2025-IT

S2

Started on	Tuesday, 11 August 2026, 11:23 PM
State	Finished
Completed on	Tuesday, 11 August 2026, 11:29 PM
Time taken	6 mins 12 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

void Factor(int num) {
    int count = 0;

    for (int i = 1; i <= num; ++i) {
        count++;

        count++;
        if (num % i == 0) {
            count++;
        }
    }
    count++;

    printf("%d", count);
}

int main() {
    int n;
    if (scanf("%d", &n) == 1) {
        Factor(n);
    }
    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Srinivasan R 251001269-2025-IT

S2

Started on	Tuesday, 11 August 2026, 11:29 PM
State	Finished
Completed on	Tuesday, 11 August 2026, 11:33 PM
Time taken	3 mins 45 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

void function(int n) {
    int count = 0; // Initialize counter variable to trace executions
  int c = 0;
  count++;
    for (int i = n / 2; i < n; i++) {
        count++;
        for (int j = 1; j < n; j = 2 * j) {
            count++;
            for (int k = 1; k < n; k = k * 2) {
                count++;

                c++;
                count++;
            }
            count++;
            }
        count++;
    }
    count++;

    printf("%d", count);
}

int main() {
    int n;
    if (scanf("%d", &n) == 1) {
        function(n);
    }
    return 0;
}
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Srinivasan R 251001269-2025-IT

S2

Started on	Wednesday, 26 August 2026, 9:28 AM
State	Finished
Completed on	Wednesday, 26 August 2026, 9:31 AM
Time taken	3 mins 34 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

void reverse(int n) {
    int count = 0;
    int rev = 0, remainder;

    count++;

    while (n != 0) {
        count++;

        remainder = n % 10;
        count++;

        rev = rev * 10 + remainder;
        count++;

        n /= 10;
        count++;
    }
    count++;

    count++;

    printf("%d\n", count);
}

int main() {
    int n;
    if (scanf("%d", &n) == 1) {
        reverse(n);
    }
    return 0;
}

```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course