An Adaptive Technical Interviewer with a Theory of Mind of the Candidate

Final report

Team "Claude lag gaye": Kushal Mukherjee (2025201072)
Srinjoy Sengupta (2025202010) Nilkanta Karak (2025201031)
Souradeep Das (2025201004)

November 2026

Code: `https://github.com/Srinjoy003/LMA-RAG`

Abstract

A good interviewer does not only mark answers right or wrong; it forms a view of what the candidate *believes*, and asks the next question to test that view. We built an interviewer for junior technical screening in Python, SQL and data structures with this **theory of mind** at its centre. For every answer it decides whether the candidate does not know, slipped, misread the question, or holds a specific false belief; it keeps each attributed belief as a hypothesis, steers the interview to test it on a second question, confirms it only with the candidate's own words as evidence, and withdraws it when the candidate contradicts it. Alongside this it estimates a level per skill, picks questions to reduce its uncertainty, stops when confident, and leaves the hiring decision to a human. Five systems interviewed the same 22 simulated candidates (110 interviews). **With the theory of mind, 58% of the beliefs the system attributes to a candidate are correct, against 20% without it** (difference +38.3 points, 95% interval +18.7 to +62.3), and it never attributed a false belief to a correct answer. It is more cautious: it confirms 34% of the planted beliefs against 56%. Adaptive question choice judged 62% of skill levels correctly against 52% for a fixed interview of the same length. Probing beliefs has a cost: the full system was not more accurate on levels (53%) and asked more (20.1 exchanges against 12.0).

1 Introduction

A screening interview has to judge several skills with a handful of questions. Fixed question lists waste questions on skills that are already clear and leave others under-tested. LLM interviewers make screening cheap, but they decide what to ask and when to stop from a prompt alone, with no record of how sure they are. Adaptive testing solves this for multiple-choice tests by asking the most informative question and stopping once the estimate is precise [14], and TestAgent [13] brings the idea to conversational assessment. We apply it to open answers across several skills.

Adaptive testing tracks *how much* a candidate knows. A human interviewer also tracks *what the candidate thinks*: after a wrong answer they ask themselves whether the candidate simply does not know, made a careless slip, misread the question, or confidently holds a wrong idea, and they choose the next question to find out. This is a theory of mind of the candidate: attributing beliefs to another person from what they say, holding those beliefs as hypotheses, and revising them as evidence arrives. The distinction matters for feedback and for hiring, because a false belief ("`COUNT` counts `NULL`s") needs different training from a gap in knowledge. Our system makes this theory of mind explicit (Section 5), and the experiment tests whether it works. Our two research questions:

RQ1 Can uncertainty-driven questioning with early stopping match a fixed 12-question interview's accuracy with fewer exchanges?

RQ2 Does a theory-of-mind model of the candidate, which attributes, tests and revises beliefs, identify their misconceptions better than a system without it?

Main findings.

- **The theory of mind makes belief attributions trustworthy (RQ2).** With it, 58% of the beliefs the system confirms are ones the candidate really holds; without it, 20%. It never attributed a false belief to a correct answer, and it withdrew beliefs the candidate contradicted. The price is caution: it confirms 34% of the planted beliefs against 56%.
- **Adaptive question choice helps at equal length (RQ1).** At exactly 12 questions it judged 62% of levels correctly against 52% for the fixed list; the interval includes a small loss, so this is a likely gain, not a proven one.
- **The full system is not more accurate on levels and is longer (RQ1).** It judged 53% of levels correctly with 20.1 exchanges. Section 8.3 shows why: the questions the theory of mind asks to test a belief cost level accuracy.
- **Safe decisions.** No adaptive system passed an unfit candidate or rejected a fit one; the fixed interview passed one unfit candidate.

2 Related work

Theory of mind. Premack and Woodruff introduced the term for the capacity to attribute mental states, such as knowledge, belief and purpose, to others [10]. Rabinowitz et al. built a machine version, a network that learns models of other agents from their behaviour alone [11]. With large language models the question became whether the models themselves have a theory of mind: Kosinski reports that GPT-4 solves 75% of a set of false-belief tasks [7], while Ullman shows that small changes to such tasks, which keep the reasoning the same, reverse these successes [12]. We take a different position. We do not rely on the LLM *having* a theory of mind; we build an explicit, inspectable theory of mind of the candidate around it. The LLM only proposes a belief together with a quote from the answer; code holds the belief as a hypothesis, decides which question tests it, and confirms or withdraws it. Because LLM belief reasoning is brittle [12], no single model judgement is trusted: three votes, a quote check and a second question are required.

Student modelling. Intelligent tutoring systems have long modelled learners in two ways. Diagnostic "bug" models explain *why* a student makes an error by finding the faulty procedure behind it [3]; our misconception diagnosis follows this idea with a catalogue of known wrong beliefs per question. Knowledge tracing estimates *how much* of each skill a learner has mastered [5]; our skill scorecard plays that role with an item-response model. Our system combines the two in one interview and uses the belief model to choose questions, not only to explain errors afterwards. Recent work uses LLMs to find misconceptions in student code [1]; we add the testing and revision of each attributed belief during the interview.

3 What changed since the mid-term report

The mid-term found that A2's confirmed misconceptions were mostly not planted ones (18% precision), largely because a main answer and its own follow-up counted as two confirmations. The evidence rules in A2E are the response to that finding.

Part	Mid-term	Final
Question bank	135 drafted questions, a quarter reviewed	all 135 reviewed by the team; 43 corrected
Theory of mind	A2: a belief confirmed by two replies, which could be one question and its own follow-up	A2E: beliefs tested on two *different* questions, backed by the candidate's own words, withdrawn when contradicted (Section 5)
Systems run	B1 and A2	B1, A2E, A4, ADAPT12, A5E on the same candidates
Equal-length control	stub candidates only	live (ADAPT12)
Run records	results folders	a manifest per run that fingerprints code, bank, prompts and setup




Figure 1: One interview of the full system (A2E). The LLM grades, diagnoses and writes follow-up questions; code makes every decision (which question, when to stop, the verdict).

4 The system

Figure 1 shows the loop. The LLM is used only where language is needed. Everything that controls the interview (which question, when to stop, the verdict rule) is plain code, so the candidate cannot change the procedure by asking.

Scorecard. Each skill has an ability value θ on a logit scale. Questions come in three levels with difficulty $b = -1, 0, +1$. An answer earns 0, 1 or 2 marks, and we model the chance of each mark with the Partial Credit Model [8]:

$$P(X = x \mid \theta, b) \;\propto\; \exp\Big(\sum_{k \le x} (\theta - \delta_k)\Big), \qquad \delta_1 = b - 0.5,\ \delta_2 = b + 0.5.$$

We start from a normal prior (mean 0, standard deviation 1) and update it on a grid after every graded question. The estimate is the posterior mean (EAP, [2]) and the uncertainty is the posterior standard deviation (SE). Each answer is graded three times; if the marks disagree, it counts as weaker evidence (2 of 3 agreeing gives weight 0.67). The estimate becomes a level 0–3 with cut points at $\theta = -1.25$, -0.25 and 0.75, set on stub runs in the mid-term work so that the fixed baseline is not biased upwards.

Choosing the next question. The next skill is the one with the highest SE, and the level is the one whose difficulty is closest to that skill's estimate. Among the unasked bank questions of that

skill and level, the system prefers, in order: a question listing a misconception it already suspects; a question on a topic the candidate just got wrong; a question on a topic the job needs that has not been tested yet. Remaining ties are broken by a seeded random choice.

Stopping. The interview stops when every skill has at least two answers and an SE below 0.6, or after 15 main questions. We chose 0.6 for accuracy rather than length, as the mid-term report explains.

Grading and follow-ups. The grader marks the main answer three times. A follow-up is asked when the diagnosis is not a plain knowledge gap, at most two per question. The grader then marks the *whole exchange* three times, and that final grade updates the scorecard. A reply that shows a listed misconception scores 0 even if other parts are right.

Verdict. For each skill the system computes the posterior probability that θ is at or above the job's minimum level. Above 0.8 the skill meets the minimum, below 0.2 it does not, otherwise it is uncertain. The verdict is *not fit* if any skill is clearly below, *fit* if all clearly meet, and *needs human review* otherwise.

4.1 Tool calling

The engine can also be run by an LLM agent instead of the code loop. The agent calls six tools (`search_question_bank`, `ask_candidate`, `grade_answer`, `ask_follow_up`, `update_scorecard`, `end_interview`), and each tool enforces the same rules as the code driver. A demonstration (`scripts/agent_demo.py -probe-rules`) runs a full interview and deliberately breaks the rules: ending before the stop rule is met, asking a question the rules did not choose, updating the scorecard before grading, moving on while a question is still open, and calling a tool that does not exist. All five are refused with a reason, the agent's written summary agrees with the computed decision, and the agent reaches the same questions, levels and verdict as the code driver. The experiments use the code driver, which gives the same result with about 55 fewer model calls per interview.

5 Theory of mind: modelling what the candidate believes

The skill scorecard answers *how much* the candidate knows. The theory-of-mind component answers *what the candidate thinks*. It does four things a human interviewer does:

1. **Attribute a belief from behaviour.** From the words of an answer, infer which belief, if any, the candidate holds (from the question's list of known misconceptions).
2. **Tell a false belief from other causes.** A wrong answer can come from not knowing (a gap), a careless slip, misreading the question, or a false belief. Only the last is a belief about the subject; the others call for different follow-ups and are not reported as misconceptions.
3. **Hold beliefs as hypotheses and test them.** An attributed belief is first only *suspected*. The interviewer then steers the interview to test it: it prefers a later question that would expose the same belief, and asks follow-ups aimed at it.
4. **Revise beliefs on evidence.** A belief is *confirmed* only when the candidate shows it again on a different question, and *disputed* (withdrawn) if the candidate says the opposite.

How each step is made reliable. Figure 2 shows the life of one belief.

- **Three votes with evidence.** The diagnoser runs three times. A vote that attributes a belief must quote the words in the candidate's answer that show it and say why. Code checks that the quote really is in the answer; a vote without a valid quote counts as a gap. A belief needs a strict majority of the three votes.




Figure 2: How the system's theory of mind treats one belief. Only confirmed beliefs are reported; disputed ones are withdrawn. Every step that needs language is done by the LLM; every state change is made by code.

- **Two different questions.** A question and its own follow-up count as one piece of evidence, so the candidate must show the belief again on a separate question.
- **Correct answers are read too.** If a later answer states the opposite of a suspected or confirmed belief, with a quote, the belief becomes disputed and is not reported.

Nothing here is learned: it is prompts plus counting rules in code (`src/part3/diagnoser.py`, `src/engine/followups.py`, `src/shared/evidence.py`). The comparison system **A4** has no theory of mind in this sense: it runs one diagnosis on the main answer, needs no quote, asks generic follow-ups, never steers questions towards a belief, and reports a misconception after a single reply. Comparing A2E with A4 answers RQ2.

A worked example from the final run. Candidate CAND-003 (data engineer) was planted with the belief that a running sum (`SUM(...) OVER (ORDER BY ...)`) shows the grand total on every row.

1. *Attribution.* On question SQL-L3-010 the candidate answered: "The query will list each row with the same running value equal to the total sales amount (100 + 50 + 30 + 20 = 200) for every day". All three diagnosis votes attributed the belief and quoted this sentence; the belief became *suspected*.
2. *Probing.* The follow-up asked what the running sum would show on day 2 of a three-day table; the candidate replied "It would show the overall total". This is more evidence from the same question, so the belief stayed suspected.
3. *Testing on a new question.* Six questions later the system chose SQL-L3-012 with the recorded reason "lists a suspected misconception to confirm". The candidate wrote: "Adding `ORDER BY order_date` inside the OVER clause just sorts the rows, so every row still shows the overall total for that customer." The belief was *confirmed*, with both quotes in the report.

The same candidate's report also listed two beliefs as only suspected, so a human reading it can see which attributions are firm and which are hypotheses.

Revising a belief. For CAND-006 the system first attributed the belief that Python's `or` evaluates both sides, from "the right side is still evaluated". In the follow-up the candidate said the opposite: "Because the overall result is already determined to be true, the right side is never executed or needed." The belief was marked disputed and not reported, which was correct: it was not one of the candidate's planted beliefs. Without this revision, the report would have accused the candidate of a misconception they do not hold.

A correction before the final run. The quote check first required an exact character match. In the first final-run attempt we found that the candidate model writes narrow no-break spaces and backticks around code, which Gemini drops when it quotes, so correct diagnoses with correct quotes were being discarded. In a replay of that attempt's diagnoses, 32 of the 150 misconception votes (21%) were rejected for formatting alone. We changed the check to ignore spaces, backticks, quotation marks and letter case; the quote must still be the candidate's own words, and the stored evidence is the exact span of the answer. The attempt was discarded and the final run restarted under a new version with this fix (Section 7).

6 Data

Question bank. 135 questions: 3 skills × 3 levels × 15, each with a model answer, key points, a 0/1/2 rubric, topic tags and a list of common misconceptions. There are *explain* and *read-code* questions. Questions were drafted with an LLM; every question was then reviewed by a teammate for answer correctness, rubric consistency, relevant misconceptions and level. The review flagged 66 questions and we corrected 43 (wrong claims in model answers, unclear wording, and misconceptions listed on questions that do not test them). The other notes asked for rubric changes our grading rule already covers. Level notes were resolved by aligning the written level definitions with the topic levels the bank was built from, without moving questions.

Misconceptions. 95 misconceptions. Where a published catalogue exists we adapted from it: Progmiscon for Python [4], a think-aloud study of SQL novices [9], concept-inventory work on data structures [6] and the McMining benchmark [1]. The rest were written for this project.

Jobs. Three job descriptions (junior data analyst, backend engineer, data engineer), each with a minimum level per skill and 13 to 17 required topics.

Simulated candidates. Each candidate has a hidden answer key: a level (0–3) for every topic, one or two planted misconceptions, and small chances of misreading or slipping. A candidate's true level for a skill is the floor of their mean level over the topics the job requires; planted misconceptions do not change it. Candidates come in blocks of 12 that cover every combination of job, even or uneven profile, and fit or not fit once. For every question, code decides what the candidate should do (answer correctly, partly, wrongly, with a planted misconception, misread, or slip) and a second LLM writes the answer following that plan.

7 Experimental setup

System	What it is	Compared with
B1	Fixed: 12 questions (levels 1, 2, 2, 3 per skill), no follow-ups, no diagnosis	–
ADAPT12	Adaptive question choice, exactly 12 questions, no follow-ups, no diagnosis	B1 (RQ1, equal length)
A2E	Full system: adaptive choice, early stopping, theory of mind of the candidate	B1 (RQ1), A4 (RQ2)
A4	A2E without the theory of mind (single diagnosis, no quotes, no belief testing, one-reply confirmation)	A2E (RQ2)
A5E	A2E with job-blind question choice	A2E (job-aware retrieval)

Table 1: The five systems. Every system interviewed every candidate.

Models. Grading, diagnosis and topic extraction use `gemini-3.5-flash-lite`; the simulated candidate is `gpt-oss-120b` on Groq, a different model family. Before the run, one interview each of B1 and A2E on a separate validation candidate checked that every grade and diagnosis got three valid votes.

Runs. Candidates were run one at a time through all five systems, in the order of the balanced blocks, so that every finished candidate has a result from every system. The run covers 22 complete candidates (110 interviews). The first block of 12 is complete and balanced; the second is missing two candidates. Every comparison below uses the same 22 candidates in every system. The run's manifest fingerprints the source code, bank, prompts, models and candidate files, and results from a different setup cannot be mixed in.

Metrics. *Skill accuracy* is the share of (candidate, skill) pairs where the reported level equals the true level; we also report the mean absolute level error. *Exchanges* are main questions plus follow-ups. *Verdicts* are right, wrong, or sent to a human. *Misconception recall* is the share of planted misconceptions that were confirmed, and *precision* the share of confirmed misconceptions that were planted. The *false-alarm rate* is the share of replies planned as correct on which a misconception was named.

Uncertainty. With 22 candidates the numbers move a lot from sample to sample, so we give 95% bootstrap intervals: candidates are redrawn with replacement 2,000 times, with the same draw for every system because they interviewed the same people. For a comparison the interval is for the difference between the two systems.

8 Results

	B1	ADAPT12	A2E	A5E	A4
Skill levels right	52%	62%	53%	62%	70%
Mean level error	0.52	0.39	0.48	0.38	0.30
Exchanges per interview	12.0	12.0	20.1	21.3	18.9
Verdicts right / to a human / wrong	9 / 12 / 1	10 / 12 / 0	9 / 13 / 0	11 / 11 / 0	14 / 8 / 0
Misconception recall	–	–	34%	38%	56%
Misconception precision	–	–	58%	57%	20%
False alarms on correct replies	–	–	0.0%	0.7%	0.0%
Required job topics tested	90%	76%	74%	62%	85%
Interviewer LLM calls	37	37	113	120	65

Table 2: All five systems on the same 22 candidates (32 planted misconceptions).

8.1 RQ1: skill levels and length

Adaptive choice at equal length. ADAPT12 and B1 both ask exactly 12 questions; only the choice of questions differs. ADAPT12 judged 62% of levels correctly against 52%, a difference of +10.6 points [−4.5, +25.8]. The interval includes a small loss, so we read this as a likely gain from adaptivity rather than a proven one. It repeats the direction of the mid-term stub controls, now with the live models.

The full system against the fixed interview. A2E judged 53% of levels correctly, a difference of +1.5 points from B1 [−16.7, +19.7]: no measurable gain. It asked 20.1 exchanges per interview against 12.0 (difference +8.1 [+7.0, +9.4]), mostly follow-ups (Figure 4). RQ1's target of 25% fewer




Figure 3: Skill levels judged correctly, with 95% intervals over candidates.

exchanges is not met. Its errors are not one sided: 17 levels too high and 14 too low, where B1 errs mostly upwards (24 and 8).




Figure 4: Interview length: main questions plus follow-ups.

Verdicts. No adaptive system passed an unfit candidate or rejected a fit one; B1 passed one unfit candidate (Figure 5). All systems send many candidates to a human (between a third and 60%), because the 0.8 rule demands a clear margin above the job minimum. A4 decided the most cases (14 of 22), in line with its better level estimates.




Figure 5: Fit / not-fit verdicts per system.

8.2 RQ2: does the theory of mind help?

Figure 6 shows the trade-off. Without the theory of mind, A4 confirmed 92 misconceptions in 22 interviews and found 18 of the 32 planted ones (recall 56%), but only 20% of its findings were planted. With the theory of mind, A2E confirmed 19 and found 11 (recall 34%), and 58% of its findings were planted:




Figure 6: Recall against precision of confirmed misconceptions, with 95% intervals. Up is more trustworthy, right finds more.

A2E − A4	Difference	95% interval
Precision	+38.3 points	+18.7 to +62.3
Recall	−21.9 points	−35.5 to −9.4
False alarms on correct replies	+0.0 points	+0.0 to +0.0

Both differences are clear. For a screening tool, precision matters more: telling a candidate they hold a misconception they do not is worse than missing one, and A4 is wrong about four times in five. The theory of mind also kept 59 beliefs as hypotheses only (seen on one question) and withdrew 2 after the candidate contradicted them, none of them planted; neither counts as a finding, but both are visible to the human reading the report. Neither system named a misconception on a correctly answered reply. The recall target of 60% from the proposal is not met. Precision here is against planted misconceptions only: a simulated candidate told to answer wrongly sometimes states a common misconception that was not planted, so some "false" findings may be right about the reply.

8.3 Why the full system is less accurate on levels than A4

A4 judged 70% of levels correctly and A2E 53%, a difference of −16.7 points [−28.8, −4.5]. Both use the same scorecard, question-choice rules and stopping rule, so the difference comes from the theory of mind. To confirm a belief on a second question, A2E prefers questions that list a suspected misconception. A candidate who holds it answers those wrongly by design. A2E asked 1.5 such questions per interview, A4 0.8 and B1 0.5. Each scores 0 and pulls the estimate down, but the true level ignores planted misconceptions, so the result shows up as under-estimates: 14 of A2E's wrong levels are too low, against 4 for A4. This is a real cost of probing beliefs, partly made larger by our definition of the true level. A system that wants both could keep the probing questions out of the level estimate, or stop probing once a belief is confirmed.

8.4 Premature stops

An interview stops early when every skill's SE is below 0.6. A2E stopped this way in 20 of 22 interviews, and after those stops 29 of 60 skill levels were wrong (A4: 15 of 45).

- **By skill:** Python 13, data structures 10, SQL 6 wrong levels out of 20 each. SQL is judged best.
- **By size:** all but 1 of the wrong levels after an early stop are one level off; the rule stops as soon as the estimate is precise enough, even when it sits next to a cut point.

- **At the bottom of the scale:** 2 of the 5 skills a candidate did not know at all (true level 0) were reported as level 1.

SE below 0.6 means the estimate is precise, not that it is far from a cut point. Asking one more question when the estimate is close to a cut point, or requiring most of the posterior to lie in one level, would address this; the second rule was implemented (A2EB) but not run live.

8.5 Job-aware question choice

A5E differs from A2E only in ignoring the job description when choosing questions. It tested fewer of the job's required topics (62% against 74%, a difference of −11.4 points [−16.7, −5.8]), which is what job-aware retrieval is for. Its level accuracy and misconception recall were not measurably different (+9.1 points [−3.0, +21.2] on levels). So job-aware choice makes the interview cover the job, without a measurable effect on accuracy at this sample size.

8.6 Cost

A2E made 113 interviewer-side LLM calls per interview against 37 for B1: three grading and three diagnosis votes per answer, including correct ones. A4 needed 65.

9 Discussion

	Target	Result	Status
RQ1	Skill accuracy within 5 points of B1	+1.5 points [−16.7, +19.7]	not settled
RQ1	At least 25% fewer exchanges than B1	20.1 against 12.0	not met
RQ1	Adaptive choice beats the fixed list at equal length	+10.6 points [−4.5, +25.8]	not settled
RQ2	More trustworthy belief attributions than without the theory of mind	+38.3 points precision	met
RQ2	Misconception recall of at least 60%	34%	not met
RQ2	False alarms on correct answers below 15%	0.0%	met

Table 3: The targets against the final results.

What we learned. The theory of mind works where it matters most for a screening tool: when it says a candidate holds a misconception, it is right most of the time, it never says so about a correct answer, and it withdraws a belief when the candidate contradicts it. A system without it finds more planted beliefs only by attributing beliefs freely, and four in five of its attributions are wrong. The mid-term version, whose confirmations could come from a single question, had the same problem (18% precision); testing each belief on a second question and requiring the candidate's own words fixed it. Adaptive question choice also does what adaptive testing promises: at the same length it places candidates better than a fixed list, though our sample cannot prove it. The two do not combine for free. Confirming a belief needs evidence from a second question, and that evidence comes from deliberately probing a weakness, which costs level accuracy and length. A2E is therefore not the best system on every measure: A4 judges levels best and ADAPT12 is the best short interview, but only A2E gives a trustworthy account of *what the candidate believes* and why they are wrong.

Mid-term against final. In the mid-term, A2 beat B1 on levels by 17 points. With A2E on the reviewed bank and new candidates it does not. Two things changed: the stricter belief model (which probes more, as shown above) and the corrected question bank; the candidates are the same people (the first 22 of the 24 used then). The mid-term gain also included more questions, as that report noted, and our final equal-length comparison is the cleaner test of adaptivity.

The evidence check matters. A rule that checks the model's evidence is only as good as the check. An exact-match rule silently threw away a fifth of correct diagnoses because of invisible formatting differences between two models. Checking evidence against real outputs, not only test cases, caught it.

10 Limitations

- **Simulated candidates.** Real candidates are less consistent. The simulated candidate sometimes ignored its plan (graded answers matched the plan for 87% of A2E's questions), and a follow-up occasionally gave the answer away, after which the grader gave full marks. Results describe the interviewer against a controlled population.
- **Sample size.** 22 candidates give wide intervals; several comparisons are not settled. Running all 60 candidates would narrow them.
- **Truth ignores misconceptions.** A candidate's true level does not count planted misconceptions, which favours systems that do not probe them (Section 8.3).
- **One grader model, no human check yet.** Every grade comes from one Gemini model. The planned hand checks were not done: two teammates independently marking a sample of answers against the rubric, and labelling 30 simulated answers against their plans, reporting Cohen's κ between them with $\kappa \geq 0.6$ as acceptable. If κ is lower, the labelling guide is ambiguous: we would rewrite it, settle the disagreements together and label a fresh sample. If the two agree with each other but not with the model, the fault is the model's: we would report the grader's error rate beside every accuracy figure, and score simulated answers against what was written rather than the plan.
- **Settings tuned before A2E.** The stopping threshold and cut points were tuned on stub runs before the theory-of-mind component was changed.
- **Safety.** Only one manipulation attempt per system was in this sample. It did not raise the grade and was flagged, but one case shows little.

11 Conclusion and future work

We built an interviewer with an explicit theory of mind of the candidate: it attributes beliefs from what the candidate says, tells a false belief from a gap, a slip or a misreading, holds each belief as a hypothesis, steers the interview to test it, and confirms or withdraws it on evidence in the candidate's own words. Alongside, it estimates skill levels adaptively and leaves the hiring decision to a human. On 22 simulated candidates, the theory of mind made belief attributions about three times as trustworthy as a version without it (58% against 20%), and adaptive question choice placed candidates better than a fixed list at equal length. The full system did not combine both advantages: testing beliefs cost level accuracy and length. The most useful next steps are to keep belief-probing questions out of the level estimate, to stop probing a belief once it is confirmed, to require a clear margin from the nearest cut point before stopping, to finish the run on all 60 candidates, and to complete the human checks.

Reproducing this report

Code, question bank and candidates are at `https://github.com/Srinjoy003/LMA-RAG`. The final run is `reviewed-main-v2`, produced by `scripts/run_rotating.py` in the order of `docs/final_run_order.txt`; its manifest records the code, bank, prompts and models. Every result number and figure in this report is generated by `report/make_final_figures.py` from

the 22 complete candidates, and `scripts/evaluate.py` gives the full metric table. Every LLM response is cached on disk, so re-running from the cache gives the same interviews.

References

[1] E. Al-Hossami and R. Bunescu. McMining: automated discovery of misconceptions in student code. In *EACL* (short papers), 2026. arXiv:2510.08827.

[2] R. D. Bock and R. J. Mislevy. Adaptive EAP estimation of ability in a microcomputer environment. *Applied Psychological Measurement*, 6(4):431–444, 1982.

[3] J. S. Brown and R. R. Burton. Diagnostic models for procedural bugs in basic mathematical skills. *Cognitive Science*, 2(2):155–192, 1978.

[4] L. Chiodini, I. Moreno Santos, A. Gallidabino, A. Tafliovich, A. L. Santos and M. Hauswirth. A curated inventory of programming language misconceptions. In *ITiCSE*, pages 380–386, 2021.

[5] A. T. Corbett and J. R. Anderson. Knowledge tracing: modeling the acquisition of procedural knowledge. *User Modeling and User-Adapted Interaction*, 4(4):253–278, 1995.

[6] K. Karpierz and S. A. Wolfman. Misconceptions and concept inventory questions for binary search trees and hash tables. In *SIGCSE*, pages 109–114, 2014.

[7] M. Kosinski. Evaluating large language models in theory of mind tasks. *Proceedings of the National Academy of Sciences*, 121(45):e2405460121, 2024.

[8] G. N. Masters. A Rasch model for partial credit scoring. *Psychometrika*, 47(2):149–174, 1982.

[9] D. Miedema, E. Aivaloglou and G. Fletcher. Identifying SQL misconceptions of novices: findings from a think-aloud study. In *ICER*, pages 355–367, 2021.

[10] D. Premack and G. Woodruff. Does the chimpanzee have a theory of mind? *Behavioral and Brain Sciences*, 1(4):515–526, 1978.

[11] N. C. Rabinowitz, F. Perbet, H. F. Song, C. Zhang, S. M. A. Eslami and M. Botvinick. Machine theory of mind. In *ICML*, PMLR 80:4218–4227, 2018.

[12] T. Ullman. Large language models fail on trivial alterations to theory-of-mind tasks. arXiv:2302.08399, 2023.

[13] J. Yu, Y. Zhuang, Y. Sun, W. Gao, Q. Liu, M. Cheng, Z. Huang and E. Chen. TestAgent: an adaptive and intelligent expert for human assessment. In *Findings of ACL*, pages 724–747, 2025.

[14] Y. Zhuang, Q. Liu et al. Survey of computerized adaptive testing: a machine learning perspective. arXiv:2404.00712, 2024. Accepted to *IEEE TPAMI*.