

LAPORAN PROJEK AKHIR
PEMROGRAMAN WEB LANJUT



Oleh :

Srirahmi Lutfiah Aprilia

NIM : 1931710151

MI - 2D

PRODI DIII-MANAJEMEN INFORMATIKA

JURUSAN TEKNOLOGI INFORMASI

2020

MEMBUAT PROJEK LARAVEL

1. Pastikan Composer telah terinstall, kemudian masuk CMD
2. Running composer pada Command Prompt, arahkan dulu direktori ke folder htdocs dengan memasukkan sintaks `cd c:\xampp\htdocs/`
3. Kemudian buat projek baru laravel dengan memasukkan sintaks `composer create-project --prefer-dist laravel/laravel <projectname> <versi>`

```
C:\WINDOWS\system32\cmd.exe
Microsoft Windows [Version 10.0.19041.630]
(c) 2020 Microsoft Corporation. All rights reserved.

C:\Users\LENOVO>cd c:\xampp\htdocs

c:\xampp\htdocs>composer create-project --prefer-dist laravel/laravel projectpwl "7.*"
Creating a "laravel/laravel" project at "./projectpwl"
```

Tunggu proses sampai selesai


```
- Installing nikic/php-parser (v4.10.2): Loading from cache
- Installing psy/psysh (v0.10.4): Loading from cache
- Installing laravel/tinker (v2.5.0): Loading from cache
- Installing filp/whoops (2.9.1): Loading from cache
- Installing facade/ignition-contracts (1.0.2): Loading from cache
- Installing facade/flare-client-php (1.3.7): Loading from cache
- Installing facade/ignition (2.5.2): Loading from cache
- Installing fakerphp/faker (v1.11.0): Loading from cache
- Installing hamcrest/hamcrest-php (v2.0.1): Loading from cache
- Installing mockery/mockery (1.4.2): Loading from cache
- Installing nunomaduro/collision (v4.3.0): Loading from cache
- Installing sebastian/version (3.0.2): Loading from cache
- Installing sebastian/type (2.3.1): Loading from cache
- Installing sebastian/resource-operations (3.0.3): Loading from cache
- Installing sebastian/recursion-context (4.0.4): Loading from cache
- Installing sebastian/object-reflector (2.0.4): Loading from cache
- Installing sebastian/object-enumerator (4.0.4): Loading from cache
- Installing sebastian/global-state (5.0.2): Loading from cache
- Installing sebastian/exporter (4.0.3): Loading from cache
- Installing sebastian/environment (5.1.3): Loading from cache
- Installing sebastian/diff (4.0.4): Loading from cache
- Installing sebastian/comparator (4.0.6): Loading from cache
- Installing sebastian/code-unit (1.0.8): Loading from cache
- Installing sebastian/cli-parser (1.0.1): Loading from cache
- Installing phpunit/php-timer (5.0.3): Loading from cache
- Installing phpunit/php-text-template (2.0.4): Loading from cache
```

```
phpunit/php-invoker suggests installing ext-pcntl (*)
phpunit/php-code-coverage suggests installing ext-pcov (*)
phpunit/php-code-coverage suggests installing ext-xdebug (*)
phpunit/phpunit suggests installing ext-soap (*)
phpunit/phpunit suggests installing ext-xdebug (*)
Writing lock file
Generating optimized autoload files
> Illuminate\Foundation\ComposerScripts::postAutoloadDump
> @php artisan package:discover --ansi
Discovered Package: facade/ignition
Discovered Package: fideloper/proxy
Discovered Package: fruitcake/laravel-cors
Discovered Package: laravel/tinker
Discovered Package: nesbot/carbon
Discovered Package: nunomaduro/collision
Package manifest generated successfully.
71 packages you are using are looking for funding.
Use the `composer fund` command to find out more!
> @php artisan key:generate --ansi
Application key set successfully.
```

```
c:\xampp\htdocs>
```

LOGIN

1. Buat database baru pada phpmyadmin bernama “*projectpwl*”



2. Buka Visual Studio Code kemudian buka file **.env** yang ada pada direktori paling luar dalam projek laravelnya. Koneksikan database laravel yang telah dibuat.

```
projectpwl > .env
9   DB_CONNECTION=mysql
10  DB_HOST=127.0.0.1
11  DB_PORT=3306
12  DB_DATABASE=projectpwl
13  DB_USERNAME=root
14  DB_PASSWORD=
```

3. Buka folder migration kemudian buka file *create-users-table*. Pada folder ini laravel sudah menyediakan file migration untuk table user . Untuk bisa membedakan antara admin dan user/customer pada saat login, maka tambahkan kolom baru bernama “*is_admin*” pada table users.

database/migration/...create_users_table.php

```
...
public function up()
{
    Schema::create('users', function (Blueprint $table) {
        $table->id();
        $table->string('name');
        $table->string('email')->unique();
        $table->timestamp('email_verified_at')->nullable();
        $table->boolean('is_admin')->nullable();
        $table->string('password');
        $table->rememberToken();
        $table->timestamps();
    });
}
...
```

4. Tambahkan juga kolom *is_admin* pada model User yang telah tersedia


App/User.php

```
...  
  
protected $fillable = [  
    'name', 'email', 'password', 'is_admin'  
];  
  
...
```

5. Jalankan migrate dengan perintah artisan

```
PS C:\xampp\htdocs\projectpwl> php artisan migrate  
Migration table created successfully.  
Migrating: 2014_10_12_000000_create_users_table  
Migrated: 2014_10_12_000000_create_users_table (2.26 seconds)  
Migrating: 2014_10_12_100000_create_password_resets_table  
Migrated: 2014_10_12_100000_create_password_resets_table (1.34 seconds)  
Migrating: 2019_08_19_000000_create_failed_jobs_table  
Migrated: 2019_08_19_000000_create_failed_jobs_table (0.61 seconds)  
PS C:\xampp\htdocs\projectpwl>
```

6. Lihat pada phpmyadmin , apakah table berhasil dibuat.
Table berhasil dibuat :



The screenshot shows the phpMyAdmin interface for a database named 'projectpwl'. The 'Structure' tab is selected, displaying a table list. The tables listed are 'failed_jobs', 'migrations', 'password_resets', and 'users'. Each table has a star icon, a 'Browse' button, and a 'Structure' button. The 'Structure' button is highlighted for the 'users' table. The table list includes columns for 'Table', 'Action', 'Rows', 'Type', 'Collation', 'Size', and 'Overhead'. The 'users' table has 0 rows, is of type 'InnoDB', and has a collation of 'utf8mb4_unicode_ci'. The 'migrations' table has 3 rows, is of type 'InnoDB', and has a collation of 'utf8mb4_unicode_ci'. The 'password_resets' table has 0 rows, is of type 'InnoDB', and has a collation of 'utf8mb4_unicode_ci'. The 'failed_jobs' table has 0 rows, is of type 'InnoDB', and has a collation of 'utf8mb4_unicode_ci'. The 'Sum' row shows a total of 3 rows, type 'InnoDB', and collation 'utf8mb4_general_ci'.

Table	Action	Rows	Type	Collation	Size	Overhead
<input type="checkbox"/> failed_jobs	★ Browse Structure Search Insert Empty Drop	0	InnoDB	utf8mb4_unicode_ci	16.0 KiB	-
<input type="checkbox"/> migrations	★ Browse Structure Search Insert Empty Drop	3	InnoDB	utf8mb4_unicode_ci	16.0 KiB	-
<input type="checkbox"/> password_resets	★ Browse Structure Search Insert Empty Drop	0	InnoDB	utf8mb4_unicode_ci	32.0 KiB	-
<input type="checkbox"/> users	★ Browse Structure Search Insert Empty Drop	0	InnoDB	utf8mb4_unicode_ci	32.0 KiB	-
4 tables	Sum	3	InnoDB	utf8mb4_general_ci	96.0 KiB	0 B

7. Kolom pada table users

Server: 127.0.0.1 » Database: projectpwl » Table: users

[Browse](#)
[Structure](#)
[SQL](#)
[Search](#)
[Insert](#)
[Export](#)
[Import](#)
[Privileges](#)
[Operations](#)
[Tracking](#)
[Triggers](#)

[Table structure](#)
[Relation view](#)

#	Name	Type	Collation	Attributes	Null	Default	Comments	Extra	Action
<input type="checkbox"/> 1	id	bigint(20)		UNSIGNED	No	None		AUTO_INCREMENT	Change Drop More
<input type="checkbox"/> 2	name	varchar(255)	utf8mb4_unicode_ci		No	None			Change Drop More
<input type="checkbox"/> 3	email	varchar(255)	utf8mb4_unicode_ci		No	None			Change Drop More
<input type="checkbox"/> 4	email_verified_at	timestamp			Yes	NULL			Change Drop More
<input type="checkbox"/> 5	is_admin	tinyint(1)			Yes	NULL			Change Drop More
<input type="checkbox"/> 6	password	varchar(255)	utf8mb4_unicode_ci		No	None			Change Drop More
<input type="checkbox"/> 7	remember_token	varchar(100)	utf8mb4_unicode_ci		Yes	NULL			Change Drop More
<input type="checkbox"/> 8	created_at	timestamp			Yes	NULL			Change Drop More
<input type="checkbox"/> 9	updated_at	timestamp			Yes	NULL			Change Drop More

☐ Check all
 With selected:
 [Browse](#)
[Change](#)
[Drop](#)
[Primary](#)
[Unique](#)
[Index](#)
[Fulltext](#)
[Add to central columns](#)

[Remove from central columns](#)

8. Membuat auth scaffolding dengan perintah *composer require laravel/ui:^2.4* pada CMD

```
c:\xampp\htdocs\projectpwl>composer require laravel/ui:^2.4
./composer.json has been updated
Loading composer repositories with package information
Updating dependencies (including require-dev)
Package operations: 1 install, 0 updates, 0 removals
  - Installing laravel/ui (v2.4.0): Loading from cache
Writing lock file
Generating optimized autoload files
> Illuminate\Foundation\ComposerScripts::postAutoloadDump
> @php artisan package:discover --ansi
Discovered Package: facade/ignition
Discovered Package: fideloper/proxy
Discovered Package: fruitcake/laravel-cors
Discovered Package: laravel/tinker
Discovered Package: laravel/ui
Discovered Package: nesbot/carbon
Discovered Package: nunomaduro/collision
Package manifest generated successfully.
71 packages you are using are looking for funding.
Use the `composer fund` command to find out more!

c:\xampp\htdocs\projectpwl>composer require laravel/ui:^2.4_
```

9. Generate auth, buka CMD ketik perintah :

php artisan ui vue --auth

```
c:\xampp\htdocs\projectpwl>php artisan ui vue --auth
Vue scaffolding installed successfully.
Please run "npm install && npm run dev" to compile your fresh scaffolding.
Authentication scaffolding generated successfully.
```

npm install && npm run dev

```
c:\xampp\htdocs\projectpw1>php artisan ui vue --auth
Vue scaffolding installed successfully.
Please run "npm install && npm run dev" to compile your fresh scaffolding.
Authentication scaffolding generated successfully.

c:\xampp\htdocs\projectpw1>npm install && npm run dev
npm WARN deprecated popper.js@1.16.1: You can find the new Popper v2 at @popperjs/core, this package is dedicated to the legacy v1
npm WARN deprecated chokidar@2.1.8: Chokidar 2 will break on node v14+. Upgrade to chokidar 3 with 15x less dependencies.
npm WARN deprecated urix@0.1.0: Please see https://github.com/lydell/urix#deprecated
npm WARN deprecated fsevents@1.2.13: fsevents 1 will break on node v14+ and could be using insecure binaries. Upgrade to fsevents 2.
npm WARN deprecated resolve-url@0.2.1: https://github.com/lydell/resolve-url#deprecated
npm notice created a lockfile as package-lock.json. You should commit this file.
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@~1.2.7 (node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@1.2.13: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})
npm WARN optional SKIPPING OPTIONAL DEPENDENCY: fsevents@~2.1.2 (node_modules\watchpack\node_modules\chokidar\node_modules\fsevents):
npm WARN notsup SKIPPING OPTIONAL DEPENDENCY: Unsupported platform for fsevents@2.1.3: wanted {"os":"darwin","arch":"any"} (current: {"os":"win32","arch":"x64"})

added 1094 packages from 501 contributors and audited 1097 packages in 210.218s

52 packages are looking for funding
  run `npm fund` for details

found 1 high severity vulnerability
  run `npm audit fix` to fix them, or `npm audit` for details

> @ dev c:\xampp\htdocs\projectpw1
> npm run development

> @ development c:\xampp\htdocs\projectpw1
> cross-env NODE_ENV=development node_modules\webpack\bin\webpack.js --progress --config=node_modules/laravel-mix/setup/webpack.config.js

98% after emitting SizeLimitsPlugin

DONE Compiled successfully in 20506ms                                     19:03:34
   Asset      Size  Chunks             Chunk Names
  /css/app.css  178 KiB    /js/app  [emitted]    /js/app
  /js/app.js    1.41 MiB    /js/app  [emitted]    /js/app

c:\xampp\htdocs\projectpw1>
```

10. Membuat middleware admin yang hanya dapat diakses oleh admin ke route tersebut.
Buka terminal pada Visual Code

```
PS C:\xampp\htdocs\projectpw1> php artisan make:middleware IsAdmin
Middleware created successfully.
```

app/Http/Middleware/IsAdmin.php

```
<?php

namespace App\Http\Middleware;

use Closure;

class IsAdmin
{
    /**
     * Handle an incoming request.
     *
     * @param \Illuminate\Http\Request $request
     * @param \Closure $next
     * @return mixed
     */
    public function handle($request, Closure $next)
    {
        if(auth()->user()->is_admin ==1){
            return $next($request);
        }
    }
}
```

```

        return redirect('home')->with('error',"Maaf, Anda tidak memiliki hak akses.");
    }
}

```

app/Http/Kernel.php

```

...
protected $routeMiddleware = [
    'auth' => \App\Http\Middleware\Authenticate::class,
    'auth.basic' => \Illuminate\Auth\Middleware\AuthenticateWithBasicAuth::class,
    'bindings' => \Illuminate\Routing\Middleware\SubstituteBindings::class,
    'cache.headers' => \Illuminate\Http\Middleware\SetCacheHeaders::class,
    'can' => \Illuminate\Auth\Middleware\Authorize::class,
    'guest' => \App\Http\Middleware\RedirectIfAuthenticated::class,
    'password.confirm' => \Illuminate\Auth\Middleware\RequirePassword::class,
    'signed' => \Illuminate\Routing\Middleware\ValidateSignature::class,
    'throttle' => \Illuminate\Routing\Middleware\ThrottleRequests::class,
    'verified' => \Illuminate\Auth\Middleware\EnsureEmailIsVerified::class,
    'is_admin' => \App\Http\Middleware\IsAdmin::class,
];
...

```

11. Route untuk halaman home admin

routes/web.php

```

Route::get('admin/home', 'HomeController@adminHome')->name('admin.home')->middleware('is_admin');

```

12. Menambahkan method untuk adminHome pada HomeController

app/Http/Controllers/HomeController.php

```

...
public function adminHome()
{
    return view('adminHome');
}
...

```

13. Mengupdate file view user yaitu home.blade, dan membuat file view baru untuk admin yaitu adminHome.blade

resources/views/home.blade.php

```

@extends('layouts.app')
@section('content')
<div class="container">
    <div class="row justify-content-center">

```

```

        <div class="col-md-8">
            <div class="card">
                <div class="card-header">{{ __('Dashboard') }}</div>
                <div class="card-body">
                    @if (session('status'))
                        <div class="alert alert-success" role="alert">
                            {{ session('status') }}
                        </div>
                    @endif
                    {{ __('You are User !') }}
                </div>
            </div>
        </div>
    </div>
</div>
@endsection

```

resources/views/adminHome.blade.php

```

@extends('layouts.app')
@section('content')

<div class="container">
    <div class="row justify-content-center">
        <div class="col-md-8">
            <div class="card">
                <div class="card-header">{{ __('Dashboard') }}</div>
                <div class="card-body">
                    @if (session('status'))
                        <div class="alert alert-success" role="alert">
                            {{ session('status') }}
                        </div>
                    @endif
                    {{ __('You are Admin !') }}
                </div>
            </div>
        </div>
    </div>
</div>
</div>
@endsection

```

14. Memodifikasi LoginController. Ketika user/customer akan login, kita redirect sesuai dengan akses user yaitu ke route asal (/home) dan untuk admin ke route /adminHome.

App/Http/Controllers/Auth/LoginController.php

```

<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Foundation\Auth\AuthenticatesUsers;

```



```

use Illuminate\Http\Request;

class LoginController extends Controller
{
    . . .

    use AuthenticatesUsers;

    . . .
    protected $redirectTo = '/home';
    . . .

    public function __construct()
    {
        $this->middleware('guest')->except('logout');
    }

    public function login(Request $request)
    {
        $input = $request->all();

        $this->validate($request, [
            'email' => 'required|email',
            'password' => 'required',
        ]);

        if(auth()-
>attempt(array('email' => $input['email'], 'password' => $input['password'])))
        {
            if (auth()->user()->is_admin == 1) {
                return redirect()->route('admin.home');
            }else{
                return redirect()->route('home');
            }
        }else{
            return redirect()->route('login')
                ->with('error','Email dan Password Salah !');
        }
    }
}

```

15. Membuat Seeder untuk akun admin dan user baru

```

PS C:\xampp\htdocs\projectpwl> php artisan make:seeder CreateUsersSeeder
Seeder created successfully.

```

database/seeds/CreateUserSeeder.php

```

<?php

use Illuminate\Database\Seeder;
use App\User;

class CreateUsersSeeder extends Seeder
{

```

```

...
public function run()
{
    $user = [
        [
            'name'=>'Admin',
            'email'=>'admin@coffee.com',
            'is_admin'=>'1',
            'password'=> bcrypt('123456'),
        ],
        [
            'name'=>'User',
            'email'=>'user@gmail.com',
            'is_admin'=>'0',
            'password'=> bcrypt('123456'),
        ],
    ];

    foreach ($user as $key => $value) {
        User::create($value);
    }
}
}

```

16. Jalankan seeder dengan artisan


```

PS C:\xampp\htdocs\projectpwl> php artisan db:seed --class=CreateUsersSeeder
Database seeding completed successfully.


```

17. Jalankan project dengan perintah php artisan serve


Tampilan welcome :



Login oleh Admin :




A screenshot of a web browser displaying the Laravel login page. The browser's address bar shows the URL "127.0.0.1:8000/login". The page header includes the word "Laravel" on the left and "Login Register" on the right. The main content area features a "Login" form with a light gray header. Inside the form, there are two input fields: "E-Mail Address" containing "admin@coffee.com" and "Password" containing six dots. Below the password field is a checkbox labeled "Remember Me". At the bottom of the form are a blue "Login" button and a blue link "Forgot Your Password?".




A screenshot of a web browser displaying the Laravel admin dashboard. The browser's address bar shows the URL "127.0.0.1:8000/admin/home". The page header includes the word "Laravel" on the left and "Admin" with a dropdown arrow on the right. The main content area features a "Dashboard" section with a light gray header. Below the header, a white box contains the text "You are Admin !".

Login oleh User :





The screenshot shows a web browser window with the address bar displaying "127.0.0.1:8000/login". The page title is "Laravel". In the top right corner, there are links for "Login" and "Register". The main content area features a "Login" form with a light gray header. The form contains two input fields: "E-Mail Address" with the value "user@gmail.com" and "Password" with masked characters "*****". Below the password field is a checkbox labeled "Remember Me". At the bottom of the form, there is a blue "Login" button and a link "Forgot Your Password?".



The screenshot shows a web browser window with the address bar displaying "127.0.0.1:8000/home". The page title is "Laravel". In the top right corner, there is a user profile dropdown labeled "User". The main content area features a "Dashboard" section with a light gray header. Below the header, there is a white box containing the text "You are User!".

Register dengan akun baru



Kolom user pada database :

				id	name	email	email_verified_at	is_admin	password	remember
<input type="checkbox"/>	Edit	Copy	Delete	1	Admin	admin@coffee.com	NULL	1	\$2y\$10\$WSxJqxFnA91g7z/pVXIMQuRY9qWj5Hjf7Oh5esFaJWY...	NULL
<input type="checkbox"/>	Edit	Copy	Delete	2	User	user@gmail.com	NULL	0	\$2y\$10\$PSrRmC64J1zy2pQO07IP5e63DHwWvfNUJyrq6S6NEtl...	NULL
<input type="checkbox"/>	Edit	Copy	Delete	3	Lutfiah	lutfiahprilia28@gmail.com	NULL	NULL	\$2y\$10\$jnwebEWselHDVyaNpMY4bOfpjoXU6UeWhe3LfEpVyb...	NULL

18. Modifikasi tampilan welcome, login, dan register laravel

resource/views/welcome.blade.php

```
...  
html, body {  
    background-image: url('img/banner.jpeg');  
    background-size: cover;  
    font-family: sans-serif;
```

```

        font-weight: 100;
        color: white;
        height: 100vh;
        margin: 0;
    }
    body:before{
        content: '';
        display: block;
        position: absolute;
        top: 0px;
        left: 0px;
        right: 0px;
        bottom: 0px;
        background-color: rgba(60, 60, 19, 0.7);
    }
    .full-height {
        height: 100vh;
    }
    ...
    <div class="content">
        <div class="title m-b-md">
            GRANDMA COFFEE
        </div>
    </div>
    ...

```

Pada login dan register dapat dimodifikasi pada public\css\app.css

Output



HOME

1. Modifikasi app.blade.php. Untuk mengganti nama Laravel menjadi nama kedai kopi (Grandma Coffee). Dan menambahkan navbar di sebelah kanan. Untuk admin kita menggunakan layouts baru bernama 'appadmin.blade.php'

-Untuk User

resource/views/layouts/app.blade.php

```
...
<!-- Styles -->
<link href="{{ asset('css/app.css') }}" rel="stylesheet">
</head>
<body>
    <div id="app">
        <nav class="navbar navbar-expand-md navbar-light bg-white shadow-sm">
            <div class="container">
                <a class="navbar-brand" href="{{ url('/') }}">
                    {{ config('app.name', 'GRANDMA COFFEE') }}
                </a>
            ...
            <!-- Right Side Of Navbar -->
            <ul class="navbar-nav ml-auto">
                <!-- Authentication Links -->
                @guest
                    <li class="nav-item">
                        <a class="nav-link" href="{{ route('login') }}">{{ __('Login') }}</a>
                    </li>
                    @if (Route::has('register'))
                        <li class="nav-item">
                            <a class="nav-link" href="{{ route('register') }}">{{ __('Register') }}</a>
                        </li>
                    @endif
                @else
                    <li class="nav-item dropdown">
                        <a class="nav-link" href="{{ url('home') }}">HOME <span class="sr-only"></span>
                        </a>
                    </li>
                    <li class="nav-item dropdown">
                        <a class="nav-link" href="{{ url('menu') }}">MENU <span class="sr-only"></span>
                        </a>
                    </li>
                    <li class="nav-item dropdown">
                        <a class="nav-link" href="{{ url('order') }}">ORDER <span class="sr-only"></span>
                        </a>
                    </li>
                    <li class="nav-item dropdown">
                        <a class="nav-link" href="{{ url('contact') }}">CONTACT <span class="sr-only"></span>
                        </a>
                    </li>
                </ul>
            </div>
        </nav>
    </div>
</body>
</html>
```

```

        <li class="nav-item dropdown">
            <a id="navbarDropdown" class="nav-link dropdown-
toggle" href="#" role="button" data-toggle="dropdown" aria-haspopup="true" aria-expanded="false" v-
pre>
                {{ Auth::user()->name }}
            </a>
        ...

```

-Untuk Admin

resource/views/layouts/appadmin.blade.php

Sama seperti app.blade hanya merubah Right Side Of Navbar

```

...
<!-- Right Side Of Navbar -->
<ul class="navbar-nav ml-auto">
    <!-- Authentication Links -->
    @guest
        <li class="nav-item">
            <a class="nav-
link" href="{{ route('login') }}">{{ __('Login') }}</a>
        </li>
        @if (Route::has('register'))
            <li class="nav-item">
                <a class="nav-
link" href="{{ route('register') }}">{{ __('Register') }}</a>
            </li>
        @endif
    @else
        <li class="nav-item dropdown">
            <a class="nav-
link" href="{{ url('menuadmin') }}">MENU <span class="sr-only"></span>
            </a>
        </li>

        <li class="nav-item dropdown">
            <a class="nav-
link" href="{{ url('orderadmin') }}">ORDER <span class="sr-only"></span>
            </a>
        </li>

        <li class="nav-item dropdown">
            <a id="navbarDropdown" class="nav-link dropdown-
toggle" href="#" role="button" data-toggle="dropdown" aria-haspopup="true" aria-
expanded="false" v-pre>
                {{ Auth::user()->name }}
            </a>
        ...

```


Output :



2. Modifikasi views home.blade.php dan adminHome.blade.php

resource/views/home.blade.php

```
@extends('layouts.app')

@section('title', 'Home')
@section('content')
<link rel="stylesheet" href="{{asset('css/home.css')}}" >

<section class="banner">
    <h2>WELCOME TO GRANDMA COFFEE<br>Jl. Ronggomulyo 14 Tuban</h2>
</section>

<!--about-->
<section class="about">
    <h3>Tentang Kami</h3>
    <p>
        Grandma Coffee coffee shop dengan suasana hangat, menu yang unik dengan harga<br>
        yang terjangkau. Kami siap mengantar menu favorit ke rumah Anda!<br>
        Booking tempat untuk acara silahkan beralih ke menu <li2><a href="contact"><strong>CONTACT</strong></a></li2>.
    </p>
</section>
<!--footer-->
<footer>
    <div class="container"></div>
    <small>Copyright &copy; 2020 - Grandma Coffee</small>
</footer>
@endsection
```

resource/views/adminHome.blade.php

```
@extends('layouts.appadmin')

@section('title', 'Home')
@section('content')
<link rel="stylesheet" href="{{asset('css/home.css')}}" >
    <br>
<section class="banner">
    <h2>You Are Admin.</h2>
</section>
    <br><br><br>
```

```

<!--footer-->
<footer>
  <div class="container"></div>
  <small>Copyright &copy; 2020 - Grandma Coffee </small>
</footer>
@endsection

```

3. Buat file css baru dengan nama home.css

public/css/home.css


```

*{
  padding: 0;
  margin: 0;
  font-family: sans-serif;
}.banner{
  height: 70vh;
  background-image: url('img/banner.jpeg');
  background-size: cover;
  position: relative;
  justify-content: center;
  display: flex;
  align-items: center;
}
.banner::after{
  content: '';
  display: block;
  position: absolute;
  top: 0px;
  left: 0px;
  right: 0px;
  bottom: 0px;
  background-color: rgba(60, 60, 19, 0.5);
}
.banner h2{
  color: white;
  z-index: 1;
  padding: 20px 25px;
  border: 3px solid white;
  text-align: center;
}
section{
  padding: 50px 0px;
}
/* about */
h3{
  text-align: center;
  padding: 20px 0;
  color: #7f8584;
  margin-bottom: 20px;
}
.about p{
  color: #276b62;
  word-spacing: 2px;
  line-height: 25px;
  text-align: center;
}
/* footer */
footer{
  padding: 10px;
  background-color: #333;
  color: white;
  text-align: center;
}


```

Output :

- User



- Admin



MENU

1. Masih menggunakan database *projectpwl* . Buat migration untuk membuat table menu dengan nama "create_menu_table"

```
PS C:\xampp\htdocs\projectpwl> php artisan make:migration create_menu_table
Created Migration: 2020_12_05_171344_create_menu_table
```

2. Isi kolom table


```
...

public function up()
{
    Schema::create('menu', function (Blueprint $table) {
        $table->increment('id');
        $table->string('image');
        $table->string('name');
        $table->string('description');
        $table->float('price');
        $table->timestamps();
    });
}
...
```

3. Migrate kolom table

```
PS C:\xampp\htdocs\projectpwl> php artisan migrate
Migrating: 2020_12_05_171344_create_menu_table
Migrated: 2020_12_05_171344_create_menu_table (1.1 seconds)
PS C:\xampp\htdocs\projectpwl>
```

4. Table menu pada database



The screenshot shows the phpMyAdmin interface with the 'Table structure' tab selected for the 'menu' table in the 'projectpwl' database. The table structure is as follows:

#	Name	Type	Collation	Attributes	Null	Default	Comments	Extra	Action
1	id	int(10)		UNSIGNED	No	None		AUTO_INCREMENT	Change Drop More
2	image	varchar(255)	utf8mb4_unicode_ci		No	None			Change Drop More
3	name	varchar(255)	utf8mb4_unicode_ci		No	None			Change Drop More
4	description	varchar(255)	utf8mb4_unicode_ci		No	None			Change Drop More
5	price	double(8,2)			No	None			Change Drop More
6	created_at	timestamp			Yes	NULL			Change Drop More
7	updated_at	timestamp			Yes	NULL			Change Drop More

At the bottom, there are checkboxes for 'Check all' and 'With selected:'. Below these are icons and labels for 'Browse', 'Change', 'Drop', 'Primary', 'Unique', 'Index', 'Fulltext', and 'Add to central columns'. There is also a 'Remove from central columns' link.

5. Membuat model Menu

```
PS C:\xampp\htdocs\projectpw1> php artisan make:model Menu
Model created successfully.
```

app/Menu.php

```
<?php

namespace App;

use Illuminate\Database\Eloquent\Model;

class Menu extends Model
{
    protected $table='menu';
    protected $guarded=[];
}
```

Menu Admin

Setelah membuat migration dan Model, selanjutnya adalah membuat tampilan untuk menu admin

1. Membuat routes

```
Route::get('/menuadmin', 'MenuController@menuadmin')->name('menuadmin');
```

2. Membuat controller untuk menu admin

```
PS C:\xampp\htdocs\projectpw1> php artisan make:controller MenuController
Controller created successfully.
```

app/Http/Controllers/MenuController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\Menu;


class MenuController extends Controller
{
    public function menuadmin(){
        $data_menu = Menu::all();
        return view ('menuadmin',compact('data_menu'));
    }
}
```

3. Membuat view menu untuk admin dengan nama file 'menuadmin.blade.php'

resources/views/menuadmin.blade.php

```
@extends('layouts.appadmin')
@section('title','Menu')
```

Output :



```
Route::get('/menuadmin/create', 'MenuController@create')->name('menuadmin.create');
Route::PUT('/menuadmin/store', 'MenuController@store')->name('menuadmin.store');
```

5. Tambahkan fungsi untuk create dan store pada controller

Fungsi create untuk memanggil route menu create yang akan membuat menu baru. Fungsi store digunakan untuk menampilkan data baru yang telah diinputkan ke menuadmin (menu untuk admin), dan menu(menu untuk user)

app/Http/Controllers/MenuController.php

```
...

public function create(){
    return view ('menu_create');
}
public function store(Request $request){
    Menu::create($request->all());
    return redirect()->route('menuadmin','menu');
}

...
```

6. Modifikasi menuadmin. Tambahkan botton dan form baru untuk menambah data menu

resources/views/menuadmin.blade.php




```
...
<div class="card body">
    <br><p><a href="{{route('menuadmin.create')}}" class="btn btn-primary btn-
lg btn-block"> + Tambah Menu</a></p>
    <table class="table table-bordered" >
        <tr>
            <th><b>No</b></th>
            <th><b>Image</b></th>
            <th><b>Nama</b></th>
            <th><b>Keterangan</b></th>
            <th><b>Harga</b></th>
            <th><b>Action</b></th>
        </tr>
        @php $id=0; @endphp
        @foreach($data_menu as $value)
            @php $id++; @endphp
            <tr>
                <td>{{ $id }}</td>
                <td>
                    
                </td>
                <td>{{ $value->name }}</td>
                <td>{{ $value->description }}</td>
                <td>{{ $value->price }}</td>
            </tr>
        @endforeach
    </table>
</div>
...
```

7. Membuat view untuk create menu

resources/views/menu_create.blade.php

```
@extends('layouts.appadmin')
@section('content')
<div class="container">
    <div class="row justify-content-center">
        <div class="col-md-10">
            <div class="card">
                <div class="card-header">TAMBAH MENU</div>
                <div class="card body">
                    <form method="POST" action="{{route('menuadmin.store')}}">
                        @csrf
                        @method('PUT')
                        <br>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right">Gambar</label>
                            <div class="col-md-6 width="100px">
                                <input type="file" name="image" class="form-control-file">
                            </div>
                        </div>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right">Nama Menu</label>
                            <div class="col-md-6">
                                <input type="text" name="name" class="formcontrol" placeholder="Masukkan nama menu">
                            </div>
                        </div>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right">Deskripsi Menu</label>
                            <div class="col-md-6">
                                <input type="text" name="description" class="form-control" placeholder="Masukkan deskripsi menu">
                            </div>
                        </div>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right">Harga</label>
                            <div class="col-md-6">
                                <input type="text" name="price" class="form-control" placeholder="Masukkan harga">
                            </div>
                        </div>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right"></label>
                            <div class="col-md-6">
                                <button class="btn btn-success" type="submit">SIMPAN</button>
                                <a class="btn btn-danger" href="{{ route('menuadmin') }}" role="button">BATAL</a>
                            </div>
                        </div>
                    </form>
                </div>
            </div>
        </div>
    </div>
</div></div>
@endsection
```


Output :



8. Untuk mengedit data , tambahkan routes baru

Route get digunakan untuk memanggil fungsi mengedit data, Route PUT digunakan untuk memanggil fungsi pada data yang telah diedit

routes/web.php

```
Route::get('/menuadmin/edit/{id}', 'MenuController@edit')->name('menuadmin.edit');
Route::PUT('/menuadmin/update{id}', 'MenuController@update')->name('menuadmin.update');
```

9. Tambahkan fungsi edit, dan update pada controller

app/Http/Controllers/MenuController.php

```
...

public function edit($id){
    $data_menu = Menu::findorfail($id);
    return view('menu_edit',compact('data_menu'));
}

public function update(Request $request, $id){
    $data_menu = Menu::findorfail($id)
    -> update ([
        'image'      => $request['image'],
        'name'       => $request['name'],
        'description' => $request['description'],
        'price'      => $request['price'],
    ]);
    return redirect()->route('menuadmin','menu');
}

...
```

10. Memodifikasi menublade. Tambahkan button untuk edit setelah

resources/views/menuadmin.blade.php

```
...
<tr>
    <td>...</td>
    <td>...</td>
    <td>...</td>
    <td>...</td>
    <td>...</td>
    <td>
        <a href="{{route('menuadmin.edit',$value['id'])}}" class="btn btn-
warning">EDIT</a>
    </td>
</tr>
...
```

11. Menambahkan view baru untuk edit




resources/views/menu_edit.blade.php

```

@extends('layouts.appadmin')
@section('content')
<div class="container">
    <div class="row justify-content-center">
        <div class="col-md-10">
            <div class="card">
                <div class="card-header">EDIT MENU</div>
                <div class="card body">
                    <form method="POST" action="{{route('menuadmin.update', $data_menu['id
' ]}}}">
                        @csrf
                        @method('PUT')
                        <br>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right">Gambar</label>
                            <div class="col-md-6">
                                <input type="file" name="image" value="{{ $data_menu['image'] }}"
class="form-control-file">
                            </div>
                        </div>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right">Nama Menu</label>
                            <div class="col-md-6">
                                <input type="text" name="name" value="{{ $data_menu['name'] }}" cl
ass="form-control" >
                            </div>
                        </div>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right">Deskripsi Menu</label>
                            <div class="col-md-6">
                                <input type="text" name="description" value="{{ $data_menu['descr
iption'] }}" class="form-control" >
                            </div>
                        </div>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right">Harga</label>
                            <div class="col-md-6">
                                <input type="text" name="price" value="{{ $data_menu['price'] }}"
class="form-control" >
                            </div>
                        </div>
                        <div class="form-group row">
                            <label class="col-md-4 text-md-right"></label>
                            <div class="col-md-6">
                                <button class="btn btn-success" type="submit">SIMPAN</button>
                            </div>
                        </div>
                    </form>
                </div>
            </div>
        </div>
    </div>
</div>
</div>
@endsection

```

Output :



12. Untuk menghapus data tambahkan routes baru untuk memanggil fungsi delete pada controller

routes/web.php

```
Route::get('/menuadmin/delete/{id}', 'MenuController@delete')->name('menuadmin.delete');
```

13. Tambahkan fungsi delete pada controller untuk menghapus data menu

app/Http/Controllers/MenuController.php

```
...

public function delete($id){
    $data_menu = Menu::findorfail($id)
    -> delete();
    return redirect()->route('menuadmin','menu');
}

...
```

14. Modifikasi menuadmin untuk menambahkan button hapus

resources/views/menuadmin.blade.php

```
...
<tr>
    <td>...</td>
    <td>...</td>
    <td>...</td>
    <td>...</td>
    <td>...</td>
    <td>
        <a ... </a>
        <a href="{{route('menuadmin.delete',$value['id'])}}"
            onclick="return confirm('Apakah Anda yakin ingin menghapus menu {{$value['name']}}')" class="btn btn-danger">HAPUS</a>
    </td>
</tr>
...
```





Output :

127.0.0.1:8000/menuadmin?menu

GRANDMA COFFEE Login Register

MENU

+ Tambah Menu

No	Image	Nama	Keterangan	Harga	Action
1		Hot Cappuccino	Espresso susu segar, dan foam	10000	EDIT HAPUS
2		Hot Americano	Espresso dan air panas	10000	EDIT HAPUS
3		Bombon	Espresso, kental manis, bubuk kakao	12000	EDIT HAPUS
4		Latte	Espresso, susu segar, dan foam	10000	EDIT HAPUS





127.0.0.1:8000/menuadmin?menu

GRANDMA COFFEE Login Register

127.0.0.1:8000 says
Apakah Anda yakin ingin menghapus menu Hot Cappuccino

MENU

+ Tambah Menu

No	Image	Nama	Keterangan	Harga	Action
1		Hot Cappuccino	Espresso susu segar, dan foam	10000	EDIT HAPUS
2		Hot Americano	Espresso dan air panas	10000	EDIT HAPUS
3		Bombon	Espresso, kental manis, bubuk kakao	12000	EDIT HAPUS
4		Latte	Espresso, susu segar, dan foam	10000	EDIT HAPUS

127.0.0.1:8000/menuadmin/delete/%

127.0.0.1:8000/menuadmin?menu

GRANDMA COFFEE Login Register

MENU

+ Tambah Menu





No	Image	Nama	Keterangan	Harga	Action
1		Hot Americano	Espresso dan air panas	10000	EDIT HAPUS
2		Bombon	Espresso, kental manis, bubuk kakao	12000	EDIT HAPUS
3		Latte	Espresso, susu segar, dan foam	10000	EDIT HAPUS
4		Afogato	Espresso dan ice cream	15000	EDIT HAPUS

Table menu pada database :

+ Options									
			id	image	name	description	price	created_at	updated_at
<input type="checkbox"/>				6	amrc_h.jpg	Hot Americano	Espresso dan air panas	10000.00	2020-12-07 17:25:19 2020-12-07 17:26:41
<input type="checkbox"/>				7	bombon.jpg	Bombon	Espresso, kental manis, bubuk kakao	12000.00	2020-12-07 17:28:27 2020-12-07 17:28:27
<input type="checkbox"/>				8	latte.jpg	Latte	Espresso, susu segar, dan foam	10000.00	2020-12-07 17:29:50 2020-12-07 17:29:50
<input type="checkbox"/>				9	afogato.jpg	Afogato	Espresso dan ice cream	15000.00	2020-12-07 17:30:53 2020-12-07 17:30:53
<input type="checkbox"/>				10	amrc_s.jpg	Ice Americano	Espresso, air, dan es batu	10000.00	2020-12-07 17:32:22 2020-12-07 17:32:22
<input type="checkbox"/> Check all With selected: Edit Copy Delete Export									

Menu User

1. Membuat routes untuk user untuk memanggil fungsi menu

routes/web.php

```
Route::get('/menu', 'MenuController@menu')->name('menu');
```

2. Menambahkan fungsi menu pada controller

app/Http/Controllers/MenuController

```
...  
public function menu(){  
    $data_menu = Menu::all();  
    return view('menu', compact('data_menu'));  
}  
...
```

3. View menu untuk user

resources/views/menu.blade.php

```
@extends('layouts.app')  
  
@section('title','Menu')  
@section('content')  
<div class="container">  
    <div class="row justify-content-center">  
        <div class="col-md-10">  
            <div class="card">  
                <div class="card-header">MENU  
                <div class="card body">  
  
                <table class="table table-bordered">  
                    <tr>  
                        <th><b>No</b></th>  
                        <th><b>Image</b></th>  
                        <th><b>Nama</b></th>  
                        <th><b>Keterangan</b></th>  
                        <th><b>Harga</b></th>
```






```

        </tr>
        @php $id=0; @endphp

        @foreach($data_menu as $value)
        @php $id++; @endphp
        <tr>
            <td>{{ $id }}</td>
            <td>
                
            </td>
            <td>{{ $value->name }}</td>
            <td>{{ $value->description }}</td>
            <td>{{ $value->price }}</td>
        </tr>
        @endforeach
    </table>
</div>
</div>
</div>
</div>
</div>
</div>
@endsection

```

Output

No	Image	Nama	Keterangan	Harga
1		Hot Americano	Espresso dan air panas	10000
2		Bombon	Espresso, kental manis, bubuk kakao	12000
3		Latte	Espresso, susu segar, dan foam	10000
4		Afogato	Espresso dan ice cream	15000
5		Ice Americano	Espresso, air, dan es batu	10000

ORDER

Header Transaksi

```
Created Migration: 2020_12_18_122308_header_transaksi
PS C:\xampp\htdocs\projectpwl> php artisan migrate
Migrating: 2020_12_18_122308_header_transaksi
Migrated: 2020_12_18_122308_header_transaksi (0.32 seconds)
```

```
...
public function up()
{
    Schema::create('header_transaksi', function (Blueprint $table) {
        $table->increments('id_header_transaksi');
        $table->date('tanggal_transaksi');
        $table->timestamps();

    });
}
...
public function down()
{
    Schema::dropIfExists('header_transaksi');
}
...
```

Detail Transaksi

```
PS C:\xampp\htdocs\projectpwl> php artisan make:migration DetailTransaksi
Created Migration: 2020_12_18_122401_detail_transaksi
PS C:\xampp\htdocs\projectpwl> php artisan migrate
Migrating: 2020_12_18_122401_detail_transaksi
Migrated: 2020_12_18_122401_detail_transaksi (1.75 seconds)
```

```
...
public function up()
{
    Schema::create('detail_transaksi', function (Blueprint $table) {
        $table->increments('id_detail_transaksi');
        $table->integer('id_menu')->unsigned();
        $table->integer('id_header_transaksi')->unsigned();
        $table->integer('jumlah');
        $table->timestamps();

        $table->foreign('id_menu')->references('id')->on('menu');
        $table->foreign('id_header_transaksi')->references('id_header_transaksi')->on('header_transaksi');
    });
}
...
public function down()
{
    Schema::table('detail_transaksi', function(Blueprint $table){
        $table->dropForeign('detail_transaksi_menu_id_foreign');
        $table->dropForeign('detail_transaksi_header_transaksi_id_header_transaksi_foreign');
    });
}
```

```

        Schema::dropIfExists('detail_transaksi');
    }
    ...

```

Model HeaderTransaksi

```

<?php

namespace App;

use Illuminate\Database\Eloquent\Model;
use App\Menu;
use App\DetailTransaksi;

class HeaderTransaksi extends Model
{
    protected $table = 'header_transaksi';
    protected $primaryKey = 'id_header_transaksi';

    protected $fillable = [
        'tanggal_transaksi'
    ];

    static function tambah_header_transaksi(){
        $data = HeaderTransaksi::create([
            'tanggal_transaksi' => date('Y-m-d'),
        ]);
        return $data->id_header_transaksi;
    }
}

```

Model DetailTransaksi

```

<?php

namespace App;
use App\Menu;
use App\HeaderTransaksi;

use Illuminate\Database\Eloquent\Model;

class DetailTransaksi extends Model
{
    protected $table = 'detail_transaksi';
    protected $primaryKey = 'id_header_transaksi';

    protected $fillable = [
        'id_header_transaksi', 'id', 'jumlah'
    ];

    static function tambah_detail_transaksi($id, $id_header_transaksi, $jumlah){
        DetailTransaksi::create([
            'id' => $id,
            'id_header_transaksi' => $id_header_transaksi,
            'jumlah' => $jumlah,
        ]);
    }
}

```

Model Menu

```
<?php

namespace App;

use Illuminate\Database\Eloquent\Model;
use App\DetailTransaksi;
use App\HeaderTransaksi;

class Menu extends Model
{
    protected $table='menu';
    protected $guarded=[];

    protected $primaryKey = 'id';
    protected $fillable = [
        'name','price',
    ];

    static function list_menu(){
        $data_menu = Menu::all();
        return $data_menu;
    }

    static function tambah_menu($name, $price){
        Menu::create([
            'name' => $name,
            'price' => $price,
        ]);
    }

    static function detail_menu($id){
        $data_menu = Menu::where('id', $id)->first();

        return $data_menu;
    }
}
```

Route

```
//tambah order
Route::get('/cart/tambah/{id}', 'OrderController@tambah_cart')->name('tambahcart');
Route::get('/cart', 'OrderController@cart')->name('cart');
//hapus order
Route::get('/cart/hapus/{id}', 'OrderController@hapus_cart')->name('carthapus');
//pesan menu
Route::get('/pesan/tambah', 'OrderController@klikpesan')->name('klikpesan');
```

Order Controller

```
<?php
```

```

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use App\HeaderTransaksi;
use App\DetailTransaksi;
use App\Order;
use App\Menu;

class OrderController extends Controller
{
    public function index(){
        $menu = Menu::list_menu();
        return view('menu')->with('menu', $menu);
    }

    public function tambah_cart($id){
        $cart = session('cart');
        $menu = Menu::detail_menu($id);

        $cart[$id] = [
            'name' => $menu->name,
            'price' => $menu->price,
            'jumlah' => 1
        ];

        session(['cart' => $cart]);
        return redirect()->route('cart','orderan');
    }

    public function cart(){
        $cart = session('cart');
        return view('cart')->with('cart',$cart);
    }

    public function orderan(){
        DetailTransaksi::create([
            'id' => $id,
            'id_header_transaksi' => $id_header_transaksi,
            'jumlah' => $jumlah,

        ]);
        return view ('orderan');
    }

    public function hapus_cart($id){
        $cart = session('cart');
        unset($cart[$id]);
        session(['cart' => $cart]);

        return redirect('cart');
    }

    public function klikpesan(){
        session()->forget('cart');
        return view('tunggu');
    }
}

```

Cart.blade.php

```
@extends('layouts.app')

@section('title','Order')
@section('content')

    @if(empty($cart))
        <h3>
            Anda belum mempunyai pesanan, Silahkan kembali ke <li2><a href="menu"><strong>MENU</strong></a></li2> untuk memesan.
        </h3>

    @else
        <div class="container">
            <div class="row justify-content-center">
                <div class="col-md-10">
                    <div class="card-menu-menu">
                        <div class="card-header">YOUR ORDER</div>
                        <div class="card body">

                            <table class="table table-striped">
                                <tr>
                                    <th>No</th>
                                    <th>Nama</th>
                                    <th>Harga</th>
                                    <th>Jumlah</th>
                                    <th>Total</th>
                                    <th>Action</th>
                                    <th>&nbsp;</th>
                                </tr>

                                @php $id=1;
                                    $total=0;
                                    $subtotal=0;

                                @endphp

                                @foreach($cart as $ct => $value)
                                    @php
                                        $total = $value['price'] * $value['jumlah'];
                                    @endphp

                                    <tr>
                                        <td>{{$id++}}</td>
                                        <td>{{$value['name']}}</td>
                                        <td>Rp {{$value['price']}}</td>
                                        <td>{{$value['jumlah']}}</td>
                                        <td>Rp {{$total}}</td>
                                        <td><a href="{url('/cart/hapus/'.$ct)}" class="btn btn-danger">Hapus</a></td>
                                    </tr>

                                    @php
                                        $subtotal += $total;
                                    @endphp
                                @endforeach
                            </table>
                        </div>
                    </div>
                </div>
            </div>
        </div>
    @endif
@endsection
```

```

        @endphp

    @endforeach


    <tr>
        <th colspan="4">TOTAL BAYAR</th>
        <th>Rp {{ $subtotal }}</th>
        <th>&nbsp;</th>
    </tr>
</table>

    <a href="{{ route('klikpesan') }}" class="btn btn-
success">PESAN</a>

    </div>
</div>
</div>
</div>
</div>
@endif
@endsection

```

Output



Tunggu.blade.php

```

@extends('layouts.app')

@section('title','Wait')
@section('content')
<link rel="stylesheet" href="{{ asset('css/home.css') }}" >


```

```
<section class="tunggu">
  <h2>Terimakasih, Pesananmu sedang disiapkan :) </h2>

</section>

<!--footer-->
<footer>
  <div class="container"></div>
  <small>Copyright &copy; 2020 - Grandma Coffee </small>
</footer>
@endsection
```

Output



CONTACT

1. Membuat route untuk memanggil fungsi contact

routes/web.php

```
Route::get('/contact', 'ContactController@contact');
```

2. Membuat controller baru untuk contact

```
PS C:\xampp\htdocs\projectpw1> php artisan make:controller ContactController
Controller created successfully.
```

app/Http/Controllers/ContactController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

class ContactController extends Controller
{
    public function contact(){
        return view('contact');
    }
}
```

3. Membuat view contact

resources/views/contact.blade.php

```
@extends('layouts.app')

@section('title','Contact')
@section('content')
<link rel="stylesheet" href="{{asset('css/contact.css')}}" >
<link href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/5.15.1/css/all.min.css" rel="stylesheet">
<div class="cover">
<h3>CONTACT US</h3>
    <section class="contact">
        <div class="container">
            <div class="opsi">
                <h4>Address</h4>
                <p>JL Ronggomulyo 14 Latsari, Tuban, 62315</p>
            </div>
            <div class="opsi">
                <h4>Email</h4>
                <p>grandmacoffee@gmail.com</p>
            </div>
            <div class="opsi">
                <h4>Telp</h4>
            </div>
        </div>
    </section>
</div>
```



```

        <p>(021) 12345678</p>
    </div>
    <div class="opsi">
        <h4>Whatsapp</h4>
        <p>085203876900</p>
    </div>

</div>
</section>
<h3>GET SOCIAL</h3>
<section class="contact2">
    <div class="container2">
        <ul>
            <li class="sosmed">
                <a href="https://instagram.com/grandmacoffee.id?igshid=1hcyddeobqv2r" >
                    <i class="fab fa-instagram fa-3x" style="color : crimson"></i>
                    <div class="ig">Instagram</div>
                </a>
            </li>
            <li class="sosmed">
                <a href="https://www.facebook.com/grandmacoffeetuban">
                    <i class="fab fa-facebook-square fa-3x" style="color : blue"></i>
                    <div class="fb">Facebook</div>
                </a>
            </li>
            <li class="sosmed">
                <a href="https://twitter.com/gramshardcoffee">
                    <i class="fab fa-twitter fa-3x" style="color : deepskyblue"></i>
                    <div class="tw">Twitter</div>
                </a>
            </li>
        </ul>
    </div>
</section>
</div>
@endsection

```

4. Css untuk menu contact

public/css/contact.css

```

*{
    padding: 0;
    margin: 0;
}
.cover{
    background: rgba(128, 94, 44, 0.5);
}
h3{
    text-align: center;
    padding: 15px 0;
    color: wheat;
    margin-bottom: 10px;
    background-image: url('img/bgcoklat.jpg');
    border-radius: 40px;
}

```

```
    width: 30% ;
    margin-top: 10px;
    margin-left: 35%;
}
section {
    padding: 40px 0;
    width: 70%;
    margin: 0 auto;
}
.container{
    width: 80%;
    margin: 0 auto;
}
.container::after{
    content: '';
    display: block;
    clear: both;
}
.contact{
    background-color:#d6d2c4;
    margin-bottom: 5%;
}
.opsi{
    width: 25%;
    padding: 20px;
    box-sizing: border-box;
    text-align: center;
    float: left;
}
.container2{
    width: 80%;
    margin: 0 auto;
}
.container2::after{
    content: '';
    display: block;
    clear: both;
}
.contact2{
    background-color:#d6d2c4;
}
.sosmed{
    width: 33%;
    padding: 10px;
    box-sizing: border-box;
    text-align: center;
    float: left;
    font-size: 20px;
    list-style-type: none;
    color: black;
}
.sosmed .ig{
    color: crimson;
    font-family: 'Trebuchet MS';
    font-style: italic;
}
.sosmed .fb{
    color: blue;
    font-family: 'Trebuchet MS';
    font-style: bold;
}
```

```
.sosmed .tw{
  color: #00acee;
  font-family: 'Trebuchet MS';
  font-style: oblique;
}
```

Output

