

Python - Access Tuple Items

[< Previous](#)[Next >](#)

Access Tuple Items

You can access tuple items by referring to the index number, inside square brackets:

Example

Print the second item in the tuple:

```
thistuple = ("apple", "banana", "cherry")  
print(thistuple[1])
```

[Try it Yourself »](#)

Note: The first item has index 0.

Negative Indexing

Negative indexing means start from the end.

-1 refers to the last item, **-2** refers to the second last item etc.

Example



```
thistuple = ("apple", "banana", "cherry")  
print(thistuple[-1])
```

[Try it Yourself »](#)

Range of Indexes

You can specify a range of indexes by specifying where to start and where to end the range.

When specifying a range, the return value will be a new tuple with the specified items.

Example

Return the third, fourth, and fifth item:

```
thistuple = ("apple", "banana", "cherry", "orange", "kiwi", "melon",  
"mango")  
print(thistuple[2:5])
```

[Try it Yourself »](#)

Note: The search will start at index 2 (included) and end at index 5 (not included).

Remember that the first item has index 0.

By leaving out the start value, the range will start at the first item:

Example



```
thistuple = ("apple", "banana", "cherry", "orange", "kiwi", "melon",  
"mango")  
print(thistuple[:4])
```

[Try it Yourself »](#)

By leaving out the end value, the range will go on to the end of the list:

Example

This example returns the items from "cherry" and to the end:

```
thistuple = ("apple", "banana", "cherry", "orange", "kiwi", "melon",  
"mango")  
print(thistuple[2:])
```

[Try it Yourself »](#)

Range of Negative Indexes

Specify negative indexes if you want to start the search from the end of the tuple:

Example

This example returns the items from index -4 (included) to index -1 (excluded)

```
thistuple = ("apple", "banana", "cherry", "orange", "kiwi", "melon",  
"mango")  
print(thistuple[-4:-1])
```

[Try it Yourself »](#)



To determine if a specified item is present in a tuple use the **in** keyword:

Example

Check if "apple" is present in the tuple:

```
thistuple = ("apple", "banana", "cherry")
if "apple" in thistuple:
    print("Yes, 'apple' is in the fruits tuple")
```


Try it Yourself »

◀ Previous

Next ▶


NEW

We just launched
W3Schools videos



Explore now

COLOR PICKER



[HTML](#)[CSS](#)

Get certified
by completing
a course today!



Get started

CODE GAME



Play Game

Report Error

Forum

About



Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [Angular Reference](#)
- [jQuery Reference](#)

Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [Java Examples](#)
- [XML Examples](#)
- [jQuery Examples](#)

Web Courses

- [HTML Course](#)
- [CSS Course](#)
- [JavaScript Course](#)
- [Front End Course](#)
- [SQL Course](#)
- [Python Course](#)

[HTML](#)[CSS](#)[Java Course](#)[C++ Course](#)[C# Course](#)[XML Course](#)[Get Certified »](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2021 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

