

FILE PERMISSIONS

```
srivalli@DESKTOP-6S9T6SD: ~$ mkdir OSlab
mkdir: cannot create directory 'OSlab': File exists
srivalli@DESKTOP-6S9T6SD: ~$ cd OSlab
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ nano permission.c
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ gcc permission.c -o permission
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ ./permission
File created successfully.
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ ls -l sample.txt
-rw-r--r-- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ chmod 666 sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ ls -l sample.txt
-rw-rw-rw- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ chmod u+rw sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ ls -l sample.txt
-rw-rw-rw- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ chmod o+rw sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ ls -l sample.txt
-rw-rw-rw- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ chmod a+rw sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ ls -l sample.txt
-rw-rw-rw- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ |
```

Tasks:

- 1) Give Read and Write only to the owner

```
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ chmod 600 sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ ls -l sample.txt
-rw----- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD: ~/OSlab$ |
```

- 2) Give Read and Write to the owner and group

```

srivalli@DESKTOP-6S9T6SD:~/OSlab$ chmod 660 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ ls -l sample.txt
-rw-rw---- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ |

```

- 3) Only owner can read and write

```

srivalli@DESKTOP-6S9T6SD:~/OSlab$ chmod 600 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ ls -l sample.txt
-rw----- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ |

```

- 4) Owner read/write, everyone else read-only

```

srivalli@DESKTOP-6S9T6SD:~/OSlab$ chmod 644 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ ls -l sample.txt
-rw-r--r-- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ |

```

- 5) Owner can do everything, others can only read and execute

```

srivalli@DESKTOP-6S9T6SD:~/OSlab$ chmod 755 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ ls -l sample.txt
-rwxr-xr-x 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ |

```

- 6) Owner and group can read/write

```

srivalli@DESKTOP-6S9T6SD:~/OSlab$ chmod 660 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ ls -l sample.txt
-rw-rw---- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ |

```

- 7) Only owner can execute

```

srivalli@DESKTOP-6S9T6SD:~/OSlab$ chmod 100 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ ls -l sample.txt
---x----- 1 srivalli srivalli 28 Aug 17 05:16 sample.txt
srivalli@DESKTOP-6S9T6SD:~/OSlab$ |

```

Fill in the permission numbers for the following:

- 8) Owner: read + write; Group: nothing; Others: nothing → 600
- 9) Owner: read + write; Group: read; Others: read → 644
- 10) Owner: read + write + execute; Group: read + execute; Others: read + execute → 755
- 11) Owner: read + write; Group: read + write; Others: nothing → 660
- 12) Everyone: read only → 444