File Edit View Run Kernel Tabs Settings Help

Day_10_Task_5.ipynb | Day11_Task_2.ipynb | Day11_Task_5.ipynb | Day11_Task_6.ipynb | sample_student_performanc

Code | Python 3 (ipykernel)

[1]:
```
import pandas as pd
import numpy as np

df = pd.read_csv("ecommerce_dirty_sample.csv")
```

[2]:
```
df[["city", "quantity", "unit_price"]].head()
df[["city", "quantity", "unit_price"]].info()
df[["city", "quantity", "unit_price"]].isnull().sum()
```

```
<class 'pandas.DataFrame'>
RangeIndex: 104 entries, 0 to 103
Data columns (total 3 columns):
 #   Column      Non-Null Count  Dtype
---  ------      --------------  -----
 0   city        103 non-null    str
 1   quantity    104 non-null    str
 2   unit_price  102 non-null    float64
dtypes: float64(1), str(2)
memory usage: 2.6 KB
```

[2]:
```
city          1
quantity      0
unit_price    2
dtype: int64
```

[3]:
```
df["city"] = df["city"].astype("string").str.strip().str.title()
df["quantity"] = pd.to_numeric(df["quantity"], errors="coerce")
df["unit_price"] = pd.to_numeric(df["unit_price"], errors="coerce")
```

[4]:
```
df["city"] = df["city"].replace("", pd.NA)
df.loc[df["quantity"] <= 0, "quantity"] = np.nan
df.loc[df["unit_price"] < 0, "unit_price"] = np.nan

df[["city", "quantity", "unit_price"]].isnull().sum()
```

Would you like to get notified about official Jupyter news?
Open privacy policy Yes No

[4]:
```
city          1
quantity      3
unit_price    3
dtype: int64
```

[5]:
```
df["revenue"] = df["quantity"] * df["unit_price"]
```

[6]:
```
df[["order_id", "city", "quantity", "unit_price", "revenue"]].head(10)
df["revenue"].describe()
```

[6]:
```
count    9.800000e+01
mean     1.022268e+05
std      9.136653e+05
min      2.495000e+01
25%      4.900000e+01
50%      8.997000e+01
75%      1.495000e+02
max      8.999900e+06
Name: revenue, dtype: float64
```

[7]:
```
city_revenue = df.groupby("city")["revenue"].sum()
city_revenue
```

[7]:
```
city
Ahmedabad         240.000
Bengaluru        1064.765
Chennai       9008676.740
Coimbatore        270.000
Delhi         1000399.940
Hyderabad        4893.000
Jaipur            343.000
Kolkata           539.820
Lucknow           124.750
Mumbai           1046.500
Pune              540.000
Name: revenue, dtype: float64
```

Would you like to get notified about official Jupyter news?
Open privacy policy Yes N

[8]:
```
city_revenue = city_revenue.sort_values(ascending=False)
city_revenue
```

[8]:
```
city
Chennai       9008676.740
Delhi         1000399.940
Hyderabad        4893.000
Bengaluru        1064.765
Mumbai           1046.500
Pune              540.000
Kolkata           539.820
Jaipur            343.000
Coimbatore        270.000
Ahmedabad         240.000
Lucknow           124.750
Name: revenue, dtype: float64
```

[9]:
```
print("Highest revenue city:", city_revenue.idxmax())
print("Total revenue:", city_revenue.max())
```

```
Highest revenue city: Chennai
Total revenue: 9008676.74
```

[ ]:

Would you like to get notified about official Jupyter news?
Open privacy policy Yes N


Would you like to get notified about official Jupyter news?
Open privacy policy
Yes
N
4
Python 3 (ipykernel) | Idle
Mode: Command
Cell 10/10
Ln 1, Col 1
Day11_Task_6.ipynb
1