

On Detecting an Anomalous Arm in a Multi-armed Bandit with Markov Observations

Joint work with Rajesh Sundaresan

P. N. Karthik

Dept. of Electrical Communication Engg.

IISc, Bangalore

periyapatna@iisc.ac.in


STCS Annual Symposium 2020

TIFR, Mumbai

March 1, 2020


Motivation

A Visual Search Experiment



Can you identify the location of the “odd” image as quickly as possible?

A Visual Search Experiment



Can you identify the location of the “odd” image as quickly as possible?

A Closer Look at the Visual Search Experiment

- In the first example, you were told what the odd and the non-odd images are, but in the second example, you were not

A Closer Look at the Visual Search Experiment

- In the first example, you were told what the odd and the non-odd images are, but in the second example, you were not
- The above information affected the time taken to identify the odd image - shorter time in the first example

A Closer Look at the Visual Search Experiment

- In the first example, you were told what the odd and the non-odd images are, but in the second example, you were not
- The above information affected the time taken to identify the odd image - shorter time in the first example
- Time to identify the odd image $\propto \frac{1}{\text{"closeness" of the images}}$

A Closer Look at the Visual Search Experiment

- In the first example, you were told what the odd and the non-odd images are, but in the second example, you were not
- The above information affected the time taken to identify the odd image - shorter time in the first example
- Time to identify the odd image $\propto \frac{1}{\text{"closeness" of the images}}$

Can we make precise this notion of closeness?

A Closer Look at the Visual Search Experiment

- In the first example, you were told what the odd and the non-odd images are, but in the second example, you were not
- The above information affected the time taken to identify the odd image - shorter time in the first example
- Time to identify the odd image $\propto \frac{1}{\text{"closeness" of the images}}$

Can we make precise this notion of closeness?


- If the static images in the previous experiments were replaced with dynamic images (movies)[†], what is the notion of closeness of the odd and the non-odd movies?

[†]Krueger, Paul M., et al. "Evidence accumulation detected in BOLD signal using slow perceptual decision making." *Journal of neuroscience methods* 281 (2017): 21-32.

Problem Setup: Odd Arm Identification


Problem Formulation

- A multi-armed bandit with $K \geq 3$ arms
- Each arm is either an iid process or a Markov process on a finite state space
- The law of one of the arms (the **odd** arm) is P_1 , which is different from P_2 , the common law of each of the other arms
- P_1 and P_2 may or may not be known
- Sequential arm selections



Problem Formulation

- A multi-armed bandit with $K \geq 3$ arms
- Each arm is either an iid process or a Markov process on a finite state space
- The law of one of the arms (the **odd** arm) is P_1 , which is different from P_2 , the common law of each of the other arms
- P_1 and P_2 may or may not be known
- Sequential arm selections



Two quantities of interest:

- (a) (Average) time taken to identify the odd arm
- (b) Probability of error


This talk:

- **Fixed confidence setting**
- **Asymptotics as $(b) \rightarrow 0$.**

Two quantities of interest:

- (a) (Average) time taken to identify the odd arm
- (b) Probability of error

The Big Picture



OAI as a Composite Hypothesis Testing Problem

When P_1 and P_2 are known: K simple hypotheses

\mathcal{H}_1 : arm 1 is the odd arm

\mathcal{H}_2 : arm 2 is the odd arm

\vdots

\mathcal{H}_K : arm K is the odd arm

OAI as a Composite Hypothesis Testing Problem

When P_1 and P_2 are known: K simple hypotheses


\mathcal{H}_1 : arm 1 is the odd arm

\mathcal{H}_2 : arm 2 is the odd arm

\vdots

\mathcal{H}_K : arm K is the odd arm

When neither P_1 nor P_2 is known: K composite hypotheses



$\mathcal{H}_1 : (1, \cdot, \cdot)$

$\mathcal{H}_2 : (2, \cdot, \cdot)$

\vdots

$\mathcal{H}_K : (K, \cdot, \cdot)$

Notation : (odd arm, P_1 , P_2)

Overview of Classical Results

Humble Beginnings



Humble Beginnings



- SPRT
- Only one arm to choose
- Optimal




- Procedure A
- Multiple arms
- Asymptotically optimal

Humble Beginnings



- SPRT
- Only one arm to choose
- Optimal



- Procedure A
- Multiple arms
- Asymptotically optimal

All's well that starts well!

Wald's SPRT: Problem Setup

- $X_1, X_2, \dots \stackrel{iid}{\sim} P_\theta, \theta \in \{\theta_1, \theta_2\}$

Wald's SPRT: Problem Setup

- $X_1, X_2, \dots \stackrel{iid}{\sim} P_\theta, \theta \in \{\theta_1, \theta_2\}$
- To test

$$\mathcal{H}_1 : \theta = \theta_1$$

vs

$$\mathcal{H}_2 : \theta = \theta_2$$

where P_{θ_1} and P_{θ_2} are known

Wald's SPRT: Problem Setup

- $X_1, X_2, \dots \stackrel{iid}{\sim} P_\theta, \theta \in \{\theta_1, \theta_2\}$
- To test

$$\mathcal{H}_1 : \theta = \theta_1$$

vs

$$\mathcal{H}_2 : \theta = \theta_2$$

where P_{θ_1} and P_{θ_2} are **known**

- Priors: $P(\mathcal{H}_1) = w = 1 - P(\mathcal{H}_2)$

Wald's SPRT: Problem Setup

- $X_1, X_2, \dots \stackrel{iid}{\sim} P_\theta, \theta \in \{\theta_1, \theta_2\}$
- To test

$$\mathcal{H}_1 : \theta = \theta_1$$

vs

$$\mathcal{H}_2 : \theta = \theta_2$$

where P_{θ_1} and P_{θ_2} are **known**

- Priors: $P(\mathcal{H}_1) = w = 1 - P(\mathcal{H}_2)$
- At each time n :
 - Stop and declare the true hypothesis
 - Take one more sample and continue

Wald's SPRT: Problem Setup

- $X_1, X_2, \dots \stackrel{iid}{\sim} P_\theta, \theta \in \{\theta_1, \theta_2\}$
- To test

$$\mathcal{H}_1 : \theta = \theta_1$$

vs

$$\mathcal{H}_2 : \theta = \theta_2$$

where P_{θ_1} and P_{θ_2} are **known**

- Priors: $P(\mathcal{H}_1) = w = 1 - P(\mathcal{H}_2)$
- At each time n :
 - Stop and declare the true hypothesis
 - Take one more sample and continue
- Cost c per sample

Wald's SPRT: Problem Setup

- $X_1, X_2, \dots \stackrel{iid}{\sim} P_\theta, \theta \in \{\theta_1, \theta_2\}$
- To test

$$\mathcal{H}_1 : \theta = \theta_1$$

vs

$$\mathcal{H}_2 : \theta = \theta_2$$

where P_{θ_1} and P_{θ_2} are **known**

- Priors: $P(\mathcal{H}_1) = w = 1 - P(\mathcal{H}_2)$
- At each time n :
 - Stop and declare the true hypothesis
 - Take one more sample and continue
- Cost c per sample
- Average risks at the stopping time N :

$$R_1 = P_{FA} + c \mathbb{E}[N|\mathcal{H}_1], \quad R_2 = P_{MD} + c \mathbb{E}[N|\mathcal{H}_2]$$

Wald's SPRT: Problem Setup

- $X_1, X_2, \dots \stackrel{iid}{\sim} P_\theta, \theta \in \{\theta_1, \theta_2\}$
- To test

$$\mathcal{H}_1 : \theta = \theta_1$$

vs

$$\mathcal{H}_2 : \theta = \theta_2$$

where P_{θ_1} and P_{θ_2} are **known**

- Priors: $P(\mathcal{H}_1) = w = 1 - P(\mathcal{H}_2)$
- At each time n :
 - Stop and declare the true hypothesis
 - Take one more sample and continue
- Cost c per sample
- Average risks at the stopping time N :

$$R_1 = P_{FA} + c \mathbb{E}[N|\mathcal{H}_1], \quad R_2 = P_{MD} + c \mathbb{E}[N|\mathcal{H}_2]$$

- Goal: minimise $w R_1 + (1 - w) R_2$

Wald's SPRT: Main Idea

At time n , construct the statistic

$$S_n = \log \frac{P_{\theta_2}(X_1, \dots, X_n)}{P_{\theta_1}(X_1, \dots, X_n)}$$

Wald's SPRT: Main Idea

At time n , construct the statistic

$$S_n = \log \frac{P_{\theta_2}(X_1, \dots, X_n)}{P_{\theta_1}(X_1, \dots, X_n)}$$

We have

$$\mathbb{E}[S_n | \mathcal{H}_1] = -n D(P_{\theta_1} \| P_{\theta_2}), \quad \mathbb{E}[S_n | \mathcal{H}_2] = n D(P_{\theta_2} \| P_{\theta_1})$$

Wald's SPRT: Main Idea


At time n , construct the statistic

$$S_n = \log \frac{P_{\theta_2}(X_1, \dots, X_n)}{P_{\theta_1}(X_1, \dots, X_n)}$$


We have

$$\mathbb{E}[S_n | \mathcal{H}_1] = -n D(P_{\theta_1} \| P_{\theta_2}), \quad \mathbb{E}[S_n | \mathcal{H}_2] = n D(P_{\theta_2} \| P_{\theta_1})$$

By the law of large numbers, we expect the following behaviour:



Wald's SPRT: Algorithm



At time n :

If $S_n \geq A$, stop and declare \mathcal{H}_2 true

If $S_n \leq B$, stop and declare \mathcal{H}_1 true

If $B < S_n < A$, take one more observation

For small values of c (cost per observation):

$$A \approx -\log c, \quad B \approx \log c$$

Wald's SPRT: Result

For small values of c (cost per observation):

$$A \approx -\log c, \quad B \approx \log c$$

By Wald's identity, if SPRT stops at a random time N , then

$$\mathbb{E}[S_N | \mathcal{H}_1] = -\mathbb{E}[N | \mathcal{H}_1] \cdot D(P_{\theta_1} \| P_{\theta_2}), \quad \mathbb{E}[S_N | \mathcal{H}_2] = \mathbb{E}[N | \mathcal{H}_2] \cdot D(P_{\theta_2} \| P_{\theta_1})$$

Wald's SPRT: Result

For small values of c (cost per observation):

$$A \approx -\log c, \quad B \approx \log c$$

By Wald's identity, if SPRT stops at a random time N , then

$$\mathbb{E}[S_N | \mathcal{H}_1] = -\mathbb{E}[N | \mathcal{H}_1] \cdot D(P_{\theta_1} \| P_{\theta_2}), \quad \mathbb{E}[S_N | \mathcal{H}_2] = \mathbb{E}[N | \mathcal{H}_2] \cdot D(P_{\theta_2} \| P_{\theta_1})$$

Combining, we get

$$\frac{\mathbb{E}[N | \mathcal{H}_1]}{\log \frac{1}{c}} \approx \frac{1}{D(P_{\theta_1} \| P_{\theta_2})}, \quad \frac{\mathbb{E}[N | \mathcal{H}_2]}{\log \frac{1}{c}} \approx \frac{1}{D(P_{\theta_2} \| P_{\theta_1})}$$

Handling Multiple Hypotheses

- $X_1, X_2, \dots \stackrel{\text{iid}}{\sim} P_\theta, \theta \in \{\theta_1, \dots, \theta_M\}, M > 2$

Handling Multiple Hypotheses

- $X_1, X_2, \dots \stackrel{iid}{\sim} P_\theta, \theta \in \{\theta_1, \dots, \theta_M\}, M > 2$
- To test

$$\mathcal{H}_1 : \theta = \theta_1$$

$$\vdots$$

$$\mathcal{H}_M : \theta = \theta_M$$

where $P_{\theta_1}, \dots, P_{\theta_M}$ are known

Handling Multiple Hypotheses

- $X_1, X_2, \dots \stackrel{iid}{\sim} P_\theta, \theta \in \{\theta_1, \dots, \theta_M\}, M > 2$
- To test




$$\mathcal{H}_1 : \theta = \theta_1$$

$$\vdots$$

$$\mathcal{H}_M : \theta = \theta_M$$

where $P_{\theta_1}, \dots, P_{\theta_M}$ are known

A behaviour we would like S_n to have (shown for $M = 3$):



Construct the statistic

$$S_n^{(i)} = \log \frac{P_{\theta_i}(X_1, \dots, X_n)}{\max_{j \neq i} P_{\theta_j}(X_1, \dots, X_n)}, \quad i = 1, \dots, M$$

Construct the statistic

$$S_n^{(i)} = \log \frac{P_{\theta_i}(X_1, \dots, X_n)}{\max_{j \neq i} P_{\theta_j}(X_1, \dots, X_n)}, \quad i = 1, \dots, M$$

At time n , do the following:

Let $i^*(n) \in \arg \max_i S_n^{(i)}$

If $S_n^{(i^*(n))} \geq -\log c$, stop and declare $\mathcal{H}_{i^*(n)}$ true

If $S_n^{(i^*(n))} < -\log c$, take one more observation

Construct the statistic

$$S_n^{(i)} = \log \frac{P_{\theta_i}(X_1, \dots, X_n)}{\max_{j \neq i} P_{\theta_j}(X_1, \dots, X_n)}, \quad i = 1, \dots, M$$

At time n , do the following:

Let $i^*(n) \in \arg \max_i S_n^{(i)}$

If $S_n^{(i^*(n))} \geq -\log c$, stop and declare $\mathcal{H}_{i^*(n)}$ true

If $S_n^{(i^*(n))} < -\log c$, take one more observation

It can be shown that if N is the random stopping time of M-SPRT, then

$$\frac{\mathbb{E}[N|\mathcal{H}_i]}{\log \frac{1}{c}} \approx \frac{1}{\min_{j \neq i} D(P_{\theta_i} \| P_{\theta_j})}, \quad i = 1, \dots, M$$

[†] Draglia, V. P., Alexander G. Tartakovsky, and Venugopal V. Veeravalli, "Multihypothesis sequential probability ratio tests - Part I: Asymptotic optimality", IEEE Transactions on Information Theory 45.7 (1999): 2448-2461.

Active Sequential Hypothesis Testing

- $\theta \in \{\theta_1, \dots, \theta_M\}$, $M > 2$
- L experiments E_1, \dots, E_L

Active Sequential Hypothesis Testing

- $\theta \in \{\theta_1, \dots, \theta_M\}$, $M > 2$
- L experiments E_1, \dots, E_L
- $X_1, X_2, \dots \stackrel{iid}{\sim} P_{\theta_i, E_i}$ under hypothesis \mathcal{H}_i and experiment E_i

Active Sequential Hypothesis Testing

- $\theta \in \{\theta_1, \dots, \theta_M\}$, $M > 2$
- L experiments E_1, \dots, E_L
- $X_1, X_2, \dots \stackrel{IID}{\sim} P_{\theta_i, E_l}$ under hypothesis \mathcal{H}_i and experiment E_l
- All the distributions are known

Active Sequential Hypothesis Testing

- $\theta \in \{\theta_1, \dots, \theta_M\}$, $M > 2$
- L experiments E_1, \dots, E_L
- $X_1, X_2, \dots \stackrel{IID}{\sim} P_{\theta_i, E_i}$ under hypothesis \mathcal{H}_i and experiment E_i
- All the distributions are known
- At time n :
 - Stop and declare the true hypothesis
 - Choose an experiment and take one more observation

Chernoff's Procedure A and its Asymptotic Optimality

Algorithm described by Chernoff:

$$S_n^{(i)} = \log \frac{P_{\theta_i}(X_1, E^{(1)}, \dots, X_n, E^{(n)})}{\max_{j \neq i} P_{\theta_j}(X_1, E^{(1)}, \dots, X_n, E^{(n)})}$$

Let $i^*(n) \in \arg \max_i S_n^{(i)}$

If $S_n^{(i^*(n))} \geq -\log c$, stop and declare $\mathcal{H}_{i^*(n)}$ true

If $S_n^{(i^*(n))} < -\log c$, take one more observation

Chernoff's Procedure A and its Asymptotic Optimality

Algorithm described by Chernoff:

$$S_n^{(i)} = \log \frac{P_{\theta_i}(X_1, E^{(1)}, \dots, X_n, E^{(n)})}{\max_{j \neq i} P_{\theta_j}(X_1, E^{(1)}, \dots, X_n, E^{(n)})}$$

Let $i^*(n) \in \arg \max_i S_n^{(i)}$

If $S_n^{(i^*(n))} \geq -\log c$, stop and declare $\mathcal{H}_{i^*(n)}$ true

If $S_n^{(i^*(n))} < -\log c$, take one more observation

Chernoff showed that

$$\frac{\mathbb{E}[N|\mathcal{H}_i]}{\log \frac{1}{c}} \approx \frac{1}{\max_{\lambda} \min_{j \neq i} \sum_{l=1}^L \lambda(E_l) D(P_{\theta_i, E_l} \| P_{\theta_j, E_l})}, \quad i = 1, \dots, M$$

Back to Odd Arm Identification

Visual Search with Static Images

- Solved by Vaidhiyan and Sundaresan
- Experiments \equiv image locations
- $c \rightarrow 0 \equiv$ prob. of error $\rightarrow 0$
- Observation: number of neuron firings in the brain corresponding to an image observed
- Model: no. of firings is Poisson[†]
- Odd arm: $\text{Poisson}(R_1)$, non-odd arms: $\text{Poisson}(R_2)$

[†] A. P. Sripati and C. R. Olson, "Global image dissimilarity in macaque inferotemporal cortex predicts human visual search efficiency," *J. Neurosci.*, vol. 30, no. 4, pp. 1258–1269, Jan. 2010.

Visual Search with Static Images

When R_1 and R_2 are known¹ (prob. of error: ϵ)

$$\frac{\mathbb{E}[N|\mathcal{H}_i]}{\log \frac{1}{\epsilon}} \approx \frac{1}{\max_{\lambda} \min_{j \neq i} \sum_{a=1}^K \lambda(a) D(\text{Poi}(R_{i,a}) \parallel \text{Poi}(R_{j,a}))}, \quad i = 1, \dots, M$$

¹Vaidhiyan, Nidhin Koshy, Sripathi P. Arun, and Rajesh Sundaresan. "Neural dissimilarity indices that predict oddball detection in behaviour." IEEE Transactions on Information Theory 63.8 (2017): 4778-4796.

²Vaidhiyan, Nidhin Koshy, and Rajesh Sundaresan. "Learning to detect an oddball target." IEEE Transactions on Information Theory 64.2 (2017): 831-852.

Visual Search with Static Images

When R_1 and R_2 are known¹ (prob. of error: ϵ)

$$\frac{\mathbb{E}[N|\mathcal{H}_i]}{\log \frac{1}{\epsilon}} \approx \frac{1}{\max_{\lambda} \min_{j \neq i} \sum_{a=1}^K \lambda(a) D(\text{Poi}(R_{i,a}) \parallel \text{Poi}(R_{j,a}))}, \quad i = 1, \dots, M$$

When neither R_1 nor R_2 is known²:

$$\frac{\mathbb{E}[N|\mathcal{H}_i]}{\log \frac{1}{\epsilon}} \approx \frac{1}{\max_{\lambda} \min_{j \neq i, R'_1, R'_2} \sum_{a=1}^K \lambda(a) D(\text{Poi}(R_{i,a}) \parallel \text{Poi}(R_{j,a}))}, \quad i = 1, \dots, M$$

A policy similar to Chernoff's with forced exploration works

¹Vaidhiyan, Nidhin Koshy, Sripathi P. Arun, and Rajesh Sundaresan. "Neural dissimilarity indices that predict oddball detection in behaviour." IEEE Transactions on Information Theory 63.8 (2017): 4778-4796.

²Vaidhiyan, Nidhin Koshy, and Rajesh Sundaresan. "Learning to detect an oddball target." IEEE Transactions on Information Theory 64.2 (2017): 831-852.

Notion of Closeness Between Two Static Images

- The constant in the denominator captures the hardness of the problem at hand, and serves as a measure of closeness between the odd and the non-odd images
- Call this constant $D^*(i, R_1, R_2)$

Notion of Closeness Between Two Static Images

- The constant in the denominator captures the hardness of the problem at hand, and serves as a measure of closeness between the odd and the non-odd images
- Call this constant $D^*(i, R_1, R_2)$
- For two images \mathcal{I}_1 (odd) and \mathcal{I}_2 (non-odd) whose Poisson firing rates R_1 and R_2 are **known**,

$$D^*(i, R_1, R_2) = \max_{\lambda} \min_{j \neq i} \sum_{a=1}^K \lambda(a) D(\text{Poi}(R_{i,a}) \| \text{Poi}(R_{j,a}))$$

Notion of Closeness Between Two Static Images

- The constant in the denominator captures the hardness of the problem at hand, and serves as a measure of closeness between the odd and the non-odd images
- Call this constant $D^*(i, R_1, R_2)$
- For two images \mathcal{I}_1 (odd) and \mathcal{I}_2 (non-odd) whose Poisson firing rates R_1 and R_2 are **known**,

$$D^*(i, R_1, R_2) = \max_{\lambda} \min_{j \neq i} \sum_{a=1}^K \lambda(a) D(\text{Poi}(R_{i,a}) \| \text{Poi}(R_{j,a}))$$

- For two images \mathcal{I}_1 (odd) and \mathcal{I}_2 (non-odd) whose Poisson firing rates R_1 and R_2 are **not known**,

$$D^*(i, R_1, R_2) = \max_{\lambda} \min_{j \neq i, R'_1, R'_2} \sum_{a=1}^K \lambda(a) D(\text{Poi}(R_{i,a}) \| \text{Poi}(R_{j,a}))$$

From Static Images to Movies

The Restless Odd Markov Arm Problem

- A movie is a sequence of static images (frames), each of which bears a dependency on its previous one

The Restless Odd Markov Arm Problem

- A movie is a sequence of static images (frames), each of which bears a dependency on its previous one
- When a movie is not observed, its frames move ahead

The Restless Odd Markov Arm Problem

- A movie is a sequence of static images (frames), each of which bears a dependency on its previous one
- When a movie is not observed, its frames move ahead
- Restless arms + Markov observations from each arm + one odd arm

The Restless Odd Markov Arm Problem

- A movie is a sequence of static images (frames), each of which bears a dependency on its previous one
- When a movie is not observed, its frames move ahead
- Restless arms + Markov observations from each arm + one odd arm
- This setting poses technical challenges

The Restless Odd Markov Arm Problem

- A movie is a sequence of static images (frames), each of which bears a dependency on its previous one
- When a movie is not observed, its frames move ahead
- Restless arms + Markov observations from each arm + one odd arm
- This setting poses technical challenges
- As a first step, study the setting of rested arms (movie paused when not observed)

The Restless Odd Markov Arm Problem

- A movie is a sequence of static images (frames), each of which bears a dependency on its previous one
- When a movie is not observed, its frames move ahead
- Restless arms + Markov observations from each arm + one odd arm
- This setting poses technical challenges
- As a first step, study the setting of rested arms (movie paused when not observed)

Rested Markov Arms: Setup

- $K \geq 3$ arms

Rested Markov Arms: Setup

- $K \geq 3$ arms
- Each arm is a homogeneous and ergodic DTMC on a finite state space

Rested Markov Arms: Setup

- $K \geq 3$ arms
- Each arm is a homogeneous and ergodic DTMC on a finite state space
- State space is common to all the arms

Rested Markov Arms: Setup

- $K \geq 3$ arms
- Each arm is a homogeneous and ergodic DTMC on a finite state space
- State space is common to all the arms
- Odd arm has TPM P_1 , non-odd arms have TPM P_2

Rested Markov Arms: Setup

- $K \geq 3$ arms
- Each arm is a homogeneous and ergodic DTMC on a finite state space
- State space is common to all the arms
- Odd arm has TPM P_1 , non-odd arms have TPM P_2
- The Markov chain of each arm evolves only when the arm is selected; otherwise, state of the arm is frozen

Rested Markov Arms: Results³

When P_1 and P_2 are known:

$$D^*(i, P_1, P_2) = \max_{\lambda} \min_{j \neq i} \sum_{a=1}^K \lambda(a) D(P_{i,a} \| P_{j,a} | \mu_{i,a}), \quad i = 1, \dots, M$$

³P. N. Karthik and R. Sundaresan, "Learning to detect an odd markov arm," 2019. [Online]. Available: <https://arxiv.org/abs/1904.11361>

Rested Markov Arms: Results³

When P_1 and P_2 are known:

$$D^*(i, P_1, P_2) = \max_{\lambda} \min_{j \neq i} \sum_{a=1}^K \lambda(a) D(P_{i,a} \| P_{j,a} | \mu_{i,a}), \quad i = 1, \dots, M$$

When neither P_1 nor P_2 is known:

$$D^*(i, P_1, P_2) = \max_{\lambda} \min_{j \neq i, P'_1, P'_2} \sum_{a=1}^K \lambda(a) D(P_{i,a} \| P_{j,a} | \mu_{i,a}), \quad i = 1, \dots, M$$

A policy similar to Chernoff's with forced exploration works

³P. N. Karthik and R. Sundaresan, "Learning to detect an odd markov arm," 2019. [Online]. Available: <https://arxiv.org/abs/1904.11361>

- Proof of the lower bound is based on a version of data processing inequality

- Proof of the lower bound is based on a version of data processing inequality
- Wald's identity not applicable since the observations are Markov. A generalisation needed

Rested Markov Arms: Insights

- Proof of the lower bound is based on a version of data processing inequality
- Wald's identity not applicable since the observations are Markov. A generalisation needed
- The optimum distribution does not depend on where the movie of each arm was paused. This is because of ergodicity of each arm

Restless Markov Arms

- Each arm continue to evolve whether or not it is selected (movies not paused)

Restless Markov Arms

- Each arm continue to evolve whether or not it is selected (movies not paused)
- It is important to keep track of
 - how far back in time each arm was last observed (delay)

Restless Markov Arms

- Each arm continue to evolve whether or not it is selected (movies not paused)
- It is important to keep track of
 - how far back in time each arm was last observed (delay)
 - the last observed state of each arm

Restless Markov Arms

- Each arm continue to evolve whether or not it is selected (movies not paused)
- It is important to keep track of
 - how far back in time each arm was last observed (delay)
 - the last observed state of each arm

Suppose the arm delays and last observed states at time t are

$$\underline{d}(t) = (d_1(t), \dots, d_K(t)), \quad \underline{s}(t) = (s_1(t), \dots, s_K(t))$$

Restless Markov Arms

- Each arm continue to evolve whether or not it is selected (movies not paused)
- It is important to keep track of
 - how far back in time each arm was last observed (delay)
 - the last observed state of each arm

Suppose the arm delays and last observed states at time t are

$$\underline{d}(t) = (d_1(t), \dots, d_K(t)), \quad \underline{s}(t) = (s_1(t), \dots, s_K(t))$$

Suppose A_t is the arm selected at time t

Restless Markov Arms

- Each arm continue to evolve whether or not it is selected (movies not paused)
- It is important to keep track of
 - how far back in time each arm was last observed (delay)
 - the last observed state of each arm

Suppose the arm delays and last observed states at time t are

$$\underline{d}(t) = (d_1(t), \dots, d_K(t)), \quad \underline{s}(t) = (s_1(t), \dots, s_K(t))$$

Suppose A_t is the arm selected at time t

We have

$$(\underline{d}(t), \underline{s}(t)) \longrightarrow A_t \longrightarrow (\underline{d}(t+1), \underline{s}(t+1)) \longrightarrow A_{t+1}$$

Restless Markov Setting: Key Findings⁴

- $\{(\underline{d}(t), \underline{s}(t))\}$ is a controlled Markov chain, with $\{A_t\}$ as the sequence of controls

⁴Submitted to ISIT 2020

Restless Markov Setting: Key Findings⁴

- $\{(\underline{d}(t), \underline{s}(t))\}$ is a controlled Markov chain, with $\{A_t\}$ as the sequence of controls
- When A_t 's are stationary control strategies, we have an MDP on a countable state space (HARD!)

⁴Submitted to ISIT 2020

Restless Markov Setting: Key Findings⁴

- $\{(\underline{d}(t), \underline{s}(t))\}$ is a controlled Markov chain, with $\{A_t\}$ as the sequence of controls
- When A_t 's are stationary control strategies, we have an MDP on a countable state space (HARD!)
- Our objective is to characterise $D^*(i, P_1, P_2)$, which is quite non-standard in MDP literature

⁴Submitted to ISIT 2020

Restless Markov Setting: Key Findings

- When A_t is chosen according to a distribution of the form

$$P(A_t = a \mid \underline{d}(t) = \underline{d}, \underline{s}(t) = \underline{s}) = \frac{\eta}{K} + (1 - \eta) \lambda(a \mid \underline{d}, \underline{s})$$

for some $\lambda(\cdot \mid \cdot)$ and $\eta > 0$, the Markov process $\{(\underline{d}(t), \underline{s}(t))\}$ becomes ergodic

Restless Markov Setting: Key Findings

- When A_t is chosen according to a distribution of the form

$$P(A_t = a \mid \underline{d}(t) = \underline{d}, \underline{s}(t) = \underline{s}) = \frac{\eta}{K} + (1 - \eta) \lambda(a \mid \underline{d}, \underline{s})$$

for some $\lambda(\cdot \mid \cdot)$ and $\eta > 0$, the Markov process $\{(\underline{d}(t), \underline{s}(t))\}$ becomes ergodic

- When P_1 and P_2 are known,

$$D^*(i, P_1, P_2) = \sup_{\lambda(\cdot \mid \cdot)} \min_{j \neq i} \sum_{(\underline{d}, \underline{s})} \sum_{a=1}^K \nu^\lambda(\underline{d}, \underline{i}, a) D(P_{i,a}^{d_a}(\cdot \mid s_a) \parallel P_{j,a}^{d_a}(\cdot \mid s_a))$$

- Sample complexity-type results
- Generalises all the previously known results

- Analysis of the restless arms setting for the case when neither P_1 nor P_2 is known

- Analysis of the restless arms setting for the case when neither P_1 nor P_2 is known
- Characterising the second-order term:

$$\mathbb{E}[N|\mathcal{H}_i] \approx \frac{\log \frac{1}{\epsilon}}{D_i^*} + ?? \quad \left(\text{e.g., } ?? = C \cdot \log \log \frac{1}{\epsilon} \right)$$

- Analysis of the restless arms setting for the case when neither P_1 nor P_2 is known
- Characterising the second-order term:

$$\mathbb{E}[N|\mathcal{H}_i] \approx \frac{\log \frac{1}{\epsilon}}{D_i^*} + ?? \quad \left(\text{e.g., } ?? = C \cdot \log \log \frac{1}{\epsilon} \right)$$


- Analysis for the case when each arm is a Markov process on a general state space

- Analysis of the restless arms setting for the case when neither P_1 nor P_2 is known
- Characterising the second-order term:

$$\mathbb{E}[N|\mathcal{H}_i] \approx \frac{\log \frac{1}{\epsilon}}{D_i^*} + ?? \quad \left(\text{e.g., } ?? = C \cdot \log \log \frac{1}{\epsilon} \right)$$

- Analysis for the case when each arm is a Markov process on a general state space
- General structures for Markov observations

A Final Glimpse of Where We Stand



Thank You!