

This document is proprietary and confidential. No part of this document may be disclosed in any manner to a third party without the prior written consent of Biopharmax India Pvt Ltd. and Cipla Ltd.

Client Name	: Cipla Ltd.	Prepared By :	SBG	16/06/2025
Project Name	: Modification for SVMA-II Block	Reviewed By :	AP	16/06/2025
Document No.	: xxxxxxxx	Approved By :	SS	16/06/2025
Revision No.	: P0	BPI Project No.:	IPR2300043	
Document Details	: Datasheet for Chilled Water, Hot Water & Steam Insulation			Client Project No.: NA

Sr. No	Description	Specification	Remarks
Chilled & Hot Water			
1	Manufacturer	Armaflex / K-Flex / ALP	ALP
2	Type	Nitrile Rubber Insulation with GC	Comply
3	Temperature range	-40°C To +105°C	Comply
4	Thermal Conductivity	0.035 W/m²K @ 0 Deg.C	Comply
5	Fire Rating	Class 'O'	Comply
6	Health aspect	Dust Free, CFC Free, Zero ODP	Comply
7	Density	40-55 Kg/m³	Comply
8	Water vapour resistance factor	≥ 12000	Comply
9	Water absorption	0.2% by volume	Comply
10	Thermal stability @90 Deg.C for 4Hrs.	To be specify	Stable
11	Resistance for Chemical	To be specify	Comply
12	Ageing	To be specify	No Growth
13	Non toxic smoke	To be specify	Non Toxic
14	Resistance to fungal and mould	To be specify	No Growth
15	Resistance to bacteria	To be specify	No Growth
16	Tensile strength	To be specify	Comply
Steam			
17	Type	Mineral Wool insulation with aluminum cladding.	Comply
18	Density	Density 120kg/m³ to 140kg/m³	Comply
19	Thermal conductivity	0.035 W/m²K	Comply

Notes

Sr. No	Rev.no	Change Description	Date
1	P0	First Issue	04/08/2024

