

	DESCRIPTION	Unit	Qty	Make	Compliance
5.3	Chilled Water Pipe insulation with following thickness Closed Cell Elastomeric Nitrile Rubber Glass Cloth bonded Covered with fire retardant high grade flexible adhesive & sealant Fire performance class 'O' as specified in specifications.			ALP/ Armaflex	Comply
a	450 mm dia. (50MM Thick insulation)	Rmt.	120		
d	200 mm dia. (44MM Thick insulation)	Rmt.	605		
k	U PVC Drain Piping with 13 mm thick nitrile rubber insulation as per specifications (For Drain)				Noted
a	100 mm dia	Rmt	189		
b	80 mm dia	Rmt	200		
c	50 mm dia	Rmt	185		
d	40 mm dia	Rmt	43		
e	32 mm dia	Rmt	3,300		
f	25 mm dia	Rmt	2,450		
6.3.1	Chilled Water Pipe insulation with following thickness Closed Cell Elastomeric Nitrile Rubber Glass Cloth bonded Covered with fire retardant high grade flexible adhesive & sealant ,Fire performance class 'O' as specified in specifications.				Comply
a	450 mm dia. (50MM Thick insulation)	Rmt.	89		
b	400 mm dia. (50MM Thick insulation)	Rmt.	100		
c	350 mm dia. (50MM Thick insulation)	Rmt.	322		
f	200 mm dia. (44MM Thick insulation)	Rmt.	100		
g	150 mm dia. (44MM Thick insulation)	Rmt.	120		
h	125 mm dia. (44MM Thick insulation)	Rmt.	450		
i	100 mm dia. (38MM Thick insulation)	Rmt.	1,476		
j	80 mm dia. (38MM Thick insulation)	Rmt.	1,766		
k	65 mm dia. (38MM Thick insulation)	Rmt.	2,329		
l	50 mm dia. (38MM Thick insulation)	Rmt.	3,482		
m	40 mm dia. (32MM Thick insulation)	Rmt.	1,858		
n	32 mm dia. (32MM Thick insulation)	Rmt.	4,950		
o	25 mm dia. (32MM Thick insulation)	Rmt.	2,625		
8.9	Thermal Insulation Of Ducts with Closed Cell Nitrile Rubber Insulation (class "O") of density 40-60 Kg/m3 with, Company Bonded Glass Cloth as per specifications.				Comply
a	19 MM THK	MT²	1,000		
8.10	Acoustic Insulation Of Ducts with Open Cell Nitrile Rubber (class "I") Material of density 140-180 Kg/m3 with Antifungal and Antimicrobial Properties as per specifications.				Comply
a	10 MM THK	MT²	100		
8.11	Acoustic Insulation Of AHU Room/ Return Air Box with Open Cell Nitrile Rubber (class "I") Material of density 140-180 Kg/m3 with Antifungal and Antimicrobial Properties as per specifications.				Comply
a	15 MM THK	MT²	1,200		

8.12	Underdeck/ floor Insulation with Closed Cell Nitrile Rubber Insulation (class "O") of density 40-60 Kg/m3 with Antimicrobial and Antifungal Properties, Company Bonded Glass Cloth as per specifications.			Comply
a	25 MM THK	MT ²	600	

