



Parshvanath Charitable Trust's
A. P. SHAH INSTITUTE OF TECHNOLOGY
(Approved by AICTE New Delhi & Govt. of Maharashtra, Affiliated to University of Mumbai)
(Religious Jain Minority)



Department of Computer Engineering
Academic Year: 2025-26

Year: SE

Semester: IV

Subject: DBMS Lab

Name of Student: Srushti Kiran Mohite

Roll No.: 48

Moodle Id: 24102005

Date of Performance: 10-04-2026

Date of Submission: 13-04-2026

Name of Instructor: Prof. Archana Kotangale.

Experiment No. 9

Aim: To Perform DCL and TCL commands.

Output:

```
mysql> CREATE USER 'srushti'@'localhost' IDENTIFIED BY 'ajk123';  
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> EXIT;  
Bye
```

```
mysql> CREATE DATABASE mydatabase;  
ERROR 1044 (42000): Access denied for user 'srushti'@'localhost' to database 'mydatabase'  
mysql> EXIT;  
Bye
```

mysql -u root -p

```
mysql> GRANT CREATE ON *.* TO 'srushti'@'localhost';  
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> exit;  
Bye
```

mysql -u srushti -p



```
mysql> CREATE DATABASE mydatabasee;  
Query OK, 1 row affected (0.03 sec)
```

```
mysql> use mydatabasee;  
Database changed  
mysql> CREATE TABLE student(rollno INT PRIMARY KEY, name VARCHAR(100), address VARCHAR(100), branch VARCHAR(100));  
Query OK, 0 rows affected (0.06 sec)  
  
mysql> INSERT INTO student VALUES (101, 'Rahul Singh', 'Thane', 'Computer');  
ERROR 1142 (42000): INSERT command denied to user 'srushti'@'localhost' for table 'student'  
mysql> EXIT;  
Bye
```

mysql -u root -p

```
mysql> GRANT ALL ON *.* TO 'srushti'@'localhost';  
Query OK, 0 rows affected (0.01 sec)  
  
mysql> EXIT;  
Bye
```

mysql -u srushti -p

```
mysql> USE mydatabasee;  
Database changed  
mysql> INSERT INTO student VALUES (101, 'Rahul Singh', 'Thane', 'Computer');  
Query OK, 1 row affected (0.01 sec)  
  
mysql> SELECT * FROM student;  
+-----+-----+-----+-----+  
| rollno | name      | address | branch |  
+-----+-----+-----+-----+  
|    101 | Rahul Singh | Thane   | Computer |  
+-----+-----+-----+-----+  
1 row in set (0.00 sec)  
  
mysql> DROP TABLE student;  
Query OK, 0 rows affected (0.03 sec)  
  
mysql> EXIT;  
Bye
```

mysql -u root -p



```
mysql> REVOKE ALL ON *.* FROM 'srushti'@'localhost';  
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> EXIT;  
Bye
```

```
mysql> use exp9;  
Database changed  
mysql> CREATE TABLE employee (  
->   fname VARCHAR(50),  
->   lname VARCHAR(50),  
->   salary INT  
-> );  
Query OK, 0 rows affected (0.05 sec)  
  
mysql> INSERT INTO employee (fname, lname, salary) VALUES  
-> ('Rahul', 'Sharma', 60000),  
-> ('Amit', 'Patel', 65000),  
-> ('Priya', 'Iyer', 60000),  
-> ('Sneha', 'Kulkarni', 48000),  
-> ('Arjun', 'Reddy', 72000),  
-> ('smita', 'patil', 98000);  
Query OK, 6 rows affected (0.02 sec)  
Records: 6  Duplicates: 0  Warnings: 0  
  
mysql> SET autocommit=0;  
Query OK, 0 rows affected (0.01 sec)  
  
mysql> UPDATE employee SET salary=70000 WHERE fname="Rahul";  
Query OK, 1 row affected (0.01 sec)  
Rows matched: 1  Changed: 1  Warnings: 0  
  
mysql> SELECT * FROM employee;  
+-----+-----+-----+  
| fname | lname | salary |  
+-----+-----+-----+  
| Rahul | Sharma | 60000 |  
| Amit  | Patel  | 65000 |  
| Priya | Iyer   | 60000 |  
| Sneha | Kulkarni | 48000 |  
| Arjun | Reddy  | 72000 |  
| smita | patil  | 98000 |
```



Parshvanath Charitable Trust's
A. P. SHAH INSTITUTE OF TECHNOLOGY
(Approved by AICTE New Delhi & Govt. of Maharashtra, Affiliated to University of Mumbai)
(Religious Jain Minority)



```
mysql> SELECT * FROM employee;
```

fname	lname	salary
Rahul	Sharma	70000
Amit	Patel	65000
Priya	Iyer	60000
Sneha	Kulkarni	48000
Arjun	Reddy	72000
smita	patil	98000

```
6 rows in set (0.00 sec)
```

```
mysql> ROLLBACK;
```

```
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> SELECT * FROM employee;
```

fname	lname	salary
Rahul	Sharma	60000
Amit	Patel	65000
Priya	Iyer	60000
Sneha	Kulkarni	48000
Arjun	Reddy	72000
smita	patil	98000

```
6 rows in set (0.00 sec)
```



Parshvanath Charitable Trust's
A. P. SHAH INSTITUTE OF TECHNOLOGY
(Approved by AICTE New Delhi & Govt. of Maharashtra, Affiliated to University of Mumbai)
(Religious Jain Minority)



```
mysql> SET autocommit=0;
Query OK, 0 rows affected (0.00 sec)

mysql> SAVEPOINT A;
Query OK, 0 rows affected (0.00 sec)

mysql> INSERT INTO employee VALUES("Srushti", "M", 70000);
Query OK, 1 row affected (0.00 sec)

mysql> INSERT INTO employee VALUES("Naina", "datar", 75000);
Query OK, 1 row affected (0.00 sec)

mysql> SELECT * FROM employee;
+-----+-----+-----+
| fname | lname | salary |
+-----+-----+-----+
| Rahul | Sharma | 60000 |
| Amit | Patel | 65000 |
| Priya | Iyer | 60000 |
| Sneha | Kulkarni | 48000 |
| Arjun | Reddy | 72000 |
| smita | patil | 98000 |
| Srushti | M | 70000 |
| Naina | datar | 75000 |
+-----+-----+-----+
8 rows in set (0.00 sec)

mysql> ROLLBACK TO SAVEPOINT A;
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> START TRANSACTION;
Query OK, 0 rows affected (0.01 sec)

mysql> SET autocommit=0;
Query OK, 0 rows affected (0.00 sec)

mysql> UPDATE employee SET salary=120000 WHERE fname="Arjun";
Query OK, 1 row affected (0.00 sec)
Rows matched: 1 Changed: 1 Warnings: 0

mysql> COMMIT;
Query OK, 0 rows affected (0.03 sec)

mysql> -- After commit, rollback will no longer undo the update
mysql> ROLLBACK;
Query OK, 0 rows affected (0.00 sec)

mysql> SELECT * FROM employee;
+-----+-----+-----+
| fname | lname | salary |
+-----+-----+-----+
| Rahul | Sharma | 60000 |
| Amit | Patel | 65000 |
| Priya | Iyer | 60000 |
| Sneha | Kulkarni | 48000 |
| Arjun | Reddy | 120000 |
| smita | patil | 98000 |
+-----+-----+-----+
6 rows in set (0.00 sec)
```

Conclusion: DML commands in SQL are essential for managing and manipulating data within tables. They allow users to insert, update, delete, and retrieve records efficiently. DML also supports string manipulation functions to modify or query text data effectively. Proper use of these commands ensures accurate, organized, and flexible data handling in a database.