8/9/25

Apply A^* Algorithm

- misplaced Tiles
- Manhatten distance

Q.

2	8	3
1	6	4
7		5

Initial state

1	2	3
8		4
7	6	5

goal State

$f(n) = g(n) + h(n)$

1 + 3





Q. Manhattan



initial State.

goal State

goal:

1	2	3
4	5	6
7	8	

Manhattan



Algorithm (mis placed Tiles)

1. Start → put initial state in open $
2. Pick state with smallest
3. If goal Stop
4. Expand neighbors
5. for each neighbor
   - g := parent.g + 1
   - h = misplaced tiles
   - f = g + h
   - add/update in Open
6. Repeat until goal found @ open empty

Q|P.

① 2 8 3
1 6 4
7 0 5

② 2 8 3
1 0 4
7 6 5

③ 2 0 3
1 8 4
7 6 5

④ 0 2 3
1 8 4
7 6 5

⑤ 1 2 3
0 8 4
7 6 5

⑥ 1 2 3
8 0 4
7 6 5

15

goal :-

1	2	3
8		4
7	6	5

Manhattan

2	8	3
1	6	4
7		5

R L D

2	8	3
1	6	4
	7	5

2	8	3
1	6	4
7	5	

2	8	3
1		4
7	6	5

1 2 3 4 5 6 7 8

1+1+0+0+0+1+1+2 = 6

1+1+0+0+1+1+0+2 = 6

1+1+0+0+0+ = 4

L R U D

2	8	3
	1	4
7	6	5

2	8	3
1	4	
7	6	5

2		3
1	8	4
7	6	5

2	8	3
1	6	4
7		5

2+1+0+0+0+0+0+2 = 5

1+1+0+1+0+0+0+2 = 5

1+1+0+0+0+0+1+0 = 3

1+1+0+0+0+1+0+2 = 5

L R D

	2	3
1	8	4
7	6	5

2	3	
1	8	4
7	6	5

2	8	3
1		4
7	6	5

1+0+0+0+0+0+0+2 = 4

1+1+1+0+0+0+1+0 = 4

1+1+0+0+0+0+1+2 = 4

D

1	2	3
	8	4
7	6	5

R →

1	2	3
8		4
7	6	5

0+0+0+0+0+0+0+1 = 1

Bafna Gold
Date: Page:

Algorithm.

1. Start with current pazzle state
2. Create an empty list to keep track of file matches
3. For each file from 1 to 8:
   - → if the file is in cur. pos, add 0 to the list
   - → otherwise, add 1 to the list.
4. Check the list:
   - → if the list contains all 0's the puzzel is solved = stop.
   - → otherwise, make a move to get closer to the goal.
5. Repeat steps 2 to 4 until, the puzzle is solved.

0+0+2

Output:

solution path:

2	8	3
1	6	4
7	0	5

↓

2	8	3
1	0	4
7	6	5

↓

2	0	3
1	8	4
7	6	5

0	2	3
1	8	4
7	6	5

↓

7	2	3
0	8	4
7	6	5

↓

1	2	3
8	0	4
7	6	5