TranslatorAwareInterface + setTranslator(?Translator Interface \$translator=null, \$textDomain=null) ValidatorInterface + getTranslator() static + hasTranslator() + isValid(\$value) + setTranslatorEnabled + getMessages() (\$enabled=true) + isTranslatorEnabled() + setTranslatorTextDomain (\$textDomain='default') + getTranslatorTextDomain() #\$defaultTranslator #\$defaultTranslatorTextDomain #\$messageLength **AbstractValidator** # \$value # \$abstractOptions + __construct(\$options =null) + getOption(\$option) + getOptions() + setOptions(\$options=[]) + getMessages() + __invoke(\$value) + getMessageVariables() + getMessageTemplates() + setMessage(\$messageString, \$messageKey=null) + setMessages(array \$messages) et 10 de plus... const + static setDefaultTranslator (?Translator\TranslatorInterface \$translator=null, \$textDomain=null) + static getDefaultTranslator() + static hasDefaultTranslator() + static setDefaultTranslator TextDomain(\$textDomain='default') + static getDefaultTranslator TextDomain() + static getMessageLength() + static setMessageLength (\$length=-1) # createMessage(\$messageKey, \$value) # error(\$messageKey, \$value=null) # getValue() # setValue(\$value) # translateMessage(\$messageKey, \$message) +DOES_NOT_EXIST **Exists** # \$messageTemplates # \$options # \$messageVariables __construct(\$options =null) +DOES_EXIST + getDirectory(\$asArray =false) + setDirectory(\$directory) + addDirectory(\$directory) + isValid(\$value, \$file =null) **NotExists** # \$messageTemplates

+ isValid(\$value, \$file

=null)