Formatter

+ $indentLevel
+ $indentChar
+ $break
+ $open
+ $close
+ $tagSeparator
+ $assignSeparator
+ $keepSemicolons
# $currentBlock
# $currentLine
# $currentColumn
# $sourceMapGenerator
# $strippedSemicolon

+ __construct()
+ property($name, $value)
+ customProperty($name, $value)
+ format(OutputBlock $block, SourceMapGenerator $sourceMapGenerator=null)
# indentStr()
# blockLines(OutputBlock $block)
# blockSelectors(OutputBlock $block)
# blockChildren(OutputBlock $block)
# block(OutputBlock $block)
# testEmptyChildren ($block)
# write($str)

Compact

+ __construct()
+ indentStr()

Compressed

+ __construct()
+ blockLines(OutputBlock $block)
# blockSelectors(OutputBlock $block)

Crunched

+ __construct()
+ blockLines(OutputBlock $block)
# blockSelectors(OutputBlock $block)

Debug

+ __construct()
# indentStr()
# blockLines(OutputBlock $block)
# blockSelectors(OutputBlock $block)
# blockChildren(OutputBlock $block)
# block(OutputBlock $block)

Expanded

+ __construct()
# indentStr()
# blockLines(OutputBlock $block)

Nested

+ __construct()
# indentStr()
# blockLines(OutputBlock $block)
# block(OutputBlock $block)