TranslatorAwareInterface + setTranslator(?Translator Interface \$translator=null, \$textDomain=null) ValidatorInterface + getTranslator() static + hasTranslator() + isValid(\$value) + setTranslatorEnabled + getMessages() (\$enabled=true) + isTranslatorEnabled() + setTranslatorTextDomain (\$textDomain='default') + getTranslatorTextDomain() #\$defaultTranslator #\$defaultTranslatorTextDomain #\$messageLength **AbstractValidator** # \$value # \$abstractOptions + __construct(\$options =null) + getOption(\$option) + getOptions() + setOptions(\$options=[]) + getMessages() + __invoke(\$value) + getMessageVariables() + getMessageTemplates() + setMessage(\$messageString, \$messageKey=null) + setMessages(array \$messages) et 10 de plus... const + static setDefaultTranslator (?Translator\TranslatorInterface \$translator=null, \$textDomain=null) + static getDefaultTranslator() + static hasDefaultTranslator() + static setDefaultTranslator TextDomain(\$textDomain='default') + static getDefaultTranslator TextDomain() + static getMessageLength() + static setMessageLength (\$length=-1) # createMessage(\$messageKey, \$value) # error(\$messageKey, \$value=null) # getValue() # setValue(\$value) # translateMessage(\$messageKey, \$message) +ALLOW ALL +ALLOW DNS +ALLOW IP +ALLOW_LOCAL +ALLOW_URI +CANNOT_DECODE +INVALID +INVALID DASH +INVALID HOSTNAME +INVALID_HOSTNAME _SCHEMA Hostname + const INVALID LOCAL NAME + const INVALID_URI + const IP_ADDRESS_NOT _ALLOWED + const LOCAL_NAME_NOT

- ALLOWED
- + const UNDECIPHERABLE_TLD + const UNKNOWN_TLD
- + return
- # \$messageTemplates
- # \$messageVariables
- # \$validTlds
- # \$validIdns
- # \$idnLength
- # \$tld
- # \$options + __construct(\$options=[])
- + getIpValidator()
- + setlpValidator(?lp
- \$ipValidator=null)
- + getAllow()
- + setAllow(\$allow) + getIdnCheck()
- + useldnCheck(\$useldnCheck)
- + getTldCheck()
- + useTldCheck(\$useTldCheck)
- + isValid(\$value) # decodePunycode(\$encoded)