## HandlerInterface + isHandling(array \$record) + handle(array \$record) + handleBatch(array \$records) + close() Handler ResettableInterface + handleBatch(array \$records) + close() reset() + \_\_destruct() \_\_sleep() AbstractHandler # \$level # \$bubble + \_\_construct(\$level =Logger::DEBUG, bool ProcessableHandlerInterface FormattableHandlerInterface \$bubble=true) + isHandling(array pushProcessor(callable + setFormatter(FormatterInterface \$record) \$callback) \$formatter) + setLevel(\$level) popProcessor() + getFormatter() + getLevel() + setBubble(bool \$bubble) + getBubble() + reset() AbstractProcessingHandler reset() write(array \$record) TelegramBotHandler + \_\_construct(string

- + \_\_construct(string \$apiKey, string \$channel, \$level=Logger::DEBUG, bool \$bubble=true, string \$parseMode =null, bool \$disableWebPagePreview =null, bool \$disableNotification=null, bool \$splitLongMessages=false, bool \$delayBetweenMessages=false)
- + setParseMode(string \$parseMode=null)
- + disableWebPagePreview (bool \$disableWebPagePreview=null)
- + disableNotification (bool \$disableNotification=null)
- + splitLongMessages (bool \$splitLongMessages =false)
- + delayBetweenMessages (bool \$delayBetweenMessages =false)
- # write(array \$record)
- # send(string \$message)
- # sendCurl(string \$message)