

computeFriendlyName()

- DatabaseInstance

cleanLockeds()

+ post_getEmpty() + getLogTypeID() + post_deleteFromDB() + cleanDBonPurge() et 87 de plus...

+ static forceTable(

+ static getTableField

+ static getFromIter (DBmysqlIterator \$iter) + static unsetUndisclosedFields

+ static getIndexName() + static isNewID(\$ID) + static getNameField()

et 26 de plus... # saveInput()

clearSavedInput() # restoreInput(array \$default=[]) # restoreSavedValues (array \$saved=[]) # cleanLockedsOnAdd()

+ static getCompleteNameField()

(&\$fields)

=null)

\$table)

+ static getTable(\$classname

+ static getForeignKeyField()

(\$field, \$classname=null)

- # \$usenotepad
- + useDeletedToLockIfDynamic() + defineTabs(\$options=[])
- (\$input) + rawSearchOptions()
- + cleanDBonPurge()
- + pre purgeInventory() + getTabNameForItem

+ getCloneRelations()

+ prepareInputForAdd

+ \$dohistory

- (CommonGLPI \$item, \$withtemplate=0)
- + static getTypeName (\$nb=0)
- Display(\$field, \$values, array \$options=[]) + static displayTabContent

ForItem(CommonGLPI \$item,

+ static getSpecificValueTo

\$tabnum=1, \$withtemplate=0) + static getIcon()