MessageInterface

- + getBodyAsStream()
- + getBodyAsString()
- + getBody()
- + setBody(\$body)
- + getHeaders()
- + hasHeader(string \$name)
- + getHeader(string \$name)
- + getHeaderAsArray(string \$name)
- + setHeader(string \$name, \$value)
- + setHeaders(array \$headers)
- + addHeader(string \$name, \$value)
- + addHeaders(array \$headers)
- + removeHeader(string \$name)
- + setHttpVersion(string \$version)
- + getHttpVersion()

RequestInterface

- + getMethod()
- + setMethod(string \$method)
- + getUrl()
- + setUrl(string \$url)
- + getAbsoluteUrl()
- + setAbsoluteUrl(string \$url)
- + getBaseUrl()
- + setBaseUrl(string \$url)
- + getPath()
- + getQueryParameters()
- + getPostData()
- + setPostData(array \$postData)
- + getRawServerValue (string \$valueName)
- + setRawServerData(array \$data)

Message

- # \$body
- # \$headers
- # \$httpVersion
- + getBodyAsStream()
- + getBody()
- + setBody(\$body)
- + getHeaders()
- + hasHeader(string \$name)
- + getHeader(string \$name)
- + getHeaderAsArray(string \$name)
- + setHeader(string \$name, \$value)
- + setHeaders(array \$headers)
- + addHeader(string \$name, \$value)
- + addHeaders(array \$headers)
- + removeHeader(string \$name)
- + setHttpVersion(string \$version)
- + getHttpVersion()

ResponseInterface

- + getStatus()
- + getStatusText()
- + setStatus(\$status)

Request

- # \$method
- # \$url
- # \$absoluteUrl
- # \$baseUrl
- # \$postData
- # \$rawServerData
- _construct(string \$method, string \$url, array \$headers=[], \$body=null)
- + getMethod()
- + setMethod(string \$method)
- + getUrl()
- + setUrl(string \$url)
- + getQueryParameters()
- + setAbsoluteUrl(string \$url)
- + getAbsoluteUrl()
- + setBaseUrl(string
- + getBaseUrl() et 6 de plus...

Response

- + static \$statusCodes
- # \$status
- # \$statusText
- + __construct(\$status =500, array \$headers =null, \$body=null)
- + getStatus()
- + getStatusText()
- + setStatus(\$status)
- + __toString()

ResponseDecorator

- _construct(ResponseInterface \$inner)
- + getStatus()
- + getStatusText()
- + setStatus(\$status)
- _toString()

RequestDecorator

- _construct(RequestInterface \$inner)
- + getMethod()
- + setMethod(string \$method)
- + getUrl()
- + setUrl(string \$url)
- + getAbsoluteUrl()
- + setAbsoluteUrl(string \$url)
- + getBaseUrl()
- + setBaseUrl(string \$url)
- + getPath() et 6 de plus...