HandlerInterface + isHandling(array \$record) + handle(array \$record) + handleBatch(array \$records) + close() Handler ResettableInterface + handleBatch(array \$records) + close() reset() __destruct() _sleep() AbstractHandler # \$level # \$bubble + __construct(\$level =Logger::DEBUG, bool ProcessableHandlerInterface FormattableHandlerInterface \$bubble=true) + isHandling(array + pushProcessor(callable + setFormatter(FormatterInterface \$record) \$formatter) \$callback) + setLevel(\$level) + getFormatter() popProcessor() + getLevel() + setBubble(bool \$bubble) + getBubble() + reset() AbstractProcessingHandler reset() write(array \$record) MailHandler # send(string \$content, array \$records) # write(array \$record) # getHighestRecord(array \$records) # isHtmlBody(string \$body) # getDefaultFormatter() NativeMailerHandler # \$to # \$subject # \$headers # \$parameters # \$maxColumnWidth # \$contentType # \$encoding + __construct(\$to, string \$subject, string \$from, \$level=Logger::ERROR, bool \$bubble=true, int \$maxColumnWidth=70) + addHeader(\$headers) + addParameter(\$parameters) + getContentType() + getEncoding() + setContentType(string \$contentType)

+ setEncoding(string \$encoding)

send(string \$content, array \$records)