Countable SeekableIterator ArrayAccess AbstractStorage # \$has # \$iterationPos # \$iterationMax # \$messageClass + __get(\$var) + getCapabilities() + countMessages() + getSize(\$id=0) + getMessage(\$id) + getRawHeader(\$id, \$part=null, \$topLines=0) + getRawContent(\$id, \$part=null) + __construct(\$params) + __destruct() + close() et 15 de plus... Maildir # \$messageClass # \$files # static \$knownFlags + countMessages(\$flags =null) + getSize(\$id=null) + getMessage(\$id) + getRawHeader(\$id, \$part=null, \$topLines=0) FolderInterface + getRawContent(\$id, \$part=null) + getFolders(\$rootFolder + __construct(\$params) =null) + close() + selectFolder(\$globalName) + noop() + getCurrentFolder() + removeMessage(\$id) + getUniqueId(\$id=null) + getNumberByUniqueId(\$id) # getFileData(\$id, \$field=null) # isMaildir(\$dirname) # openMaildir(\$dirname) # getMaildirFiles(\$dh, \$dirname, \$defaultFlags=[]) Maildir # \$rootFolder # \$rootdir # \$currentFolder # \$delim + __construct(\$params) + getFolders(\$rootFolder =null) + selectFolder(\$globalName) + getCurrentFolder() # buildFolderTree() Maildir # \$quota + __construct(\$params) + createFolder(\$name, \$parentFolder=null) + removeFolder(\$name) + renameFolder(\$oldName, \$newName) + appendMessage(\$message, \$folder=null, \$flags =null, \$recent=false) + copyMessage(\$id, \$folder) + moveMessage(\$id, \$folder) + setFlags(\$id, \$flags) + removeMessage(\$id) + setQuota(\$value) + getQuota(\$fromStorage =false)

+ checkQuota(\$detailedResponse =false, \$forceRecalc=false)

+ static initMaildir

createUniqueId()
createTmpFile(\$folder

getInfoString(&\$flags)
calculateMaildirsize()

addQuotaEntry(\$size,

calculateQuota(\$forceRecalc

='INBOX')

=false)

\$count=1)

(\$dir)