

| AbstractProvider  |
|---|
| + const ACCESS_TOKEN_RESOURCE_OWNER_ID                      |
| + const METHOD_GET  |
| + const METHOD_POST   |
| # \$clientId  |
| # \$clientSecret  |
| # \$redirectUri   |
| # \$state   |
| # \$grantFactory  |
| # \$requestFactory  |
| # \$httpClient  |
| # \$optionProvider  |
| + __construct(array \$options=[], array \$collaborators=[]) |
| + setGrantFactory(GrantFactory \$factory)                   |
| + getGrantFactory()   |
| + setRequestFactory(RequestFactory \$factory)               |
| + getRequestFactory()                                       |
| + setHttpClient(HttpClientInterface \$client)               |
| + getHttpClient()   |
| + setOptionProvider(OptionProviderInterface \$provider)     |
| + getOptionProvider()                                       |
| + getState()<br>et 12 de plus...                            |
| # getAllowedClientOptions(array \$options)                  |
| # getRandomState(\$length=32)                               |
| # getDefaultScopes()  |
| # getScopeSeparator()                                       |
| # getAuthorizationParameters(array \$options)               |
| # getAuthorizationQuery(array \$params)                     |
| # appendQuery(\$url, \$query)                               |
| # getAccessTokenMethod()                                    |
| # getAccessTokenResourceOwnerId()                           |
| # getAccessTokenQuery(array \$params)<br>et 14 de plus...   |

| Azure  |
|--|
| + const ENDPOINT_VERSION_1_0   |
| + const ENDPOINT_VERSION_2_0   |
| + const ENDPOINT_VERSIONS  |
| + \$urlLogin   |
| + \$scope  |
| + \$scopeSeparator   |
| + \$tenant   |
| + \$defaultEndPointVersion   |
| + \$urlAPI   |
| + \$resource   |
| + \$API_VERSION  |
| + \$authWithResource   |
| # \$openIdConfiguration  |
| + __construct(array \$options=[], array \$collaborators=[])                              |
| + getBaseAuthorizationUrl()  |
| + getBaseAccessTokenUrl(array \$params)  |
| + getAccessToken(\$grant, array \$options=[])  |
| + getResourceOwner(\League\OAuth2\Client\Token\AccessToken \$token)                      |
| + getResourceOwnerDetailsUrl(\League\OAuth2\Client\Token\AccessToken \$token)            |
| + getObjects(\$tenant, \$ref, &\$accessToken, \$headers=[])                              |
| + getRootMicrosoftGraphUri(\$accessToken)  |
| + get(\$ref, &\$accessToken, \$headers=[], \$doNotWrap=false)                            |
| + post(\$ref, \$body, &\$accessToken, \$headers=[])<br>et 10 de plus...                  |
| # getOpenIdConfiguration(\$tenant, \$version)  |
| # getVersionUriInfix(\$version)  |
| # checkResponse(ResponseInterface \$response, \$data)                                    |
| # getDefaultScopes()   |
| # getScopeSeparator()  |
| # createAccessToken(array \$response, AbstractGrant \$grant)                             |
| # createResourceOwner(array \$response, \League\OAuth2\Client\Token\AccessToken \$token) |

| ProviderInterface                             |
|---|
| + __construct(array \$options=[])             |
| + getAuthorizationUrl(array \$options=[])     |
| + getAccessToken(\$grant, array \$options=[]) |
| + getResourceOwner(AccessToken \$token)       |
| + static getName()                            |
| + static getAdditionalParameters()            |

| Azure                                     |
|---|
| + __construct(array \$options=[])         |
| + getAuthorizationUrl(array \$options=[]) |
| + static getName()                        |
| + static getAdditionalParameters()        |