FolderInterface

- + getFolders(\$rootFolder =null)
- + selectFolder(\$globalName)
- + getCurrentFolder()

Maildir

- # \$rootFolder
- # \$rootdir
- # \$currentFolder
- # \$delim
- + __construct(\$params)
- + getFolders(\$rootFolder =null)
- + selectFolder(\$globalName)
- + getCurrentFolder()
- # buildFolderTree()

Mbox

- # \$rootFolder
- # \$rootdir
- # \$currentFolder
- + __construct(\$params)
- + getFolders(\$rootFolder =null)
- + selectFolder(\$globalName)
- + getCurrentFolder()
- + __sleep()
- + __wakeup()
- # buildFolderTree(\$current Dir, \$parentFolder=null, \$parentGlobalName=")

Imap

- # \$protocol
- # \$currentFolder
- # \$delimiter
- # static \$knownFlags
- # static \$searchFlags
- + countMessages(\$flags =null)
- + getSize(\$id=0)
- + getMessage(\$id)
- + getRawHeader(\$id, \$part=null, \$topLines=0)
- + __construct(\$params)
- + close()
- + noop()
- + removeMessage(\$id)
- + getUniqueId(\$id=null) et 12 de plus...

Maildir

\$quota

- + __construct(\$params)
- + createFolder(\$name, \$parentFolder=null)
- + removeFolder(\$name)
- + renameFolder(\$oldName, \$newName)
- + appendMessage(\$message, \$folder=null, \$flags =null, \$recent=false)
- + copyMessage(\$id, \$folder)
- + moveMessage(\$id, \$folder)
- + setFlags(\$id, \$flags)
- + removeMessage(\$id)
- + setQuota(\$value)
- + getQuota(\$fromStorage =false)
- + checkQuota(\$detailedResponse =false, \$forceRecalc=false)
- + static initMaildir (\$dir)
- # createUniqueId()
- # createTmpFile(\$folder ='INBOX')
- # getInfoString(&\$flags)
- # calculateMaildirsize()
- # calculateQuota(\$forceRecalc =false)
- # addQuotaEntry(\$size, \$count=1)