## TranslatorAwareInterface + setTranslator(?Translator Interface \$translator=null, \$textDomain=null) ValidatorInterface + getTranslator() + hasTranslator() + isValid(\$value) + setTranslatorEnabled + getMessages() (\$enabled=true) + isTranslatorEnabled() + setTranslatorTextDomain (\$textDomain='default') + getTranslatorTextDomain() AbstractValidator # \$value # \$abstractOptions # static \$defaultTranslator # static \$defaultTranslator TextDomain # static \$messageLength \_construct(\$options =null) + getOption(\$option) + getOptions() + setOptions(\$options=[]) + getMessages() + \_\_invoke(\$value) + getMessageVariables() + getMessageTemplates() + setMessage(\$messageString, \$messageKey=null) + setMessages(array \$messages) et 10 de plus... + static setDefaultTranslator (?Translator\TranslatorInterface \$translator=null, \$textDomain=null) + static getDefaultTranslator() + static hasDefaultTranslator() static setDefaultTranslator TextDomain(\$textDomain='default') + static getDefaultTranslator TextDomain() + static getMessageLength() static setMessageLength (\$length=-1) # createMessage(\$messageKey, \$value) # error(\$messageKey, \$value=null) # getValue() # setValue(\$value) # translateMessage( \$messageKey, \$message) Csrf + const NOT\_SAME # \$messageTemplates # \$hash # \$name # \$salt # \$session # \$timeout

## # static \$hashCache + \_\_construct(\$options=[]) + isValid(\$value, \$context =null) + setName(\$name) + getName() + setSession(SessionContainer \$session) + getSession() + setSalt(\$salt) + getSalt() + getHash(\$regenerate =false) + getSessionName() + setTimeout(\$ttl) + getTimeout() # initCsrfToken() # generateHash() # generateTokenId() # getValidationToken (\$tokenId=null) # formatHash(string \$token, string \$tokenId)

# getTokenFromHash(
 ?string \$hash)
# getTokenIdFromHash
 (string \$hash)