TranslatorAwareInterface

- setTranslator(?Translator Interface \$translator=null, \$textDomain=null)
- + getTranslator()
- + hasTranslator()
- + setTranslatorEnabled (\$enabled=true)
- + isTranslatorEnabled()
- + setTranslatorTextDomain (\$textDomain='default')
- + getTranslatorTextDomain()

ValidatorInterface

- + isValid(\$value)
- + getMessages()



AbstractValidator

- # \$value
- # \$abstractOptions
- # static \$defaultTranslator
 # static \$defaultTranslator
- TextDomain
- # static \$messageLength
 + __construct(\$options
- =null)
 + getOption(\$option)
- + getOptions()
- + setOptions(\$options=[])
- + getMessages()
- + __invoke(\$value)+ getMessageVariables()
- + getMessageTemplates()
- + setMessage(\$messageString, \$messageKey=null)
- + setMessages(array \$messages)
 - et 10 de plus...
- + static setDefaultTranslator (?Translator\TranslatorInterface \$translator=null, \$textDomain=null)
- + static getDefaultTranslator()
- + static hasDefaultTranslator()
- + static setDefaultTranslator TextDomain(\$textDomain='default')
- + static getDefaultTranslator TextDomain()
- + static getMessageLength()+ static setMessageLength
- (\$length=-1)
 # createMessage(\$messageKey,
 \$value)
- # error(\$messageKey, \$value=null)
- # getValue()
- # setValue(\$value)
- # translateMessage(
 \$messageKey, \$message)

BusinessIdentifierCode

- + const INVALID
- + const NOT_STRING
- + const NOT_VALID_COUNTRY # \$messageTemplates
- + isValid(\$value)