## TranslatorAwareInterface

- + setTranslator(?Translator Interface \$translator=null, \$textDomain=null)
- + getTranslator()
- + hasTranslator()
- + setTranslatorEnabled (\$enabled=true)
- + isTranslatorEnabled()
- + setTranslatorTextDomain (\$textDomain='default')
- + getTranslatorTextDomain()

## ValidatorInterface

- + isValid(\$value)
- + getMessages()



## AbstractValidator 4 6 1

- # \$value
- # \$abstractOptions
- # static \$defaultTranslator
- # static \$defaultTranslator TextDomain
- # static \$messageLength
- \_construct(\$options =null)
- + getOption(\$option)
- + getOptions()
- + setOptions(\$options=[])
- + getMessages()
- + \_\_invoke(\$value)
- + getMessageVariables()
- + getMessageTemplates()
- + setMessage(\$messageString, \$messageKey=null)
- + setMessages(array \$messages)
  - et 10 de plus...
- + static setDefaultTranslator (?Translator\TranslatorInterface \$translator=null, \$textDomain=null)
- + static getDefaultTranslator()
- + static hasDefaultTranslator()
- static setDefaultTranslator TextDomain(\$textDomain='default')
- + static getDefaultTranslator TextDomain() + static getMessageLength()
- + static setMessageLength (\$length=-1)
- # createMessage(\$messageKey, \$value)
- # error(\$messageKey, \$value=null)
- # getValue()
- # setValue(\$value)
- # translateMessage( \$messageKey, \$message)



## IsInt

- + const INVALID + const NOT\_INT
- + const NOT\_INT\_STRICT
- # \$messageTemplates # \$locale
- # \$strict
- + \_\_construct(\$options=[])
- + getLocale()
- + setLocale(\$locale)
- + getStrict() + setStrict(\$strict)
- + isValid(\$value)