TranslatorAwareInterface + setTranslator(?Translator Interface \$translator=null, \$textDomain=null) ValidatorInterface + getTranslator() + hasTranslator() + isValid(\$value) + setTranslatorEnabled + getMessages() (\$enabled=true) + isTranslatorEnabled() + setTranslatorTextDomain (\$textDomain='default') + getTranslatorTextDomain() AbstractValidator 4 6 1 # \$value # \$abstractOptions # static \$defaultTranslator # static \$defaultTranslator TextDomain # static \$messageLength __construct(\$options =null) + getOption(\$option) + getOptions() + setOptions(\$options=[]) + getMessages() + __invoke(\$value) + getMessageVariables() + getMessageTemplates() + setMessage(\$messageString, \$messageKey=null) + setMessages(array \$messages) et 10 de plus... + static setDefaultTranslator (?Translator\TranslatorInterface \$translator=null, \$textDomain=null) + static getDefaultTranslator() + static hasDefaultTranslator() + static setDefaultTranslator TextDomain(\$textDomain='default') + static getDefaultTranslator TextDomain() + static getMessageLength() + static setMessageLength (\$length=-1) # createMessage(\$messageKey, \$value) # error(\$messageKey, \$value=null) # getValue() # setValue(\$value) # translateMessage(\$messageKey, \$message) **Digits** + const NOT_DIGITS + const STRING_EMPTY + const INVALID

\$messageTemplates

static \$filter + isValid(\$value)