AbstractProtocol

- + const EOL
- + const TIMEOUT_CONNECTION
- # \$maximumLog
- # \$host
- # \$port
- # \$validHost
- # \$socket
- # \$request
- # \$response
- + __construct(\$host ='127.0.0.1', \$port=null)
- + __destruct()
- + setMaximumLog(\$maximumLog)
- + getMaximumLog()
- + connect()
- + getRequest()
- + getResponse()
- + getLog()
- + resetLog()
- # _addLog(\$value)
- # _connect(\$remote)
- # _disconnect()
- # _send(\$request)
- # _receive(\$timeout =null)
- # _expect(\$code, \$timeout

Smtp

- + const SMTP_LINE_LIMIT
- # \$transport
- # \$secure
- # \$sess
- # \$auth
- # \$mail
- # \$rcpt # \$data
- # \$useCompleteQuit
- _construct(\$host ='127.0.0.1', \$port =null, array \$config=null)
- + setUseCompleteQuit (\$useCompleteQuit)
- + useCompleteQuit()
- + connect()
- + helo(\$host='127.0.0.1')
- + hasSession()
- + mail(\$from)
- + rcpt(\$to)
- + data(\$data)
- + rset()
- + noop()
- + vrfy(\$user)
- + quit() + auth()
- + disconnect()
- # ehlo(\$host)
- # _disconnect()
- # startSession()
- # stopSession()

Crammd5

- # \$username
- # \$password + __construct(\$host
- ='127.0.0.1', \$port =null, \$config=null)
- + auth()
- + setUsername(\$username)
- + getUsername()
- + setPassword(\$password)
- + getPassword()
- # hmacMd5(\$key, \$data, \$block=64)

Login

- # \$username
- # \$password
- + __construct(\$host ='127.0.0.1', \$port =null, \$config=null)
- + auth()
- + setUsername(\$username) + getUsername()
- + setPassword(\$password)
- + getPassword()

Plain

- # \$username
- # \$password
- + __construct(\$host ='127.0.0.1', \$port =null, \$config=null)
- + auth()
- + setUsername(\$username)
- + getUsername()
- + setPassword(\$password)
- + getPassword()