## MessageInterface

- + getBodyAsStream()
- + getBodyAsString()
- + getBody()
- + setBody(\$body)
- + getHeaders()
- + hasHeader(string \$name)
- + getHeader(string \$name)
- + getHeaderAsArray(string \$name)
- + setHeader(string \$name, \$value)
- + setHeaders(array \$headers)
- + addHeader(string \$name, \$value) + addHeaders(array

\$headers)

- + removeHeader(string \$name)
- + setHttpVersion(string \$version)
- + getHttpVersion()



## Message

- # \$body
- # \$headers # \$httpVersion
- + getBodyAsStream()
- + getBody()
- + setBody(\$body)
- + getHeaders()
- + hasHeader(string \$name)
- + getHeader(string \$name)
- + getHeaderAsArray(string \$name)
- + setHeader(string \$name, \$value)
- + setHeaders(array \$headers) + addHeader(string
- \$name, \$value) + addHeaders(array
- \$headers) + removeHeader(string \$name)
- + setHttpVersion(string \$version)
- + getHttpVersion()

## Request

- # \$method
- # \$url
- # \$absoluteUrl
- # \$baseUrl
- # \$postData
- # \$rawServerData \_construct(string \$method, string \$url,
- array \$headers=[], \$body=null)
- + setMethod(string

+ getMethod()

- \$method) + getUrl()
- + setUrl(string \$url)
- + getQueryParameters()
- + setAbsoluteUrl(string \$url)
- + getAbsoluteUrl()
- + setBaseUrl(string \$url)
- + getBaseUrl()
- et 6 de plus...

## Response

- + static \$statusCodes
- # \$status
- # \$statusText
- \_construct(\$status =500, array \$headers =null, \$body=null)
- + getStatus()
- + getStatusText()
- + setStatus(\$status)
- + \_\_toString()