
TranslatorAwareInterface + setTranslator(?Translator Interface \$translator=null, \$textDomain=null) + getTranslator() + hasTranslator() + setTranslatorEnabled (\$enabled=true) + isTranslatorEnabled() + setTranslatorTextDomain (\$textDomain='default')

+ getTranslatorTextDomain()



#\$defaultTranslator #\$defaultTranslatorTextDomain #\$messageLength

const

AbstractValidator # \$value # \$abstractOptions + __construct(\$options =null) + getOption(\$option) + getOptions() + setOptions(\$options=[]) + getMessages() + __invoke(\$value) + getMessageVariables() + getMessageTemplates() + setMessage(\$messageString, \$messageKey=null) + setMessages(array \$messages) et 10 de plus... + static setDefaultTranslator

(?Translator\TranslatorInterface \$translator=null, \$textDomain=null) + static getDefaultTranslator() + static hasDefaultTranslator() + static setDefaultTranslator TextDomain(\$textDomain='default') + static getDefaultTranslator TextDomain() + static getMessageLength() + static setMessageLength (\$length=-1) # createMessage(\$messageKey, \$value) # error(\$messageKey, \$value=null) # getValue() # setValue(\$value) # translateMessage(\$messageKey, \$message)

+INVALID +NOT_HEX # \$messageTemplates + isValid(\$value)

Hex