PenCentral Partner API

Employer Onboarding API Guide

A practical guide to validating, attaching, listing, and revoking employer access through the Partner API.

Phase	Phase 0 — Confirm and Attach an Employer
Scope	employers:manage — validate, attach, list, and revoke employer access
Base URL	https://newhrpartnersapi.pensioncentral.ng

Purpose

This guide explains how an integration partner can confirm that an employer code is valid, show the official employer name to the user, attach the employer to the partner account, and later list or revoke that access.

Important: validating an employer is read-only. It does not grant access. The partner must explicitly attach the employer after the user confirms the returned employer name.

Integration sequence

1. Validate	2. Confirm	3. Attach	4. Manage
Check employer code	Show official name	Grant access	List or revoke

1. Before You Start

Use the sandbox environment while building and testing the integration. All requests below use the Partner API, not the Internal Admin API.

Base URL: https://newhrpartnersapi.pensioncentral.ng

Authentication: send the partner's API key as a Bearer token.

```
Authorization: Bearer YOUR_PARTNER_API_KEY
Content-Type: application/json
```

Required scope: employers:manage. This scope covers validation, attachment, listing, and revocation of employer access.

Validation IDs are bound to the authenticated partner and expire after 30 minutes. Complete the confirmation and attach steps before the validation expires.

2. Endpoint Overview

Method	Endpoint	Purpose
POST	/partner-api/v1/employers/validations	Validates an employer code and returns the official employer name plus a short-lived validation ID.
POST	/partner-api/v1/employers	Attaches the confirmed employer to the authenticated partner using the validation ID.
GET	/partner-api/v1/employers	Lists employers currently attached to the authenticated partner.
DELETE	/partner-api/v1/employers/{employer_code}	Revokes the partner's access to the specified employer.

3. Step 1 — Validate an Employer Code

Endpoint

POST /partner-api/v1/employers/validations

Use this endpoint to check whether the supplied employer code can be recognised. This request is read-only: it does not attach the employer or grant access.

Request payload

```
{
  "employer_code": "PR0000126311"
}
```

Example successful response

```
{
  "validation_id": "ev_abc123",
  "employer_code": "PR0000126311",
  "employer_name": "Verified Company Limited",
  "valid": true,
  "expires_at": "2026-10-11T14:30:00Z"
}
```

What the application should do: display the returned employer code and official company name to the user. Ask the user to confirm that this is the correct employer before making the attach request.

Key fields

Field	Meaning
validation_id	Short-lived ID used in the attach request; it is bound to the authenticated partner.
employer_code	The employer code that was checked.
employer_name	Official company name to show for user confirmation.
valid	Indicates whether the code was validated as valid.
expires_at	Time when the validation ID expires. The flow must be completed within 30 minutes.

4. Step 2 — Attach the Confirmed Employer

Endpoint

POST /partner-api/v1/employers

Call this endpoint only after the user confirms the employer name returned by validation. The validation ID proves that the employer code was checked recently.

Request payload

```
{
  "validation_id": "ev_abc123"
}
```

Example successful response

```
{
  "id": "grant_abc123",
  "employer_code": "PR0000126311",
  "employer_name": "Verified Company Limited",
  "status": "active",
  "attached_at": "2026-10-11T14:05:00Z"
}
```

What success means: the employer is attached to the authenticated partner, and the partner can use the API for that employer subject to its other permissions.

Behaviour to know

- Calling attach again while the employer is active returns the existing grant rather than creating a duplicate active grant.
- The same validation ID may be used again until it expires if the employer is revoked and then reattached.
- If the validation ID expires, run the validation step again and obtain a fresh ID before attaching.

5. Step 3 — List Attached Employers

Endpoint

GET /partner-api/v1/employers

Use this endpoint to retrieve the employers attached to the authenticated partner. It is useful for displaying the partner's current employer access in a settings or administration screen.

Request body

No request body is required for this GET request.

The response is a list of employer grants. Use the returned employer code, name, status, and grant ID where those fields are included in the API response to display the current access state.

Tip: verify the actual response schema in Swagger for the environment you are testing, especially if your client needs to depend on optional fields.

6. Step 4 — Revoke Employer Access

Endpoint

DELETE /partner-api/v1/employers/{employer_code}

Use this endpoint when the partner should no longer have access to a particular employer. Replace {employer_code} in the URL with the actual employer code; do not send it as a JSON body unless the API specification explicitly requires one.

Example request

```
DELETE https://newhrpartnersapi.pensioncentral.ng/partner-api/v1/employers/PR0000126311

Authorization: Bearer YOUR_PARTNER_API_KEY
```

Important effect of revocation

Revocation immediately blocks new and historical API access for that employer. It does not delete existing schedules, payments, reports, or audit records.

To attach the employer again after the original validation expires, run a fresh employer validation and then attach using the new validation ID.

7. Recommended Integration Logic

Step	Application behaviour
1. Enter code	User provides an employer code.
2. Validate	Call POST /employers/validations with employer_code.
3. Confirm	Show the returned employer code and official company name; ask the user to confirm.
4. Attach	After confirmation, call POST /employers with validation_id.
5. Display access	Call GET /employers to refresh the list of attached employers.
6. Revoke if needed	Call DELETE /employers/{employer_code} when access should be removed.

8. Security and Testing Notes

- Keep partner API keys on the server side; do not expose them in browser or mobile application code.
- Confirm that the key belongs to the Sandbox environment when testing against the sandbox base URL.
- The key must have the employers:manage scope for these four operations.
- Treat employer names and access status as data that should be shown only to authorised users.
- Test the expired-validation scenario, the repeated-attach scenario, listing after attachment, and listing after revocation.
- Revocation removes API access; it is not a data-deletion operation.

Before production use, confirm the live base URL and current endpoint response schemas in the deployed Swagger documentation.

Quick reference

Action	Method + path	Payload
Validate	POST /partner-api/v1/employers/validations	{"employer_code":"PR0000126311"}
Attach	POST /partner-api/v1/employers	{"validation_id":"ev_abc123"}
List	GET /partner-api/v1/employers	No body
Revoke	DELETE /partner-api/v1/employers/{employer_code}	Employer code in URL

Sandbox Swagger: https://newhrpartnersapi.pensioncentral.ng/swagger