

EDGE AI COMPUTER · NVIDIA JETSON ORIN NX

SEALED SINTRONES IBOX-602P-IP66 EDGE AI COMPUTER

An IP66, fanless Jetson Orin NX box that starts at -40 °C, takes two GMSL-2 cameras on coax, and powers them itself. Every connector is M-coded – nothing on this machine shakes loose.



■ WHY THIS COMPUTER

- **NVIDIA Jetson Orin NX, 16 GB or 8 GB** – 1024-core Ampere GPU with 32 Tensor Cores, 8- or 6-core Arm Cortex-A78AE at 2.0 GHz, running JetPack 6.2
- **2 × GMSL-2 camera inputs over FAKRA** – synchronized coax capture from the qualified oToBrite, e-con Systems and StereoLabs modules, up to 8 MP per channel
- **IP66 sealed aluminium enclosure, fanless** – dust-tight and rated against powerful water jets, with no moving parts to service
- **Built-in low-temperature heater** – cold start from -40 °C and operation to 65 °C with 0.6 m/s airflow
- **M-coded connectors throughout** – M12 X-code Ethernet, M12 K-code power, M8 for CAN FD, COM and DIO; no RJ-45 to vibrate out of its latch
- **2 × PoE at 15.4 W per port** (PSE Class 3, 32 W budget) – the cameras draw from the same box that processes them
- **9–60 V DC input** with OCP, surge and reverse-polarity protection, ignition sensing, and an optional BBU for 5–10 minutes of orderly shutdown
- **EN 50155, EN 45545-2 (R25), E-mark, CE, FCC Class A and UKCA**, with MIL-STD-810G shock and vibration qualification

IP66

INGRESS PROTECTION

-40 °C

COLD START

2 × GMSL-2

CAMERA INPUTS

9–60 V

DC INPUT RANGE

■ APPLICATION SCENARIOS



AMR & AGV PLATFORMS

On-vehicle inference for autonomous chassis



RAIL & ROLLING STOCK

EN 50155 / EN 45545-2 onboard compute



GMSL-2 VISION

Two synchronized cameras over coax



OFF-HIGHWAY VEHICLES

Sealed compute for outdoor and mobile duty

